



Fakultät für
**Mathematik und
Informatik**

NCCL and Host-Initiated NVSHMEM ISC 2024

*Lena Oden,
FernUniversität in Hagen*

Motivation

- MPI is **not** (yet [1]) aware of CUDA streams
- Explicit synchronization between GPU-compute kernel and CPU communication calls is required
- CUDA-aware MPI is GPU-**memory**-aware communication
- For better efficiency: CUDA-**stream**-aware communication
 - Communication, which is aware of CUDA-streams or use CUDA streams
 - NCCL and (Host-API) of NVSHMEM

What will you Learn?

- How to use NCCL inside an MPI Application to use CUDA-stream-aware P2P communication
- NVSHMEM memory model
- How to use stream-aware NVSHMEM communication operations in MPI Programs


[1] MPI Forum Hybrid Working Group - Stream and Graph Based MPI Operations: <https://github.com/mpiwg-hybrid/hybrid-issues/issues/5>

Optimized inter-GPU communication

NCCL : NVIDIA Collective Communication Library

Communication library running on GPUs, for GPU buffers.

- *Library for efficient communication with GPUs*
- *First: Collective Operations (e.g. Allreduce), as they are required for DeepLearning*
- *Since 2.8: Support for Send/Recv between GPUs*
- *Library running on GPU: Communication calls are translated to GPU a kernel (running on a stream)*



Binaries : <https://developer.nvidia.com/nccl> and in NGC containers

Source code : <https://github.com/nvidia/nccl>

Perf tests : <https://github.com/nvidia/nccl-tests>

NCCL-API (With MPI) - Initialization

First, we need a NCCL-Communicator for, this, we need a NCCL UID

```
MPI_Init(&argc,&argv)
MPI_Comm_size(MPI_COMM_WORLD,&size);
MPI_Comm_rank(MPI_COMM_WORLD,&rank);

ncclUniqueId nccl_uid;
if (rank == 0) ncclGetUniqueId(&nccl_uid);
MPI_Bcast(&nccl_uid, sizeof(ncclUniqueId), MPI_BYTE, 0, MPI_COMM_WORLD);

ncclComm_t nccl_comm;
ncclCommInitRank(&nccl_comm, size, nccl_uid, rank);
...
...
ncclCommDestroy(nccl_comm);
MPI_Finalize();
```




Supported
for NCCL
2.8+

```
ncclSend(void* sbuff, size_t count, ncclDataType_t type, int peer, ncclComm_t comm, cudaStream_t stream);  
ncclRecv(void* rbuff, size_t count, ncclDataType_t type, int peer, ncclComm_t comm, cudaStream_t stream);
```

```
ncclAllReduce(void* sbuff, void* rbuff, size_t count, ncclDataType_t type, ncclRedOp_t op, ncclComm_t comm, cudaStream_t stream);  
ncclBroadcast(void* sbuff, void* rbuff, size_t count, ncclDataType_t type, int root, ncclComm_t comm, cudaStream_t stream);  
ncclReduce(void* sbuff, void* rbuff, size_t count, ncclDataType_t type, ncclRedOp_t op, int root, ncclComm_t comm, cudaStream_t stream);  
ncclReduceScatter(void* sbuff, void* rbuff, size_t count, ncclDataType_t type, ncclRedOp_t op, ncclComm_t comm, cudaStream_t stream);  
ncclAllGather(void* sbuff, void* rbuff, size_t count, ncclDataType_t type, ncclComm_t comm, cudaStream_t stream);
```

Fused Communication Calls

- Multiple calls to `ncclSend()` and `ncclRecv()` should be fused with `ncclGroupStart()` and `ncclGroupEnd()` to
 - Avoid deadlocks
(if calls need to progress concurrently)
 - For more performance
(can be more efficiently)

SendRecv:

```
ncclGroupStart();
ncclSend(sendbuff, sendcount, sendtype, peer, comm, stream);
ncclRecv(recvbuff, recvcount, recvtype, peer, comm, stream);
ncclGroupEnd();
```

Bcast:

```
ncclGroupStart();
if (rank == root) {
    for (int r=0; r<n ranks; r++)
        ncclSend(sendbuff[r], size, type, r, comm, stream);}
ncclRecv(recvbuff, size, type, root, comm, stream);
ncclGroupEnd();
```

Neighbor exchange:

```
ncclGroupStart();
for (int d=0; d<ndims; d++) {
    ncclSend(sendbuff[d], sendcount, sendtype, next[d], comm, stream);
    ncclRecv(recvbuff[d], recvcount, recvtype, prev[d], comm, stream);
}
ncclGroupEnd();
```

Jacobi solver communication with NCCL

```
launch_jacobi_kernel(a_new, a, l2_norm_d, iy_start, iy_end, nx, compute_stream);  
ncclGroupStart();  
ncclRecv(a_new, nx, NCCL_REAL_TYPE, top, nccl_comm, compute_stream);  
ncclSend(a_new + (iy_end - 1)*nx, nx, NCCL_REAL_TYPE, btm, nccl_comm, compute_stream);  
ncclRecv(a_new + (iy_end*nx), nx, NCCL_REAL_TYPE, btm, nccl_comm, compute_stream);  
ncclSend(a_new + iy_start * nx, nx, NCCL_REAL_TYPE, top, nccl_comm, compute_stream);  
ncclGroupEnd();
```

Performance Improvement

- *So far, no overlap of communication and computation*
- *Use techniques from previous session to overlap communication and computation*
- *Make sure that communication streams are scheduled*
 - *CUDA high priority streams!*

```
int leastPriority = 0;
int greatestPriority = leastPriority;
cudaDeviceGetStreamPriorityRange(&leastPriority, &greatestPriority);

cudaStream_t compute_stream;
cudaStream_t push_stream;

cudaStreamCreateWithPriority(&compute_stream, cudaStreamDefault, leastPriority);
cudaStreamCreateWithPriority(&push_top, cudaStreamDefault, greatestPriority);
```


Jacobi using NCCL and Overlapping Communication and Computation

```
launch_jacobi_kernel(a_new, a, l2_norm_d, iy_start,      iy_start + 1), nx, push_stream);
launch_jacobi_kernel(a_new, a, l2_norm_d, (iy_end - 1),  iy_end,      nx, push_stream);
launch_jacobi_kernel(a_new, a, l2_norm_d, (iy_start + 1), (iy_end - 1), nx, compute_stream);

ncclGroupStart();
ncclRecv(a_new,      nx, NCCL_REAL_TYPE, top, nccl_comm, push_stream);
ncclSend(a_new + (iy_end - 1) * nx, nx, NCCL_REAL_TYPE, btm, nccl_comm, push_stream);
ncclRecv(a_new + (iy_end * nx), nx, NCCL_REAL_TYPE, btm, nccl_comm, push_stream);
ncclSend(a_new + iy_start * nx, nx, NCCL_REAL_TYPE, top, nccl_comm, push_stream);
ncclGroupEnd();
```

How to Compile an MPI+NCCL Application

- *Include header files and link against CUDA NCCL library*

```
#include <nccl.h>
```

```
MPICXX_FLAGS = -I$(CUDA_HOME)/include -I$(NCCL_HOME)/include
```


```
LD_FLAGS = -L$(CUDA_HOME)/lib64 -lcudart -lnccl
```

```
$(NVCC) $(NVCC_FLAGS) jacobi_kernels.cu -c -o jacobi.o
```


```
$(MPICXX) $(MPICXX_FLAGS) jacobi.cpp jacobi_kernels.o $(LD_FLAGS) -o jacobi
```

NVSHMEM – Overview

- *Implements the OpenSHMEM API for clusters of NVIDIA GPUs*
- Partitioned Global Address Space (PGAS) programming model
 - One sided Communication with put/get
 - Shared memory Heap
- GPU Centric communication APIs
 - GPU Initiated: thread, warp, block
 - Stream/Graph-Based (communication kernel or cudaMemcpyAsync)
 - CPU Initiated
- prefixed with “*nvshmem*” to allow use with a CPU OpenSHMEM library
- *Interoperability with OpenSHMEM and MPI*



*With some
extensions to
the API*



Symmetric objects are allocated collectively with the same size on every PE

Symmetric memory: `nvshmem_malloc(shared_size);`

Private memory: `cudaMalloc(...)`


Must be the
same on all
PEs

Interoperability with MPI and OpenSHMEM

```
MPI_Init(&argc, &argv);
MPI_Comm mpi_comm = MPI_COMM_WORLD;
nvshmemx_init_attr_t attr;
attr.mpi_comm = mpi_comm;
nvshmemx_init_attr(NVSHMEMX_INIT_WITH_MPI_COMM, &attr);
assert( size == nvshmem_n_pes() );
assert( rank == nvshmem_my_pe() );
...
nvshmem_finalize()
MPI_Finalize();

shmem_init();
nvshmemx_init_attr_t attr;
nvshmemx_init_attr(NVSHMEMX_INIT_WITH_SHMEM, &attr);
my_pe_node = nvshmem_team_my_pe(NVSHMEMX_TEAM_NODE);
...
```

NVSHMEM Host API Put




Copies nelems data elements of type T from symmetric objects src to dest on PE pe

```
void nvshmem_<T>_put(T*dest, const T*source, size_t nelems, int pe);
void nvshmemx_<T>_put_on_stream(T*dest, const T*src, size_t nelems, int pe, cudaStream_t stream);
```

The x marks extensions to the OpenSHMEM API

NVSHMEM Barrier (on Host)



Synchronizes all PEs and ensures communication performed prior to the barrier has completed

```
void nvshmem_barrier_all(void);  
void nvshmemx_barrier_all_on_stream(cudaStream_t stream)
```

Chunk size must be the same on all PEs.
Otherwise, you get
Undefined Behavior!

Jacobi solver communication with NVSHMEM

```
real* a      = (real*) nvshmem_malloc(nx * (chunk_size+ 2) * sizeof(real));  
real* a_new = (real*) nvshmem_malloc(nx * (chunk_size+ 2) * sizeof(real));
```

```
launch_jacobi_kernel(a_new, a, l2_norm_d, iy_start, iy_end, nx, compute_stream);  
nvshmemx_float_put_on_stream(a_new, a_new +iy_end - 1) * nx, nx, btm, compute_stream);  
nvshmemx_float_put_on_stream((a_new+iy_end)*nx, (a_new+1)*nx, nx, top, compute_stream);  
nvshmemx_barrier_all_on_stream(compute_stream);
```



Use high priority stream!

Jacobi with NVSHMEM

```
real* a = (real*) nvshmem_malloc(nx * (chunk_size+ 2) * sizeof(real));
real* a_new = (real*) nvshmem_malloc(nx * (chunk_size+ 2) * sizeof(real));

launch_jacobi_kernel(a_new, a, l2_norm_d, iy_start,      iy_start + 1, nx, push_stream);
launch_jacobi_kernel(a_new, a, l2_norm_d, iy_end - 1,    iy_end,      nx, push_stream);
launch_jacobi_kernel(a_new, a, l2_norm_d, iy_start + 1, iy_end - 1), nx, compute_stream);

nvshmemx_float_put_on_stream(a_new, a_new + (iy_end-1) * nx,      nx, btm, push_stream);
nvshmemx_float_put_on_stream((a_new+iy_end)*nx, (a_new+1)*nx, nx, top, push_stream);
nvshmemx_barrier_all_on_stream(push_stream);
```

How to compile NVSHMEM + MPI applications

- *Compile CUDA-kernel*
 - Use the *-rdc=true* compile flag due to the device interface
 - Link against the nvshmem library *-lnvshmem*

```
#include <nvshmem.h>
#include <nvshmemx.h>
```

```
nvcc -rdc=true -ccbin g++ -gencode=$NVCC_GENCODE -I $NVSHMEM_HOME/include \
nvshmem_hello.cu -o nvshmem_hello -L $NVSHMEM_HOME/lib -lnvshmem -lcuda
```

```
nvcc -rdc=true -ccbin g++ -gencode=$NVCC_GENCODE -I $NVSHMEM_HOME/include -c \
jacobi_kernels.cu -o jacobi_kernels.o
```

```
$mpixx -I $NVSHMEM_HOME/include jacobi.cpp jacobi_kernels.o -lnvshmem \
-lcuda -o jacobi
```

- *NCCL and NVSHMEM support CUDA stream aware communication*
- *Both are interoperable with MPI*
- *NCCL support send/receive semantics*
- *NVSHMEM supports the OpenSHMEM library, supporting one sided communication operation*
- *Both allow to issue communication request asynchronous with respect to the CPU-thread, but synchronous to CUDA streams*
- *High priority streams are required to overlap communication and computation*