

# Widoki

---

## Course\_information

Widok przedstawia informacje o stworzonych kursach dostępnych i nie dostępnych. Przedstawia również informacje o ilości modułów i maksymalnej ilości miejsc na kursie (wyznaczana na podstawie limitu w modułach stacjonarnych).

```
create view course_information as
with count_modules as (select CourseID, count(ModuleID) as count_module
                        from Modules
                        group by CourseID
), limit_for_course as (select Courses.CourseID, min(Limit) as min_limit
                        from Courses inner join Modules on Courses.CourseID = Modules.CourseID
                        inner join In_person_Modules on Modules.ModuleID = In_person_Modules.ModuleID
                        group by Courses.CourseID)

select Courses.CourseID,
       Name,
       Description,
       concat(FirstName, ' ', LastName) as Coordinator_full_name,
       StartDate,
       EndDate,
       isnull(count_module, 0) as Total_modules,
       min_limit as Total_places
from Courses left join Employees on Courses.CoordinatorID = Employees.EmployeeID
left join count_modules on Courses.CourseID = count_modules.CourseID
left join limit_for_course on Courses.CourseID = limit_for_course.CourseID;
```

---

## Employees\_information

Widok przedstawia informacje danych pracowników w systemie.

```
CREATE view employees_information as
select EmployeeID,
       FirstName,
       LastName,
       Phone,
       Email,
       Address,
       City,
       PostalCode,
       PositionName
from Employees inner join Employees_Postions on Employees.PositionID = Employees_Postions.PositionID
```

---

## Future\_course\_sign

Widok przedstawia informacje o ilości osób zapisanych na przyszłe kursy. Przyszłe kursy oznaczają wydarzenia o dalszej dacie niż aktualna.

```
CREATE view future_course_sign as
select future_courses.CourseID,
       Name,
       StartDate,
       EndDate,
       count(UserID) as Total_users
from future_courses left join Users_Courses on Users_Courses.CourseID = future_courses.CourseID
group by future_courses.CourseID, Name, StartDate, EndDate
```

---

## Future\_courses

Widok przedstawia informacje o przyszłych kursach.

```
create view future_courses as
select *
from course_information
where getdate() < StartDate
```

---

## Future\_studie\_sign

Widok przedstawia informacje o ilości osób zapisanych na przyszłe studia.

```
CREATE view future_studie_sign as
select future_studies.StudiesID,
       Name,
       StartDate,
       EndDate,
       count(UserID) as Total_users
from future_studies left join Users_Studies on Users_Studies.StudiesID = future_studies.StudiesID
group by future_studies.StudiesID, Name, StartDate, EndDate;
```

---

### Future\_studies

Widok przedstawia informacje o przyszłych studiach.

```
create view future_studies as
select *
from studie_information
where getdate() < StartDate
```

---

### Future\_webinar\_sign

Widok przedstawia informacje o ilości zapisanych osób na przyszłe webinary.

```
CREATE view future_webinar_sign as
select future_webinars.WebinarID,
       Name,
       DateAndBeginningTime,
       Duration,
       count(UserID) as Total_users
from future_webinars left join Users_Webinars on Users_Webinars.WebinarID = future_webinars.WebinarID
group by future_webinars.WebinarID, Name, Duration, DateAndBeginningTime
```

---

### Future\_webinars

Widok przedstawia informacje o przyszłych webinarach.

```
create view future_webinars as
select *
from webinar_information
where getdate() < DateAndBeginningTime
```

---

### In\_person\_module\_information

Widok przedstawia informacje o modułach stacjonarnych w kursach.

```
create view in_person_module_information as
select ModuleID,
       Classroom,
       concat(FirstName, ' ', LastName) as Translator_full_name,
       LanguageName,
       Limit
from In_person_Modules left join Translators on In_person_Modules.TranslatorID = Translators.TranslatorID
left join Languages on In_person_Modules.LanguageID = Languages.LanguageID;
```

---

### Languages\_count\_translators

Widok przedstawia ilu tłumaczy mówi w danych językach.

```
create view languages_count_translators as
select LanguageName,
       count(TranslatorID) as Translators_count
from Languages
inner join Translators_Languages on Languages.LanguageID = Translators_Languages.LanguageID
group by LanguageName;
```

---

## Module\_information

Widok przedstawia informacje o modułach w kursach.

```
create view module_information as
select ModuleID,
       concat(FirstName, ' ', LastName) as Teacher_full_name,
       CourseID,
       Name,
       Description,
       DateAndBeginningTime,
       Duration,
       TypeName
from Modules inner join Employees on Modules.TeacherID = Employees.EmployeeID
inner join Types on Modules.TypeID = Types.TypeID;
```

---

## Online\_sync\_module\_information

Widok przedstawia informacje o modułach online-synchronicznych w kursach.

```
create view online_sync_module_information as
select ModuleID,
       MeetingLink,
       RecordingLink,
       concat(FirstName, ' ', LastName) as Translator_full_name,
       LanguageName
from Online_Sync_Modules inner join Translators on Online_Sync_Modules.TranslatorID = Translators.TranslatorID
inner join Languages on Online_Sync_Modules.LanguageID = Languages.LanguageID;
```

---

## Online\_async\_module\_information

Widok przedstawia informacje o modułach online-asynchronicznych w kursach.

```
create view online_async_module_information as
select ModuleID,
       RecordingLink
from Online_Async_Modules;
```

---

## Studie\_information

Widok przedstawia informacje o studiach wraz z ilością przedmiotów, ilością spotkań oraz maksymalną ilością miejsc na studiach (wyznaczaną po podstawie spotkań stacjonarnych).

```
create view studie_information as
with count_subjects as (select StudiesID, count(SubjectID) as total_subjects
                        from Subjects
                        group by StudiesID
), count_meetings as (select StudiesID, count(MeetingID) as total_meetings
                     from Meetings
                     inner join Subjects on Meetings.SubjectID = Subjects.SubjectID
                     group by StudiesID
), limit_for_studie as (select StudiesID, min(Limit) as min_limit
                       from In_person_Meetings inner join Meetings on In_person_Meetings.MeetingID = Meetings.MeetingID
                       inner join Subjects on Meetings.SubjectID = Subjects.SubjectID
                       group by StudiesID
)
select Studies.StudiesID,
       concat(FirstName, ' ', LastName) as Coordinator_full_name,
       Name,
       Description,
       StartDate,
       EndDate,
       Price,
       isnull(total_subjects, 0) as Total_subjects,
       isnull(total_meetings, 0) as Total_meetings,
       min_limit as Total_places
from Studies left join Employees on Studies.CoordinatorID = Employees.EmployeeID
left join count_subjects on Studies.StudiesID = count_subjects.StudiesID
left join count_meetings on Studies.StudiesID = count_meetings.StudiesID
left join limit_for_studie on Studies.StudiesID = limit_for_studie.StudiesID;
```

---

## Translators\_information

Widok przedstawia informacje o tłumaczach pracujących na platformie.

```
CREATE view translators_information as
select TranslatorID,
       FirstName,
       LastName,
       Phone,
       Email,
       Address,
       City,
       PostalCode
from Translators;
```

## Translators\_language

Widok przedstawia zestawienia tłumaczy wraz z językami, które tłumaczą

```
create view translators_language as
select concat(FirstName, ' ', LastName) as fullName,
       LanguageName
from Translators
     inner join Translators_Languages on Translators.TranslatorID = Translators_Languages.TranslatorID
     inner join Languages on Languages.LanguageID = Translators_Languages.LanguageID;
```

## Users\_information

Widok przedstawia informacje o użytkownikach systemu.

```
CREATE view users_information as
select UserID,
       FirstName,
       LastName,
       Phone,
       Email,
       Address,
       City,
       PostalCode
from Users;
```

## Webinar\_information

Widok przedstawia informacje o webinarach dostępnych czy nie dostępnych.

```
create view webinar_information as
select WebinarID,
       Name,
       Description,
       DateAndBeginningTime,
       Duration,
       concat(C.FirstName, ' ', C.LastName) as full_name_coordinator,
       concat(T.FirstName, ' ', T.LastName) as full_name_teacher,
       concat(isnull(Translators.FirstName, ''), ' ', isnull(Translators.LastName, '')) as full_name_translator,
       Price,
       LanguageName,
       RecordingLink,
       MeetingLink
from Webinars inner join Employees T on Webinars.TeacherID = T.EmployeeID
left join Employees C on C.EmployeeID = Webinars.CoordinatorID
left join Translators on Webinars.TranslatorID = Translators.TranslatorID
left join Languages on Webinars.LanguageID = Languages.LanguageID;
```

## Course\_module\_types

Widok ten przedstawia ile jest modułów każdego typu w każdym kursie.

```
create view course_module_types as
with in_person_count as (
```

```

select CourseID, count(Modules.ModuleID) as in_person
from Modules inner join In_person_Modules on Modules.ModuleID = In_person_Modules.ModuleID
group by CourseID
), online_sync_count as (
select CourseID, count(Modules.ModuleID) as online_sync
from Modules inner join Online_Sync_Modules on Modules.ModuleID = Online_Sync_Modules.ModuleID
group by CourseID
), online_async_count as (
select CourseID, count(Modules.ModuleID) as online_async
from Modules inner join Online_Async_Modules on Modules.ModuleID = Online_Async_Modules.ModuleID
group by CourseID
)

select Courses.CourseID, in_person, online_sync, online_async
from Courses left join in_person_count on Courses.CourseID = in_person_count.CourseID
left join online_async_count on Courses.CourseID = online_async_count.CourseID
left join online_sync_count on Courses.CourseID = online_sync_count.CourseID

```

## Course\_passes

Widok ten przedstawia listę ze zdawalnościami w modułach odpowiednich kursów dla osób zapisanych.

```

create view course_passes as
select CourseID,
       Modules.ModuleID,
       FirstName,
       LastName,
       Passed
from Users_Modules_Passes inner join Modules on Users_Modules_Passes.ModuleID = Modules.ModuleID
inner join Users on Users_Modules_Passes.UserID = Users.UserID

```

## Course\_sign\_limit

Widok przedstawia dla każdego kursu ile miejsc się na niego sprzedało i jaki jest limit.

```

create view course_sign_limit as
with course_limits as (
select CourseID, min(Limit) as total_limit
from Modules inner join In_person_Modules on Modules.ModuleID = In_person_Modules.ModuleID
group by CourseID
)

select Courses.CourseID, total_product_orders, total_limit
from Courses left join products_orders on products_orders.ProductID = Courses.CourseID
left join course_limits on course_limits.CourseID = Courses.CourseID

```

## Dont\_make\_payment\_in\_time

Widok ten przedstawia użytkowników, którzy nie zapłacili do wymaganego czasu (nawet jak czas został przedłużony).

```

create view dont_make_payment_in_time as
select UserID,
       case
       when ExtendedPaymentDeadline is not null then ExtendedPaymentDeadline
       else PaymentDeadline
       end official_payment_date,
       ProductID
from Orders_Details inner join Orders on Orders_Details.OrderID = Orders.OrderID
where
       case
       when ExtendedPaymentDeadline is not null then ExtendedPaymentDeadline
       else PaymentDeadline
       end < getdate() and Payment is null

```

## Financial\_report

Widok przedstawia raport finansowy z każdego produktu w bazie.

```

create view financial_report as
with count_products_sales as (
select Orders_Details.ProductID, sum(Payment) as total_payment

```

```

    from Orders_Details inner join Products on Orders_Details.ProductID = Products.ProductID
    inner join Categories on Products.CategoryID = Categories.CategoryID
    where Name <> 'Reunion'
    group by Orders_Details.ProductID
)

```

```

select Products.ProductID, Name
from Products left join Categories on Products.CategoryID = Categories.CategoryID
left join count_products_sales on Products.ProductID = count_products_sales.ProductID
where Name != 'Reunion'

```

## Future\_meetings

Widok przedstawia przyszłe spotkania studyjne.

```

create view future_meetings as
select *
from meetings_information
where getdate() < DateAndBeginningTime

```

## Future\_meetings\_sign

Widok przedstawia ile osób zapisało się na przyszłe spotkania.

```

create view future_meetings_sign as
with meetings_sign_count as (
    select MeetingID, count(UserID) as sign_count
    from Users_Meetings_Attendance
    group by MeetingID
)

select future_meetings.MeetingID, sign_count
from future_meetings inner join meetings_sign_count on future_meetings.MeetingID = meetings_sign_count.MeetingID;

```

## Meeting\_sign\_limit

Widok przedstawia ilość osób zapisanych na dane spotkanie i jego limit.

```

create view meeting_sign_limit as
with meeting_limits as (
    select Meetings.MeetingID, min(Limit) as total_limit
    from Meetings inner join In_person_Meetings on Meetings.MeetingID = In_person_Meetings.MeetingID
    group by Meetings.MeetingID
)

select Meetings.MeetingID, total_product_orders, total_limit
from Meetings left join products_orders on Meetings.MeetingID = products_orders.ProductID
left join meeting_limits on meeting_limits.MeetingID = Meetings.MeetingID

```

## Meetings\_information

Widok przedstawia ogólne informacje o spotkaniach studyjnych.

```

create view meetings_information as
select MeetingID,
    FirstName,
    LastName,
    Name,
    ReunionID,
    DateAndBeginningTime,
    Duration,
    Price,
    TypeName
from Meetings inner join Employees on Meetings.TeacherID = Employees.EmployeeID
inner join Subjects on Meetings.SubjectID = Subjects.SubjectID
inner join Types on Meetings.TypeID = Types.TypeID

```

## Orders\_Payment\_informations

Widok przedstawia informacje o szczegółach wszystkich zamówień.

```
create view orders_payment_informations as
select Orders.OrderID,
       SubOrderID,
       FirstName,
       LastName,
       Orders_Details.ProductID,
       Name,
       case
         when ExtendedPaymentDeadline is null then PaymentDeadline
         else ExtendedPaymentDeadline
       end as official_payment_deadline,
       FullPrice,
       PaymentDate
from Orders_Details inner join Orders on Orders_Details.OrderID = Orders.OrderID
inner join Users on Orders.UserID = Users.UserID
inner join Products on Orders_Details.ProductID = Products.ProductID
inner join Categories on Products.CategoryID = Categories.CategoryID
```

---

## Products\_orders

Widok przedstawia ile razy każdy produkt został zamówiony.

```
create view products_orders as
select ProductID, count(SubOrderID) as total_product_orders
from Orders_Details
group by ProductID
```

---

## Studie\_sign\_limit

Widok przedstawia ile osób zapisało się na studia i jaki jest ich limit.

```
create view studie_sign_limit as
with studie_limits as (
  select Studies.StudiesID, min(Limit) as total_limit
  from Studies inner join Subjects on Studies.StudiesID = Subjects.StudiesID
  inner join Meetings on Subjects.SubjectID = Meetings.SubjectID
  inner join In_person_Meetings on Meetings.MeetingID = In_person_Meetings.MeetingID
  group by Studies.StudiesID
)

select Studies.StudiesID, total_product_orders, total_limit
from Studies left join products_orders on products_orders.ProductID = Studies.StudiesID
left join studie_limits on studie_limits.StudiesID = Studies.StudiesID
```

---

## Studies\_meetings\_list

Widok ten przedstawia listę obecności dla spotkań studyjnych wraz z datą odbycia się ich.

```
create view studies_meetings_list as
select
  Users_Meetings_Attendance.MeetingID,
  format(DateAndBeginningTime, 'yyyy-mm-dd') as date,
  FirstName,
  LastName,
  Present
from Users_Meetings_Attendance inner join Users on Users_Meetings_Attendance.UserID = Users.UserID
inner join Meetings on Users_Meetings_Attendance.MeetingID = Meetings.MeetingID
```