

# Learning Job Run-Times in HPC Systems

Valentin Reis

LIG, AMA Team.

Under supervision of: Eric Gaussier and Denis Trystram.

June 16, 2014

# Resource Management in HPC Systems

High Performance Computing is:

- Complex architectures.
- Uncertain data.


# Jobs

This is a job:



# Jobs

This is a job on a system:



# Objectives

- $\sum_{i=0}^{i=n} C_i$  (Minsum)
- $\max_{i=0}^{i=n} C_i$  (Makespan)
- $\sum_{i=0}^{i=n} C_i - r_i$  (Flow Time)
- $\sum_{i=0}^{i=n} \frac{C_i - r_i}{C_i - \sigma(i)}$  (Sum Stretch)
- $\max_{i=0}^{i=n} \frac{C_i - r_i}{C_i - \sigma(i)}$  (Max Stretch)
- Many others
- And their combinations!

# Objectives


- $\sum_{i=0}^{i=n} C_i$  (Minsum)
- $\max_{i=0}^{i=n} C_i$  (Makespan)
- $\sum_{i=0}^{i=n} C_i - r_i$  (Flow Time)
- $\sum_{i=0}^{i=n} \frac{C_i - r_i}{C_i - \sigma(i)}$  (Sum Stretch)
- $\max_{i=0}^{i=n} \frac{C_i - r_i}{C_i - \sigma(i)}$  (Max Stretch)
- Many others
- And their combinations!

And: functional constraints. **no starvation**, please!

# What problem is it?


- Offline Scheduling, a.k.a. strip packing?

# Offline Scheduling





# Offline Scheduling



# What problem is it?

- Offline Scheduling, a.k.a. strip packing?


# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no


# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no
- Online Scheduling?


# Online Scheduling




# Online Scheduling



# Uncertainty in Run-times



: Marginal



: Ratio

# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no
- Online Scheduling?



# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no
- Online Scheduling? – no


# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no
- Online Scheduling? – no
- Online Scheduling under Uncertainty


# What problem is it?

- Offline Scheduling, a.k.a. strip packing? – no
- Online Scheduling? – no
- Online Scheduling under Uncertainty – yes!

# Online Scheduling under Uncertainty



# Online Scheduling under Uncertainty



# Optimization under Uncertainty

# Optimization under Uncertainty

## Robust Optimization

# Optimization under Uncertainty


Robust Optimization      Stochastic Programming  
+ Input Modeling



# Optimization under Uncertainty


Robust Optimization

Stochastic Programming  
+ Input Modeling




# Optimization under Uncertainty


Robust Optimization




Stochastic Programming  
+ Input Modeling




# The FCFS algorithm



# The FCFS algorithm



# FCFS with EASY(conservative) backfilling



# Runtime Prediction

Problem Statement: How to best Predict the Runtime of a job on a given system?



# Nature of the Prediction

- Single-valued?
- Probability distribution?
- Confidence Interval?

# Nature of the Prediction

- **Single-valued**
- Probability distribution
- Confidence Interval



# Hypotheses on the Runtime

- Independent and identically distributed?
- Function of job characteristics?

# Hypotheses on the Runtime

- Independent and identically distributed? **No.**
- Is a function of job characteristics? **Yes.**

# State of the Art

A very popular predictor:

$$p_i^u = \frac{p_{i-1}^u + p_{i-2}^u}{2}$$

Baseline for evaluating our method.

# Our Approach

Machine Learning: Regression problem.

# Our Approach

Machine Learning: Regression problem.  
Build vectors containing:

# Our Approach

Machine Learning: Regression problem.

Build vectors containing:

- Job characteristics (e.g., required time and nodes)

# Our Approach

Machine Learning: Regression problem.

Build vectors containing:

- Job characteristics (e.g., required time and nodes)
- Status of the system (e.g., day of the week)

# Our Approach

Machine Learning: Regression problem.

Build vectors containing:

- Job characteristics (e.g., required time and nodes)
- Status of the system (e.g., day of the week)
- Characteristics of the last jobs of this user (e.g., the baseline)



# Our Approach

Machine Learning: Regression problem.

Build vectors containing:

- Job characteristics (e.g., required time and nodes)
- Status of the system (e.g., day of the week)
- Characteristics of the last jobs of this user (e.g., the baseline)

Perform Regression using the Random Forest algorithm.

# Random Forests

- Training:
  - Randomly partition the training data.
  - Learn a decision tree on each subset.

# Decision Tree Learning

$$X = \begin{pmatrix} x \\ y \end{pmatrix}, (\alpha, \beta, a, b, c) \in \mathbb{R}^5$$




Figure: A decision tree for predicting the value of  $X$ .

# Random Forests

- Training:
  - Randomly partition the training data.
  - Learn a decision tree on each subset.
- Predict a value by averaging the results from all the decision trees.


# Experiments

On the CURIE log:

The features are extracted with the SimPy discrete event simulation package.

The RF is trained on the CURIE log using the first 80% of the jobs, using the Scikit-Learn package.

# Results: Absolute Error Distribution



# Results: metrics

Measure	Baseline	Random Forest
MSE	$1.984\,975\,15 \times 10^8$	$1.582\,022\,18 \times 10^8$
MAE	$4.680\,836 \times 10^3$	$5.551\,237 \times 10^3$
Standard Error	$5.312\,812 \times 10^1$	$4.512\,378 \times 10^1$

# Perspectives

- Online Algorithm
- More datasets, more features.
- Sensitivity analysis, objective/cost functions.



# Thank you!