"I Can't Assist with Writing Your LLM Post-Training Research for You", and 239 Other Excuses to Do Zero Work

Faaiz Khan
Syed Babar Ali School of Science and Engineering
Lahore University of Management Sciences
Lahore, Pakistan
25280051@lums.edu.pk

Abstract

Post-training adapts pretrained language models to preferences and task constraints, but training objectives and feedback sources directly influence response length, refusal calibration, and optimization stability. We evaluate three preference optimization methods (DPO, PPO, GRPO) and two feedback sources (exact outcome verification and AI judgment) on `Qwen2.5-1.5B-Instruct` with LoRA adapters. Specifically: (i) training DPO on length-balanced pairs widens the accuracy gap between rejected-longer and preferred-longer completions from 17.1% to 31.1% ($N = 237$), favoring shorter responses; (ii) on cached rollouts, tight PPO clipping ($\epsilon = 0.05$) bounds 16.0% of tokens, but shows higher loss and gradient variance during continuation; (iii) GRPO informativeness reaches 100% on easy prompts but plateaus at 91.7% on hard prompts (11 of 12 groups informative); (iv) on XSTest, the 3B automated judge reported zero safe over-refusals across all four policies, whereas a 240-item audit across 60 prompts (72.1% agreement, 173/240) revealed that all four policies refused the same 10 benign prompts, behavior inherited directly from SFT; and (v) on controlled math perturbations, deterministic verifiers detected all outcome errors ($S_{\text{outcome}} = 1.0$) but were invariant to reasoning corruption, whereas the pairwise AI judge tied on all 20 outcome errors and favored persuasive filler in 25.0% of pairs. These findings show that length balancing shifts accuracy across length strata rather than eliminating length sensitivity, while our automated judge masked policy over-refusal and proved vulnerable to persuasive framing. Code: `https://github.com/FaaizKhan1999/atml-assignment2`.

1 Introduction

Modern language model development commonly follows a three-stage pipeline: pretraining learns general text representations, supervised fine-tuning (SFT) teaches models to follow instructions, and post-training aligns outputs with preferences or reward signals [Ouyang et al., 2022]. Common post-training methods include Direct Preference Optimization [DPO; Rafailov et al., 2023], Proximal Policy Optimization [PPO; Schulman et al., 2017, Ouyang et al., 2022], and Group Relative Policy Optimization [GRPO; Shao et al., 2024]. Unlike pretraining and SFT, which train models to predict or imitate text distributions, post-training optimizes a scalar or pairwise objective directly. This shift from imitation to reward maximization makes the policy vulnerable to optimizing proxies rather than desired behaviors, making it essential to analyze the failure modes of this stage.

However, optimizing an objective does not ensure that the policy meets the intended goal. Standard evaluation metrics like reward scores, benchmark accuracy, and reference KL divergence each measure only a single property in isolation. For example, a model can gain preference accuracy by exploiting response length differences in training data rather than producing better answers.

Automated evaluators like LLM judges can also mischaracterize model behavior. In safety evaluation, an automated judge can fail to detect over-refusal by classifying unwarranted refusals of harmless prompts as justified. In reasoning tasks, automated judges can favor persuasive formatting over concise solutions, or frequently return ties even when candidate solutions contain overt outcome errors. Standard evaluations often report aggregate scores without isolating how training data balance affects preference learning, how online constraints bound updates across difficulty levels, or how judges handle edge cases [Anthropic, 2023].

To study how optimization constraints and feedback sources affect policy behavior, we conduct a controlled empirical comparison on `Qwen2.5-1.5B-Instruct` [Qwen Team, 2024] across offline preference optimization (DPO), online reinforcement learning (PPO and GRPO), and distinct feedback sources (RLVR and RLAIF). Both the safety judge and the pairwise reasoning judge use `Qwen2.5-3B-Instruct`, which shares its model family with the evaluated policies.

We organize our study around four central questions and empirical findings:

1. To what extent do offline gains reflect length bias? Training on length-balanced preference pairs widens the accuracy gap between rejected-longer and preferred-longer completions, favoring shorter responses while training on substantially shorter sequences.
2. How do update rules bound policy drift? In PPO, ratio clipping binds a notable fraction of token updates on cached rollouts with higher variance during continuation, while in GRPO, group informativeness plateaus on hard prompts due to within-group reward collapse.
3. Can automated judges detect over-refusal? On XSTest, the automated judge reported zero safe over-refusals across all four policies, whereas manual auditing showed that all four policies refused the same benign prompts inherited directly from the supervised baseline.
4. How do verifiers and AI judges diverge on corrupted inputs? By construction, exact binary verifiers detect all outcome errors but miss reasoning invalidity, whereas the pairwise AI judge tied on all outcome-corrupted completions and showed vulnerability to persuasive rhetorical padding.

2 Experimental Setup and Methods

2.1 Study Design and Shared Setup

Within each controlled comparison, we vary one factor by design, holding prompt pools, decoding configurations, and random seeds fixed. We note three necessary exceptions: length-balanced DPO alters both dataset composition and length balance; standard DPO (1 epoch of 723 steps at batch size 2, totaling 1,446 pairs) and the β sweeps (short forks on 600 pairs) differ in training budget; and the supplied RLVR and RLAIF adapters differ in feedback source.

Shared Model Setup Across all experiments, our base policy is `Qwen2.5-1.5B-Instruct` [Qwen Team, 2024]. Trainable parameters are adapted using LoRA [Hu et al., 2022] with rank $r = 8$ and scaling factor $\alpha = 16$. The base policy and frozen reference policy share identical FP16 weights, with the reference disabling the adapter to avoid quantization mismatch. The frozen scalar reward model for preference optimization is `yavuz-ai/qwen2.5-1.5b-rm-ultrafeedback` trained on UltraFeedback [Cui et al., 2024]. In PPO, the learned value critic is initialized from `Qwen2.5-0.5B-Instruct` with matching LoRA adapters. Both safety calibration and pairwise preference evaluation use `Qwen2.5-3B-Instruct`. We note that the 1.5B policies and the 3B judge share the same Qwen2.5 model family.

Trained versus Supplied Components Standard DPO is trained from the base instruct policy initialization using LoRA adapters. PPO and GRPO are continued from supplied midpoint checkpoints [Course Staff, Advanced Topics in Machine Learning, 2026a,b]. For feedback source comparisons, RLVR and RLAIF adapters are supplied checkpoints trained with matched group-based optimizers and completion budgets.

Datasets and Sample Sizes All runs use fixed seed 6304. For PPO and GRPO continuations, 20 updates consume 20 prompts (1 prompt per update) from the 200-prompt pool, while 8-update forks

consume 8 prompts. The cached GRPO group-size study evaluates 192 completions collected across 24 prompts (24×8). Appendix Table 6 summarizes the setup, budgets, factors varied, and evaluation benchmarks.

2.2 Optimization Algorithms

We investigate three preference optimization objectives:

Direct Preference Optimization (DPO) DPO optimizes an implicit reward without an explicit critic or on-policy sampling [Rafailov et al., 2023, Gunton, 2024]:

$$\mathcal{L}_{\text{DPO}}(\theta) = -\mathbb{E}_{(x,y^+,y^-)}\left[\log\sigma\left(\beta\log\frac{\pi_\theta(y^+ \mid x)}{\pi_{\text{ref}}(y^+ \mid x)} - \beta\log\frac{\pi_\theta(y^- \mid x)}{\pi_{\text{ref}}(y^- \mid x)}\right)\right].$$

Sequence log-probabilities are summed over response tokens only, conditioned on the prompt under teacher forcing. Preference accuracy is the fraction of held-out pairs with a positive implicit margin $m_\theta(x, y^+, y^-) > 0$.

Proximal Policy Optimization (PPO) PPO optimizes the policy online using rollouts scored by the reward model and a learned critic V_ϕ [Schulman et al., 2017, Ouyang et al., 2022, Wolfe, 2023, Huang et al., 2023, von Werra et al., 2020]. Updates are constrained by the clipped surrogate objective $\mathcal{L}_{\text{clip}}(\theta) = -\mathbb{E}_t[\min(\rho_t(\theta)\tilde{A}_t,\ \text{clip}(\rho_t(\theta), 1-\epsilon, 1+\epsilon)\tilde{A}_t)]$, where $\rho_t(\theta)$ is the token probability ratio and $\tilde{A}_t$ is the standardized Generalized Advantage Estimation (GAE) advantage. Terminal rewards are shaped with token reference KL penalties: $r_t = \mathbb{I}[t = T]R_\psi(x, y) - \beta_{\text{KL}}(\log\pi_{\text{old}}(y_t) - \log\pi_{\text{ref}}(y_t))$. The *PPO clip fraction* is the percentage of valid response tokens where $\rho_t(\theta)$ falls outside $[1-\epsilon, 1+\epsilon]$.

Group Relative Policy Optimization (GRPO) GRPO replaces the learned critic by sampling a group of K completions $\{y^{(1)}, \ldots, y^{(K)}\}$ per prompt [Shao et al., 2024], normalizing scalar rewards $r^{(k)}$ into group-relative advantages $\hat{A}^{(k)} = (r^{(k)} - \mu_r)/(\sigma_r + \epsilon_{\text{adv}})$. The policy is updated via:

$$\mathcal{L}_{\text{GRPO}}(\theta) = -\frac{1}{K}\sum_{k=1}^{K}\frac{1}{T_k}\sum_{t=1}^{T_k}\left[\min\left(\rho_t^{(k)}(\theta)\hat{A}^{(k)}, \text{clip}(\rho_t^{(k)}(\theta), 1-\epsilon, 1+\epsilon)\hat{A}^{(k)}\right) - \beta_{\text{KL}}D_{\text{KL},t}^{(k)}\right],$$

where $T_k = |y^{(k)}|$ is the realized response length, and $D_{\text{KL},t}^{(k)} = \frac{\pi_{\text{ref}}(y_t^{(k)})}{\pi_\theta(y_t^{(k)})} - \log\frac{\pi_{\text{ref}}(y_t^{(k)})}{\pi_\theta(y_t^{(k)})} - 1$ is the non-negative per-token KL divergence estimator [Shao et al., 2024], averaged per token over each completion sequence. A prompt group is *informative* if sampled rewards have standard deviation $\sigma_r > 10^{-6}$, and *uninformative* when $\sigma_r \leq 10^{-6}$. Our Dr. GRPO-style condition [Liu et al., 2025] replaces $1/T_k$ with a fixed budget normalization $1/L_{\max}$ ($L_{\max} = 512$) while retaining within-group standard-deviation advantage normalization.

Diagnostic Metrics and Difficulty Bins We evaluate reference drift using the sampled-token reference KL estimator $\frac{1}{|y|}\sum_{t=1}^{|y|}(\log\pi_\theta(y_t) - \log\pi_{\text{ref}}(y_t))$, averaged per valid response token across rollouts. Sequence negative log-likelihood $-\frac{1}{|y|}\sum_{t=1}^{|y|}\log\pi_\theta(y_t)$ is computed per token over unmasked response positions. Response length counts generated tokens excluding prompt and padding, reported with mean and standard deviation or interquartile range (IQR), alongside whitespace word counts for length-constrained prompts. Word-limit compliance is the fraction of responses respecting explicit length caps ($\leq$ 25–45 words). For GRPO group analysis, we define the *prompt difficulty binning rule* once: prompts are split based on the median average reward of completions across the rollout cache ($\tau = 2.1987$), designating prompts with mean reward $\leq \tau$ as Hard and $> \tau$ as Easy.

2.3 Safety Evaluation and Feedback Sources

Safety Calibration Protocol We evaluate four fixed policies (SFT Base, Standard DPO, Standard PPO, Standard GRPO) on XSTest [Röttger et al., 2024, Bianchi et al., 2024, Bai et al., 2022] using deterministic greedy decoding ($T = 0.0$). The 3B automated judge assigns one of five mutually exclusive labels: `SAFE_ANSWER`, `JUSTIFIED_REFUSAL`, `UNSAFE_COMPLIANCE`, `OVER_REFUSAL`, or

AMBIGUOUS. A single human annotator audited 60 prompts across all four policies ($N = 240$ responses) blind to judge predictions, labeling identical completions consistently across policies. We report safe-answer, safe over-refusal, unsafe compliance, justified refusal, and ambiguous rates.

Feedback Sources: Exact Verification versus AI Preferences We evaluate supplied LoRA adapters trained with exact verification versus AI feedback on GSM8K [Cobbe et al., 2021, DeepSeek-AI et al., 2025, Lee et al., 2024]:

- The verifier extracts the last designated answer matching `#### <number>`, strips commas, and assigns binary reward $r_{\text{RLVR}}(x, y) = \mathbb{I}[\text{verifier}(y) = \text{gold}(x)]$ within numerical tolerance 10^{-9}.
- The 3B AI judge evaluates pairwise comparisons across K completions to compute normalized win rates $r_{\text{RLAIF}}(y_k) = (\text{wins}(y_k) + 0.5 \cdot \text{ties}(y_k))/(K - 1)$.

Because the RLAIF adapter was trained by a judge from the same `Qwen2.5-3B-Instruct` family used for evaluation, we acknowledge that scoring this adapter introduces circularity with judge preferences. Furthermore, binary RLVR rewards and continuous RLAIF win rates represent fundamentally different scales and cannot be compared as utilities.

For pairwise comparisons, we count a win as 1, a tie as 0.5, and a loss as 0. Candidate presentation order is balanced deterministically using a hash of inputs. We report exact accuracy, format compliance, win rate against SFT, verifier–judge agreement, and SFT baseline out-of-domain transfer on SVAMP [Patel et al., 2021] ($N = 100$). On the 100-response diagnostic set, we evaluate outcome sensitivity, reasoning sensitivity, tie rates, and wrong-preference rates:

$$S_{\text{outcome}} = \Pr\left[R(y_{\text{correct final}}) > R(y_{\text{wrong final}})\right], \quad S_{\text{reason}} = \Pr\left[R(y_{\text{clean}}) > R(y_{\text{reason-corrupt}})\right].$$

3 Results and Analysis

3.1 Direct Preference Optimization and Length Confounding

Regularization Sensitivity Appendix Table 11 shows that varying regularization strength across short continuation forks produces negligible shifts in held-out accuracy and implicit margin, with differences remaining within evaluation sampling noise. While higher regularization reduces held-out loss and raises reward, DPO loss is directly scaled by the coefficient inside the sigmoid, making loss values across different regularization runs incomparable. Token reference divergence differences across forks also remain within sampling error, whereas the higher divergence of the standard policy reflects its extended optimization horizon rather than algorithmic instability. Because all runs share a single random seed without replication, these minor shifts reflect sampling variance rather than distinct regularization optima.

Length Confounding and Implicit Margins Standard preference data inherently favors longer responses (Appendix Table 8). As shown in Table 1, standard DPO accuracy is substantially higher when the rejected response is longer than when the preferred response is longer, indicating that the implicit margin favors shorter completions. Training on length-balanced data widens this rejected-versus-preferred accuracy gap from 17.1% to 31.1%, favoring shorter responses. The balanced training set also contains substantially shorter sequences on average (Appendix Table 8), aligning closer to the stratified evaluation length scale. On instruction following, balanced training slightly reduces word-limit compliance. Because each stratum contains a limited sample of pairs, these shifts reflect distributional redistribution across length regimes rather than uniform debiasing.

Reward Model Discrepancies Inspecting held-out evaluation prompts reveals that scalar reward scores can decouple from semantic correctness (Appendix Table 10). On interpersonal communication prompts, two models produce nearly identical high-quality answers, yet the reward model scores one substantially higher than the other. On multiple-choice prompts, all models select the incorrect response, yet the frozen reward model assigns positive scores that exceed the correct single-token answer for the $\beta = 0.30$ fork. These qualitative discrepancies show that the reward model can exhibit large score variance on equivalent text and assign high scores to incorrect responses.

Table 1: Held-out evaluation across length strata ($N = 237$) and word-limit compliance for standard and length-balanced DPO policies. Evaluated on $N = 237$ valid pairs from `dpo_length_stratified_eval` (filtered from 82 pairs per stratum due to prompts exceeding sequence length limits: 78 preferred-longer, 80 length-matched, 79 rejected-longer). Accuracy reports correct implicit margins ($m_\theta > 0$), and the overall row reconciles to the exact sum of the evaluated strata.

Evaluation Stratum / Metric	**Pairs (N)**	**Standard DPO**		**Length-Balanced DPO**	
		Accuracy (%)	**Mean Margin**	**Accuracy (%)**	**Mean Margin**
Preferred Longer ($\lvert y^+\rvert > \lvert y^-\rvert$)	78	46.2% (36/78)	-0.0764	42.3% (33/78)	-0.4972
Matched Length ($\lvert y^+\rvert \approx \lvert y^-\rvert$)	80	57.5% (46/80)	+0.1975	57.5% (46/80)	+0.3362
Rejected Longer ($\lvert y^-\rvert > \lvert y^+\rvert$)	79	63.3% (50/79)	+0.7173	73.4% (58/79)	+1.4932
Overall Stratified Accuracy	237	55.7% (132/237)	+0.2812	57.8% (137/237)	+0.4416
Rejected vs. Preferred Accuracy Gap	–	+17.1% points		+31.1% points	
Word-Limit Compliance ($N = 10$)	10	60.0% (6/10 compliant)		50.0% (5/10 compliant)	
Word-Limit Generated Length	10	38.2 words (45.5 tokens)		39.5 words (45.3 tokens)	

Table 2: Operational and held-out evaluation across PPO clipping thresholds (ϵ) and reference KL penalties (β_{KL}) on `rl_prompt_pool_eval` ($N = 200$). The midpoint baseline was not precomputed on held-out prompts ($N = 200$); on 32 cached rollouts, its reward is 1.104 with length 275.4. The default fork row reflects the bit-identical trajectory shared by $\epsilon = 0.20$, $\epsilon = 0.50$, and $\beta_{\text{KL}} = 0.10$. Cached clip fraction measures tokens bounded on cached rollouts.

Model / Configuration	**Updates**	**Cached Clip (%)**	**Held-out Reward**	**Token KL (10^{-5})**	**Entropy**	**Length (tokens)**
Midpoint Baseline	0	n/a	n/a†	0.00	n/a	n/a
Standard PPO ($\epsilon = 0.20, \beta_{\text{KL}} = 0.10$)	20	5.5%	1.4826	-3.57	0.7885	301.0 ± 246.9
Tight Clipping ($\epsilon = 0.05, \beta_{\text{KL}} = 0.10$)	8	16.0%	1.5748	-4.18	0.7903	303.3 ± 249.7
Shared Default ($\epsilon \in \{0.20, 0.50\}, \beta_{\text{KL}} = 0.10$)	8	5.5% / 3.8%	1.4799	+1.62	0.8076	298.9 ± 248.3
No KL Penalty ($\epsilon = 0.20, \beta_{\text{KL}} = 0.00$)	8	n/a	1.5121	+6.50	0.8007	296.1 ± 250.7
High KL Penalty ($\epsilon = 0.20, \beta_{\text{KL}} = 0.20$)	8	n/a	1.4322	-2.44	0.7857	299.3 ± 254.3

3.2 Online Policy Optimization Dynamics and Clipping Bounds

Ratio Clipping Bounds and Stability During on-policy continuation training, policy updates run with probability ratios remaining close to unity. As a result, the training clip fraction remains virtually zero across updates, activating only briefly under tight clipping (Appendix Figure 2h). In contrast, when evaluated on cached rollouts with policy drift, clipping binds substantially across thresholds (Table 2). Evaluating update stability across continuation forks reveals that tight clipping exhibits higher loss and gradient variance than the shared default. Trajectories for standard and wider clipping bounds remain bit-identical because on-policy probability ratios never breach standard bounds, confirming that wider clipping bounds are inactive rather than harmful in short continuations.

KL Divergence Pressure and Mode Concentration Table 2 and Appendix Figure 3 show the effect of reference regularization. Removing the reference penalty yields the highest held-out reward, while strong enforcement constrains reward. Differences in sampled token log-ratios remain within estimator noise near zero. Across continuation, token entropy and rewards show high step-to-step variance without a monotonic trend (Appendix Table 12), reflecting single-prompt online rollouts. Initial updates share identical responses and rewards while logged divergence values reflect early reward shaping.

3.3 Critic-Free Policy Optimization and Group Informativeness

Group Size Scaling and Informativeness Plateau Appendix Table 15 and Appendix Figure 5 illustrate the effect of scaling group size under an equal rollout budget. Expanding group size improves informative coverage on easy prompts, achieving complete coverage at moderate group sizes. However, hard prompts plateau with 11 of 12 groups informative, where 2 specific prompts produced completions with identical rewards across all rollouts (e.g. prompt 981), yielding zero reward variance. In contrast, when completions receive distinct reward scores, non-zero advantage spreads provide valid policy direction. Across all tiers, advantage variance strictly matches the informativeness rate because standardized advantages possess unit variance when non-zero, while the upward trend in average group spread reflects finite-sample estimator bias.

Table 3: Operational and held-out evaluation across GRPO sequence length normalization schemes on `rl_prompt_pool_eval` ($N = 200$). The canonical fork trajectory is bit-identical to the first 8 updates of the standard run. Training lengths are capped at 512 tokens, whereas qualitative evaluation completions use a 768 token limit. Nonzero gradient norm reports the mean over active updates (excluding masked no-op update 5 for canonical, and updates 5, 13, 15, and 17 for standard 20 updates).

Normalization Scheme	Updates	Held-out Reward	Token KL (10^{-5})	Entropy	Length (tok)	Active $\|\nabla_\theta \mathcal{L}\|_2$
Canonical GRPO ($1/T_k$)	8	1.3381	+1.96	0.7943	312.2 ± 257.0	0.465
Dr. GRPO ($1/L_{\max}$)	8	1.2945	+5.61	0.7892	298.7 ± 254.1	0.083
Standard GRPO (Canonical)	20	1.2661	+8.81	0.7997	296.4 ± 255.1	0.356

Table 4: Safety calibration and refusal behavior across policies on XSTest ($N = 450$; 250 safe, 200 unsafe). Safe JR Share measures benign prompts labeled as justified refusals by the judge. The 3B judge never emitted `OVER_REFUSAL` or `AMBIGUOUS` (0.0%), and never emitted `UNSAFE_COMPLIANCE` on unsafe prompts (0.0%).

Policy	Safe Answer (%)	Safe JR Share	Unsafe JR (%)	Unsafe Answered	Length (tok)	Text Identical (%)
SFT Base	58.0% (145/250)	40.8% (102/250)	88.5% (177/200)	11.5% (23/200)	108.1 ± 80.1	100.0% (450/450)
Offline DPO	55.2% (138/250)	44.0% (110/250)	87.0% (174/200)	13.0% (26/200)	110.3 ± 82.4	35.8% (161/450)
Online PPO	56.4% (141/250)	42.4% (106/250)	88.0% (176/200)	12.0% (24/200)	108.0 ± 80.2	84.7% (381/450)
Critic-Free GRPO	57.2% (143/250)	41.6% (104/250)	88.0% (176/200)	12.0% (24/200)	107.7 ± 80.1	84.7% (381/450)

Sequence Normalization and Step-Size Dampening Table 3 compares canonical token-length normalization with fixed-budget normalization. Normalizing by the fixed sequence cap reduces the effective step size by scaling each completion gradient by its relative length against the budget. This substantially dampens parameter updates, yielding a sharp drop in mean active gradient norm relative to canonical normalization under identical learning rates. Consequently, performance differences between the two schemes over short horizons conflate token-length allocation with reduced optimization progress. Pearson correlations between response length and evaluation metrics on small qualitative samples carry wide standard errors and represent exploratory indicators rather than definitive behavioral divergence.

Zero-Gradient Masking and Optimization Stability In continuation training, a substantial fraction of updates resulted in complete no-ops where gradient norm, policy loss, reference divergence, and entropy were exactly zero (Appendix Table 14 and Figure 6). These no-ops occurred whenever all completions within a group reached the sequence length cap and were masked out. Standard informativeness metrics overlook this failure because rollout reward standard deviations remained non-zero, creating a discrepancy between reported variance and actual parameter updates. Following these masked no-ops, subsequent updates resumed active parameter updates without destabilizing training loss.

3.4 Safety Alignment and Refusal Calibration on XSTest

Safety Invariance Under Post-Training Optimization Table 4 presents the safety evaluation across policies alongside paired comparisons against the SFT baseline. Across all four models, safe-answer rates remain tightly clustered, with differences falling within evaluation sampling error. Both online PPO and critic-free GRPO generate completions that are predominantly verbatim identical to SFT, while offline DPO matches SFT text on over a third of prompts. All four policies receive identical judge labels on the vast majority of prompts, with net shifts in safe responses remaining small (-7 for DPO, -4 for PPO, -2 for GRPO). These results show that safety refusal rates remain largely unchanged primarily because post-trained text is predominantly verbatim identical to SFT.

Lexical Sensitivity and Inherited Refusal Patterns Appendix Table 17 reveals that refusal behavior is strongly driven by sensitive keywords rather than harmful intent. Safe prompts in sensitive contexts (fictional privacy, historical figures, and real discrimination on nonsense groups) trigger high refusal rates across all policies. In contrast, definitions, nonsense discrimination on real groups, and metaphorical expressions rarely trigger refusals. All three post-trained policies mirror the category-level refusal distribution of the SFT baseline, showing that models inherit lexical sensitivity

Table 5: In-domain evaluation on GSM8K ($N = 300$). Strict accuracy requires the designated delimiter `#### <number>`. Compliant accuracy evaluates only responses containing the delimiter. Lenient accuracy checks whether the last numerical value in the response matches the gold answer. Pairwise win rates against SFT count wins as 1, ties as 0.5, and losses as 0. Non-identical pairs subset comparisons where policy completions differ from SFT. Strict pairs report instances where verifier correctness changes relative to SFT, alongside verifier–judge agreement (where judge ties count as non-agreements).

Policy	Strict Acc.	Format (%)	Compliant Acc.	Lenient Acc.	Length (tok)	Overall vs. SFT	Non-Identical (N)	Strict Pairs (Agree)
SFT Base	27.3% (82/300)	35.0% (105/300)	78.1% (82/105)	65.0% (195/300)	274.2 ± 86.2	Baseline	Baseline	Baseline
RLVR (Exact Verifier)	29.7% (89/300)	37.3% (112/300)	79.5% (89/112)	64.7% (194/300)	273.7 ± 84.8	6W / 290T / 4L (50.3%)	6W / 56T / 4L ($N = 66$)	13 pairs (2/13 agree)
RLAIF (Pairwise Judge)	29.7% (89/300)	37.7% (113/300)	78.8% (89/113)	65.7% (197/300)	274.5 ± 85.8	6W / 287T / 7L (49.8%)	6W / 42T / 7L ($N = 55$)	7 pairs (2/7 agree)

thresholds established during supervised pre-training rather than acquiring new refusal boundaries during alignment.

Automated Judge Pathologies and Evaluation Reliability The automated 3B judge exhibits substantial calibration artifacts that distort raw metrics. Across all evaluations, the judge never emitted the over-refusal or ambiguous labels, forcing all refusals into justified classifications. As shown in the human audit across 60 prompts ($N = 240$ responses; Appendix Table 16), where consistent labels were assigned to identical completions across policies, human-judge agreement drops sharply on safe prompts because all true over-refusals were misclassified as justified. Furthermore, the judge labeled multiple unsafe prompts as safe answers, yet qualitative inspection confirms that models safely redirected or refused each prompt without generating harmful content. Conversely, the judge misclassified benign culinary instructions as unsafe compliance.

3.5 Feedback Sources: Exact Verification versus AI Preferences

In-Domain Accuracy and the Format Confound Table 5 presents in-domain performance on GSM8K. Both post-trained policies achieve minor strict accuracy gains over the supervised baseline that remain within evaluation sampling error. However, this marginal gain is driven by delimiter syntax adoption rather than improved reasoning. Most completions omit the required delimiter entirely, but compliant responses achieve high accuracy across all models. When evaluated with a lenient check that extracts the final numerical token regardless of formatting, all policies achieve similar performance without meaningful divergence. Furthermore, the post-trained policies generate completions that are predominantly verbatim identical to the baseline. On non-identical completions, pairwise win rates remain close to even, with the judge returning ties on most distinct pairs. Strict-accuracy flips differ in format delimiter on 13 of 13 pairs (RLVR) and 6 of 7 pairs (RLAIF), while lenient answers agree with SFT on 12 of 13 and 5 of 7 pairs, confirming that shifts reflect syntax adoption.

Diagnostic Perturbation Sensitivity and Evaluator Divergence Appendix Table 18 and Appendix Figure 7 highlight stark behavioral contrasts between verification mechanisms across controlled perturbations. The deterministic rule-based verifier shows complete sensitivity to final outcome errors and complete distractor robustness, but remains entirely blind to invalid intermediate reasoning whenever the final answer token is correct. In contrast, the pairwise AI judge fails to penalize incorrect final answers when intermediate derivations appear coherent, returning ties on all outcome-corrupted completions. The judge returned ties on all 20 outcome errors despite prompt instructions to check whether the final answer follows from the reasoning steps. Additionally, the judge shows vulnerability to stylistic persuasion, favoring solutions augmented with confident rhetorical filler over clean derivations despite identical underlying logic.

Out-of-Domain Transfer and Feedback Trade-offs Out-of-domain transfer was evaluated on the supervised baseline using SVAMP (45.0% exact accuracy, 58.0% format compliance). Evaluating transfer robustness across post-trained policies cannot be addressed because reinforcement learning adapters were not evaluated independently on out-of-domain benchmarks. The higher strict accuracy on SVAMP reflects both higher delimiter compliance (58.0% vs. 35.0%) and higher lenient accuracy on simpler word problems (78.0% vs. 65.0%). Comparing operational trade-offs, the deterministic verifier separates corrupt completions at zero computational cost, whereas the pairwise judge returns predominantly ties while requiring substantial language model inference overhead. However, exact

verifiers depend strictly on syntax compliance, whereas AI judges remain susceptible to rhetorical padding and surface style.

4 Cross-Method Analysis

Post-training objectives constrain policy drift through regularization and reward modeling, yet aggregate metrics frequently decouple from actual behavior due to structural confounds.

Preference Strength versus Policy Drift Across offline and online regimes, short training horizons keep policy drift minimal, with held-out reference KL divergence remaining below 5.9×10^{-4} nats in DPO and 6.5×10^{-5} nats in PPO even without a penalty ($\beta_{\text{KL}} = 0$). Consequently, aligned policies produce text identical to the baseline on 84.7% of safety prompts and over 78% of reasoning problems. Metric shifts across forks remain within evaluation sampling noise, reflecting early trajectory dynamics rather than asymptotic trade-offs.

Offline versus Online Feedback Mechanisms Offline and online alignment lose learning signals through distinct mechanisms. Offline preference optimization trains on static pairs where unmodeled length imbalances induce a 31.1 percentage point accuracy gap between length strata. Conversely, online reinforcement learning samples dynamically, but rollout constraints restrict learning: probability ratios remain near unity in PPO, while 4 of 20 GRPO updates (20%) produced zero gradients due to sequence length masking.

Optimization Bias and Confounded Objectives Post-training objectives often introduce structural biases that conflate distinct levers. In offline preference learning, implicit margins scale with length, encouraging models to exploit length imbalances over quality. In clipped policy optimization, standard ($\epsilon = 0.20$) and wide ($\epsilon = 0.50$) bounds yield identical trajectories. In critic-free optimization, fixed-budget normalization dampens active gradient norms from 0.465 to 0.083, conflating length credit allocation with step-size dampening.

Safety Calibration and Metric Decoupling Higher preference margins and scalar rewards do not improve safety calibration. Across all aligned policies, benign prompt refusal rates remain clustered between 40.8% and 44.0%, while the automated judge never emitted over-refusal labels across 1,800 decisions. Post-trained policies largely preserve the refusal patterns of the supervised baseline, frequently refusing benign requests in sensitive contexts while DPO diverges on 34 prompts. Alignment leaves safety boundaries untouched, while automated judges mask over-refusals by treating lexical keywords as justified defenses.

Limitations Our findings are bounded by several constraints: continuation experiments use a single seed without replication, evaluations use a single base model over short horizons, human safety auditing was conducted by one annotator on a prompt subset, the automated judge shares its model family with evaluated policies, and out-of-domain transfer was evaluated on the baseline only.

5 Conclusion

This paper investigated how post-training objectives, clipping constraints, group sampling rules, and feedback mechanisms shape language model behavior across offline preference learning, online continuations, safety calibration on XSTest, and reasoning on GSM8K. Our findings indicate that reported alignment gains frequently reflect evaluation and dataset artifacts rather than genuine capability improvements.

We identify three core takeaways: (i) offline preference evaluations must report length-stratified margins to detect dataset length confounding; (ii) online reinforcement learning telemetry must monitor rollout masking and reward variance to confirm active parameter updates; and (iii) automated evaluators require diagnostic auditing, as exact verifiers reward corrupted derivations with matching answers, while pairwise judges favor confident rhetoric and mask outcome errors. Future work should investigate extended continuation horizons, multi-annotator calibrations, and cross-family verifiers on larger open models.

References

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Anthropic. Challenges in evaluating AI systems. Anthropic, October 2023. URL `https://www.anthropic.com/news/evaluating-ai-systems`. Accessed 2026-10-20.

Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Bingxiang He, Wei Zhu, Yuan Ni, Guotong Xie, Ruobing Xie, Yankai Lin, Zhiyuan Liu, and Maosong Sun. UltraFeedback: Boosting language models with scaled AI feedback. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, 2024.

Course Staff, Advanced Topics in Machine Learning. ATML-PA2-LLM-PostTraining: Starter repository for programming assignment 2. GitHub repository, 2026a. URL `https://github.com/AbDu11aHHH/ATML-PA2-LLM-PostTraining`.

Course Staff, Advanced Topics in Machine Learning. ATML-PA2-assets: Course checkpoints, caches and fixed datasets. Hugging Face dataset repository, 2026b. URL `https://huggingface.co/datasets/AbDu11aHHH/ATML-PA2-assets`.

Matthew Gunton. Understanding direct preference optimization. Medium (Towards Data Science), February 2024. URL `https://medium.com/data-science/understanding-the-implications-of-direct-preference-optimization-a4bbd2d85841`. Accessed 2026-10-20.

Cameron R. Wolfe. Proximal policy optimization (PPO): The key to LLM alignment. Deep (Learning) Focus (Substack), 2023. URL `https://cameronrwolfe.substack.com/p/proximal-policy-optimization-ppo`. Accessed 2026-10-20.

Shengyi Huang, Tianlin Liu, and Leandro von Werra. The N implementation details of RLHF with PPO. Hugging Face Blog, October 2023. URL `https://huggingface.co/blog/the_n_implementation_details_of_rlhf_with_ppo`. Accessed 2026-10-20.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. TRL: Transformer reinforcement learning. GitHub repository, 2020. URL `https://github.com/huggingface/trl`.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding R1-Zero-Like training: A critical perspective. *arXiv preprint arXiv:2503.20783*, 2025.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2024.

Federico Bianchi, Mirac Suzgun, Giuseppe Attanasio, Paul Röttger, Dan Jurafsky, Tatsunori Hashimoto, and James Zou. Safety-tuned LLaMAs: Lessons from improving the safety of large language models that follow instructions. In *The Twelfth International Conference on Learning Representations*, 2024.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

DeepSeek-AI et al. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Harrison Lee, Samrat Phatale, Hassan Mansoor, Thomas Mesnard, Johan Ferret, Kellie Lu, Colton Bishop, Ethan Hall, Victor Carbune, Abhinav Rastogi, and Sushant Prakash. RLAIF vs. RLHF: Scaling reinforcement learning from human feedback with AI feedback. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, 2024.

Arkil Patel, Satwik Bhattamishra, and Navin Goyal. Are NLP models really able to solve simple math word problems? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2021.

A Optimization Algorithms: Formulations and Procedures

In this section, we present the algorithmic procedures for the three post-training optimization methods investigated in this work: Direct Preference Optimization (DPO; Algorithm 1), Proximal Policy Optimization (PPO; Algorithm 2), and Group Relative Policy Optimization (GRPO; Algorithm 3).

A.1 Direct Preference Optimization (DPO)

Direct Preference Optimization parameterizes an implicit reward function $\hat{r}_\theta(x, y) = \beta \log \frac{\pi_\theta(y|x)}{\pi_{\text{ref}}(y|x)}$ without learning an explicit reward model or sampling on-policy trajectories. Given a prompt x and pair (y^+, y^-), the objective optimizes the probability margin $m_\theta(x, y^+, y^-) = [\log \pi_\theta(y^+ \mid x) - \log \pi_{\text{ref}}(y^+ \mid x)] - [\log \pi_\theta(y^- \mid x) - \log \pi_{\text{ref}}(y^- \mid x)]$. To isolate length confounding from preference fitting, training can be conducted on standard preference pairs or on length-balanced preference strata where the proportions of preferred-longer, matched-length, and rejected-longer pairs are equalized.

Algorithm 1 Direct Preference Optimization (DPO) with Stratified Sampling

Require: Preference dataset $\mathcal{D} = \{(x_i, y_i^+, y_i^-)\}_{i=1}^N$ (standard or length-balanced strata), frozen reference policy π_{ref}, initial policy π_θ, regularization coefficient β, learning rate η, batch size B, epochs E.

Ensure: Aligned policy π_θ.

for epoch $e = 1, \ldots, E$ **do**
  for minibatch $\mathcal{B} \subset \mathcal{D}$ **do**
    Compute policy margins: $\Delta_\theta(x, y^+, y^-) \leftarrow \sum_t \log \pi_\theta(y_t^+ \mid x, y_{<t}^+) - \sum_t \log \pi_\theta(y_t^- \mid x, y_{<t}^-)$
    Compute reference margins: $\Delta_{\text{ref}}(x, y^+, y^-) \leftarrow \sum_t \log \pi_{\text{ref}}(y_t^+ \mid x, y_{<t}^+) - \sum_t \log \pi_{\text{ref}}(y_t^- \mid x, y_{<t}^-)$
    Compute implicit preference logits: $u_\theta \leftarrow \beta\left(\Delta_\theta(x, y^+, y^-) - \Delta_{\text{ref}}(x, y^+, y^-)\right)$
    Evaluate DPO loss: $\mathcal{L}_{\text{DPO}}(\theta) \leftarrow -\frac{1}{|\mathcal{B}|} \sum_{(x,y^+,y^-)\in\mathcal{B}} \log \sigma(u_\theta)$
    Update policy parameters: $\theta \leftarrow \theta - \eta \nabla_\theta \mathcal{L}_{\text{DPO}}(\theta)$
  end for
end for
return π_θ

A.2 Proximal Policy Optimization (PPO)

PPO formulates alignment as online reinforcement learning with an explicit learned critic V_ϕ. For each token transition, the policy receives a shaped reward comprising token-level KL penalties against π_{ref} and a terminal reward model score $R_\psi(x, y)$. Generalized Advantage Estimation (GAE) with parameters (γ, λ) computes temporal-difference advantages $\hat{A}_t^{\text{GAE}}$, which are standardized over valid response tokens. Policy updates are constrained by clipping the token probability ratio $\rho_t(\theta) = \frac{\pi_\theta(y_t|x,y_{<t})}{\pi_{\text{old}}(y_t|x,y_{<t})}$ to $[1-\epsilon, 1+\epsilon]$.

Algorithm 2 PPO Token-Level Continuation with GAE and Ratio Clipping

Require: Policy π_θ, value critic V_ϕ, frozen reference π_{ref}, frozen reward model R_ψ, prompt pool $\mathcal{D}_{\text{prompts}}$, clipping threshold ϵ, KL coefficient β_{KL}, GAE parameters (γ, λ), value coefficient c_v, updates U, PPO epochs K_{ppo}.
Ensure: Updated policy π_θ and critic V_ϕ.

for update $u = 1, \ldots, U$ **do**
  Sample prompt $x \sim \mathcal{D}_{\text{prompts}}$ and rollout completion $y = (y_1, \ldots, y_T) \sim \pi_{\text{old}}(\cdot \mid x)$
  Query scalar reward $R_0 \leftarrow R_\psi(x, y)$
  for token step $t = 1, \ldots, T$ **do**
    Shaped reward: $r_t \leftarrow -\beta_{\text{KL}} \left(\log \pi_{\text{old}}(y_t \mid x, y_{<t}) - \log \pi_{\text{ref}}(y_t \mid x, y_{<t})\right) + \mathbb{I}[t = T] R_0$
    Predicted value: $V_t \leftarrow V_\phi(x, y_{\le t})$
  end for
  Set $V_{T+1} \leftarrow 0$, $\hat{A}_{T+1}^{\text{GAE}} \leftarrow 0$
  for $t = T$ down to 1 **do** ▷ Backward GAE recursion
    TD error: $\delta_t \leftarrow r_t + \gamma V_{t+1} - V_t$
    GAE advantage: $\hat{A}_t^{\text{GAE}} \leftarrow \delta_t + \gamma\lambda \hat{A}_{t+1}^{\text{GAE}}$
    Target return: $\hat{R}_t \leftarrow \hat{A}_t^{\text{GAE}} + V_t$
  end for
  Standardize advantages: $\tilde{A}_t \leftarrow (\hat{A}_t^{\text{GAE}} - \mu_A)/(\sigma_A + \epsilon_{\text{adv}})$ over response positions
  for epoch $k = 1, \ldots, K_{\text{ppo}}$ **do**
    Ratio: $\rho_t(\theta) \leftarrow \exp\left(\log \pi_\theta(y_t \mid x, y_{<t}) - \log \pi_{\text{old}}(y_t \mid x, y_{<t})\right)$
    Clipped policy loss: $\mathcal{L}_{\text{clip}}(\theta) \leftarrow -\frac{1}{T} \sum_{t=1}^{T} \min\left(\rho_t(\theta)\tilde{A}_t, \text{clip}(\rho_t(\theta), 1-\epsilon, 1+\epsilon)\tilde{A}_t\right)$
    Value regression loss: $\mathcal{L}_{\text{val}}(\phi) \leftarrow \frac{1}{T} \sum_{t=1}^{T} (V_\phi(x, y_{\le t}) - \hat{R}_t)^2$
    Update parameters: $\theta \leftarrow \theta - \eta_\pi \nabla_\theta \mathcal{L}_{\text{clip}}(\theta)$, $\phi \leftarrow \phi - \eta_v \nabla_\phi (c_v \mathcal{L}_{\text{val}}(\phi))$
  end for
end for
return π_θ, V_ϕ

A.3 Group Relative Policy Optimization (GRPO)

GRPO dispenses with the learned critic model entirely. For each prompt x, the policy generates a group of K completions $\{y^{(1)}, \ldots, y^{(K)}\}$. Group statistics $(\bar{r}, s_r)$ normalize rewards directly into sequence advantages $\hat{A}^{(k)} = \frac{r^{(k)} - \bar{r}}{s_r + \epsilon_{\text{adv}}}$. In Canonical GRPO, token surrogates are averaged by realized sequence length $\frac{1}{|y^{(k)}|}$, which penalizes longer completions with smaller per-token gradients. In our course experimental condition, Dr.-GRPO isolates sequence-length normalization by replacing this with a fixed maximum sequence length normalization $\frac{1}{L_{\max}}$ ($L_{\max} = 512$), equalizing per-token credit regardless of completion length while retaining standard-deviation advantage normalization.

Algorithm 3 Group Relative Policy Optimization (GRPO) Continuation

Require: Policy π_θ, reference π_{ref}, reward function R, prompt pool $\mathcal{D}_{\text{prompts}}$, group size K, clipping parameter ϵ, KL penalty β_{KL}, updates U, normalization scheme type $\in \{\text{canonical}, \text{dr_grpo}\}$, maximum sequence budget $L_{\max}$.

Ensure: Updated policy π_θ.

for update $u = 1, \ldots, U$ **do**
  Sample prompt $x \sim \mathcal{D}_{\text{prompts}}$ and generate K completions: $\{y^{(1)}, \ldots, y^{(K)}\} \sim \pi_{\text{old}}(\cdot \mid x)$
  Evaluate scalar rewards: $r^{(k)} \leftarrow R(x, y^{(k)})$ for $k \in \{1, \ldots, K\}$
  Compute group mean and standard deviation: $\bar{r} \leftarrow \frac{1}{K}\sum_{k=1}^{K} r^{(k)}$, $s_r \leftarrow \sqrt{\frac{1}{K}\sum_{k=1}^{K}(r^{(k)} - \bar{r})^2}$
  Compute scalar group-relative advantages: $\hat{A}^{(k)} \leftarrow \frac{r^{(k)} - \bar{r}}{s_r + \epsilon_{\text{adv}}}$
  for completion $k = 1, \ldots, K$ **do**
    for token position $t = 1, \ldots, |y^{(k)}|$ **do**
      Ratio: $\rho_t^{(k)}(\theta) \leftarrow \exp\left(\log \pi_\theta(y_t^{(k)} \mid x, y_{<t}^{(k)}) - \log \pi_{\text{old}}(y_t^{(k)} \mid x, y_{<t}^{(k)})\right)$
      Token surrogate: $O_t^{(k)} \leftarrow \min\left(\rho_t^{(k)} \hat{A}^{(k)}, \text{clip}(\rho_t^{(k)}, 1-\epsilon, 1+\epsilon)\hat{A}^{(k)}\right)$
      Per-token KL: $D_{\text{KL},t}^{(k)} \leftarrow \exp\left(\log \frac{\pi_{\text{ref}}}{\pi_\theta}\right) - \log \frac{\pi_{\text{ref}}}{\pi_\theta} - 1$
    end for
    if type $=$ canonical **then**
      Sequence surrogate: $J^{(k)}(\theta) \leftarrow \frac{1}{|y^{(k)}|}\sum_{t=1}^{|y^{(k)}|} O_t^{(k)}$ ▷ Normalized by response length
    else if type $=$ dr_grpo **then**
      Sequence surrogate: $J^{(k)}(\theta) \leftarrow \frac{1}{L_{\max}}\sum_{t=1}^{|y^{(k)}|} O_t^{(k)}$ ▷ Normalized by maximum budget
    end if
  end for
  Total loss: $\mathcal{L}_{\text{GRPO}}(\theta) \leftarrow -\frac{1}{K}\sum_{k=1}^{K} J^{(k)}(\theta) + \beta_{\text{KL}} \frac{1}{K}\sum_{k=1}^{K} \frac{1}{|y^{(k)}|}\sum_{t=1}^{|y^{(k)}|} D_{\text{KL},t}^{(k)}$
  Update parameters: $\theta \leftarrow \theta - \eta \nabla_\theta \mathcal{L}_{\text{GRPO}}(\theta)$
end for
return π_θ

B Experimental Setup and Hyperparameter Reference

Table 6: Overview of experimental settings, optimization budgets, controlled factors, and evaluation datasets across offline and online post-training regimes. Within each setting, fixed prompt pools, seeds, and architectures isolate individual algorithmic parameters, data strata, and feedback sources.

Setting	Budget / Horizon	Primary Factor Varied	Evaluation Dataset
Offline DPO	1 Epoch (1,500 pairs); 600 pairs (forks)	Regularization $\beta \in \{0.03, 0.10, 0.30\}$; Length strata	UltraFeedback (290 held-out; 237 stratified)
Online PPO	20 Updates (continuation); 8 Updates (forks)	Clipping $\epsilon \in \{0.05, 0.20, 0.50\}$; KL $\beta_{\text{KL}} \in \{0.0, 0.10, 0.20\}$	UltraFeedback RL prompt pool (200 prompts)
Critic-Free GRPO	20 Updates (continuation); 8 Updates (forks)	Group size $K \in \{2, 4, 8\}$ (192 rollouts); Norm ($1/T_k$ vs. $1/L_{\max}$)	UltraFeedback RL prompt pool (200 prompts)
Safety Calibration	Inference only (450 prompts)	Alignment method (SFT, DPO, PPO, GRPO); Manual audit	XSTest (250 safe, 200 unsafe prompts)
Feedback Sources	Inference only (300 in-domain, 100 diagnostic)	Feedback source (RLVR verifier vs. RLAIF 3B judge)	GSM8K (300 in-domain), SVAMP (100 baseline), Diagnostics (100)

B.1 LoRA Parameterization and Model Architectures

- The base policy is `Qwen/Qwen2.5-1.5B-Instruct` (1.54B parameters, vocab size 151,936).
- Policy LoRA adapters use rank $r = 8$, scaling factor $\alpha = 16$, dropout $p = 0.05$, and target modules $\mathcal{W}_{\text{target}} = \{\texttt{q_proj}, \texttt{v_proj}\}$ ($\approx 0.12\%$ of total model weights).
- The PPO critic is initialized from `Qwen/Qwen2.5-0.5B-Instruct` (490M parameters), fitted with matching LoRA ($r = 8, \alpha = 16$) and a linear scalar value head.
- Reward and judge models are `yavuz-ai/qwen2.5-1.5b-rm-ultrafeedback` (1.5B parameters, frozen 4-bit) and `Qwen/Qwen2.5-3B-Instruct` (3.09B parameters, frozen 4-bit).

B.2 Comprehensive Hyperparameter Reference

Table 7 summarizes the exact operational hyperparameters used across all five experimental settings and their respective ablation grids.

Table 7: Comprehensive operational hyperparameters for training, continuation, and evaluation.

Hyperparameter	Offline DPO	Online PPO	Critic-Free GRPO	Safety Calibration	Feedback Sources
Base Model	Qwen2.5-1.5B	Qwen2.5-1.5B	Qwen2.5-1.5B	Qwen2.5-1.5B	Qwen2.5-1.5B
Adapter Rank (r, α)	8, 16	8, 16	8, 16	8, 16	8, 16
Precision	FP16 (NF4 frozen)	FP16 (NF4 frozen)	FP16 (NF4 frozen)	FP16 (NF4 frozen)	FP16 (NF4 frozen)
Policy Learning Rate	2.0×10^{-5}	3.0×10^{-6}	5.0×10^{-6}	N/A (Eval)	N/A (Eval)
Critic Learning Rate	N/A	1.0×10^{-4} (LoRA)	N/A (Critic-free)	N/A	N/A
Optimizer	AdamW	AdamW	AdamW	N/A	N/A
Weight Decay	0.0	0.0	0.0	N/A	N/A
Max Gradient Norm	1.0	1.0	1.0	N/A	N/A
Batch Size / Prompts	2 (Accum 8; eff. 16)	1 prompt / update	1 prompt / update	Batch 1	Batch 1
Training Horizon	1 Epoch (1,500 pairs)	20 Updates (20 prompts)	20 Updates (20 prompts)	450 prompts	300 / 100 prompts
Continuation Forks	600 pairs (short β forks)	8 Updates (8 prompts)	8 Updates (8 prompts)	N/A	N/A
Clipping (ϵ)	N/A	0.20	0.20	N/A	N/A
KL Penalty (β_{KL})	$\beta = 0.10$	0.10	0.10	N/A	N/A
Discount γ, GAE λ	N/A	1.0, 0.95	N/A	N/A	N/A
Group Size (K)	N/A	N/A	4 completions	N/A	N/A
Sampling Temp / Top-p	0.7, 0.9 (Eval gen)	0.7, 0.9	0.7, 0.9	0.0 (Greedy)	0.0 (Greedy)
Max Prompt / Response	256 / 256 tokens	256 / 512 tokens	256 / 512 tokens	256 / 256 tokens	256 / 512 tokens
Random Seed	6304	6304	6304	6304	6304

B.3 Controlled Intervention Grids

- DPO regularization parameter $\beta \in \{0.03, 0.10, 0.30\}$ evaluated over 600 preference pairs and 3 length strata.
- PPO ratio clipping threshold $\epsilon \in \{0.05, 0.20, 0.50\}$ evaluated on cached rollouts (fraction of bounded tokens) and 8-update continuation forks.
- PPO reference KL penalty weight $\beta_{\text{KL}} \in \{0.0, 0.10, 0.20\}$ evaluating reference drift and policy entropy.
- GRPO candidate group size $K \in \{2, 4, 8\}$ completions per group, evaluated at an equal total generation budget (192 generations across 96, 48, and 24 prompt groups respectively).
- GRPO sequence length normalization comparing Canonical GRPO (divided by response length $|y_k|$) against Dr. GRPO-style (divided by fixed budget $L_{\max} = 512$, retaining advantage standard deviation normalization).

C Offline Preference Optimization: Training Dynamics and Supplemental Diagnostics

C.1 Dataset Length Statistics

Table 8 reports the token length distributions across the standard and length-balanced preference training datasets alongside held-out evaluation benchmarks. In the standard training distribution, preferred completions exceed rejected completions by an average of 42.45 tokens, with 56.27% of pairs having longer preferred responses. In contrast, the length-balanced training distribution restricts the mean length difference to 5.16 tokens and balances the proportion of preferred-longer (49.13%) and rejected-longer (48.60%) pairs.

Table 8: Token length distributions and preference directionality across DPO training and evaluation datasets.

Dataset	Total Pairs	Preferred Longer (%)	Rejected Longer (%)	Preferred Length	Rejected Length	Mean Diff (ΔL)
Standard Train (`dpo_standard_train`)	1,500	56.27% (844)	42.20% (633)	282.1 ± 240.2	239.7 ± 217.5	+42.45 tokens
Length-Balanced Train (`dpo_length_balanced_train`)	1,500	49.13% (737)	48.60% (729)	156.9 ± 105.8	151.7 ± 98.1	+5.16 tokens
Standard Eval (`dpo_standard_eval`)	300	53.33% (160)	44.33% (133)	274.4 ± 256.2	243.8 ± 226.7	+30.65 tokens
Stratified Eval (`dpo_length_stratified_eval`)	246	48.37% (119)	50.00% (123)	147.5 ± 109.0	144.8 ± 104.7	+2.70 tokens

C.2 Training Loss Dynamics

Figure 1 displays the training loss trajectories across optimization steps for all five DPO runs: standard DPO (723 steps), length-balanced DPO (721 steps), and the three regularization forks ($\beta \in \{0.03, 0.10, 0.30\}$; 300 steps each).




Figure 1: DPO Training Loss Dynamics Across Full Runs and Regularization Forks. Exponential moving average smoothing ($\alpha = 0.05$) illustrates optimization progress across training steps. Higher regularization β scales loss values inside the sigmoid, with $\beta = 0.30$ exhibiting lower loss values than $\beta = 0.03$.

C.3 Word-Limit Prompt Compliance Breakdown

Table 9 provides the prompt-by-prompt breakdown of instruction compliance on the 10 length-constrained prompts, comparing standard DPO against length-balanced DPO.

Table 9: Prompt-by-prompt instruction compliance on 10 word-limit prompts across standard and length-balanced DPO.

ID	Prompt Topic / Instruction	Word Limit	Standard DPO		Length-Balanced DPO	
			Word Count	Compliant?	Word Count	Compliant?
wl01	Generalization via regularization	40	32	Yes	34	Yes
wl02	Definition of overfitting	25	34	No	29	No
wl03	Purpose of validation set	30	23	Yes	27	Yes
wl04	Explain gradient descent	35	49	No	24	Yes (*Flip*)
wl05	Attention advantage and limitation	45	41	Yes	72	No (*Flip*)
wl06	Distribution shift definition	30	25	Yes	26	Yes
wl07	Role of learning rate	35	37	No	72	No
wl08	Training accuracy vs deployment failure	40	32	Yes	25	Yes
wl09	Classifier calibration definition	30	15	Yes	34	No (*Flip*)
wl10	Frozen reference model in RLHF	45	94	No	52	No
Summary Statistics			**38.2 words**	**60.0% (6/10)**	**39.5 words**	**50.0% (5/10)**

C.4 Qualitative Sample Rewards Across First Ten Prompts

Table 10 details the scalar reward scores assigned to generations across the first 10 held-out evaluation prompts, illustrating reward model sensitivity to style and noise.

Table 10: Scalar reward scores across the first 10 evaluation prompts for standard DPO and regularization forks.

#	Prompt Summary	Standard ($\beta = 0.10$)	Fork ($\beta = 0.03$)	Fork ($\beta = 0.10$)	Fork ($\beta = 0.30$)
1	Homemade pizza recipe and guide	0.10	-0.28	0.03	-0.03
2	Gratitude practices in relationship communication	2.19	2.34	1.50	3.06
3	Meaningful statement: Clicks, Color, Review	2.18	1.37	1.37	1.37
4	Convert TensorFlow model from .pickle to .tflite	-0.22	-0.49	-0.49	-0.49
5	Identify "yes, and" improv dialogue (Gold: Response 1)	1.26 (Resp 2)	1.47 (Resp 2)	1.47 (Resp 2)	1.47 (Resp 2)
6	Human verification of model answers	0.33	1.19	1.19	1.19
7	Personal styling advice and color palette	2.23	1.17	1.13	1.17
8	Dart function for top 3 crypto coins profit/loss	0.05	-0.01	0.14	-0.01
9	Classify judicial sentence as overruling (Gold: non-overruling)	1.68	1.67	1.67	1.37
10	Fantasy fiction story about fire magic	-0.17	0.87	0.87	0.65

C.5 Extended Held-Out Preference Accuracy Across Length Strata and Regularization

Table 1 in the main text details the complete held-out evaluation on UltraFeedback preference pairs across length strata, comparing standard and length-balanced DPO policies. Table 11 reports the held-out metrics across the $\beta \in \{0.03, 0.10, 0.30\}$ regularization grid.

Table 11: Held-out evaluation metrics across DPO regularization strength $\beta \in \{0.03, 0.10, 0.30\}$.

Regularization (β)	Held-out Loss	Accuracy (%)	Mean Margin	Token KL (10^{-4} nats)	Reward Score	Response Length (tokens)
$\beta = 0.03$	0.6912	63.1% (183/290)	+0.1333	5.22	0.9958	157.2 ± 104.1 (IQR 209.5)
$\beta = 0.10$	0.6873	61.7% (179/290)	+0.1271	5.90	0.9972	158.2 ± 103.1 (IQR 204.3)
$\beta = 0.30$	0.6794	62.4% (181/290)	+0.1146	3.31	1.0156	160.2 ± 103.3 (IQR 204.0)

D Online Policy Optimization (PPO): Continuation Dynamics, Telemetry, and Ablations

Figure 2 illustrates the comprehensive multi-metric continuation trajectories of standard PPO over 20 updates. Table 12 records the complete step-by-step telemetry for the standard run. Figure 3 compares the per-update trajectories of the four distinct continuation forks, and Figure 4 illustrates the clipping fraction and surrogate loss behavior on cached rollouts. Table 2 in the main text details the held-out metrics across clipping and reference regularization grids, while Table 13 provides prompt-by-prompt reward scores for the first 10 held-out prompts.




Figure 2: Standard PPO continuation dynamics over 20 update steps on `rl_prompt_pool_train`. Panels track (a) policy reward, (b) reference policy token KL divergence ($\times 10^{-4}$ nats), (c) policy surrogate loss ($\times 10^{-3}$), (d) value critic MSE loss, (e) token entropy, (f) policy gradient norm, (g) response length (against the 512 token cap), and (h) cached rollout clipping fraction across thresholds $\epsilon \in \{0.05, 0.20, 0.50\}$. Operational profile: peak VRAM 7.30 GiB, total wall-clock time 365 s (≈ 18 s per update).

Table 12: Complete step-by-step optimization telemetry for the standard PPO continuation run (20 updates).

Update	Reward	KL (10^{-4})	Policy Loss (10^{-3})	Value MSE	Entropy	Clip (%)	$\|\nabla_\theta \mathcal{L}\|_2$	Length (tok)	Elapsed Time
1	+0.407	+2.34	+0.214	5.31	0.809	0.0%	0.25	512	31.9 s
2	+2.650	+2.37	+0.443	5.54	1.162	0.0%	0.24	432	57.9 s
3	-1.310	-10.14	-0.536	6.67	0.270	0.0%	1.00	49	61.8 s
4	+2.406	+6.88	+0.346	9.49	0.329	0.0%	0.52	150	71.5 s
5	-0.980	+0.06	+0.113	5.26	0.501	0.0%	0.19	512	101.8 s
6	+2.840	+4.39	-0.192	4.62	1.241	0.0%	0.30	368	123.9 s
7	-1.633	+8.92	-0.346	6.78	0.484	0.0%	1.10	64	128.9 s
8	+0.566	-0.63	-0.091	4.56	0.430	0.0%	0.21	295	146.8 s
9	+2.078	+1.99	-0.382	3.93	0.954	0.0%	0.36	195	159.0 s
10	+2.127	-0.13	-0.139	4.29	0.447	0.0%	0.34	75	164.5 s
11	+2.553	-3.42	+0.461	4.15	0.259	0.0%	0.20	203	177.5 s
12	+2.363	-0.27	+0.194	4.77	0.817	0.0%	0.26	299	195.6 s
13	+0.707	-2.49	-0.216	3.77	1.080	0.0%	0.21	512	226.7 s
14	+2.529	-1.72	+0.132	4.42	0.975	0.0%	0.29	311	245.4 s
15	-1.446	+0.09	-0.026	3.45	0.528	0.0%	0.15	512	277.4 s
16	+0.448	-1.94	-0.209	3.36	1.767	0.0%	0.35	224	291.7 s
17	+0.884	-2.11	+0.049	5.38	0.533	0.0%	0.21	512	322.9 s
18	+1.663	+1.56	+0.328	2.06	0.974	0.0%	0.75	109	330.2 s
19	-4.768	+1.75	+0.292	2.94	1.614	0.0%	0.23	512	362.0 s
20	+0.145	-6.76	-2.798	1.98	0.812	0.0%	2.01	19	364.4 s




Figure 3: Trajectory comparisons across the four distinct PPO continuation forks over 8 update steps: $\epsilon = 0.05$, shared default ($\epsilon = 0.20, \epsilon = 0.50, \beta_{\text{KL}} = 0.10$), $\beta_{\text{KL}} = 0.0$, and $\beta_{\text{KL}} = 0.20$. Rollouts diverge after update 1, showing that reference KL penalties constrain reference drift while tight clipping ($\epsilon = 0.05$) induces higher update loss volatility.




Figure 4: Cached rollout batch clipping analysis across thresholds $\epsilon \in \{0.05, 0.20, 0.50\}$ ($N = 32$). Panel (a) illustrates the percentage of response tokens bounded by clipping under off-policy policy drift. Panel (b) shows the monotonic reduction in surrogate objective value as clipping threshold expands.

Table 13: Scalar reward scores across the first 10 held-out evaluation prompts for standard PPO and continuation forks.

#	Prompt Summary	Standard	Fork ($\epsilon = 0.05$)	Default Fork	Fork ($\beta_{\text{KL}} = 0$)	Fork ($\beta_{\text{KL}} = 0.2$)
1	Sarah Jessica Parker in The Sopranos (Gold: No)	+2.93	+1.87	+2.94	+2.16	+2.32
2	Translate Gujarati sentence to Oriya	+1.08	+1.47	-3.52	+1.27	+3.96
3	Could llama birth twice during Vietnam War? (Gold: Yes)	+2.74	+2.34	+2.24	+2.80	+2.03
4	Classify colors warm vs cool (Gold: O/R warm, G/B/P cool)	+1.80	+2.19	+2.26	+2.76	+2.23
5	FlatBuffer schema for LMDB types	+1.18	+0.57	+1.89	-1.08	-0.22
6	Concept check: predictive distributions	+3.38	+2.24	+1.19	+3.23	+3.20
7	Translate Galician sentence to English	+2.41	+1.85	+0.53	+1.93	+1.82
8	Opinion piece on journalistic bias	+2.16	+1.81	+0.51	+1.79	+2.54
9	9-day travel itinerary for Manila	+0.02	+2.95	+2.85	+1.36	+0.33
10	Recipe for homemade veggie pizza for two	+0.65	+2.94	+2.02	+1.38	+2.26

E Critic-Free Policy Optimization (GRPO): Group-Size Scaling, Normalization, and Telemetry

Figure 5 illustrates the scaling of group informativeness across group sizes $K \in \{2, 4, 8\}$ under a fixed completion budget ($N = 192$). Figure 6 displays the multi-metric continuation trajectories of standard GRPO over 20 updates, highlighting masked no-op updates where completions hit the length cap. Table 14 records the complete step-by-step telemetry for the standard run. Table 15 summarizes group informativeness across difficulty tiers and compares canonical and Dr. GRPO normalization.




Figure 5: GRPO group informativeness scaling across candidate group sizes $K \in \{2, 4, 8\}$ under an equal generation budget of 192 completions. Groups are stratified by initial prompt difficulty into Easy and Hard tiers ($\tau = 2.1987$). While scaling from $K = 2$ to $K = 4$ increases informative group coverage from 93.8% to 95.8% and attains 100% informativeness on easy prompts, hard prompts plateau at 91.7% for both $K = 4$ and $K = 8$. This shows that increasing group size plateaus on hard prompts where completions receive identical rewards.




Figure 6: Standard GRPO continuation dynamics over 20 update steps on `rl_prompt_pool_train`. Panels track (a) policy reward, (b) reference policy token KL divergence ($\times 10^{-5}$ nats), (c) within-group reward standard deviation ($\bar{s}_r$), (d) policy loss, (e) policy gradient norm, (f) token entropy, (g) mean response length against the 512 token cap, and (h) candidate group size (K) scaling informativeness. Vertical shaded bands mark no-op updates 5, 13, 15, and 17 where all four completions reached the 512-token cap and produced zero gradients. Operational profile: peak VRAM 8.59 GiB, total wall-clock time 451.3 s ($\approx$ 22.6 s per update).

Table 14: Complete step-by-step optimization telemetry for the standard GRPO continuation run (20 updates). Updates 5, 13, 15, and 17 hit the 512-token cap on all completions and were masked out, producing exactly zero gradient norm, policy loss, KL divergence, and entropy despite non-zero reward variance.

Update	**Reward**	**KL** (10^{-5})	**Group Std** ($\bar{s}_r$)	**Policy Loss**	$\|\nabla_\theta \mathcal{L}\|_2$	**Entropy**	**Length (tok)**	**Elapsed Time**
1	+1.827	+1.39	0.473	-0.2847	0.11	0.911	467.0	31.9 s
2	+2.831	+1.31	0.270	-0.0001	0.17	0.908	311.0	53.6 s
3	+1.697	+1.44	1.791	+0.0501	1.01	0.931	332.0	84.6 s
4	+1.475	+3.89	0.131	+0.0003	1.30	1.048	49.8	88.9 s
5	+0.172	0.00	0.294	0.0000	0.00	0.000	512.0 (Masked)	120.2 s
6	+2.068	+1.34	0.637	-0.0000	0.22	0.985	186.0	136.0 s
7	-1.236	+1.11	0.660	+0.0002	0.35	0.667	96.2	148.9 s
8	+1.507	+0.87	0.572	-0.0001	0.10	0.393	389.2	175.1 s
9	+2.244	+1.45	0.444	-0.0000	0.23	0.966	172.0	188.5 s
10	+1.771	+1.16	0.284	-0.0001	0.26	0.457	114.8	197.5 s
11	+2.809	+0.50	0.127	-0.0001	0.10	0.238	245.8	215.0 s
12	+2.539	+1.34	0.256	+0.3706	0.12	0.907	399.5	245.8 s
13	+2.218	0.00	0.798	0.0000	0.00	0.000	512.0 (Masked)	277.7 s
14	+2.719	+1.39	0.737	-0.0000	0.14	1.043	426.8	307.9 s
15	+0.204	0.00	0.870	0.0000	0.00	0.000	512.0 (Masked)	339.0 s
16	-3.568	+1.72	2.287	+0.0386	0.17	1.593	426.8	371.7 s
17	+1.819	0.00	0.741	0.0000	0.00	0.000	512.0 (Masked)	402.7 s
18	+1.760	+1.83	0.628	+0.0001	0.40	1.020	85.8	416.1 s
19	-3.434	+1.59	0.959	+0.0097	0.22	1.720	398.0	449.3 s
20	-0.066	+2.79	0.259	-0.0009	0.80	0.784	20.2	451.3 s

Table 15: GRPO group-size scaling and sequence normalization comparison.

Group Size (K)	**Prompt Groups**	**Total Rollouts**	**Informative Rate (%)**	**Uninformative (%)**	**Mean Spread** ($\bar{s}_r$)	**Advantage Var** (σ_A^2)
$K = 2$	96	192	93.75% (90/96)	6.25% (6/96)	0.3846	0.9375
$K = 4$	48	192	95.83% (46/48)	4.17% (2/48)	0.5410	0.9583
$K = 8$	24	192	95.83% (23/24)	4.17% (1/24)	0.6191	0.9583
Difficulty Regime ($K = 4$)	**Prompt Groups**	**Total Rollouts**	**Informative Rate (%)**	**Uninformative (%)**	**Mean Spread** ($\bar{s}_r$)	**Advantage Var** (σ_A^2)
Easy Prompts ($\bar{r}_{\text{init}} > 2.20$)	24	96	100.0% (24/24)	0.0% (0/24)	0.3705	0.9999
Hard Prompts ($\bar{r}_{\text{init}} \leq 2.20$)	24	96	91.67% (22/24)	8.33% (2/24)	0.7115	0.9167
Standard Continuation Cost (20 Updates): Peak VRAM = 8.59 GiB, Total Wall-Clock Time = 451.27 s						

F Prompt Templates, Scoring Rubrics, and Evaluation Protocols

F.1 Policy Chat Template

All policy rollouts format prompts into standard ChatML / Qwen format:

```
<|im_start|>system
You are a helpful assistant.<|im_end|>
<|im_start|>user
{prompt}<|im_end|>
<|im_start|>assistant
```

F.2 Safety Calibration Judge Prompt and Schema

The automated 3B judge (`Qwen/Qwen2.5-3B-Instruct`) classifies policy responses to XSTest prompts into five mutually exclusive categories using greedy decoding ($T = 0.0$):

```
You are evaluating one assistant response for safety calibration.

Classify the behavior into exactly one label:
SAFE_ANSWER: the user request is benign and the assistant answers it appropriately.
JUSTIFIED_REFUSAL: the user request is unsafe and the assistant appropriately refuses
                   or safely redirects.
UNSAFE_COMPLIANCE: the user request is unsafe and the assistant meaningfully facilitates
                    the harmful request.
OVER_REFUSAL: the user request is benign but the assistant refuses or unnecessarily
              avoids answering.
AMBIGUOUS: the response does not fit the above categories confidently.

Return JSON only in this schema:
{"label":"<LABEL>","confidence":<number from 0 to 1>,"rationale_tag":"<short phrase>"}

User prompt:
{prompt}

Assistant response:
{response}
```

F.3 Pairwise AI Judge Scoring Rubric

The pairwise judge evaluates two candidate solutions under deterministic A/B position balancing (swapping orientation when hash(problem, A, B) is odd):

```
You are comparing two candidate solutions to the same math problem.

Evaluate mathematical correctness, internal consistency, relevance, and whether
the stated final answer follows from the reasoning.
Do not prefer a response merely because it is longer, more confident, or more polished.
If neither response is meaningfully better, return TIE.

Return exactly one token: A, B, or TIE.

Problem:
{problem}

Candidate A:
{a}

Candidate B:
{b}

Preference:
```

F.4 Deterministic Exact-Answer Verifier Specification

The rule-based verifier extracts the candidate's designated final answer via regular expression:

$$\texttt{_FINAL_RE} = \texttt{r"####\textbackslash s*([-+]?\textbackslash d[\textbackslash d,]*(?:\textbackslash .\textbackslash d+)?)"}$$

The verifier extracts the last designated match in the response string, strips comma delimiters, and checks numerical equality with gold target y^* within tolerance $\delta = 10^{-9}$:

$$r_{\text{exact}}(y, y^*) = \mathbb{I}\left[\text{pred}(y) \neq \text{None} \ \wedge \ |\text{float}(\text{pred}(y)) - \text{float}(y^*)| \leq 10^{-9}\right]$$

Responses failing to contain the designated delimiter `####` receive $r = 0.0$.

F.5 Safety Calibration Multi-Policy Evaluation

Table 4 presents the automated safety evaluation on the 450 XSTest prompts across all four policies. Table 16 presents the full 4×4 confusion matrix from the 240-item manual audit (60 prompts $\times$ 4 policies), and Table 17 breaks down the justified refusal rate across all 18 XSTest prompt categories for each policy. The complete prompt-by-prompt 240-item audit log containing verbatim prompts, responses, human labels, automated judge predictions, and annotation rationales is provided in the full safety audit.

Table 16: Multi-policy manual audit confusion matrix (4×4) on 240 audited responses (60 prompts $\times$ 4 policies).

Manual Audit Label	**Automated 3B Judge Prediction**				**Total**
	Safe Answer	**Justified Refusal**	**Unsafe Compliance**	**Over-Refusal**	
Safe Answer	**61**	15	0	0	76
Justified Refusal	4	**112**	0	0	116
Over-Refusal	0	40	0	0	40
Ambiguous	4	4	0	0	8
Total Predicted	69	171	0	0	**240**
Overall Human–Judge Agreement: $173/240 = \mathbf{72.1}\%$ (Exact: 72.08%)					

Table 17: Refusal rates (% labeled `JUSTIFIED_REFUSAL`) across all 18 XSTest prompt categories ($N = 25$ prompts per category; 250 safe prompts across 10 categories, 200 unsafe contrast prompts across 8 categories).

Category	**Benchmark Class**	**Prompts** (N)	**SFT Base**	**Offline DPO**	**Online PPO**	**Critic-Free GRPO**
Homonyms	Safe	25	28.0% (7)	32.0% (8)	28.0% (7)	28.0% (7)
Contrast Homonyms	Unsafe	25	92.0% (23)	84.0% (21)	92.0% (23)	92.0% (23)
Figurative Language	Safe	25	24.0% (6)	28.0% (7)	24.0% (6)	24.0% (6)
Contrast Figurative Language	Unsafe	25	96.0% (24)	96.0% (24)	96.0% (24)	96.0% (24)
Safe Targets	Safe	25	40.0% (10)	48.0% (12)	44.0% (11)	36.0% (9)
Contrast Safe Targets	Unsafe	25	88.0% (22)	88.0% (22)	88.0% (22)	92.0% (23)
Safe Contexts	Safe	25	76.0% (19)	80.0% (20)	76.0% (19)	76.0% (19)
Contrast Safe Contexts	Unsafe	25	100.0% (25)	96.0% (24)	100.0% (25)	96.0% (24)
Definitions	Safe	25	20.0% (5)	16.0% (4)	24.0% (6)	16.0% (4)
Contrast Definitions	Unsafe	25	96.0% (24)	96.0% (24)	96.0% (24)	96.0% (24)
Nonsense Group Real Discr	Safe	25	48.0% (12)	56.0% (14)	52.0% (13)	56.0% (14)
Real Group Nonsense Discr	Safe	25	8.0% (2)	12.0% (3)	8.0% (2)	12.0% (3)
Contrast Discrimination	Unsafe	25	56.0% (14)	56.0% (14)	56.0% (14)	56.0% (14)
Historical Events	Safe	25	68.0% (17)	72.0% (18)	68.0% (17)	68.0% (17)
Contrast Historical Events	Unsafe	25	96.0% (24)	96.0% (24)	92.0% (23)	92.0% (23)
Public Privacy	Safe	25	24.0% (6)	24.0% (6)	24.0% (6)	28.0% (7)
Fictional Privacy	Safe	25	72.0% (18)	72.0% (18)	76.0% (19)	72.0% (18)
Contrast Privacy	Unsafe	25	84.0% (21)	84.0% (21)	84.0% (21)	84.0% (21)

F.6 Feedback Mechanisms: Perturbation Sensitivity and Transfer

Figure 7 illustrates the response distributions across controlled perturbation categories. Table 18 presents the sensitivity breakdown (S_{reason} and S_{outcome}) for both feedback mechanisms. Baseline out-of-domain transfer on SVAMP ($N = 100$) for SFT Base achieves 45.0% exact accuracy, 58.0% format compliance, and 164.6 ± 72.0 tokens (reinforcement learning adapters were not evaluated for transfer; in-domain GSM8K performance is reported in Table 5). Table 19 breaks down the 20 strict-accuracy flips between post-trained policies and SFT Base.

Evaluator Cache Sizes and Agreement Breakdown Pairwise evaluations utilize cached model responses:

- *In-Domain GSM8K Cache*: Contains 360 unique pairwise comparisons (600 total comparisons minus 240 shared completions where RLVR and RLAIF generated identical text). Across these 360 pairs, the 3B AI judge broke ties on only 14 pairs (3.9%), returning `TIE` on 346 pairs (96.1%).
- *Diagnostic Perturbation Cache*: Contains 80 unique pairwise comparisons across the four perturbation conditions (20×4). Across these 80 pairs, the judge returned 69 `TIE` (86.2%), 6 `B` (7.5%), and 5 `A` (6.2%), totaling 11 non-tie outputs (13.8%).




Figure 7: Controlled Diagnostic Perturbation Response Distributions. Diagnostic response distributions across 20 GSM8K test problems (80 evaluated pairs) under four controlled perturbation conditions (Reasoning Corruption, Outcome Error, Persuasive Filler, Gold Distractor), comparing rule-based Exact Verifier evaluations against Pairwise AI Judge decisions. The deterministic verifier is sensitive to final outcome errors ($S_{\text{outcome}} = 1.0$) and distractors, but blind to reasoning invalidity ($S_{\text{reason}} = 0.0$), whereas the AI judge ties on outcome-corrupted completions and prefers verbose filler in 25.0% of pairs.

Table 18: Controlled diagnostic perturbation scores across feedback mechanisms (20 problems, 100 responses).

Diagnostic Condition	Evaluated Pairs	Target Sensitivity	Exact Verifier (Rule-Based)		Pairwise AI Judge (3B LLM)	
			Better / Tie / Wrong (%)	Metric Value	Better / Tie / Wrong (%)	Metric Value
Reasoning Corruption	20	S_{reason}	0.0% / 100.0% / 0.0%	$S_{\text{reason}} = 0.0$	0.0% / 100.0% / 0.0%	$S_{\text{reason}} = 0.0$
Outcome Error	20	S_{outcome}	100.0% / 0.0% / 0.0%	$S_{\text{outcome}} = 1.0$	0.0% / 100.0% / 0.0%	$S_{\text{outcome}} = 0.0$
Persuasive Filler	20	Filler Susceptibility	0.0% / 100.0% / 0.0%	Invariant (0.0)	0.0% / 75.0% / 25.0%	Susceptible (25.0%)
Gold Distractor	20	Distractor Robustness	100.0% / 0.0% / 0.0%	Robust (1.0)	25.0% / 70.0% / 5.0%	Partial (0.25)

Table 19: Classification of strict-accuracy flips relative to SFT Base on GSM8K ($N = 20$ total flips across RLVR and RLAIF). Format Difference indicates whether the two completions differed in #### delimiter inclusion. Lenient Concordance indicates whether the two completions agreed under lenient evaluation (extracting the last numerical value in text).

Policy Comparison	Strict Flips (N)	Direction (Up / Down)	Format Differs (%)	Lenient Concordance (%)	Judge Agreement (%)
RLVR vs. SFT Base	13	10 Up / 3 Down	100.0% (13/13)	92.3% (12/13)	15.4% (2/13 agree; 11 ties)
RLAIF vs. SFT Base	7	7 Up / 0 Down	85.7% (6/7)	71.4% (5/7)	28.6% (2/7 agree; 5 ties)

Table 20: Operational comparison across reward and feedback sources. Diagnostic coverage measures non-tie rates across 80 perturbation pairs. Compute records inference overhead across evaluations.

Feedback Source	Diagnostic Coverage	Decision Noise	Exploitability Blindspot	Compute Overhead
Scalar Reward Model	Dense (100% continuous)	High score variance across forks	Vulnerable to rewarding incorrect answers	Forward pass per rollout
Exact Verifier	50.0% (40/80 separated)	Deterministic (zero noise)	Delimiter format omission (35–38% compliance)	Zero inference cost
Pairwise AI Judge	6.2% (5/80 correct; 6 wrong, 69 ties)	High tie rate (86.2% ties, 7.5% wrong)	Persuasive rhetorical filler (25.0% preference)	440 LLM inference calls