

Lecture 20:  
Nested Recursive Lexicographical Search:  
Structural Estimation of Dynamic  
Directional Games with Multiple Equilibria  
Summer School on Structural Dynamics Models, Marketing and  
Business Analytics

Fedor Iskhakov, Australian National University  
John Rust, Georgetown University  
Bertel Schjerning, University of Copenhagen

Chicago Booth  
July 2019

# Estimation of stochastic dynamic games

- ➊ Several decision makers (*players*)
  - ➋ Maximize discounted expected lifetime utility
  - ➌ Anticipate consequences of their current actions
  - ➍ Anticipate actions by other players in current and future periods (*strategic interaction*)
  - ➎ Operate in a stochastic environment (*state of the game*) whose evolution depend on the collective actions of the players
- Estimate structural parameters of these models
  - Data on  $M$  independent markets over  $T$  periods
  - Multiplicity of equilibria

# Markov Perfect Equilibrium

- MPE is a pair of **strategy profile** and **value functions**:
- **Bellman Optimality**  
Each player solves their Bellman equation for values  $\mathbf{V}$  taking other players choice probabilities  $\mathbf{P}$  into account
- **Bayes-Nash Equilibrium**  
The choice probabilities  $\mathbf{P}$  are determined by the values  $\mathbf{V}$
- In compact notation

$$\mathbf{V} = \Psi^{\mathbf{V}}(\mathbf{V}, \mathbf{P}, \theta)$$

$$\mathbf{P} = \Psi^{\mathbf{P}}(\mathbf{V}, \mathbf{P}, \theta)$$

- Set of all Markov Perfect Equilibria

$$SOL(\Psi, \theta) = \left\{ (\mathbf{P}, \mathbf{V}) \mid \begin{array}{l} \mathbf{V} = \Psi^{\mathbf{V}}(\mathbf{V}, \mathbf{P}, \theta) \\ \mathbf{P} = \Psi^{\mathbf{P}}(\mathbf{V}, \mathbf{P}, \theta) \end{array} \right\}$$

# Maximum Likelihood

- Data from  $M$  independent markets from  $T$  periods  
 $\mathbf{Z} = \{\bar{\mathbf{a}}^{mt}, \bar{\mathbf{x}}^{mt}\}_{m \in \mathcal{M}, t \in \mathcal{T}}$   
Usually assume only one equilibrium is played in the data.
- For a given  $\theta$ , let  
 $(\mathbf{P}^\ell(\theta), \mathbf{V}^\ell(\theta)) \in SOL(\Psi, \theta)$  denote the  $\ell$ -th equilibrium
- Log-likelihood function is

$$\mathcal{L}(Z, \theta) = \max_{(\mathbf{P}^\ell(\theta), \mathbf{V}^\ell(\theta)) \in SOL(\Psi, \theta)} \frac{1}{M} \sum_{i=1}^N \sum_{m=1}^M \sum_{t=1}^T \log P_i^\ell(\bar{a}_i^{mt} | \bar{\mathbf{x}}^{mt}; \theta)$$

- The ML estimator is  $\theta^{ML} = \arg \max_{\theta} \mathcal{L}(Z, \theta)$

# Estimation methods for stochastic games

## Maximum likelihood estimator

- Efficient, but expensive: need full solution method
- No problem with multiple equilibria



Borkovsky, Doraszelsky and Kryukov (2010) All solution homotopy;  
Iskhakov, Rust and Schjerning (2016) RLS

## Two-step estimators

- Fast, but potentially large finite sample biases



Bajari, Benkard, Levin (2007); Pakes, Ostrovsky, and Berry (2007);  
Pesendorfer and Schmidt-Dengler (2008)

$$\max_{\theta} \mathcal{L}(\mathbf{Z}, \Psi^{\mathbf{P}}(\Gamma(\theta, \hat{\mathbf{P}}), \hat{\mathbf{P}}, \theta))$$

# Estimation methods for stochastic games

## Nested psuedo-likelihood (recursive two-step)

- Bridges the gap between efficiency and tractability
- Unstable under multiplicity



Aguirregabiria and Mira (2007); Pesendorfer and Schmidt-Dengler (2010); Kasahara and Shimotsu (2012)

## Math Programming with Equilibrium Constraints (MPEC)

- Reformulates ML problem as constrained optimization
- Should not be affected by multiplicity



Su (2013); Egedal, Lai and Su (2015)

$$\max_{(\theta, \mathbf{P}, \mathbf{V})} \mathcal{L}(\mathbf{Z}, \mathbf{P}) \text{ subject to } \mathbf{V} = \Psi^{\mathbf{V}}(\mathbf{V}, \mathbf{P}, \theta), \mathbf{P} = \Psi^{\mathbf{P}}(\mathbf{V}, \mathbf{P}, \theta)$$

# Summary of this paper

- Propose robust and computationally feasible MLE estimator for **directional dynamic games (DDG)**, finite state stochastic games with particular transition structure
- Rely of full solution algorithm that provably computes all MPE under certain regularity conditions
- Employ smart discrete programming method to maximize likelihood function over the finite set of equilibria
- Provide Monte Carlo evidence of the performance
- **Fully robust to multiplicity of MPE**
- **Relax single-equilibrium-in-data assumption**
- **Path to estimation of equilibrium selection rules**

# Nested Recursive Lexicographical Search (NRLS)

## 1 Outer loop

Maximization of the likelihood function w.r.t. to structural parameters  $\theta$

$$\theta^{ML} = \arg \max_{\theta} \mathcal{L}(Z, \theta)$$

## 2 Inner loop

Maximization of the likelihood function w.r.t. equilibrium selection

$$\mathcal{L}(Z, \theta) = \max_{(\mathbf{P}^{\ell}(\theta), \mathbf{V}^{\ell}(\theta)) \in SOL(\Psi, \theta)} \frac{1}{M} \sum_{i=1}^N \sum_{m=1}^M \sum_{t=1}^T \log P_i^{\ell}(\bar{a}_i^{mt} | \bar{\mathbf{x}}^{mt}; \theta)$$

Max of a function on a discrete set organized into RLS tree



# Branch and bound (BnB) method



Land and Doig, 1960 *Econometrica*

- Old method for solving **discrete programming** problems
- ① Form a **tree** of subdivisions of the set of admissible plans
- ② Specify a **bounding function** representing the best attainable objective on a given subset (branch)
- ③ Dismiss the subsets of the plans where the bound is below the current best attained value of the objective

# Theory of BnB: branching

$$\max f(x) \text{ s.t. } x \in \Omega$$

$f(x)$  objective function

$\Omega$  set of feasible  $x$

$\mathcal{P}_j(\Omega)$  partition of  $\Omega$  into  $k_j$  subsets,  $\mathcal{P}_1(\Omega) = \Omega$

$$\mathcal{P}_j(\Omega) = \{\Omega_{j1}, \dots, \Omega_{jk_j} : \Omega_{ji} \cap \Omega_{ji'} = \emptyset, i \neq i', \cup_{i=1}^{k_j} \Omega_{ji} = \Omega\}$$


$\{\mathcal{P}_j(\Omega)\}_{j=1, \dots, J}$  a sequence of  $J$  **gradually refined partitions**

$$k_1 \leq \dots \leq k_j \leq \dots \leq k_J$$

$$\forall j = 1, \dots, J, \forall i = 1, \dots, k_j : \forall j' < j \exists i'_{j'} \text{ such that } \Omega_{ij} \subset \Omega_{i'j'}$$

# Theory of BnB: branching

$$\max f(x) \text{ s.t. } x \in \Omega$$



# Theory of BnB: bounding

$$\max f(x) \text{ s.t. } x \in \Omega$$

$g(\Omega_{ij})$  bounding function: from subsets of  $\Omega$  to real line

$g(\Omega_{ij}) = f(x)$  for singletons, i.e. when  $\Omega_{ij} = \{x\}$

**Monotonicity of bounding function**

$$\forall j \forall \Omega_{i_1 1} \supset \Omega_{i_2 2} \supset \cdots \supset \Omega_{ij j}$$

$$g(\Omega_{i_1 1}) \geq g(\Omega_{i_2 2}) \geq \cdots \geq g(\Omega_{ij j})$$

- Inequalities are reversed for the minimization problem

## BnB with NRLS

- **Branching:** RLS tree
- **Bounding:** The bound function is **partial likelihood** calculated on the subset of states that

$$\mathcal{L}^{\text{Part}}(Z, \theta, \mathcal{S}) = \frac{1}{M} \sum_{i=1}^N \sum_{m=1}^M \sum_{t=1}^T \log P_i^{\ell}(\bar{a}_i^{mt} | \bar{\mathbf{x}}^{mt}; \theta)$$


**s.t.  $(\bar{\mathbf{x}}^{mt}, \bar{a}_i^{mt}) \in \mathcal{S}$**

- Monotonically declines as more data is added
- Equals to the full log-likelihood at the leafs of RLS tree


# BnB on RLS tree, step 1

$$\boxed{14} \cdot \boxed{13} \cdot \boxed{12} \cdot \boxed{11} \cdot \boxed{10} \text{ Partial loglikelihood} = -3.2$$

## BnB on RLS tree, step 2




# BnB on RLS tree, step 3







# BnB on RLS tree, step 4




# BnB on RLS tree, step 5




# BnB on RLS tree, step 6




# BnB on RLS tree, step 7




# BnB on RLS tree, step 8




## BnB on RLS tree, step 9




# BnB on RLS tree, step 10




# BnB on RLS tree, step 11












## BnB on RLS tree, step 14




# BnB on RLS tree, step 15







# BnB on RLS tree, step 17



# BnB on RLS tree, step 18




# BnB on RLS tree, step 19







## BnB on RLS tree, step 20




# BnB on RLS tree, step 21







# BnB on RLS tree, step 23




## BnB on RLS tree, step 24




# BnB on RLS tree, step 25




# BnB on RLS tree, step 26





# BnB on RLS tree, step 27

















# BnB on RLS tree, step 32



# BnB on RLS tree, step 33



# BnB on RLS tree, step 34



# Refinements of the BnB for NRLS

- Bounding criterion is **deterministic** → may use **statistical criterion** to decide whether to extend a given branch or not
  - Have to assess **potential likelihood contribution** of the branches that are not fully extended → choice probabilities are not known (the goal is not to compute them)
  - ① Bounds for choice probabilities? Model specific
  - ② Yet, comparing two equilibria based on the already extended parts is possible → LR type test
- ⇒ **Poly-algorithm** with dichotomous decision rule



# Battery of MC tests

A

---

Single equilibrium in the model  
Single equilibrium in the data

B

---

Multiple equilibria in the model  
Single equilibrium in the data

C

---

Multiple equilibria in the model  
Multiple equilibria in the data

- ❶ Two-step CCP estimator
  - ❷ Nested pseudo-likelihood
  - ❸ Several flavors of MPEC
- vs. NROLS estimator

# Battery of MC tests: preliminary results

A

- 
- 1 Fastest, small sample bias
  - 2 Approaching MLE
  - 3 MLE

B

- 
- 1 Small sample bias
  - 2 Failing due to multiplicity
  - 3 Local extrema

C

- 
- 1 Huge data requirements
  - 2 Failing due to multiplicity
  - 3 Curse of dimensionality

- 1 Two-step CCP estimator
- 2 Nested pseudo-likelihood
- 3 MPEC

## Monte Carlo setup (A and B)

- $n = 3$  points on the grid on the grid of costs
- 14 points in state space of the model
- 100 random samples from a single equilibrium (one market)
- 10,000 observations per market/equilibrium
- Uniform distribution over state space  $\leftrightarrow$  “ideal” data
- Data contains simulated discrete investment choices only
- Estimating one parameter in cost function

# Monte Carlo A: no multiplicity

Number of equilibria in the model: 1

Number of equilibria in the data: 1

True value of parameter k1: 1.0

	mle-mpec	pml2step	npl	mle-bnb
Parameter: k1	4.0745	1.0146	1.0203	1.0206
MCSD	3.4974	0.0221	0.0237	0.0212
Bias	3.0745	0.0146	0.0203	0.0206
Log-likelihood	-12,989.73	-12,991.88	-12,987.10	-12,987.37
$  \Psi(P) - P  $	0.00	0.04	0.01	0.00
$  \Gamma(v) - v  $	0.00	0.27	0.15	0.00
Runs converged,	92.00	100.00	100.00	100.00
CPU time, sec	4.03	0.05	0.17	7.22
K-L divergence	4.78	0.00	0.00	0.00
abs deviation	0.38	0.02	0.01	0.00

# Monte Carlo B, run 1: moderate multiplicity

Number of equilibria in the model: 5

Number of equilibria in the data: 1

True value of parameter k1: 1.0

	mle-mpec	pml2step	npl	mle-bnb
Parameter: k1	1.1090	0.9985	1.0009	0.9815
MCSD	0.0000	0.0000	0.0000	0.0000
Bias	0.1090	-0.0015	0.0009	-0.0185
Log-likelihood	-11,102.91	-11,102.91	-11,101.19	-11,092.05
$  \Psi(P) - P  $	0.00	0.03	0.01	0.00
$  \Gamma(v) - v  $	0.00	0.54	0.13	0.00
Runs converged,	100.00	100.00	100.00	100.00
CPU time, sec	2.35	0.04	0.23	11.13
K-L divergence	0.01	0.01	0.01	0.00
Abs deviation	0.03	0.03	0.04	0.01

# Monte Carlo B, run 2: larger multiplicity

Number of equilibria in the model: 95

Number of equilibria in the data: 1

True value of parameter k1: 1.0

	mle-mpec	pml2step	npl	mle-bnb
Parameter: k1	1.0910	0.9948	1.0045	0.9970
MCSD	0.3202	0.0113	0.0094	0.0065
Bias	0.0910	-0.0052	0.0045	-0.0030
Log-likelihood	-6,714.92	-6,714.32	-6,722.46	-6,695.74
$  \Psi(P) - P  $	0.00	0.10	0.12	0.00
$  \Gamma(v) - v  $	0.00	1.22	0.94	0.00
Runs converged,	100.00	100.00	5.00	100.00
CPU time, sec	7.72	0.04	0.32	13.79
Mean K-L divergence	0.27	0.01	0.02	0.00
Mean abs deviation	0.06	0.04	0.06	0.00

# Monte Carlo B, run 3: moderate multiplicity, bad start points

Number of equilibria in the model: 5

Number of equilibria in the data: 1

True value of parameter k1: 1.0

	mle-mpec	pml2step	npl	mle-bnb
Parameter: k1	6.7685	0.9948	1.0045	0.9970
MCSD	11.3401	0.0113	0.0094	0.0065
Bias	5.7685	-0.0052	0.0045	-0.0030
Log-likelihood	-6,709.38	-6,714.32	-6,722.46	-6,695.74
$  \Psi(P) - P  $	0.00	0.10	0.12	0.00
$  \Gamma(v) - v  $	0.00	1.22	0.94	0.00
Runs converged,	30.00	100.00	5.00	100.00
CPU time, sec	10.43	0.06	0.37	18.47
Mean K-L divergence	8.63	0.01	0.02	0.00
Mean abs deviation	0.25	0.04	0.06	0.00

# NRLS Monte Carlo setup (C)


---

- $n = 3$  points on the grid on the grid of costs
- 14 points in state space of the model
- 109 MPE in total
- 1000 random samples from 3 different equilibria (3 markets)
- 100 observations per market/equilibrium
- Uniform distribution over state space  $\leftrightarrow$  “ideal” data
- Data contains simulated discrete investment choices only
- Estimating one parameter in cost function



# Distribution of estimated $k_1$ parameter

---



# MC results and numerical performance of NRLS

---

- 1 Average bias and RMSE of the estimates of the cost of investment parameter (true value is 10.0)

$$\begin{aligned}\text{Bias} &= 0.0737 \\ \text{RMSE} &= 0.8712\end{aligned}$$


- 2 Average fraction of MPE computed by BnB relative to RLS  
0.321 (std=0.11635)

- 3 Average fraction of stages solved by BnB relative to RLS  
0.263 (std=0.09725)

- 4 All 3 MPE correctly identified by BnB in  
98.4% of runs

# Distribution of computational reduction factor

---



# Conclusions

- Full solution MLE estimator for dynamic games of a particular type, namely directional dynamic games (DDGs)
- Nested loop: outer likelihood max + inner model solver
- Need to maximize over the set of all equilibria  $\leftrightarrow$  daunting computational task
- Smart BnB algorithm not to waste time on unlikely MPE
- Further refinement of BnB bounding function based on statistical argument
- Horse race with existing estimators