DIP-SW User Manual for DIY-OCM

| DIP-SW | FUNCTION | STATUS | DESCRIPTION |
|--------|------------------|-----------|---|
| 1 | CPU Clock | OFF | Standard mode 3.58MHz |
| | | ON | Custom Speed mode 4.10MHz to 8.06MHz |
| 2 | Video Output | OFF | 15Khz |
| | | ON | 31Khz |
| 3 | Scanlines | OFF | Disabled |
| | | ON | Enabled |
| 4 | Cartridge Slot | OFF | External Slot-1 |
| | | ON | Slot-1: Internal ESE-MegaSCC+ 2048 KB |
| | | | External Slot-2 (if DIP-SW 5/6 are OFF / OFF) |
| 5/6 | Cartridge Slot-2 | OFF / OFF | External Slot-2 |
| | | OFF / ON | Internal ESE-MegaRAM ASCII-8K 2048 KB |
| | | ON / OFF | Internal ESE-MegaSCC+ 2048 KB |
| | | ON / ON | Internal ESE-Megaram ASCII-16K 4096 KB |
| 7 | Internal Mapper | OFF | 2048KB Mapped RAM |
| | | ON | 4096KB Mapped RAM |
| 8 | Internal MegaSD | OFF | Disabled |
| | | ON | Enabled |