

Architecture


ORFAP

Organisation for all purposes

Inhaltsverzeichnis

Architecture	1
Data Model	2
Transtats data	3
Settings	3

Architecture



The Architecture follows the Microservice Architecture and decomposes the whole application into three major Services that are interconnected by a Hypermedia API (REST maturity 3) and the required infrastructure components.

With the Microservice Architecture every service can be build/test/deployed independently. This is the main reason, why this architecture was chosen. So every service can be build and configured to perfectly meet costumer requirements.


Here are the different services of this architecture:


Service	Programming Lang.	Core technologies	Description
FAPBackend	Java	Spring, MySQL	The Flight Data Service provides an API for storing the relevant Flight Data and accessing it. This service ensures integrity and validity of the Data. Additionally it saves the global User Configurations.

Service	Programming Lang.	Core technologies	Description
FAPCrawler	Java	Spring	The Transtats Crawler Service provides the functionality to read the current transtats.com Data, transform it as necessary and store it to the Flight Data Service.
flight-analyzer	JavaScript, HTML	Polymer, ChartJS	The Web-GUI delivers a static (not-templated!) HTML + JS webpage that can be used by the Thin Client as the user frontend. It can make REST requests to the API.
FAPAPIGateway	Java	Spring, Zuul	The API Gateway unifies the public API and opens it up to the network on port 80. It may also be used to restrict requests for security reasons (e.g. allow only read on flights).

Data Model

The data model is split into two scopes: Transtats data and Settings.





Transtats data

The first scope describes the data to save from transtats. This data will be provided from the Crawler Service and is used from the GUI to show the graphs. The most important part is the route entity. It has all the quantitative data (delays, flight count, passenger count, ...) to show in the graphs. In addition to that the route has 3 relations to the qualitative data (airport, source, destination).

Settings

The second scope describes the saved settings data of a specific user. Users can save this data to hold or share a fully configured graph.