

JUG Saxony Day 2016, Dresden

Ansible für Entwickler

Sandra Parsick

mail@sandra-parsick.de

@SandraParsick

Zur meiner Person

- Freiberufliche Softwareentwickler und Consultant im Java-Umfeld
- Schwerpunkte:
 - Java Enterprise Anwendungen
 - Agile Methoden
 - Software Craftmanship
 - Automatisierung von Entwicklungsprozessen
- Softwerkskammer Dortmund




Agenda

1. Ansible – Was ist das?
2. Warum ist es für Entwickler interessant?
3. Einführung in Ansible
4. Wie unterscheidet sich Ansible zur seiner Konkurrenz?
5. Weitere Einsatzszenarien aus Entwicklersicht

Ansible
Was ist das?

Ansible

- Software für
 - Konfigurationsmanagement,
 - Softwareverteilung und
 - Ad-hoc-Kommando-Ausführung



Konfigurationsmanagement (KM)

„Das KM umfasst alle technischen, organisatorischen und beschlussfassenden Maßnahmen und Strukturen, die sich mit der Konfiguration (Spezifikation) eines Produkts befassen.“


<https://www.projektmagazin.de/glossarterm/konfigurationsmanagement>

Konfigurationsmanagement (KM)

- Softwarekonfiguration
- Hardwarekonfiguration
- Dienstleistungskonfiguration
- Systemkonfiguration

Systemkonfiguration

- „Infrastructure As Code“



Systemkonfiguration



- „Infrastructure As Code“



Warum ist es für Entwickler
interessant?


Systemkonfiguration für Entwickler

Organisatorische Ausgangslage
Wunsch




Systemkonfiguration für Entwickler

Organisatorische Ausgangslage
Realität




Systemkonfiguration für Entwickler

Prozess zwischen Development und Operation



Systemkonfiguration für Entwickler


Lösungsidee mit Ansible




Einführung in Ansible

Ansible

- Software für
 - Konfigurationsmanagement,
 - Softwareverteilung und
 - Ad-hoc-Kommando-Ausführung
- Sprache: Python
- Ansible Skripte: YAML



Funktionsweise



Exkurs: YAML


YAML

```
---
foo: "bar"
baz:
  - "qux"
  - "quxx"
corge: null
grault: 1
garply: true
waldo: "false"
fred: "undefined"
emptyArray: []
emptyObject: {}
emptyString: ""
```


JSON

```
{
  "foo": "bar",
  "baz": [
    "qux",
    "quxx"
  ],
  "corge": null,
  "grault": 1,
  "garply": true,
  "waldo": "false",
  "fred": "undefined",
  "emptyArray": [],
  "emptyObject": {},
  "emptyString": ""
}
```

Ansible Beispiel



Setup Application Server Playbook



```
1  hosts: application-server
2  vars:
3      tomcat_version: 8.0.24
4      tomcat_base_name: apache-tomcat-{{ tomcat_version }}
5      #catalina_opts: "-Dkey=value"
6
7  tasks:
8      - name: install java
9        apt: name=openjdk-7-jdk state=present
10       become: yes
11       become_method: sudo
12
13      - name: Download current Tomcat 8 version
14        local_action: get_url url="http://archive.apache.org/dist/tomcat/tomcat-8/v{{ tomcat_version
15        }}/bin/{{ tomcat_base_name }}.tar.gz" dest=/tmp
16
17      - name:
18        file: name=/opt mode=777
19        become: yes
20        become_method: sudo
21
22      - name: Install Tomcat 8
23        unarchive: src=/tmp/{{ tomcat_base_name }}.tar.gz dest=/opt creates=/opt/{{ tomcat_base_name
24        }} owner=vagrant group=vagrant
25
26      - name: Set link to tomcat 8
27        file: src=/opt/{{ tomcat_base_name }} dest=/opt/tomcat state=link force=yes
28
29      - name: setup setenv.sh
30        template: dest="/opt/{{ tomcat_base_name }}/bin/setenv.sh"
31        src="roles/tomcat8/templates/setenv.sh.j2" mode=755
32        when: catalina_opts is defined
33
34      - shell: ls /opt/{{ tomcat_base_name }}/bin/*.sh
35        register: tomcat_scripts
36        ignore_errors: yes
```

Inventories



Production

```
1 [application-server]
2 192.168.33.10
3 ubuntu-server db_host=mysql01
4
5 [mysql-db-server]
6 mysql[01:10]
7
8 [oracle-db-server]
9 db-[a:f].oracle.company.com
10
11 [database-server:children]
12 mysql-db-server
13 oracle-db-server
14
15 [application-server:vars]
16 message="Welcome"
17
18 [database-server:vars]
19 message="Hello World!"
```

Test

```
1 [application-server]
2 192.168.33.10
3
4 [database-server]
5 192.168.33.10
6
```

Inventories



```
12
13 - name: Download current Tomcat 8 version
14   local_action: get_url url="http://archive.apache.org/dist/tomcat/tomcat-8/v{{ tomcat_version
15   }}/bin/{{ tomcat_base_name }}.tar.gz" dest=/tmp
16
17 - name:
18   file: name=/opt mode=777
19   become: yes
20   become_method: sudo
21
22 - name: Install Tomcat 8
23   unarchive: src=/tmp/{{ tomcat_base_name }}.tar.gz dest=/opt creates=/opt/{{ tomcat_base_name
24   }} owner=vagrant group=vagrant
25
26 - name: Set link to tomcat 8
27   file: src=/opt/{{ tomcat_base_name }} dest=/opt/tomcat state=link force=yes
28
29 - name: setup setenv.sh
30   template: dest="/opt/{{ tomcat_base_name }}/bin/setenv.sh"
31   src="roles/tomcat8/templates/setenv.sh.j2" mode=755
32   when: catalina_opts is defined
33
34 - shell: ls /opt/{{ tomcat_base_name }}/bin/*.sh
35   register: tomcat_scripts
36   ignore_errors: yes
37
38 - name: ensure tomcat scripts are executable
39   file: name={{item}} mode=755
40   with_items: tomcat_scripts.stdout_lines
41
42 - name: install init.d script for tomcat
43   copy: src=roles/tomcat8/files/init.d/tomcat dest=/etc/init.d/tomcat owner=vagrant
44   group=vagrant mode=755
45   become: yes
46   become_method: sudo
```


Templates

- setenv.sh.j2

```
1 CATALINA_OPTS="{{ catalina_opts }}"
```


Templates - Jinja2

- Templating engine für Python


```
<title>{% block title %}{% endblock %}</title>
<ul>
  {% for user in users %}
    <li><a href="{{ user.url }}">{{ user.username }}</a></li>
  {% endfor %}
</ul>
```

- Mehr Information unter
<http://jinja.pocoo.org/docs/dev/>

Setup Application Server Playbook




Setup Database Server Playbook



```
1  hosts: database-server
2  become: yes
3  become_method: sudo
4
5  tasks:
6    - name: install mysql db
7      apt: name=mysql-server state=present
8
9    - name: installs python-mysqldb
10     apt: name=python-mysqldb state=present
11
12    - name: start mysql
13     service: name=mysql state=started
14
15    - name: set bind address
16     lineinfile: dest=/etc/mysql/my.cnf
17       line='bind-address = 0.0.0.0'
18       state=present
19       regexp=^bind-address(.)
20     notify: restart mysql
21
22    - name: creates db user dba
23     mysql_user: name=dba password=g3h3lm priv=*.*:ALL,GRANT state=present host=%
24
25  handlers:
26    - name: restart mysql
27     service: name=mysql state=restarted
28
```

Setup Database Server Playbook



Setup Database Server Playbook



```
1  hosts: application-server
2  vars:
3      tomcat_version: 8.0.24
4      tomcat_base_name: apache-tomcat-{{ tomcat_version }}
5      #catalina_opts: "-Dkey=value"
6
7  tasks:
8      - name: install java
9        apt: name=openjdk-7-jdk state=present
10       become: yes
11       become_method: sudo
12
13      - name: Download current Tomcat 8 version
14        local_action: get_url url="http://archive.apache.org/dist/tomcat/tomcat-8/v{{ tomcat_version
15        }}/bin/{{ tomcat_base_name }}.tar.gz" dest=/tmp
16
17      - name:
18        file: name=/opt mode=777
19        become: yes
20        become_method: sudo
21
22      - name: Install Tomcat 8
23        unarchive: src=/tmp/{{ tomcat_base_name }}.tar.gz dest=/opt creates=/opt/{{ tomcat_base_name
24        }} owner=vagrant group=vagrant
25
26      - name: Set link to tomcat 8
27        file: src=/opt/{{ tomcat_base_name }} dest=/opt/tomcat state=link force=yes
28
29      - name: setup setenv.sh
30        template: dest="/opt/{{ tomcat_base_name }}/bin/setenv.sh"
31        src="roles/tomcat8/templates/setenv.sh.j2" mode=755
32        when: catalina_opts is defined
33
34      - shell: ls /opt/{{ tomcat_base_name }}/bin/*.sh
35        register: tomcat_scripts
36        ignore_errors: yes
```




```
12
13 - name: Download current Tomcat 8 version
14   local_action: get_url url="http://archive.apache.org/dist/tomcat/tomcat-8/v{{ tomcat_version
15 }}/bin/{{ tomcat_base_name }}.tar.gz" dest=/tmp
16
17 - name:
18   file: name=/opt mode=777
19   become: yes
20   become_method: sudo
21
22 - name: Install Tomcat 8
23   unarchive: src=/tmp/{{ tomcat_base_name }}.tar.gz dest=/opt creates=/opt/{{ tomcat_base_name
24 }} owner=vagrant group=vagrant
25
26 - name: Set link to tomcat 8
27   file: src=/opt/{{ tomcat_base_name }} dest=/opt/tomcat state=link force=yes
28
29 - name: setup setenv.sh
30   template: dest="/opt/{{ tomcat_base_name }}/bin/setenv.sh"
31   src="roles/tomcat8/templates/setenv.sh.j2" mode=755
32   when: catalina_opts is defined
33
34 - shell: ls /opt/{{ tomcat_base_name }}/bin/*.sh
35   register: tomcat_scripts
36   ignore_errors: yes
37
38 - name: ensure tomcat scripts are executable
39   file: name={{item}} mode=755
40   with_items: tomcat_scripts.stdout_lines
41
42 - name: install init.d script for tomcat
43   copy: src=roles/tomcat8/files/init.d/tomcat dest=/etc/init.d/tomcat owner=vagrant
44   group=vagrant mode=755
45   become: yes
46   become_method: sudo
```

```
1  hosts: database-server
2  become: yes
3  become_method: sudo
4
5  tasks:
6    - name: install mysql db
7      apt: name=mysql-server state=present
8
9    - name: installs python-mysqldb
10     apt: name=python-mysqldb state=present
11
12    - name: start mysql
13      service: name=mysql state=started
14
15    - name: set bind address
16      lineinfile: dest=/etc/mysql/my.cnf
17        line='bind-address = 0.0.0.0'
18        state=present
19        regexp=^bind-address(.)
20      notify: restart mysql
21
22    - name: creates db user dba
23      mysql_user: name=dba password=g3h3lm priv=*.*:ALL,GRANT state=present host=%
24
25  handlers:
26    - name: restart mysql
27      service: name=mysql state=restarted
28
```

Roles

```
roles/  
  common/  
    files/  
    templates/  
    tasks/  
    handlers/  
    vars/  
    defaults/  
    meta/
```



Setup Playbooks mit Roles


- Setup Application Server

```
1  - hosts: application-server
2    roles:
3      - jdk
4      - { role: tomcat8, tomcat_version: 8.0.30 }
5
6
7
```

- Setup Database Server

```
1  - hosts: database-server
2    roles:
3      - mysql
4
5
6  |
```


Java Webapplikation Deployment




Deploy Application Playbook

```
1 - hosts: application-server
2   roles:
3     - {role: deploy-on-tomcat, webapp_source_path: ./demo-app-ansible-deploy-1.0-
  4       SNAPSHOT.war, webapp_target_name: demo }
```

deploy-on-tomcat Role



deploy-on-tomcat Role



The image shows a screenshot of an IDE with two panels. The left panel displays a file tree for an Ansible project. The right panel shows the content of the selected file, `stop-tomcat.yml`.


File Tree Structure:

- ansible
 - roles
 - deploy-on-tomcat
 - defaults
 - main.yml
 - tasks
 - cleanup-webapp.yml
 - deploy-webapp.yml
 - main.yml
 - start-tomcat.yml
 - stop-tomcat.yml (selected)
 - deploy-demo.yml


Task Content (stop-tomcat.yml):

```
1  name: stop tomcat
2    # service: name=tomcat state=stopped
3    command: service tomcat stop
4
5  - name: wait tomcat shutdown
6    wait_for: port=8080 state=stopped timeout=60
7
```


deploy-on-tomcat Role



deploy-on-tomcat Role




The image shows a screenshot of an IDE with two panels. The left panel displays a file explorer for an Ansible project structure:

- ansible
 - roles
 - deploy-on-tomcat
 - defaults
 - main.yml
 - tasks
 - cleanup-webapp.yml
 - deploy-webapp.yml (highlighted)
 - main.yml
 - start-tomcat.yml
 - stop-tomcat.yml
 - deploy-demo.yml


The right panel, titled 'Aktuelles Projekt', shows the content of the selected `deploy-webapp.yml` file, which contains three tasks:

```
1 name: delete previous backup
2   file: path={{ tomcat_app_base }}/{{
3     webapp_target_name }}.war.previous state=absent
4
5 - name: create new backup
6   command: mv {{ tomcat_app_base }}/{{
7     webapp_target_name }}.war {{ tomcat_app_base }}/{{
8     webapp_target_name }}.war.previous
9   ignore_errors: yes
10
11 - name: copy webapp {{ webapp_source_path }} to {{
12   webapp_target_name }}
13   copy: src={{ webapp_source_path }} dest={{
14     tomcat_app_base }}/{{ webapp_target_name }}.war
15   mode=660
```

deploy-on-tomcat Role



deploy-on-tomcat Role




Deploy Application Playbook









Ad-hoc-Kommando



Warum Roles?



Warum Roles?


	deploy-demo1-app.yml
	deploy-demo2-app.yml
	setup-demo1-app-server.yml
	setup-demo1-database.yml
	setup-demo2-app-server.yml
	setup-demo2-database.yml

Warum Roles?


```
1 - hosts: demo1-application-server
2   roles:
3     - {role: deploy-on-tomcat, webapp_source_path: ./demo1-1.0-
4       SNAPSHOT.war, webapp_target_name: demo1 }
```

```
1 - hosts: demo2-application-server
2   roles:
3     - {role: deploy-on-tomcat, webapp_source_path: ./demo2-1.0-
4       SNAPSHOT.war, webapp_target_name: demo2 }
5
```

Ansible Infrastruktur



Ansible Tower



Wie werden Ansible Skripte getestet?

- `ansible-playbook --check`
- `ansible-playbook --syntax-check`
- Jenkins + Vagrant
- Rspec tests



ServerSpec Tests

```
1 require 'spec_helper'
2
3 describe package('mysql-server') do
4   it { should be_installed }
5 end
6
7 describe service('mysql') do
8   it { should be_enabled }
9   it { should be_running }
10 end
11
12 describe 'MySQL config parameters' do
13   context mysql_config('bind-address') do
14     its(:value) { should eq '0.0.0.0' }
15   end
16 end
17
```

```
1 require 'spec_helper'
2
3 describe package('openjdk-7-jdk') do
4   it { should be_installed }
5 end
6
7 describe command('ls /etc/init.d/tomcat') do
8   its(:exit_status) { should eq 0 }
9 end
10
11 describe command('ls /opt/tomcat') do
12   its(:exit_status) { should eq 0 }
13 end
14
```

ServerSpec Tests



Wie unterscheidet sich Ansible zu seiner Konkurrenz?

Vergleich

Ansible

- Orchestrierung über SSH
- Benötigt keine Rootrechte auf Zielsystem
- Konfigurationsmgmt + Applikationsdeployment
- Monitoringtool nur in der Enterprise Variante
- Skripte mehr imperativ
- Windows-Support rudimentär
- Skripte OS- bzw. Distributions-spezifisch

Puppet

- Client-Server Architektur
- Für komfortables Arbeiten benötigt es Rootrechte
- Konfigurationsmgmt
- Monitoringtools Open Source
- Skripte mehr deklarativ
- Windows-Support
- Skripte können OS-unspezifisch sein

Vergleich

Puppet

```
▼ class nodejs {  
  ▼ class { 'apt':  
    }  
  ▼ exec { 'apt-get-update':  
    command => '/usr/bin/apt-get update',  
    }  
  ▼ package { 'software-properties-common' :  
    ensure => installed,  
    require => Exec['apt-get-update'],  
    }  
  apt::ppa { 'ppa:chris-lea/node.js' :}  
  ▼ package { 'nodejs' :  
    ensure => installed,  
    require => Apt::Ppa [ 'ppa:chris-lea/node.js' ],  
    }  
}
```


Ansible

```
- name: add nodejs ppa  
  apt_repository: repo='ppa:chris-lea/node.js'  
  
- name: install nodejs package  
  apt: name=nodejs update-cache=yes
```

Weitere Einsatzszenarien aus Entwicklersicht


Systemkonfiguration für Entwickler

Organisatorische Ausgangslage
Realität




Systemkonfiguration für Entwickler

Prozess zwischen Development und Operation




Systemkonfiguration für Entwickler

Lösungsidee mit Ansible



Systemkonfiguration für Entwickler


Variante - Prozess zwischen Development und Operation



- Rootrechte bei Systemadmins
- Developer müssen selber entscheiden, wie der Server konfiguriert sein soll.
- Deploymentvorgang in der Verantwortlichkeit der Developer


Systemkonfiguration für Entwickler

Lösungsvariante




Systemkonfiguration für Entwickler

Produktionsserver sind beim externen Hoster





Systemkonfiguration für Entwickler

Lösungsidee



Weitere Informationen



<http://docs.ansible.com/>

Weitere Informationen



Software organisieren



Ansible – warum Konfigurationsmanagement auch für Entwickler interessant sein kann

Sandra Parsick



JUnit 5
Das nächste große
Release steht vor
der Tür

Ansible
Konfigurationsmana-
gement auch für
Entwickler

Spring Boot Starter
Komfortable Modula-
risierung und Konfi-
guration



Fragen?

@SandraParsick

mail@sandra-parsick.de

<https://github.com/sparsick/ansible-talk.git>