

Prof. Dr. Friedrich, Dr. Lenzner, Boockmeyer, Neumann, Stangl
Sommersemester 2017

Week 11 – (Adv.) Competitive Programming

Abgabe 03.07.2017 17:00 Uhr, über das Judge-Interface

dhl: (100 points - 2 seconds timelimit)

You have recently been employed by the IT department of DHL. Your first assignment is to help them optimise the parcel collection process in the warehouse. To simplify, we model the problem as follows. There are two stacks of n parcels each, one containing very bulky items (stack A) and the other very heavy items (stack B). The volumes of the parcels on stack A are denoted by integers a_1, \dots, a_n , where a_i is the volume of i th parcel from the bottom. For example, a_1 is the volume of the parcel on the bottom of A , and a_n of the parcel on the top. Similarly, the weights of the parcels on stack B are denoted by integers b_1, \dots, b_n , again from bottom to top.

A machine that manipulates parcels can only access the parcel of the top of each stack. Each time a truck comes to collect parcels, the machine loads a certain number of parcels from both A and B . For example, the machine can load the top two parcels from A (pick up the top one, load it, pick up the next one, load it) and the top three parcels from B . After that the truck leaves and a new one comes. This process is repeated until there are no more parcels left. Due to a malfunction in the software, the machine must load at least one parcel from A and one from B each time, otherwise it breaks and you get fired! In particular, both stacks must become empty in the same round.

The cost of one loading is equal to $(S_a - k_a) \cdot (S_b - k_b)$, where S_a is the sum of volumes of parcels loaded from A , S_b is the sum of weights of parcels loaded from B , and k_a and k_b are the number of parcels loaded from A and B , respectively. This formula represents the difficulty of handling bulky and heavy things at the same time. For example, if in the first round the machine loads the top two parcels from A and the top three parcels from B , the cost of such loading is $(a_n + a_{n-1} - 2) \cdot (b_n + b_{n-1} + b_{n-2} - 3)$. Then, if in the second round it loads one parcel from A and two from B , the new cost is $(a_{n-2} - 1) \cdot (b_{n-3} + b_{n-4} - 2)$, since these parcels are now on top of the stack. Your job is to schedule loading as such that the sum of all costs is the smallest possible without getting fired.

Input The first line of the input contains the number of test cases $t \leq 20$. Each of the t test cases is described as follows.

- It starts with a line that contains one integer $1 \leq n \leq 300$, the number of parcels on each of the tracks.
- The following line contains integers a_1, \dots, a_n ($1 \leq a_i \leq 100$), separated by single spaces, where a_i denotes the volume of i th parcel in A from the bottom.
- The following line contains integers b_1, \dots, b_n ($1 \leq b_i \leq 100$), separated by single spaces, where b_i denotes the weight of i th parcel in B from the bottom.

Output For every test case the corresponding output appears on a separate line. It consists of one integer, the smallest possible sum of costs required to load all parcels without getting fired.

Points There are three groups of test sets. The total number of points is 100.

- easy*: For the first group of test sets, worth 20 points, you may assume that $n \leq 6$.
- medium*: For the second group of test sets, worth 50 points, you may assume that $n \leq 100$.
- hard*: For the third group of test sets, worth 30 points, you may assume that $n \leq 300$.

Sample Input

```

3
5
1 3 4 2 5
5 4 4 5 1
8
1 4 1 9 1 3 1 4
3 2 3 1 6 2 7 5
```

```

8
4 5 9 8 2 5 3 8
9 11 4 7 4 8 6 7
```

Sample Output

```

0
12
193
```