

POSIX.1c/D10 Summary

Disclaimer

Copyright (C) 1995 by Sun Microsystems, Inc.
All rights reserved.

This file is a product of SunSoft, Inc. and is provided for unrestricted use provided that this legend is included on all media and as a part of the software program in whole or part. Users may copy, modify or distribute this file at will.

THIS FILE IS PROVIDED AS IS WITH NO WARRANTIES OF ANY KIND INCLUDING THE WARRANTIES OF DESIGN, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, USAGE OR TRADE PRACTICE.

This file is provided with no support and without any obligation on the part of SunSoft, Inc. to assist in its use, correction, modification or enhancement.

SUNSOFT AND SUN MICROSYSTEMS, INC. SHALL HAVE NO LIABILITY WITH RESPECT TO THE INFRINGEMENT OF COPYRIGHTS, TRADE SECRETS OR ANY PATENTS BY THIS FILE OR ANY PART THEREOF.

IN NO EVENT WILL SUNSOFT OR SUN MICROSYSTEMS, INC. BE LIABLE FOR ANY LOST REVENUE OR PROFITS OR OTHER SPECIAL, INDIRECT AND CONSEQUENTIAL DAMAGES, EVEN IF THEY HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

SunSoft, Inc.
2550 Garcia Avenue
Mountain View, California 94043

Introduction

All source that uses POSIX.1c threads must include the header file.

```
#include <pthread.h>
```

In addition, Solaris requires the pre-processor symbol **_REENTRANT** to be defined in the source code before any C source (including header files).

```
#define_REENTRANT
```

The POSIX.1c thread library should be the last library specified on the `cc(1)` command line.

```
voyager% cc -D_REENTRANT ... -lpthread
```

Name Space

Each POSIX.1c type is of the form:

`pthread[_object]_t`

Each POSIX.1c function has the form

`pthread[_object]_operation[_np]_NP]`

where *object* is a type (not required if object is a thread), *operation* is a type-specific operation and *np* (or *NP*) is used to identify non-portable, implementation specific functions.

All POSIX.1c functions (except for `pthread_exit`, `pthread_getspecific` and `pthread_self`) return zero (0) for success or an `errno` value if the operation fails.

There are eight(8) POSIX.1c types:

Table 0-1 POSIX.1c types

Type	Description
pthread_attr_t	Thread attribute
pthread_mutexattr_t	Mutual Exclusion Lock attribute
pthread_condattr_t	Condition variable attribute
pthread_mutex_t	Mutual Exclusion Lock (mutex)
pthread_cond_t	Condition variable (cv)
pthread_t	Thread ID
pthread_once_t	Once-only execution
pthread_key_t	Thread Specific Data (TSD) key

Feature Test Macros

POSIX.1c consists of a base (or common) component and a number of implementation optional components The base is the set of required operations to be supplied by every implementation. The pre-processor symbol (**_POSIX_THREADS**) can be used to test for the presence of the POSIX.1c base. Additionally, the standards document describes a set of six (6) optional components. A pre-processor symbol can be used to test for the presence of each All of the symbols appear in the following table.

Table 0-2 POSIX.1c Feature Test Macros

Feature Test Macro	Description
_POSIX_THREADS	base threads
_POSIX_THREAD_ATTR_STACKADDR	stack address attribute
_POSIX_THREAD_ATTR_STACKSIZE	stack size attribute
_POSIX_THREAD_PRIORITY_SCHEDULING	thread priority scheduling
_POSIX_THREAD_PRIO_INHERIT	mutex priority inheritance
_POSIX_THREAD_PRIO_PROTECT	mutex priority ceiling
_POSIX_THREAD_PROCESS_SHARED	inter-process synchronization

Macro Dependency

If **_POSIX_THREAD_PRIO_INHERIT** is defined then **_POSIX_THREAD_PRIORITY_SCHEDULING** is defined.

If `_POSIX_THREAD_PRIO_PROTECT` is defined then
`_POSIX_THREAD_PRIORITY_SCHEDULING` is defined.

If `_POSIX_THREAD_PRIORITY_SCHEDULING` is defined then `_POSIX_THREADS` is defined.

If `_POSIX_THREADS` is defined then `_POSIX_THREAD_SAFE_FUNCTIONS` is defined.

POSIX.1c API

In the following sections, function arguments that are of the form:

type name = **NULL**

indicate that a value of **NULL** may safely be used for name.

```
int pthread_atfork( void (*prepare)(void) = NULL,
                  void (*parent)(void) = NULL,
                  void (*child)(void) = NULL );
```

Register functions to be called during fork execution.

errors **ENOMEM**

notes prepare functions are called in reverse order of registration.

parent and child functions are called in order of registration.

Thread Attributes

All thread attributes are set in an attribute object by a function of the form:

```
int pthread_attr_setname( pthread_attr_t *attr, Type t );
```

All thread attributes are retrieved from an attribute object by a function of the form:

```
int pthread_attr_getname( const pthread_attr_t *attr, Type *t );
```

Where *name* and *Type* are from the table below.

Table 0-3 Thread Attributes

Name and Type	Feature Test Macro	Value(s)
int inheritsched	<code>_POSIX_THREAD_PRIORITY_SCHEDULING</code>	<code>PTHREAD_INHERIT_SCHED</code> , <code>PTHREAD_EXPLICIT_SCHED</code>
int schedpolicy	<code>_POSIX_THREAD_PRIORITY_SCHEDULING</code>	<code>SCHED_FIFO</code> , <code>SCHED_RR</code> , <code>SCHED_OTHER</code>
struct sched_param schedparam	<code>_POSIX_THREADS</code>	POSIX.1b, Section 13
int contentionscope	<code>_POSIX_THREAD_PRIORITY_SCHEDULING</code>	<code>PTHREAD_SCOPE_SYSTEM</code> , <code>PTHREAD_SCOPE_PROCESS</code>
size_t stacksize	<code>_POSIX_THREAD_ATTR_STACKSIZE</code>	<code>>= PTHREAD_STACK_MIN</code>

Table 0-3 Thread Attributes

Name and Type	Feature Test Macro	Value(s)
void *stackaddr	<code>_POSIX_THREAD_ATTR_STACKADDR</code>	void *stack
int detachstate	<code>_POSIX_THREADS</code>	<code>PTHREAD_CREATE_DETACHED</code> , <code>PTHREAD_CREATE_JOINABLE</code>

```
int pthread_attr_init( pthread_attr_t *attr );
    Initialize a thread attribute object.
    errors ENOMEM

int pthread_attr_destroy( pthread_attr_t *attr );
    Destroy a thread attribute object.
    errors none
```

Thread Management

```
int pthread_create( pthread_t *thread,
                  const pthread_attr_t *attr = NULL,
                  void *(*entry)(void *), void *arg );
    Create a new thread of execution.
    errors EAGAIN, EINVAL
    note Maximum number of PTHREAD_THREADS_MAX threads per process.

int pthread_detach( pthread_t thread );
    Set the detachstate of the specified thread to PTHREAD_CREATE_DETACHED.
    errors EINVAL, ESRCH

pthread_t pthread_self( void );
    Return the thread ID of the calling thread.
    errors none

int pthread_equal( pthread_t t1, pthread_t t2 );
    Compare two thread IDs for equality.
    errors none

void pthread_exit( void *status = NULL );
    Terminate the calling thread.
    errors none

int pthread_join( pthread_t thread, void **status = NULL );
    Synchronize with the termination of a thread.
    errors EINVAL, ESRCH, EDEADLK
    note This function is a cancellation point.
```

```
#include <sched.h>

int pthread_getschedparam( pthread_t thread, int *policy, struct sched_param *param );
    Get the scheduling policy and parameters of the specified thread.
    control _POSIX_THREAD_PRIORITY_SCHEDULING
    errors ENOSYS, ESRCH

#include <sched.h>

int pthread_setschedparam( pthread_t thread, int policy,
                          const struct sched_param *param );
```

Set the scheduling policy and parameters of the specified thread.
control **_POSIX_THREAD_PRIORITY_SCHEDULING**
errors **ENOSYS, EINVAL, ENOTSUP, EPERM, ESRCH**
policy { **SCHED_RR, SCHED_FIFO, SCHED_OTHER** }

Mutex Attributes

All mutex attributes are set in a mutex attribute object by a function of the form:

```
int pthread_mutexattr_setname( pthread_attr_t *attr, Type t );
```

All mutex attributes are retrieved from a mutex attribute object by a function of the form:

```
int pthread_mutexattr_getname( const pthread_attr_t *attr, Type *t );
```

Where *name* and *Type* are from the table below

Table 0-4 Mutex Attributes

Name and Type	Feature Test Macro	Value(s)
int protocol	_POSIX_THREAD_PRIO_INHERIT, _POSIX_THREAD_PRIO_PROTECT	PTHREAD_PRIO_NONE, PTHREAD_PRIO_PROTECT, PTHREAD_PRIO_INHERIT
int pshared	_POSIX_THREAD_PROCESS_SHARED	PTHREAD_PROCESS_SHARED, PTHREAD_PROCESS_PRIVATE
int prioceiling	_POSIX_THREAD_PRIO_PROTECT	POSIX.1b, Section 13
int pthread_mutexattr_init(pthread_mutexattr_t *attr);	Initialize a mutex attribute object. errors ENOMEM	
int pthread_mutexattr_destroy(pthread_mutexattr_t *attr);	Destroy a mutex attribute object. errors EINVAL	

Mutex Usage

```
int pthread_mutex_init( pthread_mutex_t *mutex, const pthread_mutexattr_t *attr = NULL );  
pthread_mutex_t mutex = PTHREAD_MUTEX_INITIALIZER;  
Initialize a mutex.  
errors     EAGAIN, ENOMEM, EPERM, EBUSY, EINVAL  
  
int pthread_mutex_destroy( pthread_mutex_t *mutex );  
Destroy a mutex.  
errors     EBUSY, EINVAL  
  
int pthread_mutex_getprioceiling( const pthread_mutex_t *mutex, int *prioceiling );  
Get the prioceiling value of the specified mutex.  
control     _POSIX_THREAD_PRIO_PROTECT  
errors     ENOSYS, EINVAL, EPERM  
  
int pthread_mutex_setprioceiling( pthread_mutex_t *mutex, int prioceiling,  
int *old_ceiling );
```

Set the prioceiling value and return the old prioceiling value in the specified mutex.
control **_POSIX_THREAD_PRIO_PROTECT**
errors **ENOSYS, EINVAL, EPERM**

```
int pthread_mutex_lock( pthread_mutex_t *mutex );  
Acquire the indicated mutex.  
errors     EINVAL, EDEADLK  
  
int pthread_mutex_trylock( pthread_mutex_t *mutex );  
Attempt to acquire the indicated mutex.  
errors     EINVAL, EBUSY, EINVAL  
  
int pthread_mutex_unlock( pthread_mutex_t *mutex );  
Release the (previously acquired) mutex.  
errors     EINVAL, EPERM
```

Once-only Execution

```
pthread_once_t once = PTHREAD_ONCE_INIT;  
Initialize a once control variable.  
  
int pthread_once( pthread_once_t *once_control, void (*init_routine)(void) );  
Execute init_routine once.  
errors     none specified
```

Condition Variable Attributes

All condition variable attributes are set in a condition variable attribute object by a function of the form:

```
int pthread_condattr_setname( pthread_condattr_t *attr, Type t );
```

All condition variable attributes are retrieved from a condition variable attribute object by a function of the form:

```
int pthread_condattr_getname( const pthread_condattr_t *attr, Type *t );
```

Where *name* and *Type* are from the table below

Table 0-5 Condition Variable Attributes

Name and Type	Feature Test Macro	Value(s)
int pshared	_POSIX_THREAD_PROCESS_SHARED	PTHREAD_PROCESS_SHARED, PTHREAD_PROCESS_PRIVATE
int pthread_condattr_init(pthread_condattr_t *attr);	Initialize a condition variable attribute object. errors ENOMEM	
int pthread_condattr_destroy(pthread_condattr_t *attr);	Destroy a condition variable attribute object. errors EINVAL	

Condition Variable Usage

```
int pthread_cond_init( pthread_cond_t *cond,
```

```

        const pthread_condattr_t *attr = NULL );
pthread_cond_t      cond      = PTHREAD_COND_INITIALIZER;
        Initialize a condition variable.
        errors      EAGAIN, ENOMEM, EBUSY, EINVAL
int      pthread_cond_destroy( pthread_cond_t *cond );
        Destroy a condition variable.
        errors      EBUSY, EINVAL
int      pthread_cond_signal( pthread_cond_t *cond );
        Unblock at least one thread currently blocked in the specified condition variable.
        errors      EINVAL
int      pthread_cond_broadcast( pthread_cond_t *cond );
        Unblock all threads currently blocked on the specified condition variable.
        errors      EINVAL
int      pthread_cond_wait( pthread_cond_t *cond, pthread_mutex_t *mutex );
        Block on the specified condition variable.
        errors      EINVAL
        note      This function is a cancellation point.
int      pthread_cond_timedwait( pthread_cond_t *cond, pthread_mutex_t *mutex,
        const struct timespec *abstime );
        Block on the specified condition variable not longer than the specified absolute time.
        errors      ETIMEDOUT, EINVAL
        note      This function is a cancellation point.

```

Thread Specific Data

```

int      pthread_key_create( pthread_key_t *key, void (*destructor)(void *) = NULL );
        Create a thread-specific data key.
        errors      EAGAIN, ENOMEM
        note      system limit of PTHREAD_KEYS_MAX per process.
                  system limit of PTHREAD_DESTRUCTOR_ITERATIONS calls to destructor per
                  thread exit.
int      pthread_key_delete( pthread_key_t key );
        Destroy a thread-specific data key.
        errors      EINVAL
void     *pthread_getspecific( pthread_key_t key );
        Return the value bound to the given key for the calling thread.
        errors      none
int      pthread_setspecific( pthread_key_t key, const void *value );
        Set the value for the given key in the calling thread.
        errors      ENOMEM, EINVAL

```

Signal Management

```

#include <signal.h>
int      pthread_sigmask( int how, const sigset_t *newmask = NULL, sigset_t *oldmask = NULL );
        Examine or change calling threads signal mask.

```

```

        errors      EINVAL
        how      { SIG_BLOCK, SIG_UNBLOCK, SIG_SETMASK }
#include <signal.h>
int      pthread_kill( pthread_t thread, int signo );
        Deliver signal to indicated thread.
        errors      ESRCH, EINVAL
#include <signal.h>
int      sigwait( const sigset_t *set, int *sig );
        Synchronously accept a signal.
        errors      EINVAL, EINTR
        note      This function is a cancellation point.

```

Cancellation

```

int      pthread_setcancelstate( int state, int *oldstate );
        Set the cancellation state for the calling thread.
        errors      EINVAL
        state     { PTHREAD_CANCEL_ENABLE, PTHREAD_CANCEL_DISABLE }
int      pthread_setcanceltype( int type, int *oldtype );
        Set the cancellation type for the calling thread.
        errors      EINVAL
        type      { PTHREAD_CANCEL_DEFERRED, PTHREAD_CANCEL_ASYNCHRONOUS }
int      pthread_cancel( pthread_t thread );
        Cancel the specified thread.
        errors      ESRCH
        note      threads that have been cancelled terminate with a status of PTHREAD_CANCELED.
void     pthread_testcancel( void );
        Introduce a cancellation point.
        errors      none
        note      This function is a cancellation point.
void     pthread_cleanup_pop( int execute );
        Pop the top item from the cancellation stack and optionally execute it.
        errors      none specified
        note      push and pop operations must appear at the same lexical level.
        execute   { 1, 0 }
void     pthread_cleanup_push( void (*routine)(void *), void *arg );
        Push an item onto the cancellation stack.
        errors      none specified

```