

	<i>Page</i>
Table 5.27 Topographic enhancement factors	142
Table 5.28 Point–area relation of PMP with different durations in orographic regions in Henan Province, China.....	146
Table 6.1 Frequency factors Km for Chambal, Betwa, Sone and Mahi watersheds	169
Table 6.2 PMP for 1- and 2-day durations for Chambal and Betwa watersheds.....	170
Table 6.3 Catchment areas in the Chambal watershed	171
Table 6.4 Sub-basin location in the Chambal watershed.....	171
Table 6.5 SPS for the Chambal watershed in India.....	172
Table 6.6 Moisture maximization factors for three typical storms.....	172
Table 6.7 Area reduction factor for storms in the Chambal watershed	173
Table 6.8 Calculated results of PMP for the Chambal watershed.....	173
Table 6.9 MAF for each grid of either Chambal or Betwa watershed	174
Table 6.10 PMP for each grid of either Chambal or Betwa watershed	175
Table 6.11 DAD enveloping relations of typhoon storm extremes in non-orographic regions on Hainan Island (Zhang, 1988)	177
Table 6.12 Comprehensive adjustment coefficient for 24-hour storms in the Changhuajiang River basin of Hainan Island (Zhang, 1988)	178
Table 7.1 Qualitative characteristics of PMP storm model in the San-Hua region of the Yellow River	186
Table 7.2 The areal mean rainfall amount of the July 1958 storm in the San-Hua region on the Yellow River	190
Table 7.3 Table of calculation of efficiencies of the July 1958 typical storm in the San-Hua region on the Yellow River	191
Table 7.4 Calculation of moisture and efficiency amplifications of the July 1958 typical storm in the San-hua Region on the Yellow River	191
Table 7.5 Five-day PMP in the San-Hua region on the Yellow River	191
Table 7.6 Key characteristics of PMP for the Manwan project	199
Table 7.7 Table of typical storm process sequence in Manwan in 1966.....	200
Table 7.8 Table of combined storm process sequence using similar process substitution method for the 1966 typical storm in Manwan	200
Table 7.9 Watershed profiles for four key projects in China.....	206
Table 7.10 Methods for deriving PMP/PMF for four key projects in China.....	207
Table 7.11 Peak and volume of the flood at Yichang station in 1870 (CJWRC, 1997).....	208
Table 7.12 Simulated 1870 storm sequence	209
Table 7.13 PMF estimate for Three Gorges (Yichang) – scheme of simulating 1870 historical flood (Jin and Li, 1989)	210
Table A.1.1 Precipitable water (mm) between 1 000-hPa surface and indicated pressure (hPa) in a saturated pseudo-adiabatic atmosphere as a function of the 1 000-hPa dew point (°C)	213
Table A.1.2 Precipitable water (mm) between 1 000-hPa surface and indicated height (m) above that surface in a saturated pseudo-adiabatic atmosphere as a function of the 1 000-hPa dew point (°C)	215
Table A.1.3 Precipitable water (mm) in column of air above specified heights (m) as a function of the 1 000 hPa temperature (°C) (revised May 1981)	216
Table A.1.4 Mixing ratios along pseudo-adiabats for specified 1 000-hPa dew points and elevations in meters above the 1 000-hPa level	219
Table A.2.1 World's greatest known point rainfalls	222
Table A.2.2 World's near-record rainfalls	225
Table A.2.3 Maximum observed depth–area–duration data for China, the United States and India (average rainfall in mm) (Wang J., 2002)	226
Table A.2.4.1 Maximum and near-record known depth–area–duration data for northern and southern China (Wang J., 2002)	227
Table A.2.4.2 Depth–area–duration data of long-duration and large-area extraordinary storms in China (average rainfall in mm) (Wang J., 2002).....	229
Table A.2.5 Maximum observed depth–area–duration data for the United States (WMO-No. 332)...	230
Table A.2.6 Maximum observed depth–area–duration data for India (average rainfall in mm) (Wang G. and others, 2005)	231
Table A.3.1 World's greatest known floods	234
Table A.3.2 World's near-record floods	237