

	<i>Page</i>
6.2.2.7 Areal distribution	159
6.2.2.8 PMP for specific basins	160
6.2.3 Estimation of PMP for India	160
6.2.3.1 Introduction	160
6.2.3.2 Initial non-orographic PMP values	161
6.2.3.3 Adjustments to initial non-orographic PMP values	162
6.2.3.4 Final non-orographic PMP values	162
6.2.4 Estimating PMP for Chambal, Betwa, Sone and Mahi watersheds in India	166
6.2.4.1 Introduction	166
6.2.4.2 Estimating PMP for small watersheds	166
6.2.4.3 Estimating PMP for medium to large watersheds	166
6.2.4.4 Estimating PMP for super large watersheds	172
6.2.4.5 Temporal distribution of storms	172
6.2.4.6 Example application	172
6.2.5 PMP estimation for the Daguangba Project in Hainan Island, China	173
6.2.5.1 Introduction	173
6.2.5.2 Estimation of orographic components of storms in the Changhuajiang River basin	173
6.2.5.3 DAD relations of PMP for non-orographic regions on Hainan Island	174
6.2.5.4 Estimation of 24-hour PMP for Daguangba watershed	175
6.2.5.5 Analysis of the rationality of PMP estimates	178
6.3 CAUTIONARY REMARKS	178
CHAPTER 7. ESTIMATION OF PMP USING THE WATERSHED-BASED APPROACH AND ITS APPLICATION IN CHINA	179
7.1 INTRODUCTION	179
7.2 OVERVIEW OF THE APPROACH	179
7.2.1 Main characteristics	179
7.2.2 Process	179
7.2.3 Project characteristics and design requirements	179
7.2.4 Analysis of watersheds, characteristics of storms and floods, and meteorological causes	179
7.2.5 Deducing qualitative characteristics of storm models	181
7.2.5.1 Importance of correct storm model	181
7.2.5.2 Qualitative characteristics	181
7.2.5.3 Methods for determining characteristics	181
7.2.5.4 Example of qualitative characteristic analysis – San-Hua region, China	181
7.2.5.5 Similar work in other countries	183
7.2.6 Comprehensive analysis using multiple methods	184
7.2.7 Realistic results check	184
7.2.7.1 Checking each step	185
7.2.7.2 Comparison with historical extraordinary storms/floods in the watershed	185
7.2.7.3 Comparison with adjacent watersheds	185
7.2.7.4 Comparison with historical estimation results	185
7.2.7.5 Comparison with worldwide storm and flood records	185
7.2.7.6 Comparison with results of frequency analysis	186
7.2.7.7 Similar work in other countries	186
7.3 LOCAL MODEL METHOD	186
7.3.1 Applicable conditions	186
7.3.2 Model selection	186
7.3.3 Model suitability analysis	186
7.3.4 Model maximization	186
7.3.4.1 Summary	186
7.3.4.2 Selection of maximum moisture adjustment factor	187
7.3.4.3 Selection of maximum dynamic adjustment factor	187
7.3.4.4 Model maximization	187
7.3.5 Example calculations	188