

Compilers


Top-down Parsing

LEIC

FEUP-FCUP

2022

Compiler



Inter. code generation

Intermediate code

Instruction selection

Symbolic *assembly*

Register allocation

Assembly

Assembler & linker

Executable code



This lecture

Parsing

Recursive descent parsing

LL Parsing

Parsing

- ▶ Build an **AST** from a list of *tokens*
(or reject the program with a syntax error output)
- ▶ Parsing:
 - top-down* begin by the root (non-terminal initial symbol S) and find the leftmost derivation.
 - bottom-up* begin by the tokens and find the reversed rightmost derivation.
- ▶ *Top-down* parsing:
 - ▶ *recursive descent parsing*
 - ▶ predictive *parsing* (LL(1))

This lecture

Parsing

Recursive descent parsing

LL Parsing

Implemented directly in a programming language:

- ▶ Each non-terminal symbol corresponds to a **function** (or method)
- ▶ Each production correspond to a different **case**
(if the production is recursive, so it is the function)
- ▶ Consume tokens from **left to right**
- ▶ Decide which production to use using the **next token**

Example

Programming Language:

```
begin
  if 1=1 then
    begin
      print 0=11 ;  print 123=4
    end
  else
    print 11=42
  end
```

Example (cont.)

Grammar:

$$S \rightarrow \text{if } E \text{ then } S \text{ else } S$$
$$S \rightarrow \text{begin } S \ L$$
$$S \rightarrow \text{print } E$$
$$L \rightarrow \text{end}$$
$$L \rightarrow ; \ S \ L$$
$$E \rightarrow \text{num} = \text{num}$$

Implementation in C/Java

- ▶ *parsing* consumes *tokens* from the standard input

```
Token getToken(void); // read next token from the standard input
```

- ▶ Keep *look-ahead* token in a global variable:

```
Token next;           // next token
void advance(void) { // goes to next token
    next = getToken();
}
```

- ▶ *parsing* algorithm decides what to do using the *token* and the *look-ahead*
- ▶ `consume(...)` consumes a specific *token*

Implementation in C/Java (cont.)

```
void parse_S(void) {  
    switch(next) {  
        case IF:  
            advance(); parse_E(); consume(THEN);  parse_S();  
            consume(ELSE);  parse_S();  
            break;  
        case BEGIN:  
            advance();  parse_S();  parse_L();  
            break;  
        case PRINT:  
            advance(); parse_E();  
            break;  
        default:  
            error("syntax error");  
    }  
}
```

Implementation in C/Java (cont.)

```
void parse_E(void) {  
    consume(NUM);  consume(EQUAL); consume(NUM);  
}
```

```
void parse_L(void) {  
    switch(next) {  
        case END:  
            advance();  
            break;  
        case SEMI:  
            advance(); parse_S(); parse_L();  
            break;  
        default:  
            error("syntax error");  
    }  
}
```

Stop

- ▶ The program terminates without redundant *tokens*
- ▶ The parser must know when to finish
- ▶ Add a special *token* \$ meaning the end of file
- ▶ Add a new production rule $S' \rightarrow S\$$
- ▶ S' is now the new initial symbol

```
void accepted(void) {  
    parse_S();  
    consume(EOF);  
}
```

This lecture

Parsing

Recursive descent parsing

LL Parsing

- ▶ Parsing by recursive descent chooses the production rule based on the **next terminal symbol**
- ▶ We may need to rewrite the grammar to know what is the next terminal symbol

Example

$$\begin{array}{lll} E \rightarrow E + T & T \rightarrow T * F & F \rightarrow \text{num} \\ E \rightarrow E - T & T \rightarrow T / F & F \rightarrow (E) \\ E \rightarrow T & T \rightarrow F & \end{array}$$

Problems:

- ▶ How do we choose **which rule** to use from E and T ?
- ▶ How to avoid a cycle caused by **left recursion** in E and T ?

Eliminar recursão à esquerda

Consider the following grammar:

$$\begin{aligned}E &\rightarrow E + T \\E &\rightarrow T\end{aligned}$$

E produces sums of terms, i.e. $E \Rightarrow^* T + T + \dots + T$.

Let us define an equivalent grammar adding a new non-terminal symbol E' :

$$\begin{aligned}E &\rightarrow T E' \\E' &\rightarrow + T E' \\E' &\rightarrow \varepsilon\end{aligned}$$

This grammar is **right recursive**.

Eliminar recursão à esquerda (cont.)

$$E \rightarrow T E'$$

$$E' \rightarrow + T E'$$

$$E' \rightarrow \varepsilon$$

- ▶ Rules in E' have recursion on the right and not on the left
- ▶ We now may decide which rule to use based on the next symbol:
- ▶
 - + use $E' \rightarrow + T E'$
 - otherwise use $E' \rightarrow \varepsilon$

Eliminar recursão à esquerda (cont.)

Applying the same transformation to the initial grammar we get:

$$\begin{array}{lll} E \rightarrow T E' & T \rightarrow F T' & \\ E' \rightarrow + T E' & T' \rightarrow * F T' & F \rightarrow \text{num} \\ E' \rightarrow - T E' & T' \rightarrow / F T' & F \rightarrow (E) \\ E' \rightarrow \varepsilon & T' \rightarrow \varepsilon & \end{array}$$

We now may define a recursive descent parser.

Exercise: implement a recursive descent *parser* for this grammar.

Grammars $LL(1)$

- ▶ These grammars belong to a class called $LL(1)$: *Left-to-right parse, Leftmost derivation, 1-symbol look-ahead*
- ▶ $LL(1)$ contains all the grammars that may be implemented using recursive descent
- ▶ $LL(k)$ means: *Left-to-right parse, Leftmost derivation, k -symbols look-ahead*
- ▶ Let us implement a parser for $LL(1)$ grammars without recursion but using an auxiliary explicit stack.

FIRST

Let $G = (\Sigma, N, S, P)$ be a grammar and X a non-terminal symbol.

When the next token is x , we may use rule $X \rightarrow \gamma$ if

$$x \in \text{FIRST}(\gamma)$$

meaning that x is an *initial symbol* in derivations starting at γ .

To choose between two rule $X \rightarrow \gamma$ and $X \rightarrow \gamma'$ using only the next symbol we must guarantee that they do **not share initial symbols**:

$$\text{FIRST}(\gamma) \cap \text{FIRST}(\gamma') = \emptyset$$

Definition

$$\text{FIRST}(\gamma) = \{x \in \Sigma : \gamma \Rightarrow^* x\beta, \text{ for some } \beta\}$$

This means that $\text{FIRST}(\gamma)$ is the set of tokens at the beginning of words derived by γ .

- ▶ This definition is not useful to compute $\text{FIRST}(\gamma)$ for each rule $X \rightarrow \gamma$
- ▶ Let us see how to compute the set FIRST

FIRST (cont.)

$$\begin{array}{lll} E \rightarrow E + T & T \rightarrow T * F & F \rightarrow \text{num} \\ E \rightarrow T & T \rightarrow F & F \rightarrow (E) \end{array}$$

- ▶ Start computing FIRST directly for non-recursive rules e.g.

$$\text{FIRST}(F) = \{\text{num}, (\}$$

- ▶ Recursive rules must respect some equations; e.g. for T :

$$\begin{aligned} \text{FIRST}(T) &= \text{FIRST}(T * F) \cup \text{FIRST}(F) \\ \iff \text{FIRST}(T) &= \text{FIRST}(T) \cup \text{FIRST}(F) \end{aligned}$$

- ▶ The least solution for the previous equation is:

$$\text{FIRST}(T) = \text{FIRST}(F) = \{\text{num}, (\}$$

Let us see how to get the solution using an iterative method

- ▶ We will also need a predicate $\text{NULLABLE}(\gamma)$ to decide if a sequence may generate the **empty word**

Equations for FIRST and NULLABLE

- ▶ In the previous example we may define the simplification

$$\text{FIRST}(T * F) = \text{FIRST}(T)$$

because it is not possible to derive the empty word ε from T

- ▶ In general: to compute FIRST we need to know which non-terminals may derive ε

$$\text{NULLABLE}(X) = \begin{cases} \text{True} & , \text{ if } X \Rightarrow^* \varepsilon \\ \text{False} & , \text{ otherwise} \end{cases}$$

- ▶ Let us define this predicate by a set of equations

Equations for FIRST and NULLABLE (cont.)

$$\text{FIRST}(\varepsilon) = \emptyset$$

$$\text{FIRST}(a) = \{a\} \quad (a \in \Sigma)$$

$$\text{FIRST}(\alpha\beta) = \begin{cases} \text{FIRST}(\alpha) \cup \text{FIRST}(\beta), & \text{if NULLABLE}(\alpha) \\ \text{FIRST}(\alpha), & \text{otherwise} \end{cases}$$

$$\text{FIRST}(X) = \text{FIRST}(\gamma_1) \cup \dots \cup \text{FIRST}(\gamma_n),$$

where $X \rightarrow \gamma_i$ are all the rules for X

$$\text{NULLABLE}(\varepsilon) = \text{True}$$

$$\text{NULLABLE}(a) = \text{False} \quad (a \in \Sigma)$$

$$\text{NULLABLE}(\alpha\beta) = \text{NULLABLE}(\alpha) \wedge \text{NULLABLE}(\beta)$$

$$\text{NULLABLE}(X) = \text{NULLABLE}(\gamma_1) \vee \dots \vee \text{NULLABLE}(\gamma_n)$$

where $X \rightarrow \gamma_i$ are all the rules for X

Algorithm for computing FIRST and NULLABLE

Iterative algorithm:

1. Initially $\text{NULLABLE}(X) := \text{False}$ and $\text{FIRST}(X) := \emptyset$ for every non-terminal symbol
2. Compute new elements for the right-hand side of productions using the previous equations
3. Repeat this until the sets do not change (reach a *fixpoint*)

Algorithm for computing FIRST and NULLABLE

Iterative algorithm:

1. Initially $\text{NULLABLE}(X) := \text{False}$ and $\text{FIRST}(X) := \emptyset$ for every non-terminal symbol
 2. Compute new elements for the right-hand side of productions using the previous equations
 3. Repeat this until the sets do not change (reach a *fixpoint*)
-
- ▶ We may compute NULLABLE and then FIRST
 - ▶ The algorithm terminates because the previous equations define a *monotonic* function in a finite complete partial order (remember partial orders from Discrete Mathematics...)

Example: arithmetic expressions

$$\begin{array}{lll} E \rightarrow E + T & T \rightarrow T * F & F \rightarrow \text{num} \\ E \rightarrow T & T \rightarrow F & F \rightarrow (E) \end{array}$$

$\text{NULLABLE}(E) = (\text{NULLABLE}(E) \wedge \text{NULLABLE}(+) \wedge \text{NULLABLE}(T)) \vee \text{NULLABLE}(T)$

$\text{NULLABLE}(T) = (\text{NULLABLE}(T) \wedge \text{NULLABLE}(*) \wedge \text{NULLABLE}(F)) \vee \text{NULLABLE}(F)$

$\text{NULLABLE}(F) = \text{NULLABLE}(\text{num}) \vee \text{NULLABLE}((E)) = \text{False}$

non-terminals	iterations	
	0	1
$\text{NULLABLE}(E)$	False	False
$\text{NULLABLE}(T)$	False	False
$\text{NULLABLE}(F)$	False	False

Reaches a fixpoint in iteration 1.

Example: arithmetic expressions (cont.)

$$\begin{array}{lll} E \rightarrow E + T & T \rightarrow T * F & F \rightarrow \text{num} \\ E \rightarrow T & T \rightarrow F & F \rightarrow (E) \end{array}$$

$$\begin{aligned} \text{FIRST}(E) &= \text{FIRST}(E + T) \cup \text{FIRST}(T) = \text{FIRST}(E) \cup \text{FIRST}(T) \\ \text{FIRST}(T) &= \text{FIRST}(T * F) \cup \text{FIRST}(F) = \text{FIRST}(T) \cup \text{FIRST}(F) \\ \text{FIRST}(F) &= \text{FIRST}(\text{num}) \cup \text{FIRST}((E)) = \{\text{num}, (\} \end{aligned}$$

	iterations				
non-terminals	0	1	2	3	4
$\text{FIRST}(E)$	\emptyset	\emptyset	\emptyset	$\{\text{num}, (\}$	$\{\text{num}, (\}$
$\text{FIRST}(T)$	\emptyset	\emptyset	$\{\text{num}, (\}$	$\{\text{num}, (\}$	$\{\text{num}, (\}$
$\text{FIRST}(F)$	\emptyset	$\{\text{num}, (\}$	$\{\text{num}, (\}$	$\{\text{num}, (\}$	$\{\text{num}, (\}$

Reaches a fixpoint in iteration 4.

Example: arithmetic expressions (cont.)

Solutions:

$$\text{FIRST}(E) = \{\text{num}, (\}$$

$$\text{FIRST}(T) = \{\text{num}, (\}$$

$$\text{FIRST}(F) = \{\text{num}, (\}$$

Thus this grammar is not $LL(1)$ because the FIRST sets of the right-hand side of rules

$$E \rightarrow E + T$$

$$E \rightarrow T$$

are not disjoint — in fact they are both equal to $\{\text{num}, (\}$.

Exercise

Write the equations and compute NULLABLE and FIRST for the following grammar:

$$\begin{aligned} S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Exercise

Write the equations and compute NULLABLE and FIRST for the following grammar:

$$\begin{aligned} S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Solutions:

$$\text{NULLABLE}(S) = \text{NULLABLE}(A) = \text{NULLABLE}(B) = \textit{True}$$

$$\text{FIRST}(S) = \{a, b\}$$

$$\text{FIRST}(A) = \{a\}$$

$$\text{FIRST}(B) = \{b\}$$

- ▶ The set FIRST **is not enough** to characterize $LL(1)$ grammars
- ▶ For rules $X \rightarrow \gamma$ where $NULLABLE(\gamma)$ we need to know the tokens which may occur *after* X (FIRST(γ) is not enough to know this)
- ▶ Set FOLLOW(X): tokens that occur after X in a derivation beginning in S

$$FOLLOW(X) = \{c \in \Sigma : \text{existem } \alpha, \beta \text{ tais que } S \Rightarrow^* \alpha X c \beta\}$$

(FOLLOW) Equations:

Add a new non-terminal symbol $\$$ and a new rule to capture the end of the input list of token:

$$S' \rightarrow S\$$$

For each non terminal symbol X , for each rule: $Y \rightarrow \alpha X \beta$:

- ▶ $\text{FOLLOW}(X) \supseteq \text{FIRST}(\beta)$
- ▶ Se $\text{NULLABLE}(\beta)$ then $\text{FOLLOW}(X) \supseteq \text{FOLLOW}(Y)$

How to compute the set FOLLOW

$$\begin{aligned}S' &\rightarrow S\$ \\S &\rightarrow AB \\A &\rightarrow aAb \mid \varepsilon \\B &\rightarrow bB \mid \varepsilon\end{aligned}$$

$$\begin{aligned}S' &\rightarrow S\$ \\S &\rightarrow AB\end{aligned}$$

$$\text{FOLLOW}(S) \supseteq \{\$\}$$

$$\text{FOLLOW}(A) \supseteq \{b\}$$

$$\text{FOLLOW}(A) \supseteq \text{FOLLOW}(S)$$

$$\text{FOLLOW}(B) \supseteq \text{FOLLOW}(S)$$

$$A \rightarrow aAb$$

$$\text{FOLLOW}(A) \supseteq \{b\}$$

$$B \rightarrow bB$$

$$\text{FOLLOW}(B) \supseteq \text{FOLLOW}(B)$$

($A \rightarrow \varepsilon$ e $B \rightarrow \varepsilon$ are useless)

$$\text{FIRST}(\$) = \{\$\}$$

$$\text{FIRST}(B) = \{b\}$$

because $\text{NULLABLE}(B)$

$$\text{FIRST}(b) = \{b\}$$

How to compute the set FOLLOW (cont.)

We get the following equations:

$$\text{FOLLOW}(S) \supseteq \{\$\}$$

$$\text{FOLLOW}(A) \supseteq \{b\}$$

$$\text{FOLLOW}(A) \supseteq \text{FOLLOW}(S)$$

$$\text{FOLLOW}(B) \supseteq \text{FOLLOW}(S)$$

$$\text{FOLLOW}(B) \supseteq \text{FOLLOW}(B)$$

Solve the equations iteratively, beginning with \emptyset for every token.

	iterations			
non-terminals	0	1	2	3
$\text{FOLLOW}(S)$	\emptyset	$\{\$\}$	$\{\$\}$	$\{\$\}$
$\text{FOLLOW}(A)$	\emptyset	$\{b\}$	$\{b, \$\}$	$\{b, \$\}$
$\text{FOLLOW}(B)$	\emptyset	\emptyset	$\{\$\}$	$\{\$\}$

Parsing table

Use NULLABLE, FIRST and FOLLOW to build the *parsing table*:

- ▶ columns: *tokens*
- ▶ lines: *non-terminal symbols*
- ▶ write $X \rightarrow \gamma$:
 - ▶ on line X column t for each $t \in \text{FIRST}(\gamma)$;
 - ▶ if $\text{NULLABLE}(\gamma)$, on line X column t for each $t \in \text{FOLLOW}(X)$.

The grammar is $LL(1)$ if and only if **each entry in the table has at most one rule**. (this guarantees that we can choose which rule to use during parsing looking only to the next token).

Parsing table (cont.)

Example:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Parsing table (check NULLABLE, FIRST, FOLLOW in the previous slides):

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Each table entry has zero or one rules \implies the grammar is *LL(1)*.

Table for Predictive *Parsing*

- ▶ Recursive descent *Parsing* uses the programming language *exectution stack* (e.g. Java or C)
- ▶ We may implement predictive *parsing* without recursion using the parsing table and an explicit stack.

Table for Predictive *Parsing* (cont.)

Parsing algorithm:

```
stack := empty; push (S', stack);
while (stack not empty) do
  if top(stack) is a terminal then
    /* consume input */
    consume(top(stack)); pop(stack);
  else if (table[top(stack),next] is empty) then
    report_error();
  else
    /* use a grammar rule */
    symbols := right_hand_side(table[top(stack),next]);
    pop(stack);
    pushList(symbols, stack);
```


Example: *parsing* of *aabbb*

Grammar:

$$S' \rightarrow S\$$$

$$S \rightarrow AB$$

$$A \rightarrow aAb \mid \varepsilon$$

$$B \rightarrow bB \mid \varepsilon$$

stack	input	action
<u>S'</u>	<u>a</u> abbb\$	

Table:

	a	b	$\$$
S'	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
S	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
A	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
B		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Example: *parsing* of *aabbb*

Grammar:

$$S' \rightarrow S\$$$

$$S \rightarrow AB$$

$$A \rightarrow aAb \mid \varepsilon$$

$$B \rightarrow bB \mid \varepsilon$$

stack	input	action
<u>S'</u>	<u>a</u> abbb\$	$S' \rightarrow S\$$
S\$	a <u>a</u> bbb\$	

Table:

	a	b	\$
S'	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
S	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
A	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
B		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Example: *parsing* of *aabbb*

Grammar:

$$S' \rightarrow S\$$$

$$S \rightarrow AB$$

$$A \rightarrow aAb \mid \varepsilon$$

$$B \rightarrow bB \mid \varepsilon$$

stack	input	action
<u>S'</u>	<u>a</u> abbb\$	$S' \rightarrow S\$$
<u>S</u> \$	<u>a</u> abbb\$	$S \rightarrow AB$
<u>AB</u> \$	<u>a</u> abbb\$	

Table:

	<i>a</i>	<i>b</i>	\$
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

stack	input	action
<u>S'</u>	<u>a</u> abbb\$	$S' \rightarrow S\$$
<u>S</u> \$	<u>a</u> abbb\$	$S \rightarrow AB$
<u>A</u> B\$	<u>a</u> abbb\$	$A \rightarrow aAb$
<u>aAb</u> B\$	<u>a</u> abbb\$	

Table:

	<i>a</i>	<i>b</i>	\$
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

stack	input	action
<u>S'</u>	<u>a</u> abbb\$	$S' \rightarrow S\$$
<u>S</u> \$	<u>a</u> abbb\$	$S \rightarrow AB$
<u>A</u> B\$	<u>a</u> abbb\$	$A \rightarrow aAb$
<u>aAb</u> B\$	<u>a</u> abbb\$	consume <i>a</i>
<u>Ab</u> B\$	<u>a</u> bbb\$	

Table:

	<i>a</i>	<i>b</i>	\$
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>a</i></u> <i>abbb</i> \$	$S' \rightarrow S\$$
<u><i>S</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$S \rightarrow AB$
<u><i>A</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$A \rightarrow aAb$
<u><i>aAb</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	consume <i>a</i>
<u><i>Ab</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	$A \rightarrow aAb$
<u><i>aAbb</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>aabbb</i></u> <i>\$</i>	$S' \rightarrow S\$$
<u><i>S</i></u> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$S \rightarrow AB$
<u><i>A</i></u> <i>B</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aAb</i></u> <i>B</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Ab</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aAbb</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Abb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>a</i></u> <i>abbb</i> \$	$S' \rightarrow S\$$
<u><i>S</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$S \rightarrow AB$
<u><i>A</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$A \rightarrow aAb$
<u><i>aAb</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	consume <i>a</i>
<u><i>Ab</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	$A \rightarrow aAb$
<u><i>aAbb</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	consume <i>a</i>
<u><i>Abb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	$A \rightarrow \varepsilon$
<u><i>bb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>aabbb</i></u> $\$$	$S' \rightarrow S\$$
<u><i>S</i></u> $\$$	<u><i>aabbb</i></u> $\$$	$S \rightarrow AB$
<u><i>A</i></u> $\$$	<u><i>aabbb</i></u> $\$$	$A \rightarrow aAb$
<u><i>aAb</i></u> $\$$	<u><i>aabbb</i></u> $\$$	consume <i>a</i>
<u><i>Ab</i></u> $\$$	<u><i>abbb</i></u> $\$$	$A \rightarrow aAb$
<u><i>aAbb</i></u> $\$$	<u><i>abbb</i></u> $\$$	consume <i>a</i>
<u><i>Abbb</i></u> $\$$	<u><i>bbb</i></u> $\$$	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> $\$$	<u><i>bbb</i></u> $\$$	consume <i>b</i>
<u><i>bb</i></u> $\$$	<u><i>bb</i></u> $\$$	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>a</i></u> <i>abbb</i> \$	$S' \rightarrow S\$$
<u><i>S</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$S \rightarrow AB$
<u><i>A</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$A \rightarrow aAb$
<u><i>aAb</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	consume <i>a</i>
<u><i>Ab</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	$A \rightarrow aAb$
<u><i>aAbb</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	consume <i>a</i>
<u><i>Abbb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	consume <i>b</i>
<u><i>bb</i></u> \$	<u><i>b</i></u> <i>b</i> \$	consume <i>b</i>
<u><i>B</i></u> \$	<u><i>b</i></u> \$	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>aabbb</i></u> <i>\$</i>	$S' \rightarrow S\$$
<u><i>S</i></u> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$S \rightarrow AB$
<u><i>A</i></u> <i>B</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aA</i></u> <i>bB</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Ab</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aAbb</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Abbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>bb</i></u> <i>B</i> <i>\$</i>	<u><i>bb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>B</i></u> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	$B \rightarrow bB$
<u><i>bB</i></u> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>aabbb</i></u> <i>\$</i>	$S' \rightarrow S\$$
<u><i>S</i></u> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$S \rightarrow AB$
<u><i>A</i></u> <i>B</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aA</i></u> <i>bB</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Ab</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aAbb</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Abbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>bb</i></u> <i>B</i> <i>\$</i>	<u><i>bb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>B</i></u> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	$B \rightarrow bB$
<u><i>bb</i></u> <i>B</i> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	consume <i>b</i>
<u><i>B</i></u> <i>\$</i>	<u><i>\$</i></u>	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>a</i></u> <i>abbb</i> \$	$S' \rightarrow S\$$
<u><i>S</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$S \rightarrow AB$
<u><i>A</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	$A \rightarrow aAb$
<u><i>aAb</i></u> \$	<u><i>a</i></u> <i>abbb</i> \$	consume <i>a</i>
<u><i>Ab</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	$A \rightarrow aAb$
<u><i>aAbb</i></u> \$	<u><i>a</i></u> <i>bbb</i> \$	consume <i>a</i>
<u><i>Abbb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> \$	<u><i>b</i></u> <i>bb</i> \$	consume <i>b</i>
<u><i>bB</i></u> \$	<u><i>b</i></u> <i>b</i> \$	consume <i>b</i>
<u><i>B</i></u> \$	<u><i>b</i></u> \$	$B \rightarrow bB$
<u><i>bb</i></u> \$	<u><i>b</i></u> \$	consume <i>b</i>
<u><i>B</i></u> \$	<u><i>\$</i></u>	$B \rightarrow \varepsilon$
<u><i>\$</i></u>	<u><i>\$</i></u>	

Example: *parsing* of *aabbb*

Grammar:

$$\begin{aligned} S' &\rightarrow S\$ \\ S &\rightarrow AB \\ A &\rightarrow aAb \mid \varepsilon \\ B &\rightarrow bB \mid \varepsilon \end{aligned}$$

Table:

	<i>a</i>	<i>b</i>	<i>\$</i>
<i>S'</i>	$S' \rightarrow S\$$	$S' \rightarrow S\$$	$S' \rightarrow S\$$
<i>S</i>	$S \rightarrow AB$	$S \rightarrow AB$	$S \rightarrow AB$
<i>A</i>	$A \rightarrow aAb$	$A \rightarrow \varepsilon$	$A \rightarrow \varepsilon$
<i>B</i>		$B \rightarrow bB$	$B \rightarrow \varepsilon$

stack	input	action
<u><i>S'</i></u>	<u><i>aabbb</i></u> <i>\$</i>	$S' \rightarrow S\$$
<u><i>S</i></u> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$S \rightarrow AB$
<u><i>A</i></u> <i>B</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aA</i></u> <i>bB</i> <i>\$</i>	<u><i>aabbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Ab</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	$A \rightarrow aAb$
<u><i>aAbb</i></u> <i>B</i> <i>\$</i>	<u><i>abbb</i></u> <i>\$</i>	consume <i>a</i>
<u><i>Abbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	$A \rightarrow \varepsilon$
<u><i>bbb</i></u> <i>B</i> <i>\$</i>	<u><i>bbb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>bb</i></u> <i>B</i> <i>\$</i>	<u><i>bb</i></u> <i>\$</i>	consume <i>b</i>
<u><i>B</i></u> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	$B \rightarrow bB$
<u><i>bb</i></u> <i>B</i> <i>\$</i>	<u><i>b</i></u> <i>\$</i>	consume <i>b</i>
<u><i>B</i></u> <i>\$</i>	<i>\$</i>	$B \rightarrow \varepsilon$
<i>\$</i>	<i>\$</i>	consume <i>\$</i>
<i>ε</i>	<i>ε</i>	accept

Conclusions

Parsing *top-down*:

- ▶ Recursive descent *parsing*
- ▶ Recursive functions in Java or C
- ▶ $LL(1)$ is a widely used class of grammars
- ▶ Define a *parsing table*
- ▶ *Parsing* using the parsing table and an auxiliary stack

Parser generators

- ▶ We have studied *parsers* which *recognize* a language (yes or no output)
- ▶ The next step is to use parsing to also **build a syntactic tree**
- ▶ It is possible to use tools which automatically build *top-down* parsers:
 - JavaCC* for Java: <https://javacc.github.io/javacc/>
 - Parsec* for Haskell: <http://hackage.haskell.org/package/parsec>