

Product Specifications

Processor	
CPU	486DX2/50MHz
Math Coprocessor	Built-in 50 MHz
Cache Memory	8KB internal
External Cache Option	
Supports up to 256KB of SRAM	
Architecture	
Local bus video; ISA 16-bit expansion slots	
Keyboard Type	
Enhanced 101-key; PS/2 compatible	
Memory	
ROM	128KB system and video BIOS
Shadow	Yes
SETUP Program	Stored in EPROM on main system board
Standard RAM	
Type	
Tin-plated, 72-pin, 32-bit or 36-bit, fast-page mode type	
Speed	80ns or faster
Amount	4MB or 8MB
Maximum RAM	Expandable to 64MB using 1MB, 2MB, 4MB, 8MB, 16MB and 32MB SIMMs
Mass Storage Standard	
1.44MB, 3.5" floppy disk drive	
210MB IDE HDD	
420MB IDE HDD	
Drive Bays	
ActionPC 3000	Four drive bays: One 3.5" and two 5.25" front-accessible One 3.5" internal
ActionTower 3000	Seven drive bays: Two 3.5" and two 5.25" front-accessible One 3.5" front internal Two 3.5" rear internal
Video	
Local bus on-board SVGA high speed video controller with 1MB video memory; supports up to 1024 x 768 resolution in 256 colors; True Color™ support in 640 x 480 resolution	
Integrated Ports	
Serial	Two RS-232C compatible, 9-pin, D-shell, male
Parallel	8-bit Centronics compatible; 25-pin D-shell, female uni- or bi-directional
Mouse	IBM™ PS/2 compatible, 6-pin mini DIN
Keyboard	IBM PS/2 compatible, 6-pin mini DIN
Monitor	VGA interface for fixed or multi-frequency VGA monitor, low power standby mode for Energy Star compliant monitors; 15-pin, D-shell connector
Integrated Connectors	
Floppy Controller	Supports up to two floppy disk drives
Hard Drive Interface	Supports up to two IDE hard disk drives

EPSON®

USA: Call 1-800-289-3776 for the nearest dealer location

Epson America, Inc. 20770 Madrona Avenue, Torrance, CA 90503

Canada: Call 1-800-4637766 Epson Canada, Ltd.

550 McNicoll, Willowdale, Ontario M2H 2E1 Fax 416-498-4574

Latin America: Call 1-305-265-0092 Epson Latin America Inc.

6303 Blue Lagoon Drive, Suite 390, Miami, Florida 33126 Fax 301-265-0097

ActionPC/ActionTower™ 3000

I/O Slots	Five 16-bit ISA expansion slots	
Dimensions	(1 FDD and 1 HDD w/keyboard)	
ActionPC 3000		
H x L x M	4.4" x 15.8" x 16.6"	
Weight	18.5 lbs.	
	17 lbs w/FDD. no HHD or KB	
ActionTower 3000		
H x L x W	13.3" x 16.3" x 7.1"	
Weight	18.4 lbs.	
	16.3 lbs. w//FDD, no HHD or KB	
Environmental Requirements		
Temperature	41° F to 95° F (5° C to 35° C)	
Humidity	8% to 80%. non-condensing	
Power Supply	200 Watt, UL/TUV/CSA listed. fan-cooled	
Input Voltage	90-130 VAC or 180-260 VAC; switch-selectable for 110 VAC and 220 VAC input current	
Output Voltage	+5 VDC at 20 Amps, -5 VDC at 0.5 Amps, +12 VDC at 8.0 Amps, -12 VDC at 0.5 Amps; 47 to 60 Hz	
Password	System access and SETUP access passwords	
Standard Hardware		
ActionPC 3000	96/48/24 FAX/modem EPSON mouse EPSON keyboard	
ActionTower 3000	96/48/24 FAX/modem EPSON mouse & keyboard 16-bit stereo sound card External speakers Double-speed CD-ROM drive (connected to the interface on the sound card)	
Software		
ActionPC 3000	MS-DOS, Microsoft Windows, VGA drivers, and plus bundled, pre-loaded. Windows-based software	
ActionTower 3000	MS-DOS, Microsoft Windows, VGA drivers, and bundled multimedia software	
Options		
Monitors (Interlaced)		Product Code
14" .39 dot pitch - SVGA 1024 x 768		A881371
14" .28 dot pitch - SVGA 1024 x 768		A881381
Monitors (Non-interlaced)		
14" .28 dot pitch - SVGA 1024 x 768		A881391
15" .28 dot pitch - SVGA 1024 x 768		A880491
Warranty	One-year limited warranty including On-Site service	
Support		
Unlimited Technical Support		(800) 922-8911
Faxback System		(310) 782-4214
Electronic Bulletin Board		(310) 782-4531

Specifications are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation; EPSON Connection is a servicemark of Epson America, Inc.

All other product and brand names are trademarks and/or registered trademarks of their respective companies. EPSON disclaims any and all rights in these marks. The Energy Star Emblem does not represent EPA endorsement of any product or service.

© Copyright 1994 Epson America, Inc. CPD1755 100M 6/94 GAC

