

File permissions in Linux

Project description

The research team in my organization needed the file and directory permissions inside the **projects** folder to be adjusted. The current permissions didn't match the proper access levels, so I reviewed and updated them. This ensured the files had the right authorization settings and improved the overall security of the system.

Check file and directory details

The following code demonstrates how I used Linux commands to determine the existing permissions set for a specific directory in the file system.

```
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-rw--w---- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$
```

Describe the permissions string

Permissions string: 10 characters (-rw-rw-r--)

1. **1st character** → file type
 - d = directory
 - - = regular file
2. **2nd-4th characters** → owner permissions

- **r** = read
 - **w** = write
 - **x** = execute
 - **-** = no permission
3. **5th–7th characters** → group permissions (same meanings)
 4. **8th–10th characters** → others permissions (same meanings)

Example: `-rw-rw-r--` for `project_t.txt`

- **-** → regular file
- **rw-** → owner can read & write
- **rw-** → group can read & write
- **r--** → others can read only
- No execute permission for anyone

Change file permissions

The organization determined that other shouldn't have write access to any of their files. To comply with this, I referred to the file permissions that I previously returned. I determined `project_k.txt` must have the write access removed for other.

The following code demonstrates how I used Linux commands to do this:

```
researcher2@5d738f0f927b:~/projects$ chmod o-w project_k.txt
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-rw--w--- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$
```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. The `chmod` command changes the permissions on files and directories. The first argument indicates what permissions should be changed, and the second argument specifies the file or directory. In this example, I removed write permissions from other for the `project_k.txt` file. After this, I used `ls -la` to review the updates I made.

Change file permissions on a hidden file

The research team at my organization recently archived `project_x.txt`. They do not want anyone to have write access to this project, but the user and group should have read access.

The following code demonstrates how I used Linux commands to change the permissions:

```
researcher2@3213bbc1d047:~/projects$ chmod u-w,g-w,g+r .project_x.txt
researcher2@3213bbc1d047:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec 20 15:36 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec 20 15:36 ..
-r--r----- 1 researcher2 research_team  46 Dec 20 15:36 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec 20 15:36 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec 20 15:36 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec 20 15:36 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec 20 15:36 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec 20 15:36 project_t.txt
researcher2@3213bbc1d047:~/projects$
```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. I know `.project_x.txt` is a hidden file because it starts with a period (.). In this example, I removed write permissions from the user and group, and added read permissions to the group. I removed write permissions from the user with `u-w`. Then, I removed write permissions from the group with `g-w`, and added read permissions to the group with `g+r`.

Change directory permissions

My organization only wants the `researcher2` user to have access to the `drafts` directory and its contents. This means that no one other than `researcher2` should have execute permissions.

The following code demonstrates how I used Linux commands to change the permissions:

```
researcher2@5d738f0f927b:~/projects$ chmod g-x drafts
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-r--r----- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx----- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$
```

The output here displays the permission listing for several files and directories. Line 1 indicates the current directory (`projects`), and line 2 indicates the parent directory (`home`). Line 3 indicates a regular file titled `.project_x.txt`. Line 4 is the directory (`drafts`) with restricted permissions. Here you can see that only `researcher2` has execute permissions. It was previously determined that the group had execute permissions, so I used the `chmod` command to remove them. The `researcher2` user already had execute permissions, so they did not need to be added.

Summary

I updated several file and directory permissions in the `projects` folder to match the organization's required access levels. First, I ran `ls -la` to see the current permissions, which helped guide my next steps. Then, I used the `chmod` command multiple times to set the correct permissions for each file and directory.