




UNIVERSITÀ
DEGLI STUDI
DI PADOVA

DIPARTIMENTO
DI INGEGNERIA
DELL'INFORMAZIONE



Developed by:
Christian Marchiori
Fabio Zanini






Introduction

The aim of this project is to create a graph database representing the world of Formula 1.

Formula 1 (a.k.a. F1 or Formula One) is the highest category of single-seat auto racing sanctioned by the Fédération Internationale de l'Automobile (FIA) and owned by the Formula One Group.

The datasets used to create this database contain information regarding races, drivers, driver ratings, constructors, qualifying, circuits, lap times, pit stops, and championships from 1950 until the latest 2023 season.

The project also consists of some SPARQL queries to show how the database works.





Datasets



Formula 1 data:

<https://ergast.com/mrd/> or

<https://www.kaggle.com/datasets/rohanrao/formula-1-world-championship-1950-2020>

The dataset consists of all information on the Formula 1 races, drivers, constructors, qualifying, circuits, lap times, pit stops, championships from 1950 till the latest 2023 season.



Ratings data:

- ▶ 2023: <https://ratings-api.ea.com/v2/entities/f1-23-drivers-ratings>
- ▶ Older: <https://github.com/toUpperCase78/formula1-datasets>

Driver Ratings from EA & Codemasters F1 2021 / F1 22 / F1 23 Official Video Game



Country to Nationality csv:

<https://github.com/Imagin-io/country-nationality-list/tree/master>

Csv file that maps nationalities to countries.



UNIVERSITÀ
DEGLI STUDI
DI PADOVA



Development process

Graph schema

Ontology

Serialization

Queries

Graph model
designed to fit
the F1 data

Developed with
[arrows.app](#)

Ontology
according to
the Graph
model

Developed with
[Protégé](#)

Serialization
process to
produce turtle
files

Developed with
[Jupyter
Notebook](#)

Produced some
queries to test the
database


Developed with
[SPARQL](#)




Dataset

CSV files list


- **circuits.csv** (circuits where F1 races are held)
- **constructor_results.csv** (race results of the constructors' championship)
- **constructor_standings.csv** (final standings of the constructors' championship)
- **constructors.csv** (constructors in F1)
- **driver_standings.csv** (final standings of the driver's championship)
- **drivers.csv** (drivers in F1)
- **lap_times.csv** (lap times in F1)
- **pit_stops.csv** (pit stops in F1)
- **qualifying.csv** (qualifying in F1)
- **races.csv** (races in F1)
- **ratings.csv** (ratings of F1 drivers)
- **results.csv** (results of F1 races)
- **seasons.csv** (seasons of F1)
- **sprint_results.csv** (results of F1 sprint races)
- **status.csv** (Mapping of various statuses)



E-R Schema



Graph Schema






UNIVERSITÀ
DEGLI STUDI
DI PADOVA

DIPARTIMENTO
DI INGEGNERIA
DELL'INFORMAZIONE




Ontology



Ontology Class hierarchy


- **Standing** (represents championship standings)
 - **DriverStanding** (...related to drivers)
 - **ConstructorStanding** (...related to constructors)
 - **Sprint** (represents a sprint race related to a particular race)
 - **Race** (represents a particular F1 race)
 - **Person** (represents a person in general)
 - **Driver** (represents a F1 driver)
 - **Lap** (represents a single lap in a generic race)
 - **SprintLap** (represents a single lap in a sprint)
 - **RaceLap** ((represents a single lap in a race))
 - **Partecipation** (represents the participation of a driver and his related constructor team to a race/sprint/qualifying)
 - **QualifPartecipation** (...to a qualifying)
 - **SprintPartecipation** (...to a sprint)
 - **RacePartecipation** (...to a race)
 - **Season** (represents a F1 season)
 - **Rating** (represents a rating tab for a driver)
 - **Circuit** (represents the circuits on which F1 races are done)
 - **Constructor** (represents F1 teams)
 - **Qualifying** (represents a qualifying related to a particular race)
 - **Location** (represents the location/city of a circuit)
 - **PitStop** (represents a single pitstop in a F1 race)
 - **Country** (represents world countries)
 - **Status** (represents a status of a driver or a car in a race/sprint)



Ontology

Object properties

- **hasA** (Race \rightarrow Qualifying or Sprint)
- **hasCircuit** (Race \rightarrow Circuit) **F**
- **hasConstructor** (ConstructorStanding or Partecipation \rightarrow Constructor) **F**
- **hasCountry** (Location \rightarrow Country) **F**
- **hasDriver** (DriverStanding or Partecipation or Rating \rightarrow Driver) **F**
- **hasFastestLap** (RacePartecipation or SprintPartecipation \rightarrow Lap) **F**
- **hasLap** (RacePartecipation \rightarrow Lap)
- **hasLocation** (Circuit \rightarrow Location) **F**
- **hasNation** (Constructor or Driver \rightarrow Country)
- **hasPitStop** (RacePartecipation \rightarrow PitStop)
- **hasPitStopLap** (PitStop \rightarrow Lap)**F**
- **hasRace** (Standing \rightarrow Race) **F**
- **hasStatus** (RacePartecipation or SprintPartecipation \rightarrow Status) **F**
- **inSeason** (Race or Rating \rightarrow Season) **F**
- **partecipatedInQualif** (QualifPartecipation \rightarrow Qualifying) **F**
- **partecipatedInRace** (RacePartecipation \rightarrow Race) **F**
- **partecipatedInSprint** (SprintPartecipation \rightarrow Sprint) **F**



Ontology Data properties





Ontology Data properties

RACE PARTECIPATION:

Property	Datatype
hasConstructorPoints	xsd:integer
hasFastestLapRank	xsd:integer
hasFastestLapSpeed	xsd:decimal
hasFastestLapTime	xsd:time
hasLaps	xsd:integer
hasMillisecondsResultTime	xsd:integer
hasPoints	xsd:integer
hasPositionOrder	xsd:integer
hasPositionText	xsd:string
hasPositionGap	xsd:time
hasResultTime	xsd:time
hasStartingGridPosition	xsd:integer

PARTECIPATION:

Property	Datatype
hasCarNumber	xsd:integer
hasPosition	xsd:integer

SPRINT PARTECIPATION:

Property	Datatype
hasFastestLap	xsd:integer
hasFastestLapTime	xsd:time
hasLaps	xsd:integer
hasMillisecondsResultTime	xsd:integer
hasPoints	xsd:integer
hasPositionOrder	xsd:integer
hasPositionText	xsd:string
hasResultGap	xsd:time
hasResultTime	xsd:time
hasStartingGridPosition	xsd:integer

STANDING:

Property	Datatype
hasTotalPoints	xsd:integer
hasTotalPositionOrder	xsd:integer
hasTotalPositionText	xsd:string
hasWins	xsd:integer

QUALIFYING PARTECIPATION: CIRCUIT:

Property	Datatype
hasQ1Time	xsd:time
hasQ2Time	xsd:time
hasQ3Time	xsd:time

STATUS:

Property	Datatype
hasName	xsd:string

QUALIFYING and SPRINT:

Property	Datatype
hasDate	xsd:date
hasTime	xsd:time

SEASON:

Property	Datatype
hasURL	xsd:string
hasYear	xsd:gYear

LAP:

Property	Datatype
hasLapNumber	xsd:integer
hasLapTime	xsd:time

RACE LAP:

Property	Datatype
hasLapPosition	xsd:integer
hasMillisecondsTime	xsd:integer

CONSTRUCTOR:

Property	Datatype
hasConstructorRef	xsd:string
hasName	xsd:string
hasUrl	xsd:string

RACE:

Property	Datatype
hasDate	xsd:date
hasTime	xsd:time
hasFp1Date	xsd:date
hasFp2Date	xsd:date
hasFp3Date	xsd:date
hasFp1Time	xsd:time
hasFp2Time	xsd:time
hasFp3Time	xsd:time

PIT STOP:

Property	Datatype
hasDuration	xsd:time
hasMillisecondsTime	xsd:integer
hasPitStopTimeOfDay	xsd:time
hasStopNumber	xsd:integer




UNIVERSITÀ
DEGLI STUDI
DI PADOVA

DIPARTIMENTO
DI INGEGNERIA
DELL'INFORMAZIONE



Serialization





Serialization Introduction

Turtle files produced by the serialization process:


Turtle files	csv files from which we extracted the data for the turtle files
circuits.ttl	circuits.csv, countries.csv
constructors.ttl	constructors.csv, nationalities.csv
drivers.ttl	drivers.csv, nationalities.csv
laps1.ttl and laps2.ttl	lap_times.csv, results.csv, constructor_results.csv
qualifying.ttl	qualifying.csv, races.csv
race.ttl	races.csv
race_partecipation.ttl	results.csv, constructor_results.csv, lap_times.csv
ratings.ttl	ratings.csv, drivers.csv
sprint.ttl	sprint_results.csv, races.csv
standings.ttl	driver_standings.csv, constructor_standings.csv
status_season.ttl	status.csv, seasons.csv
stops.ttl	pit_stops.csv, results.csv, constructor_results.csv, lap_times.csv

Serialization

Matching columns

1. Left Join

We joined `results.csv` and `constructor_results.csv` in a single Pandas data frame. Then, all the results concerning the constructor team were matched with the driver results before managing the data frame.



2. Search

For each current row evaluated, we searched for a matching row in the second table in order to match some constraints, such as some keys.





Serialization

Nationality to country mapping

We used this approach in *drivers.ttl* and *constructors.ttl* to maintain a single class country taken by an external source.

In this way, we avoided creating an additional nationality class and it was not necessary to link each individual in the nationality class to the country class via an object property.

The mapping was done directly in the serialization step.

num_code	alpha_2_code	alpha_3_code	en_short_name	nationality
4	AF	AFG	Afghanistan	Afghan
248	AX	ALA	Åland Islands	Åland Island
8	AL	ALB	Albania	Albanian
12	DZ	DZA	Algeria	Algerian
16	AS	ASM	American Samoa	American Samoan
20	AD	AND	Andorra	Andorran
24	AO	AGO	Angola	Angolan
660	AI	AIA	Anguilla	Anguillan
10	AQ	ATA	Antarctica	Antarctic
28	AG	ATG	Antigua and Barbuda	Antiguan or Barbudan
32	AR	ARG	Argentina	Argentine

•
•
•

Serialization

Time format

We used 3 functions to manage time:

1. `time_formatter`



Function that transforms a time value to the standard %H:%M:%S.%f format, adds the zeros and the missing colon to the beginning and end of the string.

2. `gap_formatter`

Function that transforms a gap time value to the standard %H:%M:%S.%f format, adds the zeros and the missing colon to the beginning and end of the string.

3. `time_converter`

Function that calculates a driver's actual arrival time using the winner's arrival time and the time distance from it.



Driver gap time:	+122.345
Winner arrival time:	1:00:00.000
Driver arrival time:	01:02:02.345

Serialization

Qualifying and Sprint classes

In the source dataset, we have two csv files concerning the races:


- the one for the generic race (`races.csv`) and
- the one for each driver's participation in the race (`results.csv`).

For qualifying and sprints this does not happen and we only have files representing the participations (`qualifying.csv`, `sprint_results.csv`).

To make the database more consistent, we decided to **add two classes**, Sprint and Qualifying, to represent the generic sprints and qualifications, not related to the driver.

To do this, we added the generic qualification with URI "qualifying+raceId" when evaluating qualification participations. In this way, since the raceId is unique for all participations of a specific race, the individual of the generic qualification is added only once.

In addition, we took the columns `quali_date` and `quali_time` from `races.csv` and added them directly to the generic qualification, making the model consistent.



Serialization

Race and sprint laps


In the source dataset, we have the `lap_times.csv` file that contains all the laps of each driver in each race, with their positions and times.

In the case of the sprints, we do not have all the laps of each driver, but we have only the fastest lap performed by a driver, with the corresponding time.

Consequently, we decided to **create a subclass of Lap**, called SprintLap to include the fastest laps related to sprints, with related time.

We also chose to keep this information in SprintParticipation so that it would be faster to extract it in SPARQL.

In the case of qualifying, there is no information regarding drivers' laps.





Serialization

Matching of drivers' ratings

The ratings of the various drivers were extracted from a different dataset than the main dataset.

Consequently, to associate the various ratings with the drivers in the Driver class, during the rating evaluation we do this:

1. take the driver name (in full format),
2. split it into two parts (at first whitespace),
3. get the rows of the drivers dataframe with the first part of the splitted full name (point 2) **contained** in the forename value of the drivers.csv.
4. If there exists at least one row in the retrieved data frame (point 3) that in the surname field also **contains** the second part of the splitted full name (point 2),
 - a. get the row of the drivers dataframe with the splitted name values **contained** in the forename and surname respectively,
 - b. get the matching driver URL and connect it with the rating.




UNIVERSITÀ
DEGLI STUDI
DI PADOVA

DIPARTIMENTO
DI INGEGNERIA
DELL'INFORMAZIONE



Queries





Query 8.1

The 5 most winning drivers in F1 history, ordered by number of grand prix wins

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>
SELECT ?name (COUNT(?name) as ?numOfWins) WHERE {
    ?race :hasCircuit ?circuit;
    a :Race.
    ?racePart :partecipatedInRace ?race;
    :hasPositionOrder "1"^^xsd:integer;
    :hasDriver ?driver.
    ?driver a :Driver;
    :hasForename ?fname;
    :hasSurname ?surname.
    BIND(CONCAT(?fname, " ", ?surname) AS ?name).
} GROUP BY ?name
ORDER BY DESC (?numOfWins)
LIMIT 5
```

SPARQL RESULT:

	name	numOfWins
1	"Lewis Hamilton"	"103"^^xsd:integer
2	"Michael Schumacher"	"91"^^xsd:integer
3	"Max Verstappen"	"54"^^xsd:integer
4	"Sebastian Vettel"	"53"^^xsd:integer
5	"Alain Prost"	"51"^^xsd:integer

WIKIPEDIA:

Rank	Country	Driver	Wins	Seasons active	First win	Last win
1	United Kingdom	Lewis Hamilton†	103	2007–	2007 Canadian Grand Prix	2021 Saudi Arabian Grand Prix
2	Germany	Michael Schumacher‡	91	1991–2006, 2010–2012	1992 Belgian Grand Prix	2006 Chinese Grand Prix
3	Netherlands	Max Verstappen‡	54	2015–	2016 Spanish Grand Prix	2023 Abu Dhabi Grand Prix
4	Germany	Sebastian Vettel‡	53	2007–2022	2008 Italian Grand Prix	2019 Singapore Grand Prix
5	France	Alain Prost‡	51	1980–1991, 1993	1981 French Grand Prix	1993 German Grand Prix

Query 11.3

Data about fastest qualifying laps in F1 history (both q1, q2 and q3)

```

PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>
SELECT ?driversName ?qTime ?circuitName ?raceName WHERE {
    {
        ?qualPart :hasQ3Time ?qTime.
    }
    UNION
    {
        ?qualPart :hasQ2Time ?qTime.
    }
    UNION
    {
        ?qualPart :hasQ1Time ?qTime.
    }
    ?qualPart :hasDriver ?driver;
               :participatedInQualif ?quali;
               a :QualifParticipation.
    ?quali a :Qualifying.
    ?race a :Race;
          :hasA ?quali;
          :hasName ?raceName;
          :hasCircuit ?circ.
    ?circ a :Circuit;
          :hasName ?circuitName.
    ?driver a :Driver;
            :hasForename ?fname;
            :hasSurname ?sname.
    BIND(CONCAT(?fname, " ", ?sname) AS ?driversName).
    FILTER(?qTime != "00:00:00"^^xsd:time)
}
ORDER BY (?qTime)
LIMIT 100
  
```

SPARQL RESULT:

	driversName	qTime	circuitName	raceName
1	"Valtteri Bottas"	"00:00:53.377000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
2	"George Russell"	"00:00:53.403000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
3	"Max Verstappen"	"00:00:53.433000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
4	"Charles Leclerc"	"00:00:53.613000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
5	"Max Verstappen"	"00:00:53.647000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
6	"Sergio Pérez"	"00:00:53.787000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
7	"Sergio Pérez"	"00:00:53.790000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
8	"Valtteri Bottas"	"00:00:53.803000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
9	"Carlos Sainz"	"00:00:53.818000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
10	"George Russell"	"00:00:53.919000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
11	"Charles Leclerc"	"00:00:53.925000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
12	"Lance Stroll"	"00:00:53.940000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
13	"Daniil Kvyat"	"00:00:53.956000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
14	"Daniel Ricciardo"	"00:00:53.971000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
15	"Valtteri Bottas"	"00:00:53.904000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
16	"Daniil Kvyat"	"00:00:53.906000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
17	"Pierre Gasly"	"00:00:53.941000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
18	"Daniel Ricciardo"	"00:00:53.957000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"
19	"Esteban Ocon"	"00:00:53.995000"^^xsd:time	"Bahrain International Circuit"	"Sakhir Grand Prix"



Query 12

Data about 10 fastest pit stop in F1 history

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>
SELECT ?driversName ?pitDuration ?circuitName ?raceName ?raceDate WHERE {
    ?racePart :hasPitStop ?pit;
                :hasDriver ?driver;
                :partecipatedInRace ?race;
                a :RacePartecipation
    ?race a :Race;
           :hasName ?raceName;
           :hasDate ?raceDate;
           :hasCircuit ?circ
    ?circ a :Circuit;
           :hasName ?circuitName
    ?pit a :PitStop;
           :hasDuration ?pitDuration
    ?driver a :Driver;
           :hasForename ?fname;
           :hasSurname ?sname
    BIND(CONCAT(?fname, " ", ?sname) AS ?driversName)
}
ORDER BY (?pitDuration)
LIMIT 10
```

SPARQL RESULT:

	driversName	pitDuration	circuitName	raceName	raceDate
1	"Pastor Maldonado"	"00:00:12.897000""xsd:time	"Yas Marina Circuit"	"Abu Dhabi Grand Prix"	"2011-11-13""xsd:date
2	"Bruno Senna"	"00:00:12.959000""xsd:time	"Yas Marina Circuit"	"Abu Dhabi Grand Prix"	"2011-11-13""xsd:date
3	"Lewis Hamilton"	"00:00:13.173000""xsd:time	"Hungaroring"	"Hungarian Grand Prix"	"2011-07-31""xsd:date
4	"Pastor Maldonado"	"00:00:13.186000""xsd:time	"Hungaroring"	"Hungarian Grand Prix"	"2011-07-31""xsd:date
5	"Michael Schumacher"	"00:00:13.199000""xsd:time	"Hungaroring"	"Hungarian Grand Prix"	"2012-07-29""xsd:date
6	"Sergio Pérez"	"00:00:13.201000""xsd:time	"Hungaroring"	"Hungarian Grand Prix"	"2011-07-31""xsd:date
7	"Pastor Maldonado"	"00:00:13.206000""xsd:time	"Hungaroring"	"Hungarian Grand Prix"	"2012-07-29""xsd:date
8	"Felipe Massa"	"00:00:13.259000""xsd:time	"Circuit de Barcelona-Catalunya"	"Spanish Grand Prix"	"2012-05-13""xsd:date
9	"Pastor Maldonado"	"00:00:13.266000""xsd:time	"Circuit de Barcelona-Catalunya"	"Spanish Grand Prix"	"2013-05-12""xsd:date
10	"Sebastian Vettel"	"00:00:13.335000""xsd:time	"Circuit de Barcelona-Catalunya"	"Spanish Grand Prix"	"2012-05-13""xsd:date



Query 14

Constructors with most wins in the constructors' championship

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
SELECT ?name (COUNT(?name) AS ?totalWins) (GROUP_CONCAT(DISTINCT ?outerYear ; separator=",") AS ?years) WHERE{
{
    SELECT ?name ?race (AVG(?pos) AS ?finalPosition) ?outerYear WHERE{
        ?stand :hasRace ?race ;
        :hasConstructor ?cons ;
        :hasTotalPosition ?pos
        ?race :hasRound ?outerRound ;
        :inSeason ?outerSeason
        ?outerSeason :hasYear ?outerYear.
        ?cons :hasName ?name.
        FILTER(?outerRound >= ?maxRound && ?outerYear = ?year && ?pos = 1)
    {
        SELECT ?year (MAX(?round) AS ?maxRound) WHERE {
            ?race :inSeason ?season ;
            :hasRound ?round
            ?season :hasYear ?year.
        }
        GROUP BY ?year
    }
    GROUP BY ?name ?race ?outerYear
    ORDER BY (?outerYear)
}
}
GROUP BY ?name
ORDER BY DESC (?totalWins)
```

SPARQL RESULT:

name	totalWins	years
'Ferrari'	"16"^^xsd:integer	"1961,1964,1975,1976,1977,1979,1982,1983,1999,2000,2001,2002,2003,2004,2007,2008"
'Williams'	"9"^^xsd:integer	"1980,1981,1986,1987,1992,1993,1994,1996,1997"
'McLaren'	"9"^^xsd:integer	"1974,1984,1985,1988,1989,1990,1991,1998"
'Mercedes'	"8"^^xsd:integer	"2014,2015,2016,2017,2018,2019,2020,2021"
'Red Bull'	"6"^^xsd:integer	"2010,2011,2012,2013,2022,2023"
'Team Lotus'	"4"^^xsd:integer	"1970,1972,1973,1978"
'Cooper-Climax'	"2"^^xsd:integer	"1959,1960"
'Lotus-Climax'	"2"^^xsd:integer	"1963,1965"
'Brahham-Repco'	"2"^^xsd:integer	"1966,1967"
'Renault'	"2"^^xsd:integer	"2005,2006"
'Vanwall'	"1"^^xsd:integer	"1958"
'BRM'	"1"^^xsd:integer	"1962"
'Lotus-Ford'	"1"^^xsd:integer	"1968"
'Matra-Ford'	"1"^^xsd:integer	"1969"
'Tyrrell'	"1"^^xsd:integer	"1971"
'Benetton'	"1"^^xsd:integer	"1995"
'Brawn'	"1"^^xsd:integer	"2009"

WIKIPEDIA:

Constructor	Titles	Seasons
Ferrari	16	1961, 1964, 1975, 1976, 1977, 1979, 1982, 1983, 1999, 2000, 2001, 2002, 2003, 2004, 2007, 2008
Williams	9	1980, 1981, 1986, 1987, 1992, 1993, 1994, 1996, 1997
McLaren	8	1974, 1984, 1985, 1988, 1989, 1990, 1991, 1998
Mercedes		2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021
Lotus	7	1963, 1965, 1968, 1970, 1972, 1973, 1978
Red Bull	6	2010, 2011, 2012, 2013, 2022, 2023
Cooper		1959, 1960
Brabham	2	1966, 1967
Renault		2005, 2006
Vanwall		1958
BRM		1962
Matra		1969
Tyrrell		1971
Benetton		1995
Brawn		2009

Query 16

Are drivers who won the championship after 2000 older than those who won it before 2000, on average?

```

PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianFl#>
ASK WHERE{
  {
    SELECT (AVG(?age)as ?avgOldAge) WHERE{
      ?stand :hasRace ?race ;
      :hasDriver ?driv ;
      :hasTotalPosition ?pos
      ?driv :hasDateOfBirth ?dob.
      ?race :hasDate ?raceDate ;
      :inSeason ?outerSeason ;
      :hasRound ?outerRound
      ?outerSeason :hasYear ?outerYear.
      BIND((YEAR(?raceDate)- YEAR(?dob)) AS ?age)
      FILTER(?outerRound = ?maxRound && ?outerYear = ?year && ?pos = 1)
    {
      SELECT ?year (MAX(?round) AS ?maxRound) WHERE {
        ?race :inSeason ?season ;
        :hasRound ?round
        ?season :hasYear ?year.
        FILTER(?year >= 2000)
      }
      GROUP BY ?year
    }
    GROUP BY ?year
  }
}
  {
    SELECT (AVG(?age)as ?avgRecentAge) WHERE{
      ?stand :hasRace ?race ;
      :hasDriver ?driv ;
      :hasTotalPosition ?pos
      ?driv :hasDateOfBirth ?dob.
      ?race :hasDate ?raceDate ;
      :inSeason ?outerSeason ;
      :hasRound ?outerRound
      ?outerSeason :hasYear ?outerYear.
      BIND((YEAR(?raceDate)- YEAR(?dob)) AS ?age)
      FILTER(?outerRound = ?maxRound && ?outerYear = ?year && ?pos = 1)
    {
      SELECT ?year (MAX(?round) AS ?maxRound) WHERE {
        ?race :inSeason ?season ;
        :hasRound ?round
        ?season :hasYear ?year.
        FILTER(?year >= 2000)
      }
      GROUP BY ?year
    }
    FILTER(?avgRecentAge > ?avgOldAge)
  }
}
}
  
```

SPARQL RESULT:

NO

Before 2000 avg age:

33.0

After 2000 avg age:


28.8



Query 19

Championship winning drivers who won more than 2 championships, ordered by number of championships won

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianFl#>
SELECT ?name (COUNT(?name) AS ?numOfWins) (GROUP_CONCAT(DISTINCT ?outerYear ; separator=",") AS ?years) WHERE{
    ?stand :hasRace ?race ;
        :hasDriver ?driv ;
        :hasTotalPosition ?pos.
    ?driv a :Driver;
        :hasForename ?fname;
        :hasSurname ?surname
    BIND(CONCAT(?fname, " ", ?surname) AS ?name)
    ?race :hasDate ?raceDate ;
        :inSeason ?outerSeason ;
        :hasRound ?outerRound.
    ?outerSeason :hasYear ?outerYear.
    FILTER(?outerRound = ?maxRound && ?outerYear = ?year && ?pos = 1)
    {
        SELECT ?year (MAX(?round) AS ?maxRound) WHERE {
            ?race :inSeason ?season ;
                :hasRound ?round
                ?season :hasYear ?year.
        }
        GROUP BY ?year
        ORDER BY ?year
    }
}
GROUP BY ?name
HAVING (?numOfWins > 2)
ORDER BY DESC (?numOfWins)
```



SPARQL RESULT:

	name	numOfWins	years
1	"Michael Schumacher"	"7***xsd:integer"	"1994,1995,2000,2001,2002,2003,2004"
2	"Lewis Hamilton"	"5***xsd:integer"	"2008,2014,2015,2017,2018,2019,2020"
3	"Juan Fangio"	"5***xsd:integer"	"1951,1954,1955,1956,1957"
4	"Alain Prost"	"4***xsd:integer"	"1985,1986,1989,1993"
5	"Sebastian Vettel"	"4***xsd:integer"	"2010,2011,2012,2013"
6	"Jack Brabham"	"3***xsd:integer"	"1959,1960,1966"
7	"Jackie Stewart"	"3***xsd:integer"	"1969,1971,1973"
8	"Niki Lauda"	"3***xsd:integer"	"1975,1977,1984"
9	"Nelson Piquet"	"3***xsd:integer"	"1981,1983,1987"
10	"Ayrton Senna"	"3***xsd:integer"	"1988,1990,1991"
11	"Max Verstappen"	"3***xsd:integer"	"2021,2022,2023"

WIKIPEDIA:

Driver	Titles	Season(s)
Michael Schumacher	7	1994, 1995, 2000, 2001, 2002, 2003, 2004
Lewis Hamilton	5	2008, 2014, 2015, 2017, 2018, 2019, 2020
Juan Manuel Fangio	5	1951, 1954, 1955, 1956, 1957
Alain Prost	4	1985, 1986, 1989, 1993
Sebastian Vettel	4	2010, 2011, 2012, 2013
Jack Brabham	3	1959, 1960, 1966
Jackie Stewart	3	1969, 1971, 1973
Niki Lauda	3	1975, 1977, 1984
Nelson Piquet	3	1981, 1983, 1987
Ayrton Senna	3	1988, 1990, 1991
Max Verstappen	3	2021, 2022, 2023



Query 22

Winners of driver's championship and constructor's championship for each season.

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
SELECT ?outerYear ?driverName ?constructorName WHERE{
    ?driverStand :hasTotalPosition ?pos ;
        :hasRace ?race ;
        :hasDriver ?driver .
    ?constStand :hasTotalPosition ?pos ;
        :hasRace ?race ;
        :hasConstructor ?const .
    ?race :hasRound ?outerRound ;
        :inSeason ?season .
    ?season :hasYear ?outerYear .
    ?driver :hasForename ?fname ;
        :hasSurname ?sname .
    ?const :hasName ?constructorName .
    BIND(CONCAT(?fname, " ", ?sname) AS ?driverName).
    FILTER(?outerRound = ?maxRound && ?outerYear = ?year && ?pos = 1)
    {
        SELECT ?year (MAX(?round) AS ?maxRound) WHERE {
            ?race :inSeason ?season ;
                :hasRound ?round .
            ?season :hasYear ?year .
        }
        GROUP BY ?year
    }
}
ORDER BY DESC (?outerYear)
```

SPARQL RESULT:


	outerYear	driverName	constructorName
1	"2023"^^xsd:integer	'Max Verstappen'	'Red Bull'
2	"2022"^^xsd:integer	'Max Verstappen'	'Red Bull'
3	"2021"^^xsd:integer	'Max Verstappen'	'Mercedes'
4	"2020"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
5	"2019"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
6	"2018"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
7	"2017"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
8	"2016"^^xsd:integer	'Nico Rosberg'	'Mercedes'
9	"2015"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
10	"2014"^^xsd:integer	'Lewis Hamilton'	'Mercedes'
11	"2013"^^xsd:integer	'Sebastian Vettel'	'Red Bull'

Query 23

Drivers who gained the most positions during a race after 2000

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
SELECT ?driverName ?raceSeason ?positionsGained WHERE {
    ?part :hasStartingGridPosition ?grid ;
        :participatedInRace ?race ;
        :hasDriver ?driver ;
        :hasPosition ?pos .
    ?driver :hasForename ?fname ;
        :hasSurname ?surname .
    ?race :inSeason ?season ;
        :hasName ?raceName .
    ?season :hasYear ?year .
    FILTER(?year >= 2000)
    BIND((?grid - ?pos) AS ?positionsGained)
    BIND(CONCAT(?fname, " ", ?surname) AS ?driverName)
    BIND(CONCAT(?raceName, " ", STR(?year)) AS ?raceSeason)
}
ORDER BY DESC (?positionsGained)
LIMIT 15
```

BAR CHART:



SPARQL RESULT:

	driverName	raceSeason	positionsGained
1	"Sebastian Vettel"	'Abu Dhabi Grand Prix 2012'	21***xsd:integer
2	"Kimi Räikkönen"	'Bahrain Grand Prix 2006'	19***xsd:integer
3	"Michael Schumacher"	'Belgian Grand Prix 2011'	19***xsd:integer
4	"Lewis Hamilton"	'Hungarian Grand Prix 2014'	19***xsd:integer
5	"Sebastian Vettel"	'German Grand Prix 2019'	18***xsd:integer
6	"Max Verstappen"	'Russian Grand Prix 2021'	18***xsd:integer
7	"Fernando Alonso"	'Monaco Grand Prix 2010'	18***xsd:integer
8	"Heikki Kovalainen"	'Canadian Grand Prix 2007'	18***xsd:integer
9	"Jarno Trulli"	'United States Grand Prix 2006'	18***xsd:integer
10	"Juan Pablo Montoya"	'German Grand Prix 2005'	18***xsd:integer
11	"Lewis Hamilton"	'Belgian Grand Prix 2016'	18***xsd:integer
12	"Jarno Trulli"	'Australian Grand Prix 2009'	17***xsd:integer
13	"Carlos Sainz"	'Brazilian Grand Prix 2019'	17***xsd:integer
14	"Rubens Barrichello"	'German Grand Prix 2000'	17***xsd:integer
15	"Michael Schumacher"	'Monaco Grand Prix 2006'	17***xsd:integer

Query 24

Drivers ordered by pole-to-win percentage
(percentage of races won starting from the first position in grid)

```


PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
SELECT ?name ?numOfPoleWins ?numOfPoles ?winPercentage WHERE{
    {
        SELECT ?name (COUNT(?name) AS ?numOfPoleWins) WHERE{
            ?racePart :participatedInRace ?race ;
                :hasDriver ?driv ;
                :hasStartingGridPosition ?startPos ;
                :hasPosition ?pos .
            ?driv a :Driver;
                :hasForename ?fname;
                :hasSurname ?surname.
            BIND(CONCAT(?fname, " ", ?surname) AS ?name).
            FILTER(?startPos = 1 && ?pos = 1)
        }
        GROUP BY ?name
    }
    {
        SELECT ?name (COUNT(?name) AS ?numOfPoles) WHERE{
            ?racePart :participatedInRace ?race ;
                :hasDriver ?driv ;
                :hasStartingGridPosition ?startPos .
            ?driv a :Driver;
                :hasForename ?fname;
                :hasSurname ?surname.
            BIND(CONCAT(?fname, " ", ?surname) AS ?name).
            FILTER(?startPos = 1)
        }
        GROUP BY ?name
    }
    BIND((?numOfPoleWins / ?numOfPoles) * 100 AS ?winPercentage)
}
ORDER BY DESC (?winPercentage)

```

SPARQL RESULT:

	name	numOfPoleWins	numOfPoles	winPercentage
1	"Pastor Maldonado"	"1"**xsd:integer	"1"**xsd:integer	"100"**xsd:decimal
2	"Jo Bonnier"	"1"**xsd:integer	"1"**xsd:integer	"100"**xsd:decimal
3	"Pat Flaherty"	"1"**xsd:integer	"1"**xsd:integer	"100"**xsd:decimal
4	"Bill Vukovich"	"1"**xsd:integer	"1"**xsd:integer	"100"**xsd:decimal
5	"Thierry Boutsen"	"1"**xsd:integer	"1"**xsd:integer	"100"**xsd:decimal
6	"Max Verstappen"	"27"**xsd:integer	"32"**xsd:integer	"84.37500"**xsd:decimal
7	"Jody Scheckter"	"2"**xsd:integer	"3"**xsd:integer	"66.6666666666666666666666666670"**xsd:decimal
8	"Emerson Fittipaldi"	"4"**xsd:integer	"6"**xsd:integer	"66.6666666666666666666666666670"**xsd:decimal
9	"Alberto Ascari"	"9"**xsd:integer	"14"**xsd:integer	"64.28571428571428570"**xsd:decimal
10	"Fernando Alonso"	"14"**xsd:integer	"22"**xsd:integer	"63.63636363636363636400"**xsd:decimal

BAR CHART:





Query 25

Drivers who finished first in a race and were placed in the last quarter in the standing at the previous race

```
PREFIX : <https://www.dei.unipd.it/db2/groupProject/FASTianF1#>
SELECT ?driverName ?raceName ?round ?year WHERE{
    ?race :hasRound ?round ;
           :inSeason ?season ;
           :hasName ?raceName.
    ?part :participatedInRace ?race ;
           :hasPosition ?pos ;
           :hasDriver ?driver.
    ?driver :hasForename ?fname ;
             :hasSurname ?lname.
    ?season :hasYear ?year.
    BIND((?round+1) AS ?prevRound)
    BIND(CONCAT(?fname," ",?lname) AS ?driverName)
    FILTER(?pos = 1 && EXISTS{
        ?prevRace :hasRound ?prevRound ;
                   :inSeason ?season
        ?stand :hasRace ?prevRace ;
                :hasDriver ?driver ;
                :hasTotalPosition ?totPos
        FILTER (?totPos>= ((?maxPos/4)*3) && ?prevRace = ?raceMax)
        {
            SELECT ?raceMax (MAX(?totPos) AS ?maxPos) WHERE {
                ?standing a :DriverStanding ;
                           :hasRace ?raceMax ;
                           :hasTotalPosition ?totPos
            }
            GROUP BY ?raceMax
        }
    })
    ORDER BY (?year)
```

SPARQL RESULT:

	driverName	raceName	round	year
1	"Alberto Ascari"	"Belgian Grand Prix"	"3"^^xsd:integer	"1952"^^xsd:integer
2	"Jack Brabham"	"Dutch Grand Prix"	"4"^^xsd:integer	"1960"^^xsd:integer
3	"Dan Gurney"	"French Grand Prix"	"4"^^xsd:integer	"1962"^^xsd:integer
4	"John Surtees"	"Belgian Grand Prix"	"2"^^xsd:integer	"1966"^^xsd:integer
5	"Ludovico Scarfiotti"	"Italian Grand Prix"	"7"^^xsd:integer	"1966"^^xsd:integer
6	"Dan Gurney"	"Belgian Grand Prix"	"4"^^xsd:integer	"1967"^^xsd:integer
7	"Jean-Pierre Beltoise"	"Monaco Grand Prix"	"4"^^xsd:integer	"1972"^^xsd:integer
8	"Jean-Pierre Jabouille"	"French Grand Prix"	"8"^^xsd:integer	"1979"^^xsd:integer
9	"René Arnoux"	"Brazilian Grand Prix"	"2"^^xsd:integer	"1980"^^xsd:integer
10	"Kimi Räikkönen"	"Malaysian Grand Prix"	"2"^^xsd:integer	"2008"^^xsd:integer
11	"Sebastian Vettel"	"Chinese Grand Prix"	"3"^^xsd:integer	"2009"^^xsd:integer
12	"Lewis Hamilton"	"Malaysian Grand Prix"	"2"^^xsd:integer	"2014"^^xsd:integer
13	"Max Verstappen"	"Saudi Arabian Grand Prix"	"2"^^xsd:integer	"2022"^^xsd:integer



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

DIPARTIMENTO
DI INGEGNERIA
DELL'INFORMAZIONE



Thank you!

