

---

# Efficient Parallelization Layouts for Large-Scale Distributed Model Training

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract

1 Efficiently training large language models requires parallelizing across hundreds of  
2 hardware accelerators and invoking various compute and memory optimizations.  
3 When combined, many of these strategies have complex interactions regarding the  
4 final training efficiency. Prior work tackling this problem did not have access to  
5 the latest set of optimizations, such as FLASHATTENTION or sequence parallelism.  
6 In this work, we conduct a comprehensive ablation study of possible training  
7 configurations for large language models. We distill this large study into several  
8 key recommendations for the most efficient training. For instance, we find that  
9 using a micro-batch size of 1 usually enables the most efficient training layouts.  
10 Larger micro-batch sizes necessitate activation checkpointing or higher degrees  
11 of model parallelism and also lead to larger pipeline bubbles. Our most efficient  
12 configurations enable us to achieve state-of-the-art training efficiency results over  
13 a range of model sizes, most notably a Model FLOPs utilization of 70.5% when  
14 training a LLAMA 13B model.

## 15 1 Introduction

16 The number of parameters and computational resources spent on training deep neural networks is  
17 growing rapidly [1, 3, 11]. The largest models consisting of hundreds of billions of parameters do  
18 not even fit onto a single hardware accelerator. Thus, training these models requires various ways of  
19 reducing the memory requirements, such as ZeRO [13], activation checkpointing [2], and 3D-parallel  
20 (data, tensor, and pipeline parallel) training [10]. 3D parallelism, in particular, has been demonstrated  
21 to be effective for the training of Transformer-based large language models (LLMs) with hundreds of  
22 billions of parameters [10].

23 However, training these models efficiently with 3D parallelism requires significant domain expertise  
24 and extensive manual effort to determine the ideal configurations. These configurations not only  
25 need to combine data, model, and pipeline parallelism most efficiently, but also consider complex  
26 interactions with other memory and compute optimizations. FLASHATTENTION [5] in particular has  
27 had a notable impact since its release, enabling us to train models at previously impossible degrees of  
28 training efficiency. In light of these developments, we conduct a systematic study via a large-scale  
29 training efficiency sweep of these interactions. We consider up to 256 GPUs and LLAMA models  
30 with up to 65 billion parameters.

31 We expand on previous work in this direction [10], but include more complex interactions, such as  
32 varying the micro-batch size alongside the 3D-parallel configuration. We also investigate the impact  
33 of newer methods, such as FLASHATTENTION [5] and sequence parallelism [6], finding that these  
34 can affect the optimal training configuration considerably. Our paper provides several actionable  
35 insights for efficiently training LLMs. In summary, the contributions of our work are as follows:

- We conduct a large sweep over possible configurations for efficiently training LLMs.
- Our work considers more degrees of freedom in the training configurations than previous work [10] and incorporates important recent techniques such as FLASHATTENTION and sequence parallelism.
- We distill our findings into several, actionable insights that enable a more efficient large-scale training of LLMs.

## 2 Background

Training very large models requires the combination of various techniques for parallelization across devices and other memory and compute optimizations. In the following, we provide an overview of the techniques implemented in our in-house training framework <anonymized>, which we use to conduct the experiments in this paper. These techniques are also implemented in various other frameworks [25, 7, 16, 14, 22].

**Data Parallelism** Data parallelism [20] splits the dataset across GPUs during training. Each GPU holds a full model copy, computing loss, and gradients for its data shard in parallel. Gradients are then synchronized across devices before weight updates. However, this requires that the model fits entirely within a single GPU’s memory. For larger models, we can also shard the optimizer states, gradients, and model parameters across GPUs [13, 24]. However, especially when sharding parameters, this introduces additional communication overhead.

**Tensor Parallelism** Tensor parallelism splits individual weight matrices across multiple GPUs and computes the matrix multiplication in parallel across them. As each GPU only holds a shard of the full weight matrix, we can fit larger models into memory. For Transformer models, the self-attention and MLP blocks can be parallelized this way with little communication overhead [16]. Due to the natural parallelism of separate attention heads, we only need a single all-reduce operation in both the forward and backward passes. The MLP block similarly requires just a single synchronization in each pass.

**Pipeline Parallelism** Pipeline parallelism splits the model’s layers into subsequent stages across GPUs. Activations are transferred between these stages. As each GPU only holds some of the layers of the model, we can again fit larger models into memory. However, it can introduce “pipeline bubbles” of GPU inactivity due to processing delays. PipeDream [9] is a scheduling algorithm to reduce these by using micro-batches and scheduling their forward and backward computations across pipeline stages. By interleaving forward and backward passes for each micro-batch, PipeDream further reduces memory usage, discarding activations after the specific micro-batch’s backward pass.

**3D Parallelism** As shown by Megatron-LM [16], data, tensor, and pipeline parallelism can be combined, which is also referred to as 3D parallelism. In this paper, we use model parallelism as an umbrella term for both tensor and pipeline parallelism. With an efficient combination of these techniques, we can scale the training of models up to 1 trillion parameters [10].

**Sequence Parallelism** Sequence parallelism [6] builds on tensor parallelism [16] by further parallelizing normalization and dropout operations along the sequence dimension. This reduces activation memory usage, especially for longer sequences. Efficiently implemented, sequence parallelism does not introduce additional communication overhead when used together with tensor parallelism.

**Activation Checkpointing** Activation checkpointing [2] enables a tradeoff between memory and compute. Instead of storing all activations for gradients, they are recalculated on the fly during the backward pass. This enables fitting larger models into memory and can improve training throughput by enabling larger batch sizes [10].

**Fused Kernels** Fusing sequential operations into a single kernel enhances the efficiency of memory-bound computations. By executing multiple operations concurrently within a single kernel, data is loaded only once, minimizing memory accesses and optimizing computational overhead.

Model	Seq. Len.	GPUs	TP sizes	PP sizes	MB Sizes	Act. Checkpointing	RMSNorm Kernel
13B	2k	64	{1, 2}	{1, 2}	{1, 2, 4, 8}	{yes, no}	{yes, no}
13B	8k	128	{1, 2, 4}	{1, 2, 4}	{1, 2, 4}	{yes, no}	{yes, no}
30B	2k	256	{1, 2, 4}	{1, 2, 4}	{1, 2, 4}	{yes, no}	{yes, no}
30B	8k	128	{2, 4}	{2, 4, 8, 16}	{1, 2, 4}	{yes, no}	{yes, no}
65B	2k	128	{2, 4, 8}	{2, 4, 8}	{1, 2, 4}	{yes, no}	{yes, no}

Table 1: Search space of our training efficiency sweep. We sweep over the Cartesian product of all options given in set notation. In particular, we sweep over different tensor parallelization (**TP**), pipeline parallelization (**PP**), and micro-batch (**MB**) sizes, and also whether activation checkpointing was used. Models with a sequence length of 2k use a global batch size of 2,048, whereas models with a sequence length of 8k use a global batch size of 512. All runs use FLASHATTENTION-2. For runs using activation checkpointing, the RMSNorm kernel caused an error. Therefore, this combination is omitted.

**Flash Attention** Dao et al. [5, 4] introduce an IO-aware attention algorithm that builds on kernel fusion. Their method provides speedups compared to a conventional implementation by minimizing read/write operations between the slower high-bandwidth memory and the quicker on-chip SRAM in GPUs. Additionally, selective activation recomputation during the backward pass alleviates the  $\mathcal{O}(n^2)$  memory cost in the sequence length.

### 3 Experimental Setup

Our experiments are conducted on up to 32 NVIDIA DGX A100 nodes, each equipped with eight NVIDIA A100 80GB GPUs, resulting in a total of 256 GPUs. The GPUs within each node are interconnected via a third-generation NVLink<sup>1</sup>, which provides 600GB/s of bandwidth. Cross-node communication is facilitated by NVIDIA Mellanox 200Gb/s HDR Infiniband<sup>2</sup> connections.

We choose the LLAMA [18] model architecture for our experiments, due to its recent popularity. The LLAMA architecture introduces minor improvements over the standard Transformer architecture [21], which have been incorporated into other models over the past few years. The primary architecture modifications include pre-normalization and RMSNorm [23], the SwiGLU activation function [15], and rotary positional embeddings [17]. Our LLAMA models use a 128k token vocabulary. The LLAMA models have a sequence length of 2k tokens. However, the growing trend of training LLMs with longer sequences [11, 19] led us to assess the training efficiency of our LLAMA models on sequences of up to 8k in length. We use AdamW optimization [8] following the training setup of LLAMA [18]. All training is conducted with our in-house large-scale training framework <anonymized> using mixed-precision with `bf16`. We use ZeRO-1 [13] to shard the optimizer states across all data parallel ranks based on the results of previous scaling experiments [10].

We aim to provide a systematic analysis of different combinations of parallelization strategies and other memory and compute optimizations. To this end, we conduct a large-scale *training efficiency sweep*. We run this analysis for the following model types: LLAMA 13B (2k & 8k sequence length), LLAMA 30B (2k & 8k sequence length), and LLAMA 65B (2k sequence length). Depending on the model size and availability of compute, we use 64 to 256 GPUs. Table 1 lists the different configuration options for each of the model types. For our training efficiency sweep, we build the Cartesian product of possible options and benchmark each individual configuration. For each configuration, we train for 10 global steps and measure the Model FLOPS Utilization (MFU) [3]. We exclude the first step, as its performance is significantly impacted by a warm-up phase, and report the mean of the last 9 steps.<sup>3</sup> We choose MFU [3] over other metrics such as measured hardware TFLOPS, since the latter are system- and implementation-dependent.

Specifically, we compare different tensor parallelization, pipeline parallelization, and micro-batch sizes, as well as the use of activation checkpointing (yes/no). Since we operate with a fixed number of GPUs and global batch size for each model, the data parallelization size and the number of necessary accumulation steps directly follow from the other specified options and are automatically calculated.

<sup>1</sup>NVLink: [nvidia.com/en-us/data-center/nvlink](https://nvidia.com/en-us/data-center/nvlink)

<sup>2</sup>Infiniband: [nvidia.com/en-us/networking/infiniband-switching](https://nvidia.com/en-us/networking/infiniband-switching)

<sup>3</sup>Our detailed MFU calculation is reported in Appendix A.1.




Figure 1: Comparison of the MFU with different attention layer optimizations. The optimal 3D layout was selected for each respective setting. Each optimal layout is annotated with its (micro-batch size, tensor parallelism size, pipeline parallelism size). The kernel from Megatron-LM failed to operate with an 8k sequence length.

For example, using 128 GPUs with a tensor parallelization size of 4 and pipeline parallelization size of 2 results in a rank 16 data parallelization (with  $4 \times 2 \times 16 = 128$ ), each with 2 pipeline stages and each pipeline stage sharded across 4 tensor parallel splits. We provide the full results of our training efficiency sweep in Table B.1.

Additionally, we conducted a preliminary sweep over different attention kernels (native Torch implementation, Megatron-LM kernel<sup>4</sup>, FLASHATTENTION-1.0.8, and FLASHATTENTION-2). Based on the results, we concluded that FLASHATTENTION-2 is superior and thus always used it for our main sweep.

In the following section, we will distill the extensive sweep into different, actionable findings that allow us to select the optimal combination of different optimizations.

## 4 Efficient LLM Training Analysis

### 4.1 Fused Kernels and Flash Attention

Our evaluation of FLASHATTENTION expands on the evaluations present in the original papers [5, 4]. While those studies compared the efficiency of FlashAttention for models up to 2.7B parameters on a single node, we scaled our experiments to substantially larger model sizes and also up to 256 GPUs. We further compare with a more optimized baseline, the Megatron-LM softmax attention kernel. Additionally, we evaluate the use of an optimized RMSNorm kernel from the FLASHATTENTION repository.

#### 4.1.1 Attention

In Figure 1, we present results from both our main and preliminary sweeps over attention implementations, detailed in Section 3. We compare the following different kernels: FLASHATTENTION-2, FLASHATTENTION-1.0.8, the Megatron-LM kernel, and the standard PyTorch implementation. The fused kernel does not support a sequence length exceeding 2,048 tokens. Due to the underperformance of pure PyTorch attention in our LLAMA 13B evaluation, we did not include it for larger models. For LLAMA 65B and 30B with 8k sequence length, we only considered FLASHATTENTION.

Unsurprisingly, we find that FLASHATTENTION vastly outperforms the native PyTorch implementation. However, we also find that FLASHATTENTION significantly outperforms the kernel from Megatron-LM. Between the two different FLASHATTENTION versions, FLASHATTENTION-2 outperforms FLASHATTENTION-1.0.8 by 4 to 13 percentage points across model sizes. FLASHATTENTION-1.0.8 already contains many of the optimizations introduced in the FLASHATTENTION-2 paper, which measures a  $2\times$  improvement [4].

<sup>4</sup>Megatron-LM softmax attention kernel: from here (Date: 28 July 2022)




Figure 2: Comparing MFU of the optimal 3D-layout with and without activation checkpointing. LLAMA 30B with 8k sequence length did not fit into memory without checkpointing. The reported results do not use the RMSNorm kernel. Each optimal layout is annotated with its (micro-batch size, tensor parallelism size, pipeline parallelism size).

150 It is important to note that FLASHATTENTION’s improvements are two-fold: FLASHATTENTION’s  
 151 improved tiling method for an efficient IO-aware SRAM cache utilization and reduced memory  
 152 requirements through its activation recomputation approach in the attention block. Notably, all  
 153 best-performing FLASHATTENTION layouts reported in Figure 1 do not make use of activation  
 154 checkpointing, thereby also benefiting from FLASHATTENTION’s own activation recomputation.

#### 155 4.1.2 RMSNorm Kernel

156 We also evaluate the effect of FLASHATTENTION’s optimized RMSNorm kernel in Figure 1. We see  
 157 that the RMSNorm kernel provides a significant boost in training efficiency, up to 14 percentage points  
 158 compared to FLASHATTENTION-2 without the RMSNorm kernel. Notably, with the use of the kernel,  
 159 we can fit the entire LLAMA 13B model into a single GPU without model parallelization during  
 160 training (although we still employ ZeRO-1 and shard the optimizer states). In general, the RMSNorm  
 161 kernel allows us to choose more efficient parallelization layouts due to its memory savings. We do  
 162 not have results combining activation checkpointing with the RMSNorm kernel, as the combination  
 163 caused an error in our experiments. We control for this and only consider runs without the RMSNorm  
 164 kernel whenever necessary for a fair comparison.

#### 165 4.2 Activation Checkpointing

166 In Figure 2, we report the MFU of the best configurations across model sizes, both with activation  
 167 checkpointing of every layer and without. Overall, we see that not using activation checkpointing  
 168 and compensating the incurred memory cost with smaller batch sizes or a higher degree of model  
 169 parallelism achieves the best training throughputs. For a fair comparison, we do not include runs with  
 170 the RMSNorm kernel, since the kernel caused an error when coupled with checkpointing.

171 For the LLAMA 30B with 8k sequence length, activation checkpointing was necessary to fit the model  
 172 into memory during training, even with tensor parallelism sizes up to 4 and pipeline parallelism  
 173 sizes of up to 16. We could not increase the tensor parallelism because the LLAMA 30B model  
 174 has 52 attention heads, which are not divisible by 8. In Section 4.1, we show that adding the  
 175 RMSNorm kernel further reduces the required memory so that activation checkpointing does not  
 176 become necessary. In this case, we again see that a layout without activation checkpointing achieves  
 177 the best throughput.<sup>5</sup>

178 It is crucial to underline that achieving efficient performance for such model sizes without activation  
 179 checkpointing is only feasible due to FLASHATTENTION. Without FLASHATTENTION, any runs  
 180 exceeding the size of LLAMA 13B required the use of activation checkpointing due to out-of-memory  
 181 errors, despite the high degrees of parallelization we considered as part of our sweep.

<sup>5</sup>Detailed results are reported in Appendix B.5.




Figure 3: MFU of the best-performing run configurations at different fixed micro-batch sizes, visualized by the (activation checkpointing, tensor parallelism size, pipeline parallelism size) triple. The reported results do not use the RMSNorm kernel.

FLASHATTENTION already employs its own selective activation checkpointing in the attention block. These findings suggest activation checkpointing for large-scale Transformer training needs to be more targeted. Previous work [6] has also questioned the need for checkpointing in every layer and suggests a selective activation recomputation approach within the attention block. However, with the introduction of FLASHATTENTION, the focus on selective activation recomputation within the attention block becomes arguably less important, as this is already covered in an efficient manner within FLASHATTENTION. Nevertheless, a promising approach can be the application of selective activation recomputation only to the MLP block, thereby complementing FLASHATTENTION’s inherent activation recomputation of the attention block.

### 4.3 Micro-batch size

In this section, we evaluate the tradeoff between the micro-batch size and required degree of model (tensor or pipeline) parallelism and activation checkpointing. Previous work [10] benchmarked different micro-batch sizes with fixed degrees of tensor and pipeline parallelism and show that larger micro-batch sizes lead to higher throughput. However, a smaller micro-batch size might enable a different, more efficient parallelization configuration. Also, the degree of tensor and pipeline parallelism are often not fixed in practice.

In Figure 3, we show the best performing (activation checkpointing, tensor parallel size, pipeline parallel size) configuration for each of our assessed model types. To fairly evaluate activation checkpointing, we do not include runs with the RMSNorm kernel, since the kernel resulted in an error when coupled with checkpointing. We see that for all model types, a micro-batch size of 1 achieves the best MFU. In general, we find: the smaller the micro-batch size, the better the MFU. The models with an 8k sequence length did not fit into memory with any configuration when using a micro-batch size bigger than 2.

Thus, we conclude that choosing a micro-batch size of 1 is beneficial in most scenarios. The superior performance of a micro-batch size of 1 can be attributed to the following factors:




Figure 4: MFU for various model and pipeline parallel configurations for the LLAMA 13B with 8k sequence length, LLAMA 30B and LLAMA 65B models. Only runs with a micro-batch size of 1, activation checkpointing disabled, FLASHATTENTION-2, and the RMS norm kernel are included; runs that ran out of memory are excluded. The LLAMA 13B and the LLAMA 30B with 8k sequence length models are excluded due to limited model parallel configuration options in our sweep.

**Minimal Degree of Model Parallelization:** The most efficient training typically requires the least amount of model (tensor or pipeline) parallelization, which is realized when the micro-batch size is smallest.

**Avoiding Activation Checkpointing:** For some models (e.g., LLAMA 65B), a micro-batch size of 1 was the only configuration allowing training without activation checkpointing. As discussed in the previous section, not using activation checkpointing often allows for the highest throughput configurations. The LLAMA 30B 8k model did not fit into memory without using the RMSNorm kernel.

**Reduced Pipeline Bubble Time:** A smaller micro-batch size reduces the time spent in the pipeline bubble at the beginning and end of a batch. We already use the better-than-naive Pipedream 1F1B scheduling method [9] discussed in Section 2.

#### 4.4 Tensor vs. Pipeline Parallelism

Narayanan et al.’s [10] ablation studies show that neither tensor nor pipeline parallelism, when used in isolation, can achieve the performance of utilizing both at the same time. Our empirical data, especially from the LLAMA 65B model – where higher degrees of parallelism are necessary – validate this to some extent even in combination with the newly introduced optimizations, as depicted in Figure 4. Their results suggest that an even distribution between the tensor and pipeline parallelism size is optimal, up until the tensor parallelism size reaches the GPU limit in a single node. In contrast, our results favor pipeline parallelism over model parallelism. The LLAMA 65B model performed best with a (model, pipeline) parallelism size of (2, 8) compared to an evenly distributed (4, 4). Also, the (8, 2) configuration was considerably less efficient. The training efficiency measured by Megatron-LM [16] was comparable when the tensor and pipeline parallelism sizes were interchanged.

#### 4.5 Sequence Parallelism

In this section, we perform an additional efficiency sweep to assess the impact of sequence parallelism. Based on the findings from previous sections, we limited the search space to consistently use FLASHATTENTION-2, the RMSNorm kernel, while omitting the use of activation checkpointing. Furthermore, we restricted the number of GPUs for each model type due to computational constraints. The full configuration sweep for each model type is documented in Table 9.

In Figure 5, we report the MFU of the best configurations across model sizes, both with sequence parallelism enabled or disabled. For the LLAMA 13B and 30B models with a 2k sequence length, the top configurations do not employ any tensor parallelism, hence the activation of sequence parallelism shows no effect. In the case of the 13B model with an 8k sequence length, the top configuration employs a tensor parallelism size of 2; however, no improvement in training efficiency is observed. For the largest models and sequence lengths, the 30B with 8k sequence length and the 65B models, we can see 2-6 percentage point improvements when using sequence parallelism. In both cases,




Figure 5: Comparing MFU of the optimal 3D-layout with and without sequence parallelism. The reported results use the RMSNorm kernel. Each optimal layout is annotated with its (micro-batch size, tensor parallel size, pipeline parallel size).

Model	GPUs	Seq. Len.	Batch Size	MFU ( $\uparrow$ )
<anonymized> LLAMA 13B (ours)	64	2048	2048	<b>70.5%</b>
MPT 13B	64	2048	2048	52.5%
Megatron-LM 18B <sup>†</sup>	256	2048	1024	34.2%
<anonymized> LLAMA 13B (ours)	64	8192	512	<b>62.7%</b>
MPT 13B	8	8192	120	52.8%
<anonymized> LLAMA 30B (ours)	64	2048	2048	<b>61.9%</b>
MPT 30B	64	2048	3072	52.9%
Megatron-Deepspeed 22B	8	2048	4	41.5%
Megatron-LM 39B <sup>†</sup>	512	2048	1536	34.5%
<anonymized> LLAMA 30B (ours)	64	8192	512	<b>60.2%</b>
MPT 30B	8	8192	168	42.6%
<anonymized> LLAMA 65B (ours)	64	2048	2048	<b>59.6%</b>
MPT 70B	64	2048	2048	53.3%
LLAMA 65B by Meta <sup>†</sup>	2048	2048	2048	49.4%
Megatron-LM 76B <sup>†</sup>	1024	2048	1792	34.7%

Table 2: Comparison of end-to-end model training efficiency performance across comparable models, training frameworks, and hardware environments on a cluster of A100 80GB nodes. Batch size refers to the *Global* Batch size. <sup>†</sup>: MFU numbers were calculated by us based on published training times, as detailed in Appendix A. We provide the exact configurations of our runs included in this table in Appendix B.1.

sequence parallelism enables a lower degree of model parallelization due to the reduced memory requirements, leading to higher training efficiency.

Therefore, we conclude that the use of sequence parallelism, when paired with several other optimizations explored in this work, only facilitates a notable difference in training efficiency for model sizes exceeding 30B parameters or 2k sequence length.

#### 4.6 End-to-End Performance

We evaluate the recommendations distilled from our extensive training efficiency sweep against other publicly reported results in Table 2. For our runs using the in-house <anonymized> framework, we report the MFU of the best configuration for each model size, following our recommendations.



We evaluate against publicly available benchmarks from MosaicML<sup>6</sup>, Megatron-Deepspeed [6], Meta’s LLAMA [18], and Megatron-LM [10]. Other frameworks were excluded from our comparisons, because they either lacked publicly available training efficiency scores, used entirely different hardware, or trained models with vastly different parameter sizes. To the best of our knowledge, we have gathered the best performing, publicly available training efficiency benchmarks for LLMs with comparable architectures and parameter counts.

In general, our best configurations achieve the highest MFU numbers, setting the state-of-the-art for all our assessed model sizes. The improvements on top of the previous state-of-the-art range from 6–18 MFU percentage points. Noticeably our LLAMA 13B model achieves an MFU of 70.5%, outperforming the MPT and Megatron-LM models. For the 13B and 30B models with an 8k sequence length, our only point of comparison are the models by MosaicML’s framework. Here, we outperform the MPT models by 9–17 percentage points. Within the 65B parameter model range, we outperform MPT-70B, the original LLAMA 65B model by Meta, and the Megatron-LM 76B model with an MFU of 59.6% compared to 53.3%, 49.4%, and 34.7%, respectively.

We hope that our findings can contribute to pushing the envelope of efficiently utilizing hardware accelerators for large-scale model training.

**Note on comparability.** Most of the comparisons in Table 2 are not one-to-one, due to further differences such as model architecture, employed global batch size, number of used GPUs, and hardware interconnect. For example, the MPT model family employs additional efficiency optimizations, such as the use of ALiBi [12] instead of RoPE [17]. On the other hand, our models use a 128k token vocabulary, which can result in a more optimistic MFU estimate compared to smaller vocabulary sizes. The comparison made in Table 2 is not meant to be directly one-to-one, but a wholesale evaluation of the achieved end-to-end training efficiency. We hope to showcase that a careful evaluation of the training layout and optimizations used can enable a significant boost to training efficiency.

## 5 Conclusion

We conducted an exhaustive search over possible combinations of tensor, pipeline, and data parallelism layouts, fused kernels, FLASHATTENTION, activation checkpointing, micro-batch sizes, and sequence parallelism. Based on our findings, we make the following recommendations:

- Use a micro-batch size of 1 to enable the least degree of model parallelization, to avoid activation checkpointing, and to reduce pipeline bubbles.
- Prefer increasing the degree of tensor and pipeline parallelization over the use of activation checkpointing.
- Only scale the micro-batch size when you cannot further reduce the degree of model parallelization.
- Use sequence parallelization for models exceeding 30B parameters and 2k sequence length.

We experimentally verify that the efficacy of the FLASHATTENTION-2 kernel remains as we scale the model size to tens of billions of parameters and to training on multiple nodes. Additionally, we compared the end-to-end training efficiency of our most efficient configurations against several other frameworks. We achieved state-of-the-art efficiency in five out of the five model configurations we evaluated, reaching up to 70.5% MFU.

For future work, reconciling activation checkpointing with FLASHATTENTION via a more selective approach that targets the MLP block presents an exciting opportunity. Also, Nvidia’s recently released H100 GPUs with more efficient support for fp8 precision might enable new training strategies, which should be evaluated.

We will publish the full data of our sweeps and scripts to reproduce all figures on GitHub.

---

<sup>6</sup>MosaicML MPT Training Benchmarks: from here (Date: 26 September 2023)

## References

- [1] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.
- [2] Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost, 2016.
- [3] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayanan Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways, 2022.
- [4] Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning, 2023.
- [5] Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. Flashattention: Fast and memory-efficient exact attention with io-awareness, 2022.
- [6] Vijay Korthikanti, Jared Casper, Sangkug Lym, Lawrence McAfee, Michael Andersch, Mohammad Shoeybi, and Bryan Catanzaro. Reducing activation recomputation in large transformer models, 2022.
- [7] Shenggui Li, Jiarui Fang, Zhengda Bian, Hongxin Liu, Yuliang Liu, Haichen Huang, Boxiang Wang, and Yang You. Colossal-ai: A unified deep learning system for large-scale parallel training, 2022.
- [8] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization, 2019.
- [9] Deepak Narayanan, Amar Phanishayee, Kaiyu Shi, Xie Chen, and Matei Zaharia. Memory-efficient pipeline-parallel dnn training, 2020.
- [10] Deepak Narayanan, Mohammad Shoeybi, Jared Casper, Patrick LeGresley, Mostofa Patwary, Vijay Anand Korthikanti, Dmitri Vainbrand, Prethvi Kashinkunti, Julie Bernauer, Bryan Catanzaro, Amar Phanishayee, and Matei Zaharia. Efficient large-scale language model training on gpu clusters using megatron-lm, 2021.
- [11] OpenAI. Gpt-4 technical report, 2023.
- [12] Ofir Press, Noah A. Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation, 2022.
- [13] Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. Zero: Memory optimizations toward training trillion parameter models, 2020.
- [14] Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2020.
- [15] Noam Shazeer. Glue variants improve transformer, 2020.
- [16] Mohammad Shoeybi, Mostofa Patwary, Raul Puri, Patrick LeGresley, Jared Casper, and Bryan Catanzaro. Megatron-lm: Training multi-billion parameter language models using model parallelism, 2019.
- [17] Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding, 2022.
- [18] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023.

- [19] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.
- [20] Leslie G. Valiant. A bridging model for parallel computation. *Commun. ACM*, 33(8):103–111, aug 1990.
- [21] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.
- [22] Yuanzhong Xu, HyoukJoong Lee, Dehao Chen, Blake Hechtman, Yanping Huang, Rahul Joshi, Maxim Krikun, Dmitry Lepikhin, Andy Ly, Marcello Maggioni, Ruoming Pang, Noam Shazeer, Shibo Wang, Tao Wang, Yonghui Wu, and Zhifeng Chen. Gspmd: General and scalable parallelization for ml computation graphs, 2021.
- [23] Biao Zhang and Rico Sennrich. Root mean square layer normalization, 2019.
- [24] Yanli Zhao, Andrew Gu, Rohan Varma, Liang Luo, Chien-Chin Huang, Min Xu, Less Wright, Hamid Shojanazeri, Myle Ott, Sam Shleifer, Alban Desmaison, Can Balioglu, Pritam Damania, Bernard Nguyen, Geeta Chauhan, Yuchen Hao, Ajit Mathews, and Shen Li. Pytorch fsdp: Experiences on scaling fully sharded data parallel, 2023.
- [25] Lianmin Zheng, Zhuohan Li, Hao Zhang, Yonghao Zhuang, Zhifeng Chen, Yanping Huang, Yida Wang, Yuanzhong Xu, Danyang Zhuo, Eric P. Xing, Joseph E. Gonzalez, and Ion Stoica. Alpa: Automating inter- and intra-operator parallelism for distributed deep learning, 2022.

## A Measuring Model Training Efficiency Calculations

### A.1 Model FLOPs Utilization (MFU)

The calculation of Model FLOPs Utilization (MFU) follows that of PaLM [3]. We consider the theoretical peak matrix multiplication throughput of  $P$  FLOPs per second (e.g., A100 GPUs with 312 peak matmul TFLOPs). Then, the model FLOPs utilization is the ratio of the achieved throughput in tokens per second to the theoretical peak throughput  $R = P/(6N + 12LHQT)$ , where  $L$  is the number of layers,  $H$  the number of attention heads,  $Q$  the attention head size, and  $T$  the sequence length. Note that  $L \times H$  is equal to the hidden layer size of the model.

```
class HardwareType(Enum):
    A100 = "a100"
    H100 = "h100"
    RTX3090 = "rtx3090"

    @property
    def max_tflops(self):
        """
        Mappings for Maximum Throughput numbers of each GPU.
        Only includes FP16 for now.
        """
        max_tflop_mapping = {"a100": 312e12, "h100": 989.4e12, "rtx3090": 35.58e12}
        return max_tflop_mapping[self.value]

def get_model_flop_utilizations_palm(
    iter_time_s: float,
    parameter_count: int,
    topology: Any,
    architecture: Any,
    hardware: HardwareType = HardwareType.A100,
):
    tokens_per_second = (
        topology.config.global_batch_size * architecture.sequence_length
    ) / iter_time_s
```

```

theoretical_peak_matmul_throughput = (
    hardware.max_tflops * topology.config.world_size
)
attention_flops = (
    12
    * architecture.num_layers
    * architecture.hidden_size
    * architecture.sequence_length
)
model_flops = 6 * parameter_count + attention_flops
theoretical_peak_throughput = theoretical_peak_matmul_throughput / model_flops
model_flops_utilization = tokens_per_second / theoretical_peak_throughput
return model_flops_utilization

```

## 381 A.2 LLAMA MFU

382 From LLAMA paper [18]:

383 "When training a 65B-parameter model, our code processes around 380 token-  
384 s/sec/GPU on 2048 A100 GPU with 80GB of RAM. This means that training over  
385 our dataset containing 1.4T tokens takes approximately 21 days."

386 LLAMA 65B model FLOPs utilization (MFU):

```

tokens_per_second = 380 * 2048
theoretical_peak_matmul_throughput = (
    312e12 * 2048
)
attention_flops = (
    12
    * 80
    * 8192
    * 2048
)
model_flops = 6 * 65e9 + attention_flops
theoretical_peak_throughput = theoretical_peak_matmul_throughput / model_flops
model_flops_utilization = tokens_per_second / theoretical_peak_throughput

```

387 LLAMA 65B MFU = 49.46%

## 388 A.3 Megatron-LM MFU

389 Based on Megatron-LM's [10] provided formula, the end-to-end training time is given by  $\approx \frac{8TP}{nX}$ ,  
390 where  $T$  represents the number of tokens,  $P$  the number of parameters,  $n$  the number of GPUs,  
391 and  $X$  the achieved TFLOPs per GPU. Since they provide the achieved TFLOPs per GPU, we can  
392 determine the step time through the formula. Subsequently, we can compute the MFU using the  
393 specified architecture configuration of the model.

394 **Megatron-LM 18B:**

395 Step time =  $\frac{8 \cdot 1024 \cdot 2048 \cdot 18.4 \cdot 10^9}{256 \cdot 135 \cdot 10^{12}} s = 8.93s$

```

tokens_per_second = (1024 * 2048) / 8.93
theoretical_peak_matmul_throughput = (
    312e12 * 256
)
attention_flops = (
    12
    * 40
    * 6144
    * 2048
)
model_flops = 6 * 18.4e9 + attention_flops
theoretical_peak_throughput = theoretical_peak_matmul_throughput / model_flops
model_flops_utilization = tokens_per_second / theoretical_peak_throughput

```

396 Megatron-LM 18B MFU = 34.24%

397 **Megatron-LM 39B:**

398 Step time =  $\frac{8 \cdot 1536 \cdot 2048 \cdot 39.1 \cdot 10^9}{512 \cdot 138 \cdot 10^{12}} s = 13.92s$

```

tokens_per_second = (1536 * 2048) / 13.92
theoretical_peak_matmul_throughput = (
    312e12 * 512
)
attention_flops = (
    12
    * 48
    * 8192
    * 2048
)
model_flops = 6 * 39.1e9 + attention_flops
theoretical_peak_throughput = theoretical_peak_matmul_throughput / model_flops
model_flops_utilization = tokens_per_second / theoretical_peak_throughput

```

399 Megatron-LM 39B MFU = 34.56%

400 **Megatron-LM 76B:**

401 Step time =  $\frac{8 \cdot 1792 \cdot 2048 \cdot 76.1 \cdot 10^9}{1024 \cdot 140 \cdot 10^{12}} s = 15.59s$

```

tokens_per_second = (1792 * 2048) / 15.59
theoretical_peak_matmul_throughput = (
    312e12 * 1024
)
attention_flops = (
    12
    * 60
    * 10240
    * 2048
)
model_flops = 6 * 76.1e9 + attention_flops
theoretical_peak_throughput = theoretical_peak_matmul_throughput / model_flops
model_flops_utilization = tokens_per_second / theoretical_peak_throughput

```

402 Megatron-LM 76B MFU = 34.76%

## 403 B Training Efficiency Sweeps

### 404 B.1 End-to-End Best-Performing Runs

Table 3: Configurations for the end-to-end performance results of Table 2. All best-performing layouts use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing.

Model	GPUs	Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
<anonymized> LLAMA 13B	64	3.32	70.57	1	1	1	False
<anonymized> LLAMA 13B 8k seq len	64	34.84	62.78	1	1	2	True
<anonymized> LLAMA 30B	64	72.00	61.98	1	1	4	False
<anonymized> LLAMA 30B 8k seq len	64	84.37	60.22	1	4	2	True
<anonymized> LLAMA 65B	64	147.02	59.62	1	2	4	True

### 405 B.2 LLAMA 13B

Table 4: Performance analysis of a LLAMA 13B model trained on 128 A100 GPUs with the <anonymized> codebase: A comprehensive sweep of 3D parallel layout configurations. The table displays variations in step time and MFU across different activation checkpointing types, kernels, micro batch (MB) sizes, tensor parallel (TP) sizes, and pipeline parallel (PP) sizes. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
26.54	70.57	disabled	flash_attn2 + RMS kern.	1	1	1
29.70	63.05	disabled	flash_attn2 + RMS kern.	2	2	1
31.06	60.26	disabled	flash_attn2 + RMS kern.	1	1	2
31.29	59.82	disabled	flash_attn2 + RMS kern.	1	2	1
33.11	56.55	disabled	flash_attn2 + RMS kern.	2	1	2
33.58	55.71	disabled	flash_attn1.0.8	1	1	2
33.70	55.53	disabled	flash_attn2	1	1	2
33.90	55.19	disabled	flash_attn2	2	2	1

Step Time	MFU	Activation	Kernel	MB Size	TP size	PP Size
34.84	53.69	disabled	flash_attn2 + RMS kern.	1	2	2
35.05	53.37	disabled	flash_attn2 + RMS kern.	2	2	2
35.54	52.64	disabled	flash_attn2	1	2	1
36.66	51.04	every_layer	flash_attn2	4	1	1
36.69	51.02	every_layer	flash_attn2	2	1	1
37.51	49.89	every_layer	flash_attn2	1	1	1
37.57	49.80	disabled	flash_attn2 + RMS kern.	4	2	2
37.71	49.59	disabled	flash_attn1.0.8	2	2	2
38.27	48.86	disabled	flash_attn2	2	1	2
39.64	47.19	disabled	flash_attn2	1	2	2
39.83	46.97	disabled	flash_attn2	2	2	2
40.25	46.46	disabled	flash_attn1.0.8	1	2	2
40.56	46.11	disabled	flash_attn1.0.8	1	2	1
41.81	44.74	disabled	flash_attn1.0.8	2	2	1
42.30	44.21	every_layer	flash_attn1.0.8	2	1	2
42.36	44.14	every_layer	flash_attn1.0.8	1	1	2
42.54	43.96	every_layer	flash_attn1.0.8	4	1	2
43.13	43.36	every_layer	flash_attn1.0.8	4	1	1
43.24	43.26	every_layer	flash_attn2	8	2	1
43.36	43.13	disabled	fused	1	2	2
43.89	42.61	every_layer	flash_attn1.0.8	2	1	1
44.10	42.40	every_layer	flash_attn2	4	2	1
44.13	42.39	every_layer	flash_attn2	1	1	2
44.35	42.18	every_layer	flash_attn1.0.8	1	1	1
44.45	42.09	every_layer	flash_attn2	2	2	1
44.72	41.82	every_layer	flash_attn1.0.8	8	1	2
45.96	40.69	disabled	fused	1	2	1
46.86	39.90	every_layer	fused	2	1	2
47.12	39.72	every_layer	flash_attn2	1	2	1
47.09	39.71	every_layer	flash_attn1.0.8	4	2	1
47.17	39.64	every_layer	fused	4	1	2
47.37	39.51	every_layer	flash_attn2	2	1	2
47.50	39.36	every_layer	flash_attn1.0.8	2	2	1
47.82	39.11	every_layer	fused	4	1	1
47.95	39.00	every_layer	fused	1	1	2
48.93	38.23	every_layer	fused	1	1	1
49.35	37.89	disabled	torch	1	2	2
49.39	37.87	every_layer	fused	2	1	1
49.77	37.57	every_layer	flash_attn1.0.8	4	2	2
50.05	37.37	every_layer	flash_attn1.0.8	1	2	1
50.16	37.28	every_layer	flash_attn1.0.8	8	2	2
51.44	36.41	every_layer	flash_attn1.0.8	2	2	2
51.79	36.11	every_layer	fused	4	2	1
52.55	35.59	disabled	torch	1	2	1
53.50	34.95	every_layer	flash_attn1.0.8	1	2	2
53.57	34.94	every_layer	flash_attn2	2	2	2
54.17	34.52	every_layer	torch	1	1	2
54.35	34.40	every_layer	fused	2	2	1
54.56	34.27	every_layer	fused	2	2	2
55.13	33.95	every_layer	fused	4	2	2
55.35	33.78	every_layer	torch	4	1	2
55.61	33.64	every_layer	flash_attn2	4	1	2
56.21	33.41	every_layer	torch	2	1	2
55.99	33.40	every_layer	torch	1	1	1
56.61	33.06	every_layer	flash_attn2	4	2	2
57.07	32.78	every_layer	torch	2	1	1
57.25	32.66	every_layer	fused	1	2	1
58.92	31.77	every_layer	fused	1	2	2
60.24	31.04	every_layer	torch	4	2	1
60.75	30.78	every_layer	torch	2	2	1
62.60	29.87	every_layer	torch	1	2	1
62.69	29.83	every_layer	torch	2	2	2
63.28	29.58	every_layer	torch	4	2	2
65.25	28.66	every_layer	torch	1	2	2
65.47	28.57	every_layer	flash_attn2	8	2	2
72.82	25.69	every_layer	flash_attn2	8	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	8	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	8	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	8	1	1
OOM Error		disabled	flash_attn2	8	2	2
OOM Error		disabled	flash_attn2	4	2	1
OOM Error		disabled	flash_attn2	8	1	2
OOM Error		disabled	flash_attn2	4	1	2
OOM Error		disabled	flash_attn2	4	1	1
OOM Error		disabled	flash_attn2	8	2	1

Step Time	MFU	Activation	Kernel	MB Size	TP size	PP Size
OOM Error		disabled	flash_attn2	2	1	1
OOM Error		disabled	flash_attn2	1	1	1
OOM Error		disabled	flash_attn2	4	2	2
OOM Error		every_layer	torch	8	2	2
OOM Error		disabled	torch	8	2	2
OOM Error		every_layer	fused	8	2	2
OOM Error		disabled	fused	8	2	2
OOM Error		disabled	flash_attn1.0.8	8	2	2
OOM Error		disabled	torch	4	2	2
OOM Error		disabled	fused	4	2	2
OOM Error		disabled	flash_attn1.0.8	4	2	2
OOM Error		disabled	torch	2	2	2
OOM Error		disabled	fused	2	2	2
OOM Error		every_layer	torch	8	1	2
OOM Error		disabled	torch	8	1	2
OOM Error		every_layer	fused	8	1	2
OOM Error		disabled	fused	8	1	2
OOM Error		disabled	flash_attn1.0.8	8	1	2
OOM Error		disabled	torch	4	1	2
OOM Error		disabled	fused	4	1	2
OOM Error		disabled	flash_attn1.0.8	4	1	2
OOM Error		disabled	torch	2	1	2
OOM Error		disabled	fused	2	1	2
OOM Error		disabled	flash_attn1.0.8	2	1	2
OOM Error		disabled	torch	1	1	2
OOM Error		disabled	fused	1	1	2
OOM Error		every_layer	torch	8	2	1
OOM Error		disabled	torch	8	2	1
OOM Error		every_layer	fused	8	2	1
OOM Error		disabled	fused	8	2	1
OOM Error		every_layer	flash_attn1.0.8	8	2	1
OOM Error		disabled	flash_attn1.0.8	8	2	1
OOM Error		disabled	torch	4	2	1
OOM Error		disabled	fused	4	2	1
OOM Error		disabled	flash_attn1.0.8	4	2	1
OOM Error		disabled	torch	2	2	1
OOM Error		disabled	fused	2	2	1
OOM Error		every_layer	torch	8	1	1
OOM Error		disabled	torch	8	1	1
OOM Error		every_layer	fused	8	1	1
OOM Error		disabled	fused	8	1	1
OOM Error		every_layer	flash_attn1.0.8	8	1	1
OOM Error		disabled	flash_attn1.0.8	8	1	1
OOM Error		every_layer	torch	4	1	1
OOM Error		disabled	torch	4	1	1
OOM Error		disabled	fused	4	1	1
OOM Error		disabled	flash_attn1.0.8	4	1	1
OOM Error		disabled	torch	2	1	1
OOM Error		disabled	fused	2	1	1
OOM Error		disabled	flash_attn1.0.8	2	1	1
OOM Error		disabled	torch	1	1	1
OOM Error		disabled	fused	1	1	1
OOM Error		disabled	flash_attn1.0.8	1	1	1

### 406 B.3 LLAMA 13B with 8k sequence length

Table 5: Performance analysis of a LLAMA 13B model with a sequence length of 8k trained on 128 A100 GPUs with the <anonymized> codebase. All measurements use the flash attention or PyTorch kernel. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
18.41	59.41	disabled	flash_attn2 + RMS kern.	1	2	2
19.32	56.61	disabled	flash_attn2 + RMS kern.	1	2	4
21.36	51.21	disabled	flash_attn2 + RMS kern.	1	4	1
21.94	49.93	disabled	flash_attn2 + RMS kern.	1	4	2
21.93	49.88	disabled	flash_attn2	1	2	4
23.46	46.90	disabled	flash_attn2 + RMS kern.	1	4	4
23.78	46.27	disabled	flash_attn2 + RMS kern.	2	4	4
24.62	44.42	every_layer	flash_attn2	1	1	2
24.84	44.03	disabled	flash_attn1.0.8	1	2	4
25.99	42.08	disabled	flash_attn2	1	4	2
26.29	41.81	every_layer	flash_attn2	1	1	4
26.63	41.08	every_layer	flash_attn2	1	2	1
26.94	40.59	disabled	flash_attn2	1	4	4

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
27.42	39.89	every_layer	flash_attn2	1	2	2
27.53	39.73	every_layer	flash_attn2	2	1	2
28.08	38.94	every_layer	flash_attn2	1	2	4
28.15	38.85	every_layer	flash_attn2	1	1	1
28.52	38.34	disabled	flash_attn1.0.8	1	4	2
28.73	38.06	every_layer	flash_attn1.0.8	1	1	2
29.08	37.60	every_layer	flash_attn2	2	1	4
29.19	37.49	every_layer	flash_attn2	2	2	2
29.21	37.43	disabled	flash_attn1.0.8	1	4	4
30.03	36.42	every_layer	flash_attn1.0.8	1	1	4
30.08	36.36	every_layer	flash_attn2	2	2	4
30.14	36.28	every_layer	flash_attn1.0.8	1	2	1
31.65	34.55	every_layer	flash_attn1.0.8	2	1	2
31.86	34.32	every_layer	flash_attn1.0.8	1	2	2
32.13	34.04	every_layer	flash_attn2	2	4	1
32.57	33.58	every_layer	flash_attn2	1	4	1
32.91	33.23	every_layer	flash_attn1.0.8	2	2	2
34.75	32.47	every_layer	flash_attn1.0.8	1	2	4
34.33	31.85	every_layer	flash_attn1.0.8	2	1	4
34.61	31.60	every_layer	flash_attn1.0.8	2	2	4
34.64	31.58	every_layer	flash_attn2	2	4	2
34.76	31.46	every_layer	flash_attn2	1	4	2
35.86	30.49	every_layer	flash_attn1.0.8	2	4	1
36.07	30.32	every_layer	flash_attn2	2	4	4
36.33	30.10	every_layer	flash_attn1.0.8	1	4	1
36.71	29.92	every_layer	flash_attn2	1	4	4
37.63	29.06	every_layer	flash_attn1.0.8	1	4	2
38.26	28.59	every_layer	flash_attn1.0.8	2	4	2
38.61	28.33	every_layer	flash_attn1.0.8	1	4	4
39.76	27.50	every_layer	flash_attn1.0.8	2	4	4
51.95	21.05	every_layer	torch	1	2	1
54.97	19.89	every_layer	torch	1	2	2
55.08	19.85	every_layer	torch	1	1	2
58.37	18.73	every_layer	torch	1	4	1
58.61	18.66	every_layer	torch	1	2	4
59.00	18.56	every_layer	torch	1	1	4
60.64	18.03	every_layer	torch	1	4	2
62.00	17.64	every_layer	torch	2	4	2
64.25	17.02	every_layer	torch	2	2	4
64.48	16.96	every_layer	torch	1	4	4
66.48	16.45	every_layer	torch	2	4	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	1
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	1
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	1	1	4
OOM Error		disabled	flash_attn2 + RMS kern.	1	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	1	1	1
OOM Error		every_layer	flash_attn2	4	1	1
OOM Error		every_layer	flash_attn2	4	4	1
OOM Error		every_layer	flash_attn2	4	2	2
OOM Error		every_layer	flash_attn2	4	4	2
OOM Error		every_layer	flash_attn2	4	1	2
OOM Error		every_layer	flash_attn2	4	4	4
OOM Error		every_layer	flash_attn2	2	2	1
OOM Error		every_layer	flash_attn2	4	2	1
OOM Error		every_layer	flash_attn2	4	1	4
OOM Error		every_layer	flash_attn2	4	2	4
OOM Error		every_layer	flash_attn2	2	1	1
OOM Error		disabled	flash_attn2	4	4	4
OOM Error		disabled	flash_attn2	4	4	2
OOM Error		disabled	flash_attn2	4	4	1
OOM Error		disabled	flash_attn2	4	2	4
OOM Error		disabled	flash_attn2	4	2	2
OOM Error		disabled	flash_attn2	4	2	1
OOM Error		disabled	flash_attn2	4	1	4



Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
OOM Error		disabled	flash_attn2	4	1	2
OOM Error		disabled	flash_attn2	4	1	1
OOM Error		disabled	flash_attn2	2	4	4
OOM Error		disabled	flash_attn2	2	4	2
OOM Error		disabled	flash_attn2	2	4	1
OOM Error		disabled	flash_attn2	2	2	4
OOM Error		disabled	flash_attn2	2	2	2
OOM Error		disabled	flash_attn2	2	2	1
OOM Error		disabled	flash_attn2	2	1	4
OOM Error		disabled	flash_attn2	2	1	2
OOM Error		disabled	flash_attn2	2	1	1
OOM Error		disabled	flash_attn2	1	4	1
OOM Error		disabled	flash_attn2	1	2	2
OOM Error		disabled	flash_attn2	1	2	1
OOM Error		disabled	flash_attn2	1	1	4
OOM Error		disabled	flash_attn2	1	1	2
OOM Error		disabled	flash_attn2	1	1	1
OOM Error		every_layer	flash_attn1.0.8	4	4	4
OOM Error		every_layer	flash_attn1.0.8	4	4	1
OOM Error		every_layer	flash_attn1.0.8	4	2	2
OOM Error		every_layer	flash_attn1.0.8	4	1	4
OOM Error		every_layer	flash_attn1.0.8	2	2	1
OOM Error		every_layer	flash_attn1.0.8	4	1	1
OOM Error		every_layer	flash_attn1.0.8	4	2	1
OOM Error		every_layer	flash_attn1.0.8	4	4	2
OOM Error		every_layer	flash_attn1.0.8	4	1	2
OOM Error		every_layer	flash_attn1.0.8	4	2	4
OOM Error		every_layer	flash_attn1.0.8	2	1	1
OOM Error		every_layer	flash_attn1.0.8	1	1	1
OOM Error		disabled	flash_attn1.0.8	4	4	4
OOM Error		disabled	flash_attn1.0.8	4	4	2
OOM Error		disabled	flash_attn1.0.8	4	4	1
OOM Error		disabled	flash_attn1.0.8	4	2	4
OOM Error		disabled	flash_attn1.0.8	4	2	2
OOM Error		disabled	flash_attn1.0.8	4	2	1
OOM Error		disabled	flash_attn1.0.8	4	1	4
OOM Error		disabled	flash_attn1.0.8	4	1	2
OOM Error		disabled	flash_attn1.0.8	4	1	1
OOM Error		disabled	flash_attn1.0.8	2	4	4
OOM Error		disabled	flash_attn1.0.8	2	4	2
OOM Error		disabled	flash_attn1.0.8	2	4	1
OOM Error		disabled	flash_attn1.0.8	2	2	4
OOM Error		disabled	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	2	2	1
OOM Error		disabled	flash_attn1.0.8	2	1	4
OOM Error		disabled	flash_attn1.0.8	2	1	2
OOM Error		disabled	flash_attn1.0.8	2	1	1
OOM Error		disabled	flash_attn1.0.8	1	4	1
OOM Error		disabled	flash_attn1.0.8	1	2	2
OOM Error		disabled	flash_attn1.0.8	1	2	1
OOM Error		disabled	flash_attn1.0.8	1	1	4
OOM Error		disabled	flash_attn1.0.8	1	1	2
OOM Error		disabled	flash_attn1.0.8	1	1	1
OOM Error		every_layer	torch	4	4	4
OOM Error		every_layer	torch	4	2	2
OOM Error		every_layer	torch	4	4	2
OOM Error		every_layer	torch	4	4	1
OOM Error		every_layer	torch	4	1	2
OOM Error		every_layer	torch	4	2	4
OOM Error		every_layer	torch	2	4	1
OOM Error		every_layer	torch	2	1	4
OOM Error		every_layer	torch	2	2	2
OOM Error		every_layer	torch	4	1	1
OOM Error		every_layer	torch	4	1	4
OOM Error		every_layer	torch	4	2	1
OOM Error		every_layer	torch	2	2	1
OOM Error		every_layer	torch	2	1	2
OOM Error		every_layer	torch	2	1	1
OOM Error		every_layer	torch	1	1	1
OOM Error		disabled	torch	4	4	4
OOM Error		disabled	torch	4	4	2
OOM Error		disabled	torch	4	4	1
OOM Error		disabled	torch	4	2	4
OOM Error		disabled	torch	4	2	2
OOM Error		disabled	torch	4	2	1
OOM Error		disabled	torch	4	1	4
OOM Error		disabled	torch	4	1	2
OOM Error		disabled	torch	4	1	1
OOM Error		disabled	torch	2	4	4

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
OOM Error		disabled	torch	2	4	2
OOM Error		disabled	torch	2	4	1
OOM Error		disabled	torch	2	2	4
OOM Error		disabled	torch	2	2	2
OOM Error		disabled	torch	2	2	1
OOM Error		disabled	torch	2	1	4
OOM Error		disabled	torch	2	1	2
OOM Error		disabled	torch	2	1	1
OOM Error		disabled	torch	1	4	4
OOM Error		disabled	torch	1	4	2
OOM Error		disabled	torch	1	4	1
OOM Error		disabled	torch	1	2	4
OOM Error		disabled	torch	1	2	2
OOM Error		disabled	torch	1	2	1
OOM Error		disabled	torch	1	1	4
OOM Error		disabled	torch	1	1	2
OOM Error		disabled	torch	1	1	1

#### 407 B.4 LLAMA 30B

Table 6: Performance analysis of a LLAMA 30B model trained on 256 A100 GPUs with the <anonymized> codebase. The analysis also includes Out of Memory (OOM) error occurrences and errors where the fused kernel does not support this specific tensor parallel configuration.

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
22.67	49.22	disabled	flash_attn2 + RMS kern.	1	2	4
24.00	46.76	disabled	flash_attn2 + RMS kern.	1	1	4
24.26	46.01	disabled	flash_attn2 + RMS kern.	2	2	4
24.70	45.16	disabled	flash_attn2	1	2	4
25.05	44.55	disabled	flash_attn2 + RMS kern.	4	4	4
25.32	44.06	disabled	flash_attn2 + RMS kern.	2	4	4
26.06	42.80	disabled	flash_attn1.0.8	1	2	4
26.26	42.48	disabled	flash_attn2 + RMS kern.	2	4	2
26.28	42.45	disabled	flash_attn2 + RMS kern.	1	4	4
26.94	41.42	disabled	flash_attn2 + RMS kern.	1	4	2
28.34	39.39	disabled	flash_attn2 + RMS kern.	1	2	2
29.08	38.37	every_layer	flash_attn2	1	1	4
29.13	38.32	disabled	flash_attn2	1	2	2
29.16	38.26	every_layer	flash_attn1.0.8	1	1	4
29.45	37.88	disabled	flash_attn2	2	4	4
29.55	37.75	disabled	flash_attn1.0.8	2	4	4
29.64	37.67	disabled	flash_attn1.0.8	1	2	2
29.76	37.48	every_layer	flash_attn2	2	1	4
29.96	37.23	every_layer	flash_attn1.0.8	2	1	4
30.08	37.09	disabled	flash_attn2	1	4	4
31.13	35.84	every_layer	flash_attn2	2	2	4
31.38	35.54	disabled	flash_attn1.0.8	1	4	4
31.47	35.46	disabled	flash_attn2	1	4	2
31.66	35.24	disabled	flash_attn2	2	4	2
31.77	35.15	disabled	flash_attn2 + RMS kern.	1	4	1
31.81	35.08	every_layer	flash_attn2	1	2	4
31.94	34.93	every_layer	flash_attn2	1	2	2
32.17	34.68	every_layer	flash_attn1.0.8	2	2	4
32.27	34.57	every_layer	flash_attn2	2	2	2
32.42	34.41	disabled	flash_attn1.0.8	1	4	2
32.73	34.08	every_layer	fused	1	1	4
32.84	33.96	every_layer	flash_attn1.0.8	1	2	2
33.08	33.72	every_layer	fused	2	1	4
33.29	33.51	every_layer	flash_attn1.0.8	1	2	4
33.47	33.33	every_layer	flash_attn1.0.8	4	2	2
33.70	33.11	every_layer	flash_attn2	4	2	4
33.75	33.05	every_layer	flash_attn1.0.8	4	1	4
33.79	33.01	every_layer	flash_attn1.0.8	4	2	4
33.97	32.85	disabled	flash_attn1.0.8	2	4	2
34.22	32.61	every_layer	flash_attn2	4	1	4
34.45	32.39	every_layer	flash_attn2	4	2	2
35.07	31.84	every_layer	flash_attn2	1	1	2
35.23	31.67	every_layer	flash_attn1.0.8	2	2	2
35.32	31.61	disabled	flash_attn2 + RMS kern.	2	4	1
35.88	31.09	every_layer	fused	2	2	4
36.42	30.66	every_layer	flash_attn1.0.8	1	1	2
36.48	30.58	every_layer	fused	4	2	4
37.12	30.06	every_layer	flash_attn2	4	4	2
37.76	29.58	every_layer	flash_attn2	2	1	2

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
37.81	29.50	every_layer	flash_attn1.0.8	4	4	2
37.94	29.40	every_layer	fused	4	1	4
37.99	29.38	every_layer	fused	1	1	2
38.07	29.32	every_layer	flash_attn1.0.8	2	1	2
38.28	29.15	every_layer	flash_attn2	4	4	4
38.51	28.97	every_layer	flash_attn2	2	4	4
38.60	28.90	every_layer	flash_attn1.0.8	4	4	4
39.57	28.19	every_layer	flash_attn2	2	4	2
39.61	28.17	every_layer	fused	4	2	2
39.65	28.14	every_layer	flash_attn1.0.8	2	4	4
39.70	28.10	every_layer	flash_attn2	1	2	1
39.74	28.07	every_layer	fused	2	1	2
39.81	28.03	disabled	flash_attn2	1	4	1
40.07	27.84	every_layer	flash_attn2	1	4	2
40.22	27.73	every_layer	fused	4	4	2
40.29	27.68	every_layer	flash_attn1.0.8	2	4	2
41.01	27.20	every_layer	flash_attn2	1	4	4
41.74	26.73	every_layer	fused	4	4	4
41.80	26.69	every_layer	flash_attn1.0.8	1	2	1
41.84	26.66	every_layer	flash_attn1.0.8	4	4	1
41.94	26.60	every_layer	flash_attn1.0.8	1	4	4
42.13	26.48	every_layer	flash_attn2	2	4	1
42.22	26.42	every_layer	fused	4	4	1
42.41	26.30	every_layer	flash_attn1.0.8	1	4	2
43.24	25.80	disabled	flash_attn1.0.8	1	4	1
43.51	25.64	every_layer	flash_attn1.0.8	2	4	1
43.92	25.40	every_layer	flash_attn2	4	4	1
44.09	25.30	every_layer	flash_attn2	1	4	1
45.56	24.49	every_layer	flash_attn1.0.8	1	4	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	1
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	1	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	1	1
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	1
OOM Error		disabled	flash_attn2 + RMS kern.	1	1	2
OOM Error		disabled	flash_attn2 + RMS kern.	1	1	1
OOM Error		every_layer	flash_attn2	2	2	1
OOM Error		every_layer	flash_attn2	4	2	1
OOM Error		every_layer	flash_attn2	4	1	2
OOM Error		every_layer	flash_attn2	4	1	1
OOM Error		every_layer	flash_attn2	2	1	1
OOM Error		every_layer	flash_attn2	1	1	1
OOM Error		disabled	flash_attn2	4	4	4
OOM Error		disabled	flash_attn2	4	4	2
OOM Error		disabled	flash_attn2	4	4	1
OOM Error		disabled	flash_attn2	4	2	4
OOM Error		disabled	flash_attn2	4	2	2
OOM Error		disabled	flash_attn2	4	2	1
OOM Error		disabled	flash_attn2	4	1	4
OOM Error		disabled	flash_attn2	4	1	2
OOM Error		disabled	flash_attn2	4	1	1
OOM Error		disabled	flash_attn2	4	1	1
OOM Error		disabled	flash_attn2	2	4	1
OOM Error		disabled	flash_attn2	2	2	4
OOM Error		disabled	flash_attn2	2	2	2
OOM Error		disabled	flash_attn2	2	2	1
OOM Error		disabled	flash_attn2	2	1	4
OOM Error		disabled	flash_attn2	2	1	2
OOM Error		disabled	flash_attn2	2	1	1
OOM Error		disabled	flash_attn2	1	2	1
OOM Error		disabled	flash_attn2	1	1	4
OOM Error		disabled	flash_attn2	1	1	2
OOM Error		disabled	flash_attn2	1	1	1
OOM Error		every_layer	fused	4	2	1
OOM Error		every_layer	fused	4	1	2
OOM Error		every_layer	fused	4	1	1
OOM Error		every_layer	fused	2	2	1
OOM Error		every_layer	fused	2	1	1
OOM Error		every_layer	fused	1	1	1
OOM Error		every_layer	flash_attn1.0.8	4	2	1
OOM Error		every_layer	flash_attn1.0.8	4	1	2
OOM Error		every_layer	flash_attn1.0.8	4	1	1

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
OOM Error		every_layer	flash_attn1.0.8	2	2	1
OOM Error		every_layer	flash_attn1.0.8	2	1	1
OOM Error		every_layer	flash_attn1.0.8	1	1	1
OOM Error		disabled	fused	4	4	4
OOM Error		disabled	fused	4	4	2
OOM Error		disabled	fused	4	4	1
OOM Error		disabled	fused	4	2	4
OOM Error		disabled	fused	4	2	2
OOM Error		disabled	fused	4	2	1
OOM Error		disabled	fused	4	1	4
OOM Error		disabled	fused	4	1	2
OOM Error		disabled	fused	4	1	1
OOM Error		disabled	fused	2	2	4
OOM Error		disabled	fused	2	2	2
OOM Error		disabled	fused	2	2	1
OOM Error		disabled	fused	2	1	4
OOM Error		disabled	fused	2	1	2
OOM Error		disabled	flash_attn1.0.8	4	4	4
OOM Error		disabled	flash_attn1.0.8	4	4	2
OOM Error		disabled	flash_attn1.0.8	4	4	1
OOM Error		disabled	flash_attn1.0.8	4	2	4
OOM Error		disabled	flash_attn1.0.8	4	2	2
OOM Error		disabled	flash_attn1.0.8	4	2	1
OOM Error		disabled	flash_attn1.0.8	4	1	4
OOM Error		disabled	flash_attn1.0.8	4	1	2
OOM Error		disabled	flash_attn1.0.8	4	1	1
OOM Error		disabled	flash_attn1.0.8	2	4	1
OOM Error		disabled	flash_attn1.0.8	2	2	4
OOM Error		disabled	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	2	2	1
OOM Error		disabled	flash_attn1.0.8	2	1	4
OOM Error		disabled	flash_attn1.0.8	2	1	2
OOM Error		disabled	flash_attn1.0.8	2	1	1
OOM Error		disabled	flash_attn1.0.8	1	2	1
OOM Error		disabled	flash_attn1.0.8	1	1	4
OOM Error		disabled	flash_attn1.0.8	1	1	2
OOM Error		disabled	flash_attn1.0.8	1	1	1
Kernel unavail.		every_layer	fused	2	4	4
Kernel unavail.		every_layer	fused	2	4	2
Kernel unavail.		every_layer	fused	2	4	1
Kernel unavail.		every_layer	fused	2	2	2
Kernel unavail.		every_layer	fused	1	4	4
Kernel unavail.		every_layer	fused	1	4	2
Kernel unavail.		every_layer	fused	1	4	1
Kernel unavail.		every_layer	fused	1	2	4
Kernel unavail.		every_layer	fused	1	2	2
Kernel unavail.		every_layer	fused	1	2	1
Kernel unavail.		disabled	fused	2	4	4
Kernel unavail.		disabled	fused	2	4	2
Kernel unavail.		disabled	fused	2	4	1
Kernel unavail.		disabled	fused	1	4	4
Kernel unavail.		disabled	fused	1	4	2
Kernel unavail.		disabled	fused	1	4	1
Kernel unavail.		disabled	fused	1	2	4
Kernel unavail.		disabled	fused	1	2	2
Kernel unavail.		disabled	fused	1	2	1

## 408 B.5 LLAMA 30B with 8k sequence length

Table 7: Performance analysis of a LLAMA 30B model with 8k sequence length trained on 128 A100 GPUs with the <anonymized> codebase. All measurements use the flash attention kernel. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
49.43	51.40	disabled	flash_attn2 + RMS kern.	1	4	4
50.23	50.57	disabled	flash_attn2 + RMS kern.	1	4	8
54.78	46.37	disabled	flash_attn2 + RMS kern.	1	4	16
62.84	40.43	every_layer	flash_attn2	1	2	4
62.99	40.33	every_layer	flash_attn2	1	2	2
63.99	39.70	every_layer	flash_attn2	1	2	8
66.69	38.09	every_layer	flash_attn2	1	2	16
66.71	38.08	every_layer	flash_attn2	2	2	4
68.99	36.82	every_layer	flash_attn2	2	2	8
69.45	36.58	every_layer	flash_attn1.0.8	1	2	2

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
70.01	36.29	every_layer	flash_attn1.0.8	1	2	4
71.81	35.38	every_layer	flash_attn2	2	2	16
71.87	35.34	every_layer	flash_attn1.0.8	1	2	8
72.42	35.08	every_layer	flash_attn2	1	4	2
73.33	34.64	every_layer	flash_attn2	2	4	2
75.02	33.86	every_layer	flash_attn1.0.8	2	2	4
75.53	33.64	every_layer	flash_attn2	1	4	4
76.53	33.20	every_layer	flash_attn2	2	4	4
77.42	32.81	every_layer	flash_attn1.0.8	2	2	8
77.86	32.63	every_layer	flash_attn2	1	4	8
79.71	31.87	every_layer	flash_attn1.0.8	1	4	2
79.74	31.86	every_layer	flash_attn2	2	4	8
80.25	31.65	every_layer	flash_attn1.0.8	2	4	2
82.16	30.92	every_layer	flash_attn1.0.8	1	4	4
82.62	30.75	every_layer	flash_attn2	1	4	16
84.01	30.24	every_layer	flash_attn1.0.8	2	4	4
85.34	29.77	every_layer	flash_attn2	2	4	16
85.53	29.70	every_layer	flash_attn1.0.8	1	4	8
87.18	29.14	every_layer	flash_attn1.0.8	2	4	8
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	16
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	8
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	8
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	16
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	16
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	16
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	16
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	8
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	8
OOM Error		every_layer	flash_attn2	4	4	16
OOM Error		every_layer	flash_attn2	4	2	2
OOM Error		every_layer	flash_attn2	4	2	4
OOM Error		every_layer	flash_attn2	4	2	16
OOM Error		every_layer	flash_attn2	4	4	2
OOM Error		every_layer	flash_attn2	4	2	8
OOM Error		every_layer	flash_attn2	4	4	4
OOM Error		every_layer	flash_attn2	2	2	2
OOM Error		every_layer	flash_attn2	4	4	8
OOM Error		disabled	flash_attn2	4	4	16
OOM Error		disabled	flash_attn2	4	4	8
OOM Error		disabled	flash_attn2	4	4	4
OOM Error		disabled	flash_attn2	4	4	4
OOM Error		disabled	flash_attn2	4	4	2
OOM Error		disabled	flash_attn2	4	2	16
OOM Error		disabled	flash_attn2	4	2	8
OOM Error		disabled	flash_attn2	4	2	4
OOM Error		disabled	flash_attn2	4	2	2
OOM Error		disabled	flash_attn2	2	4	16
OOM Error		disabled	flash_attn2	2	4	8
OOM Error		disabled	flash_attn2	2	4	4
OOM Error		disabled	flash_attn2	2	4	2
OOM Error		disabled	flash_attn2	2	2	16
OOM Error		disabled	flash_attn2	2	2	8
OOM Error		disabled	flash_attn2	2	2	4
OOM Error		disabled	flash_attn2	2	2	2
OOM Error		disabled	flash_attn2	1	4	16
OOM Error		disabled	flash_attn2	1	4	8
OOM Error		disabled	flash_attn2	1	4	4
OOM Error		disabled	flash_attn2	1	4	2
OOM Error		disabled	flash_attn2	1	2	16
OOM Error		disabled	flash_attn2	1	2	8
OOM Error		disabled	flash_attn2	1	2	4
OOM Error		disabled	flash_attn2	1	2	2
OOM Error		disabled	flash_attn1.0.8	4	4	4
OOM Error		disabled	flash_attn1.0.8	4	2	8
OOM Error		every_layer	flash_attn1.0.8	4	2	4
OOM Error		every_layer	flash_attn1.0.8	4	2	2
OOM Error		every_layer	flash_attn1.0.8	4	4	2
OOM Error		every_layer	flash_attn1.0.8	4	4	4
OOM Error		every_layer	flash_attn1.0.8	4	4	8
OOM Error		every_layer	flash_attn1.0.8	4	2	8
OOM Error		every_layer	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	4	4	8
OOM Error		disabled	flash_attn1.0.8	4	4	2
OOM Error		disabled	flash_attn1.0.8	4	2	4
OOM Error		disabled	flash_attn1.0.8	4	2	2
OOM Error		disabled	flash_attn1.0.8	2	4	8
OOM Error		disabled	flash_attn1.0.8	2	4	4
OOM Error		disabled	flash_attn1.0.8	2	4	2
OOM Error		disabled	flash_attn1.0.8	2	2	8
OOM Error		disabled	flash_attn1.0.8	2	4	4
OOM Error		disabled	flash_attn1.0.8	2	4	2
OOM Error		disabled	flash_attn1.0.8	2	2	8
OOM Error		disabled	flash_attn1.0.8	2	2	4

Step Time	MFU	Activation	Kernel	MB Size	TP Size	PP Size
OOM Error		disabled	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	1	4	8
OOM Error		disabled	flash_attn1.0.8	1	4	4
OOM Error		disabled	flash_attn1.0.8	1	4	2
OOM Error		disabled	flash_attn1.0.8	1	2	8
OOM Error		disabled	flash_attn1.0.8	1	2	4
OOM Error		disabled	flash_attn1.0.8	1	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	1	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	2

## 409 B.6 LLAMA 65B

Table 8: Performance analysis of a LLAMA 65B model trained on 128 A100 GPUs with the <anonymized> codebase. All measurements use the flash attention kernel. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	Activation	Kernel	MB Size	TP size	PP Size
79.31	55.26	disabled	flash_attn2 + RMS kern.	1	2	4
79.54	55.10	disabled	flash_attn2 + RMS kern.	1	2	8
82.88	52.88	disabled	flash_attn2 + RMS kern.	2	4	4
86.55	50.63	disabled	flash_attn2 + RMS kern.	2	4	8
86.61	50.60	disabled	flash_attn2 + RMS kern.	1	4	4
87.14	50.30	disabled	flash_attn2 + RMS kern.	1	4	2
88.16	49.71	disabled	flash_attn2	1	2	8
92.61	47.32	disabled	flash_attn2 + RMS kern.	1	4	8
101.28	43.28	disabled	flash_attn2 + RMS kern.	2	8	2
101.97	42.98	disabled	flash_attn2	1	4	4
103.17	42.48	disabled	flash_attn2 + RMS kern.	2	8	4
106.59	41.11	disabled	flash_attn1.0.8	1	4	4
107.39	40.81	every_layer	flash_attn2	2	2	4
107.85	40.64	disabled	flash_attn2 + RMS kern.	1	8	2
107.97	40.59	disabled	flash_attn2	1	4	8
108.59	40.36	disabled	flash_attn1.0.8	1	4	8
109.04	40.19	every_layer	flash_attn2	4	2	4
110.87	39.53	every_layer	flash_attn1.0.8	2	2	4
111.35	39.36	every_layer	flash_attn2	1	2	4
111.83	39.19	disabled	flash_attn2 + RMS kern.	1	8	4
111.83	39.19	every_layer	flash_attn1.0.8	4	2	4
112.77	38.86	every_layer	flash_attn2	2	2	8
114.42	38.30	every_layer	flash_attn2	4	2	8
115.05	38.09	every_layer	flash_attn1.0.8	1	2	4
115.58	37.92	disabled	flash_attn2 + RMS kern.	2	8	8
116.25	37.70	every_layer	flash_attn1.0.8	4	2	8
116.27	37.69	every_layer	flash_attn1.0.8	2	2	8
118.39	37.02	every_layer	flash_attn2	1	2	8
118.68	36.93	every_layer	flash_attn2	1	2	2
121.70	36.01	every_layer	flash_attn1.0.8	1	2	8
121.93	35.95	disabled	flash_attn2 + RMS kern.	1	8	8
125.11	35.03	every_layer	flash_attn2	4	4	4
126.61	34.61	every_layer	flash_attn2	4	4	2
128.06	34.22	every_layer	flash_attn1.0.8	4	4	2
129.68	33.80	every_layer	flash_attn2	2	4	4
129.92	33.73	every_layer	flash_attn1.0.8	4	4	4
132.34	33.11	every_layer	flash_attn1.0.8	2	4	2
133.07	32.93	every_layer	flash_attn1.0.8	2	4	4
133.56	32.81	every_layer	flash_attn2	4	4	8
136.43	32.12	every_layer	flash_attn2	1	4	2
137.73	31.82	every_layer	flash_attn1.0.8	4	4	8
139.67	31.38	disabled	flash_attn2	1	8	2
140.15	31.28	disabled	flash_attn1.0.8	1	8	2
140.12	31.28	every_layer	flash_attn1.0.8	1	4	2
140.95	31.09	every_layer	flash_attn2	1	4	4
141.87	30.89	every_layer	flash_attn2	2	4	8
142.77	30.70	disabled	flash_attn2	1	8	4
144.59	30.31	every_layer	flash_attn1.0.8	1	4	4

Step Time	MFU	Activation	Kernel	MB Size	TP size	PP Size
144.83	30.26	every_layer	flash_attn1.0.8	2	4	8
151.95	28.84	disabled	flash_attn2	1	8	8
153.61	28.53	disabled	flash_attn1.0.8	1	8	8
156.54	28.00	every_layer	flash_attn2	1	4	8
159.57	27.46	every_layer	flash_attn1.0.8	1	4	8
164.21	26.69	every_layer	flash_attn2	4	8	2
168.64	25.99	every_layer	flash_attn1.0.8	4	8	2
168.97	25.94	every_layer	flash_attn2	4	8	4
173.16	25.31	every_layer	flash_attn1.0.8	4	8	4
174.43	25.13	every_layer	flash_attn2	2	8	2
178.66	24.53	every_layer	flash_attn1.0.8	2	8	2
180.93	24.22	every_layer	flash_attn2	2	8	4
184.98	23.69	every_layer	flash_attn2	4	8	8
187.81	23.33	every_layer	flash_attn1.0.8	2	8	4
192.53	22.76	every_layer	flash_attn1.0.8	4	8	8
192.69	22.75	every_layer	flash_attn2	1	8	2
200.12	21.90	every_layer	flash_attn1.0.8	1	8	2
203.08	21.58	every_layer	flash_attn2	2	8	8
209.24	20.95	every_layer	flash_attn2	1	8	4
210.89	20.78	every_layer	flash_attn1.0.8	2	8	8
215.12	20.37	every_layer	flash_attn1.0.8	1	8	4
237.99	18.42	every_layer	flash_attn2	1	8	8
247.97	17.67	every_layer	flash_attn1.0.8	1	8	8
OOM Error		disabled	flash_attn2 + RMS kern.	4	8	8
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	8
OOM Error		disabled	flash_attn2 + RMS kern.	4	8	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	4	8	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	4	4	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	4	2
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	8
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	4
OOM Error		disabled	flash_attn2 + RMS kern.	2	2	2
OOM Error		disabled	flash_attn2 + RMS kern.	1	2	2
OOM Error		every_layer	flash_attn2	4	2	2
OOM Error		every_layer	flash_attn2	2	2	2
OOM Error		disabled	flash_attn2	4	8	8
OOM Error		disabled	flash_attn2	4	8	4
OOM Error		disabled	flash_attn2	4	8	2
OOM Error		disabled	flash_attn2	4	4	8
OOM Error		disabled	flash_attn2	4	4	4
OOM Error		disabled	flash_attn2	4	4	2
OOM Error		disabled	flash_attn2	4	2	8
OOM Error		disabled	flash_attn2	4	2	4
OOM Error		disabled	flash_attn2	4	2	2
OOM Error		disabled	flash_attn2	2	8	8
OOM Error		disabled	flash_attn2	2	8	4
OOM Error		disabled	flash_attn2	2	8	2
OOM Error		disabled	flash_attn2	2	4	8
OOM Error		disabled	flash_attn2	2	4	4
OOM Error		disabled	flash_attn2	2	4	2
OOM Error		disabled	flash_attn2	2	2	8
OOM Error		disabled	flash_attn2	2	2	4
OOM Error		disabled	flash_attn2	2	2	2
OOM Error		disabled	flash_attn2	1	4	2
OOM Error		disabled	flash_attn2	1	2	4
OOM Error		disabled	flash_attn2	1	2	2
OOM Error		disabled	flash_attn1.0.8	1	2	8
OOM Error		disabled	flash_attn1.0.8	1	2	4
OOM Error		disabled	flash_attn1.0.8	1	2	2
OOM Error		every_layer	flash_attn1.0.8	4	2	2
OOM Error		every_layer	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	4	8	8
OOM Error		disabled	flash_attn1.0.8	4	4	8
OOM Error		disabled	flash_attn1.0.8	4	2	4
OOM Error		disabled	flash_attn1.0.8	4	4	4
OOM Error		disabled	flash_attn1.0.8	2	8	4
OOM Error		disabled	flash_attn1.0.8	2	8	8
OOM Error		disabled	flash_attn1.0.8	4	2	2
OOM Error		disabled	flash_attn1.0.8	2	4	4
OOM Error		disabled	flash_attn1.0.8	2	8	2
OOM Error		disabled	flash_attn1.0.8	2	4	2
OOM Error		disabled	flash_attn1.0.8	4	8	4
OOM Error		disabled	flash_attn1.0.8	2	2	8
OOM Error		disabled	flash_attn1.0.8	4	4	2
OOM Error		disabled	flash_attn1.0.8	4	8	2
OOM Error		disabled	flash_attn1.0.8	4	2	8

Step Time	MFU	Activation	Kernel	MB Size	TP size	PP Size
OOM Error		disabled	flash_attn1.0.8	2	4	8
OOM Error		disabled	flash_attn1.0.8	2	2	4
OOM Error		disabled	flash_attn1.0.8	2	2	2
OOM Error		disabled	flash_attn1.0.8	1	4	2



## 410 C Sequence Parallelism Training Efficiency Sweep

### 411 C.1 Sweep Configurations

Model	Seq. Len.	GPUs	TP sizes	PP sizes	MB Sizes	Seq. Parallelism
13B	2k	32	{1, 2}	{1, 2}	{1, 2, 4, 8}	{yes, no}
13B	8k	64	{1, 2, 4}	{1, 2, 4}	{1, 2, 4}	{yes, no}
30B	2k	64	{1, 2, 4}	{1, 2, 4}	{1, 2, 4}	{yes, no}
30B	8k	64	{2, 4}	{2, 4, 8, 16}	{1, 2, 4}	{yes, no}
65B	2k	64	{2, 4, 8}	{2, 4, 8}	{1, 2, 4}	{yes, no}

Table 9: Search space of additional sequence parallel training efficiency sweep. We sweep over the Cartesian product of all mentioned options similar to Table 1. All runs use FLASHATTENTION-2, the RMSNorm kernel and do not use activation checkpointing.

### 412 C.2 LLAMA 13B

Table 10: Performance analysis of a LLAMA 13B model trained on 32 A100 GPUs, with and without sequence parallelism. All measurements use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
53.81	69.66	1	1	1	False
53.99	69.45	1	1	1	True
57.61	65.04	2	2	1	False
58.01	64.54	1	1	2	True
58.62	63.88	1	1	2	False
59.55	62.86	2	1	2	True
61.12	62.28	2	2	1	True
60.23	62.15	2	1	2	False
60.96	61.43	1	2	1	True
62.09	60.34	1	2	1	False
65.04	57.55	2	2	2	True
66.13	56.59	2	2	2	False
66.26	56.47	1	2	2	True
67.47	55.44	4	2	2	True
67.94	55.08	1	2	2	False
68.48	54.62	4	2	2	False
OOM Error	4	1	2	2	True
OOM Error	8	2	2	2	True
OOM Error	4	1	1	1	True
OOM Error	8	1	2	2	True
OOM Error	8	2	1	1	True
OOM Error	4	2	1	1	True
OOM Error	2	1	1	1	True
OOM Error	2	1	1	1	False
OOM Error	8	2	2	2	False
OOM Error	8	2	1	1	False
OOM Error	8	1	1	1	False
OOM Error	4	2	1	1	False
OOM Error	4	1	2	2	False
OOM Error	8	1	2	2	False
OOM Error	4	1	1	1	False

### 413 C.3 LLAMA 13B 8k sequence length

Table 11: Performance analysis of a LLAMA 13B model with 8k sequence length trained on 64 A100 GPUs, with and without sequence parallelism. All measurements use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
34.84	62.78	1	2	2	True

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
34.85	62.76	1	2	2	False
35.80	61.10	1	2	4	True
36.60	59.76	1	2	4	False
36.99	59.13	1	4	1	True
38.85	56.31	1	4	2	True
38.90	56.23	1	4	1	False
40.70	53.74	1	4	2	False
40.82	53.58	1	4	4	True
41.06	53.27	2	4	4	True
43.49	50.29	1	4	4	False
44.03	49.68	2	4	4	False
46.37	47.18	1	8	1	True
46.89	46.65	2	8	2	True
49.96	43.79	1	8	2	True
51.03	42.87	1	8	1	False
51.91	42.14	2	8	4	True
54.78	39.93	1	8	4	True
56.23	38.90	1	8	2	False
59.62	36.69	2	8	4	False
62.04	35.26	1	8	4	False
OOM Error		4	1	1	True
OOM Error		4	8	2	True
OOM Error		4	8	4	True
OOM Error		4	4	1	True
OOM Error		4	8	1	True
OOM Error		4	4	4	True
OOM Error		4	4	2	True
OOM Error		4	2	4	True
OOM Error		4	1	2	True
OOM Error		4	2	1	True
OOM Error		4	1	4	True
OOM Error		4	8	2	False
OOM Error		4	4	4	False
OOM Error		4	4	1	False
OOM Error		4	2	4	False
OOM Error		4	2	2	False
OOM Error		4	1	2	False
OOM Error		4	2	1	False
OOM Error		4	8	4	False
OOM Error		4	8	1	False
OOM Error		4	4	2	False
OOM Error		4	1	4	False
OOM Error		4	1	1	False
OOM Error		2	8	1	True
OOM Error		2	2	1	True
OOM Error		2	2	4	True
OOM Error		2	4	2	True
OOM Error		2	2	2	True
OOM Error		2	4	1	True
OOM Error		1	2	1	True
OOM Error		2	2	1	False
OOM Error		2	2	4	False
OOM Error		2	8	2	False
OOM Error		2	8	1	False
OOM Error		2	4	1	False
OOM Error		2	2	2	False
OOM Error		2	4	2	False
OOM Error		1	2	1	False

#### 414 C.4 LLAMA 30B

Table 12: Performance analysis of a LLAMA 30B model trained on 64 A100 GPUs, with and without sequence parallelism. All measurements use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
72.00	61.98	1	1	4	False
72.60	61.47	1	1	4	True
72.66	61.42	2	2	4	True
74.86	59.61	2	2	4	False
76.58	58.27	1	2	4	True
76.84	58.07	1	2	2	True

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
77.59	57.52	4	4	4	True
78.43	56.89	1	2	4	False
80.17	55.66	1	2	2	False
81.06	55.05	2	4	2	True
82.22	54.28	2	4	4	True
83.11	53.71	4	4	2	True
83.76	53.30	4	4	2	True
84.88	52.57	2	4	2	False
85.21	52.37	2	4	1	True
85.47	52.21	1	4	2	True
86.44	51.63	4	4	4	False
86.67	51.49	4	4	4	False
87.68	50.89	1	4	4	True
89.33	49.95	1	4	1	True
89.76	49.71	2	4	4	False
89.86	49.66	1	4	2	False
94.12	47.42	1	4	1	False
95.52	46.72	1	4	4	False
OOM Error		4	4	1	True
OOM Error		4	1	1	True
OOM Error		4	1	4	True
OOM Error		4	2	2	True
OOM Error		4	1	2	True
OOM Error		4	2	1	True
OOM Error		4	2	4	True
OOM Error		4	4	1	True
OOM Error		2	4	1	False
OOM Error		4	4	2	False
OOM Error		4	4	1	False
OOM Error		4	4	2	False
OOM Error		4	2	2	False
OOM Error		4	4	1	False
OOM Error		4	1	4	False
OOM Error		4	2	1	False
OOM Error		4	1	2	False
OOM Error		4	1	1	False
OOM Error		4	2	4	False
OOM Error		2	1	2	True
OOM Error		2	1	4	True
OOM Error		2	2	2	True
OOM Error		1	1	2	True
OOM Error		2	1	2	False
OOM Error		2	1	4	False
OOM Error		2	2	2	False
OOM Error		1	1	2	False

## 415 C.5 LLAMA 30B 8k sequence length

Table 13: Performance analysis of a LLAMA 30B model with 8k sequence length trained on 64 A100 GPUs, with and without sequence parallelism. All measurements use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
84.37	60.22	1	4	2	True
85.69	59.35	1	4	4	True
86.16	58.97	1	4	16	True
86.17	58.97	1	4	8	True
93.84	54.15	1	4	4	False
96.70	52.54	1	4	8	False
98.37	51.65	1	4	16	False
OOM Error		1	2	2	True
OOM Error		2	2	4	True
OOM Error		1	2	4	True
OOM Error		4	2	4	True
OOM Error		4	2	2	True
OOM Error		2	2	2	True
OOM Error		4	4	4	True
OOM Error		4	4	2	True
OOM Error		2	4	2	True
OOM Error		4	4	8	False
OOM Error		4	2	16	False
OOM Error		4	2	8	False

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
OOM Error		4	4	16	False
OOM Error		4	4	4	False
OOM Error		4	4	2	False
OOM Error		2	2	4	False
OOM Error		2	4	2	False
OOM Error		1	2	2	False
OOM Error		4	2	2	False
OOM Error		2	2	2	False
OOM Error		1	2	4	False
OOM Error		2	4	4	False
OOM Error		4	2	4	False
OOM Error		1	4	2	False
OOM Error		4	4	16	False
OOM Error		4	2	16	False
OOM Error		4	2	8	False
OOM Error		4	4	8	False

## 416 C.6 LLAMA 65B

Table 14: Performance analysis of a LLAMA 65B model trained on 64 A100 GPUs, with and without sequence parallelism. All measurements use FLASHATTENTION-2, the RMS norm kernel and do not make use of activation checkpointing. The analysis also includes Out of Memory (OOM) error occurrences.

Step Time	MFU	MB Size	TP size	PP Size	Sequence Parallel
147.02	59.62	1	2	4	True
149.92	58.47	2	4	4	True
149.97	58.44	1	2	8	True
152.65	57.42	1	2	8	False
156.40	56.04	2	4	8	True
158.74	55.22	2	4	4	False
159.57	54.93	1	4	4	True
162.32	54.00	1	4	2	True
166.36	52.69	1	4	8	True
166.49	52.65	4	8	4	False
167.70	52.27	4	8	8	False
168.70	51.96	2	4	8	False
169.39	51.75	1	4	2	False
172.11	50.93	1	4	4	False
178.64	49.07	2	8	2	True
179.78	48.76	1	4	8	False
179.87	48.74	2	8	4	True
186.54	47.16	2	8	8	True
192.45	45.55	1	8	2	True
193.69	45.26	2	8	2	False
198.11	44.25	1	8	4	True
201.44	43.52	1	8	8	True
202.20	43.35	2	8	4	False
207.26	42.29	1	8	2	False
220.27	39.80	1	8	4	False
223.09	39.29	2	8	8	False
233.00	37.62	1	8	8	False
OOM Error		4	4	2	True
OOM Error		4	2	2	True
OOM Error		4	2	4	True
OOM Error		2	4	2	True
OOM Error		2	2	8	True
OOM Error		2	2	4	True
OOM Error		2	2	2	True
OOM Error		1	2	2	True
OOM Error		2	2	2	False
OOM Error		2	4	2	False
OOM Error		2	2	4	False
OOM Error		2	2	8	False
OOM Error		1	2	4	False
OOM Error		1	2	2	False
OOM Error		4	8	2	False
OOM Error		4	4	2	False
OOM Error		4	4	8	False
OOM Error		4	2	8	False
OOM Error		4	4	4	False
OOM Error		4	2	2	False
OOM Error		4	2	4	False