

Lab CudaVision

Learning Vision Systems on Graphics Cards (MA-INF 4308)

Generative Adversarial Networks

06.07.2021


PROF. SVEN BEHNKE, ANGEL VILLAR-CORRALES

Contact: villar@ais.uni-bonn.de

GANs

Let's Play a Game...

Generator



Discriminator




REAL

FAKE

Let's Play a Game...

Generator



Discriminator



REAL

FAKE

Principle of GANs



Generative Adversarial Networks

Generative Adversarial Nets

Ian J. Goodfellow,^{*} Jean Pouget-Abadie,[†] Mehdi Mirza, Bing Xu, David Warde-Farley,
 Sherjil Ozair,[‡] Aaron Courville, Yoshua Bengio[§]
 Département d'informatique et de recherche opérationnelle
 Université de Montréal
 Montréal, QC H3C 3J7

Abstract

We propose a new framework for estimating generative models via an adversarial process, in which we simultaneously train two models: a generative model G that captures the data distribution, and a discriminative model D that estimates the probability that a sample came from the training data rather than G . The training procedure for G is to maximize the probability of D making a mistake. This framework corresponds to a minimax two-player game. In the space of arbitrary functions G and D , a unique solution exists, with G recovering the training data distribution and D equal to $\frac{1}{2}$ everywhere. **In the case where G and D are defined by multilayer perceptrons, the entire system can be trained with backpropagation.** There is no need for any Markov chains or unrolled approximate inference networks during either training or generation of samples. Experiments demonstrate the potential of the framework through qualitative and quantitative evaluation of the generated samples.



1 Introduction

The promise of deep learning is to discover rich, hierarchical models [2] that represent probability distributions over the kinds of data encountered in artificial intelligence applications, such as natural images, audio waveforms containing speech, and symbols in natural language corpora. So far, the most striking successes in deep learning have involved discriminative models, usually those that map a high-dimensional, rich sensory input to a class label [14, 20]. These striking successes have primarily been based on the backpropagation and dropout algorithms, using piecewise linear units [17, 8, 9] which have a particularly well-behaved gradient. Deep *generative* models have had less of an impact, due to the difficulty of approximating many intractable probabilistic computations that arise in maximum likelihood estimation and related strategies, and due to difficulty of leveraging the benefits of piecewise linear units in the generative context. We propose a new generative model estimation procedure that sidesteps these difficulties.¹



Why GANs?

- State-of-the-art* models in:
 - Image generation: **BigGan**
 - Text-to-Speech: **GAN-TTS**
 - Instrument score synthesis: **GANSynth**
- Understanding of adversarial attacks
- Wide use of adversarial training



* State-of-the-art in 2020


Training GANs

Training GANs

Make $G(\mathbf{z})$ indistinguishable from real data for D

$$\mathcal{L}_G = \log(1 - D(G(\mathbf{z})))$$



$$\mathcal{L}_D = \log(1 - D(\mathbf{X})) + \log(D(G(\mathbf{z})))$$



Training Difficulties

- Failure to converge
 - Discrimination is easier than generation
 - Unstable training of generator


- Mode collapse:
 - mapping several inputs to the same output
 - *“when something works, why change it?”*




Popular GANs

Deep Convolutional GAN (DCGAN)

- Fully convolutional generator and discriminator
 - Strided convolutions instead of pooling
 - G: ReLU activation and TanH in output
 - D: Leaky ReLU activation
 - Batch normalization
- Extremely popular architecture
 - DCGAN-like autoencoders
 - ≈10,000 citations








Epoch 1

Conditional GAN (CGAN)



Dog



Cat



Tiger



Cycle Consistent GANs

- Model that performs image-to-image translation
- Paired images are expensive/impossible to obtain
- **Cycle consistency loss:** trainable inverse mapping F such that:

$$F(G(\mathbf{x})) \approx \mathbf{x} \quad \text{and} \quad G(F(\mathbf{y})) \approx \mathbf{y}$$



zebra \rightarrow horse





Cycle Consistent GANs

- Use two generators (G and F) and two discriminators (D_X and D_Y)

$$\mathcal{L}_{Cyc}(G, F) = \|F(G(\mathbf{x})) - \mathbf{x}\|_1 + \|G(F(\mathbf{y})) - \mathbf{y}\|_1$$

$$\mathcal{L} = \mathcal{L}_{GAN}(G, D_X) + \mathcal{L}_{GAN}(F, D_Y) + \lambda \mathcal{L}_{Cyc}(G, F)$$





References

1. <https://towardsdatascience.com/all-you-want-to-know-about-deep-learning-8d68dcffc258>
2. Goodfellow, Ian, et al. Deep learning. Vol. 1. No. 2. Cambridge: MIT press, 2016.
3. Brock, Andrew, Jeff Donahue, and Karen Simonyan. "Large scale GAN training for high fidelity natural image synthesis." arXiv preprint arXiv:1809.11096 (2018).
4. Bińkowski, Mikołaj, et al. "High fidelity speech synthesis with adversarial networks." arXiv preprint arXiv:1909.11646 (2019).
5. Engel, Jesse, et al. "Gansynth: Adversarial neural audio synthesis." arXiv preprint arXiv:1902.08710 (2019).
6. <https://salu133445.github.io/ismir2019tutorial/>
7. <https://machinelearningmastery.com/practical-guide-to-gan-failure-modes/>
8. Radford, Alec, Luke Metz, and Soumith Chintala. "Unsupervised representation learning with deep convolutional generative adversarial networks." arXiv preprint arXiv:1511.06434 (2015).

References

9. Mirza, Mehdi, and Simon Osindero. "Conditional generative adversarial nets." arXiv preprint arXiv:1411.1784 (2014).
10. Zhu, Jun-Yan, et al. "Unpaired image-to-image translation using cycle-consistent adversarial networks." Proceedings of the IEEE international conference on computer vision. 2017.