

Lab CudaVision  
Learning Vision Systems on Graphics Cards (MA-INF 4308)

# CNN Architectures

---

01.06.2021

PROF. SVEN BEHNKE, ANGEL VILLAR-CORRALES


Contact: [villar@ais.uni-bonn.de](mailto:villar@ais.uni-bonn.de)

# Early Architectures

---


# LeNet-5 (1998)

- Very first CNN, and inspiration for future architectures
- Key Features:
  - Conv. of spatial features
  - Subsampling through average pooling
  - Convolutional feature extractor
  - MLP classifier head




# AlexNet (2012)

- Winner of 2012 Imagenet challenge  $\Rightarrow$  Breakthrough of CNNs
- Architectural Features:
  - 8 layers deep
  - Overlapping max-pooling
  - Big convolutional kernels
  - ReLU activation function




# AlexNet (2012)

- Winner of 2012 Imagenet challenge  $\Rightarrow$  Breakthrough of CNNs
- Regularization Features:
  - Dropout regularization with  $p=0.5$  in Fully-Connected layers
  - Data augmentation





# AlexNet (2012)

- Winner of 2012 Imagenet challenge  $\Rightarrow$  Breakthrough of CNNs
- Training Strategy:
  - Mini-batch SGD with Momentum + L2 regularization
  - Trained on 2 GPUs




# ZF-Net (2013)

- Mostly a fine-tuned version of AlexNet
- Use of smaller convolutional kernels
- Gave insights about what CNNs learn



# VGG (2014)

- Based on two pillars: simplicity and depth
- Consolidated rules for modern convolutional layers
  - Small convolutional kernels
  - Many kernels per layer
- Exploiting hierarchy of features
  - Spatial size decreases
  - Depth increases






# Deeper Models


---

# Evolution of Depth




# Advantages of Deeper Networks


- Exponential feature reuse



- Hierarchical and increasingly abstract features




# The Degradation Problem




- Deeper models tend to have higher **training & test error** than shallow ones
  - Not just due to overfitting!
- Possible reasons:
  - **Vanishing gradients** due to activations
  - **Co-variate shifts** due to non-centered activations or normalizations
  - Poor **backpropagation** of activations and gradients

# Residual Learning


- Learning a residual mapping  $\mathcal{F}(\mathbf{x}) + \mathbf{x}$  instead of a direct one  $\mathcal{F}(\mathbf{x})$
- Reformulating learning as a refinement of the inputs
- Gradients backpropagated through identity do not vanish



# Loss Landscapes





(a) without skip connections




(b) with skip connections

# Residual Networks (2015)


- Winner of the 2015 ImageNet Challenge
- Deep cascade of residual blocks
- Super-human performance of several computer vision tasks



# Residual Networks (2015)



Plain networks






Residual networks

- Gradients backpropagated through residual connections do not vanish
- Deeper networks obtain better train & validation loss!



# DenseNet (2016)

- **Standard CNNs:**
  - Cascade of convolutional layers
- **ResNets:**
  - Element-wise addition of residual and convolved features
- **DenseNets:**
  - Channel-wise concatenation



# DenseNet (2016)


---



# DenseNet (2016)

- Advantages:

- Strong gradient flow
- Diversified features
- Classifier uses feature of all



- Disadvantages:

- Large number of parameters
- Low parameter efficiency
- Excessive computational power required

# More CNN Architectures...

---

SparseNet

ResNeXt

SqueezeNet

ResNet-of-ResNets

InceptionNet

Inception-Resnet

NasNet

SENet

Wide-Residual Networks


- Architectures for Object Detection
- Architectures for Semantic Segmentation
- Transformer-Bases Architectures



# Global Average Pooling

---

# From Convolutional to MLP




How do we know the exact dimensionality?

What if images have different sizes?


# Global Average Pooling

- Take the average activation over all spatial values
- $C \times H \times W \Rightarrow C \times 1 \times 1$
- Advantages:
  - Less constraints on input size
  - Reduce overfitting
  - Significantly less parameters




```
avgpool = nn.AdaptiveAvgPool2d((1, 1))
```


# Architectures with GAP



## MobileNet



## Mask R-CNN



**and many more...**





# References

---

1. Russakovsky, Olga, et al. "Imagenet large scale visual recognition challenge." International journal of computer vision 115.3 (2015): 211-252.
2. Simonyan, Karen, and Andrew Zisserman. "Very deep convolutional networks for large-scale image recognition." arXiv preprint arXiv:1409.1556 (2014).
3. Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E. Hinton. "Imagenet classification with deep convolutional neural networks." Advances in neural information processing systems 25 (2012): 1097-1105.
4. Zeiler, Matthew D., and Rob Fergus. "Visualizing and understanding convolutional networks." European conference on computer vision. Springer, Cham, 2014.
5. He, Kaiming, et al. "Deep residual learning for image recognition." Proceedings of the IEEE conference on computer vision and pattern recognition. 2016.
6. Huang, Gao, et al. "Densely connected convolutional networks." Proceedings of the IEEE conference on computer vision and pattern recognition. 2017.

# References

---

7. Li, Hao, et al. "Visualizing the loss landscape of neural nets." arXiv preprint arXiv:1712.09913 (2017).
8. <https://towardsdatascience.com/review-densenet-image-classification-b6631a8ef803>
9. <http://ethereon.github.io/netscope/#/gist/db945b393d40bfa26006>
10. <https://alexisbcook.github.io/2017/global-average-pooling-layers-for-object-localization/>