SPEC CPU®2017 Integer Speed Result Copyright 2017-2023 Standard Performance Evaluation Corporation My Corporation SPECspeed®2017_int_base 94 SPECspeed®2017 int **Mot Run** Test Date: CPU2017 License: nnn (Your SPEC license number) Jun-2023 Hardware Availability: **Test Sponsor:** My Corporation Software Availability: Tested by: My Corporation Threads 0 600.perlbench_s 602.gcc_s 9.94 605.mcf_s 620.omnetpp_s 623.xalancbmk_s 625.x264 s 631.deepsjeng_s 641.leela s 648.exchange2_s 657.xz_s SPECspeed®2017_int_base (9.94) Hardware Software OS: Ubuntu 18.04.6 LTS

CPU Name: Intel Core i7-10750H

Max MHz:

Nominal:

Enabled: cores, 1 chip, threads/core

Cache L1:

L2:

L3:

Other:

Memory:

Storage:

Øther:

Orderable:

15.469 GB fixme: If using DDR4, the format is:

'N GB (Nx N GB nRxn PC4-nnnnX-X)'

16 GB add more disk info here

Errors

Compiler:

Parallel:

Other:

Firmware:

File System:

System State:

Base Pointers:

Peak Pointers:

Power Management: --

5.4.0-150-generic

Yes

ext4

64-bit

Not Applicable

GNU Compiler Collection

Run level 5 (add definition here)

C/C++/Fortran: Version 7.2.1 of GCC, the

'reportable' flag not set during run

600.perlbench s (base) did not have enough runs!

641.leela_s(base) did not have enough runs!

648.exchange2/s (base) did not have enough runs!

657.xz_s (base) did not have enough runs!

625.x264_s (base) did not have enough runs!

620.omnetpp_s (base) did not have enough runs!

631.deepsjeng_s (base) did not have enough runs!

623.xalancbmk_s (base) did not have enough runs!

602.gcc_s (base) did not have enough runs!

Page 1

Copyright 2017-2023 Standard Performance Evaluation Corporation

My Corporation

Test Sponsor:

Tested by:

SPECspeed®2017_int_base

SPECspeed®2017 int **Mot Run**

CPU2017 License: nnn (Your SPEC license number)

My Corporation My Corporation Test Date: Jun-2023 Hardware Availability:

Software Availability:

94

Results Table

	Base							Peak						
Benchmark	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s										1				
602.gcc_s						\wedge								
605.mcf_s	4	<u>475</u>	<u>9.94</u>	474	9.97	$\langle \ \ \rangle$)/					
620.omnetpp_s									~					
623.xalancbmk_s														
625.x264_s						(5						
631.deepsjeng_s														
641.leela_s)	_			<i>)</i>)~						
648.exchange2_s			>											
657.xz_s														

SPECspeed®2017_int_base = 9.94

SPECspeed®2017_int_peak = **Not Run**

Results appear in the order in which they were run. Fold underlined text indicates a median measurement.

Environment Variables Notes

by runcpu before the start of the run: Environment variables set LD_LIBRARY_PATH = "/vsr/lib64/:/usr/lib64"

Platform Notes

```
Sysinfo program
```

/media/fabricio/679cbc52-a115-43bd-b089-5d44b8abcd6f/spec-cpu-2017/bin/sysinfo

Rev: r6365 of 2019-08-21 295195f888a3d7edb1e6e46a485a0011

on fabricio-gerver Wed Jun 14 21:15:26 2023 running

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From \proc/cpuinfo

model pame : Intel(R) Core(TM) i7-10750H CPU @ 2.60GHz

"physical id"s (chips)

12 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following

excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 6 siblings : 12

physical 0: cores 0 1 2 3 4 5

From lscpu:

(Continued on next page)

Copyright 2017-2023 Standard Performance Evaluation Corporation

My Corporation

Test Sponsor:

Tested by:

SPECspeed®2017_int_base

94

SPECspeed®2017_int_peak > Not Run

CPU2017 License: nnn (Your SPEC license number)

My Corporation

My Corporation

Test Date: Jun-2023

Hardware Availability: Software Availability:

Platform Notes (Continued)

```
Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Byte Order: Little Endian
CPU(s): 12
```

On-line CPU(s) list: 0-11
Thread(s) per core: 2
Core(s) per socket: 6
Socket(s): 1
NUMA node(s): 1

Vendor ID: Genuine Intel

CPU family: 6
Model: 165

Model name: /Intel(R) Core(TM) 17-10750H CPU @ 2.60GHz

 Stepping:
 2

 CPU MHz:
 4548.681

 CPU max MHz:
 5000.8000

 CPU min MHz:
 800.0000

 BogoMIPS:
 5199.98

BogoMIPS: 5199.98
Virtualization: VT-x
L1d cache: 32k
L1i cache: 256K

L3 cache: 12288K

NUMA node0 CPU(sV: 0-11

fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc cpuid aperfmperf pni pclmulqdq dtes64 monitor ds_cpl vmx est tm2 sse3 sdbg fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb invpcid_single ssbd ibrs ibpb stibp ibrs_enhanced tpr_shadow vnmi flexpriority ept vpid ept_ad fsgsbase tsc_adjust bmil avx2 smep bm12 erms invpcid mpx rdseed adx smap clflushopt intel_pt xsaveopt xsavec xgetbv1 xsaves dtherm ida arat pln pts hwp hwp_notify hwp_act_window hwp_epp pku ospke md_clear flush_l1d arch_capabilities

/proc/cpuinfo cache data cache size : 12288 KB

From number --hardware WARNING: a number of might or might not correspond to a physical chip.

From /proc/meminfo

MemTotal: 16220164 kB HugePages_Total: 0 Hugepagesize: 2048 kB

/usr/bin/lsb_release -d

(Continued on next page)

Copyright 2017-2023 Standard Performance Evaluation Corporation

My Corporation

SPECspeed[®]2017_int_base =

SPECspeed®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Jun-2023

94

Hardware Availability: Software Availability:

Platform Notes (Continued)

```
Ubuntu 18.04.6 LTS
From /etc/*release* /etc/*version*
   debian_version: buster/sid
   os-release:
      NAME="Ubuntu"
      VERSION="18.04.6 LTS (Bionic Beaver)
      ID=ubuntu
      ID_LIKE=debian
      PRETTY_NAME="Ubuntu 18.04. LTS"
      VERSION_ID="18.04"
      HOME URL="https://www.ubuntu.com/
      SUPPORT_URL="https://help.ub/mtu.com/
uname -a:
   Linux fabricio-server 5.4.0-150-generic #167~18.04.1-Ubuntu SMP Wed May 24 00:51:42
   UTC 2023 x86_64 x86_64 x86_64 SNU/Linux
Kernel self-reported vulnerability status:
itlb_multihit:
                                          KVM: Mitigation: Split huge pages
CVE-2018-3620 (L1 Terminal Fault
                                          Not affected
Microarchitectural Data Sampling
                                          Not affected
CVE-2017-5754 (Meltdown):
                                          Not affected
mmio_stale_data:
                                          Mitigation: Clear CPU buffers; SMT vulnerable
retbleed:
                                          Mitigation: Enhanced IBRS
CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store Bypass disabled
                                          via prctl and seccomp
                                         Mitigation: usercopy/swapgs barriers and __user
              Spectre variant 1):
CVE-2017
                                          pointer sanitization
         5715
              (Spectre variant 2):
                                          Mitigation: Enhanced IBRS, IBPB: conditional,
                                          RSB filling, PBRSB-eIBRS: SW sequence
srbds:
                                          Mitigation: Microcode
tsx_async_abort
                                          Not affected
run level 5 Jun 14 20:43
SPEC is set to: /media/fabricio/679cbc52-a115-43bd-b089-5d44b8abcd6f/spec-cpu-2017
                  Type Size Used Avail Use% Mounted on
   Filesystem
   /dev/nvme0n1p1 ext4 916G
                              17G 853G
   /media/fabricio/679cbc52-a115-43bd-b089-5d44b8abcd6f
From /sys/devices/virtual/dmi/id
    BIOS:
             American Megatrends Inc. N.1.02 07/17/2020
    Vendor: Avell High Performance
    Product: C62 LIV
    Product Family: C62 LIV
```

(Continued on next page)

Copyright 2017-2023 Standard Performance Evaluation Corporation

My Corporation

SPECspeed®2017_int_base =

SPECspeed®2017_int_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Jun-2023

Hardware Availability: Software Availability:

Platform Notes (Continued)

Cannot run dmidecode; consider saying (as root)
 chmod +s /usr/sbin/dmidecode

(End of data from sysinfo program)

Compiler Version Notes

C | 605.mcf s(base)

C | 605.mci_s(base)

Using built-in specs.

COLLECT_GCC=/usr/bin/gcc

COLLECT_LTO_WRAPPER=/usr/Tib/scc/x86_64-linux-gnu/7/lto-wrapper

OFFLOAD_TARGET_NAMES=nvptx-none

OFFLOAD_TARGET_DEFAULT=1
Target: x86_64-linux-gnu

Configured with: ../src/configure -v -with-pkgversion='Ubuntu

7.5.0-3ubuntu1~18.04' (-with bugurl=1/11e:///usr/share/doc/gcc-7/README.Bugs

--enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --prefix=/usr

--with-gcc-major-version-only --program-suffix=-7

--program-prefix=286_64-linux-ghu- --enable-shared --enable-linker-build-id

--libexecdir=/usr/lib --without/included-gettext --enable-threads=posix

--libdir=/usr/Nib --anable-nls --enable-bootstrap --enable-clocale=gnu

--enable-libstdcxx-debug --enable-libstdcxx-time=yes

--with-default-libstdcx-abi=new --enable-gnu-unique-object

--disable-vtable-verify --enable-libmpx --enable-plugin

--enable-default-pie --with-system-zlib --with-target-system-zlib

--enable-objc-gc=auto --enable-multiarch --disable-werror

--with-multilib-list=m32,m64,mx32

--enable multillb /-with-tune=generic --enable-offload-targets=nvptx-none

--without-auda-driver --enable-checking=release --build=x86_64-linux-gnu

- host=x86_64-linux-gnu --target=x86_64-linux-gnu

Thread model: posix

gcc version 7.5.0 (Ubuntu 7.5.0-3ubuntu1~18.04)

Base Runtime Environment

C benchmarks:

605.mcf_s: No flags used

Copyright 2017-2023 Standard Performance Evaluation Corporation

My Corporation

SPECspeed®2017_int_base

SPECspeed®2017 int

Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Jun-2023

Hardware Availability: Software Availability:

Base Compiler Invocation

C benchmarks:

605.mcf_s: gcc

Base Portability Flags

605.mcf_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

605.mcf_s: -m64 -std=c99 -g 03 -march=hative

- -fno-unsafe-math-optimizations -fno-tree-loop-vectorize -fopenmp
- -DSPEC_OPENMP -fno-strict aliasing -fgmu89-inline

Base Other Flags

C benchmarks:

605.mcf_s: No flags used

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU*2017 v1.1.0 on 2023-06-14 21:15:26-0300.

Report generated on 2023-06-14 21:32:49 by CPU2017 PDF formatter v6255.