

A comparative analysis of Von-Heijne, SVM and Perceptron Models for the detection of Signal Peptides.

Abstract

Motivation: This is the motivation

Results: This are the results.

Materials and Methods

Data Collection

Protein sequences were queried from UniprotKB, and collected into 2 distinct sets, positive and negative. For Positive sequences, we selected sequences having experimental evidence for the presence of a signal peptide (ft_signal_exp:*) For the negative set, proteins not annotated with a signal peptide and endowed with experimental evidence for subcellular localization in non-secretory compartments, namely nucleus (cc_scl_term_exp:SL-0191), peroxisome (cc_scl_term_exp:SL-0204), cell membrane / plasma membrane (cc_scl_term_exp:SL-0039), cytosol (cc_scl_term_exp:SL-0091), plastid (cc_scl_term_exp:SL-0209) or mitochondrion (cc_scl_term_exp:SL-0173).

Both sets were also limited to the taxa of eukaryotes and reviewed entries, and non-fragment nature.

Further selection on the positive entries was made to select proteins which had information about the cleavage site and a Signal Peptide with a length of at least 14bp.

For the negative set, additional information was added to the data representing the presence of a transmembrane helix, whose hydrophobicity profile mimicks the one of a signal peptide.

Von-Heijne Model

The full dataset was split into a training and a test set with a ratio of 0.8. A Position-Specific Weight Matrix (PSWM) was then generated using 16bp windows (13bp upstream to 2bp downstream) surrounding the cleavage site. Amino acid frequencies were normalized using background amino acid frequencies from SwissProt. After initializing the matrix with pseudocounts of 1, the weights are computed as follows:

$$w(a, i) = \log_2 \left(\frac{f(a, i)}{f(a)} \right)$$

Where $f(a, i)$ is the frequency of amino acid a at position i in the training set, and $f(a)$ is the background frequency of amino acid a in SwissProt. The score for a given sequence is then computed as:

$$S = \max_{j=1}^{90-16+1} \sum_{i=1}^{16} w(a_{j+i-1}, i)$$

scores are computed over the first 90bp of the given sequence, using a sliding window 16bp long.

Clustering

Clustering was performed using mmseqs2 [cit], using parameters `=c 0.4 --min-seq-id 0.3 --cov-mode 0 --cluster-mode 1`, giving clusters with less than 30% pairwise identity.