

Stochastic programming & Robust optimisation

Lecture 2/4

Fabricio Oliveira

Systems Analysis Laboratory
Department of Mathematics and Systems Analysis

Aalto University
School of Science

UFMG, Belo Horizonte, Brazil
23.08.2024

Outline of this lecture

Introduction

Scenario trees

Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)

Outline of this lecture

Introduction

Scenario trees

Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)

Stochastic programming models

Mathematical programming models in which some of the parameters are assumed to be **random variables**.

It comprises the following parts:

1. A mathematical programming model
2. **Deterministic** parameter values
3. Description of the **stochasticity**, e.g.,
 - a known probability distribution;
 - historical data;
 - distribution properties (average, standard deviation, i.e., moments)

Stochastic programming models

Mathematical programming models in which some of the parameters are assumed to be **random variables**.

It comprises the following parts:

1. A mathematical programming model
2. **Deterministic** parameter values
3. Description of the **stochasticity**, e.g.,
 - a known probability distribution;
 - historical data;
 - distribution properties (average, standard deviation, i.e., moments)

The most widespread use of stochastic programs relies on **scenarios**:

- ▶ Lead to **tractable** deterministic equivalents;
- ▶ Are **approximations** of the original stochastic process

Stochastic programming models

A scenario tree ξ comprises **sequentially observed realisations** of ξ^t , for $t = 1, \dots, H$:

- ▶ $\xi = (\xi^t)_{t \in [H]}$, where (\cdot) denotes a **sequence** and $\xi^t \in \Xi_t$;
- ▶ a **scenario** is denoted $\xi_s = (\xi_s^t)_{t \in [H]}$ forming a “path” through ξ ;
- ▶ Thus, $\xi = \{\xi_s\}_{s \in [S]}$, where S is the number of scenarios.

Stochastic programming models

A scenario tree ξ comprises **sequentially observed realisations** of ξ^t , for $t = 1, \dots, H$:

- ▶ $\xi = (\xi^t)_{t \in [H]}$, where (\cdot) denotes a **sequence** and $\xi^t \in \Xi_t$;
- ▶ a **scenario** is denoted $\xi_s = (\xi_s^t)_{t \in [H]}$ forming a “path” through ξ ;
- ▶ Thus, $\xi = \{\xi_s\}_{s \in [S]}$, where S is the number of scenarios.

Example:




Figure: A 4-stage (**lattice**) scenario tree with 2 scenarios per stage. $\xi = (\xi^1, \xi^2, \xi^3)$;

Outline of this lecture

Introduction

Scenario trees


Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)


Taxonomy of scenario trees

Terminology




Taxonomy of scenario trees

Terminology




Taxonomy of scenario trees

Terminology




Taxonomy of scenario trees

Terminology



Taxonomy of scenario trees



Branching indicates a decision upon arrival of **new information**

- ▶ No branching, no additional information;
- ▶ **Fan trees** represent **multi-period 2-stage problems**.

Outline of this lecture

Introduction

Scenario trees

Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)

Trade-off approximation quality vs. tractability

Two parameters govern the geometry of a scenario tree:

- ▶ **Depth:** number of stages H
- ▶ **Breadth (or width):** number of realisations per stage $|\xi^t|$

Trade-off approximation quality vs. tractability

Two parameters govern the geometry of a scenario tree:

- ▶ **Depth:** number of stages H
- ▶ **Breadth (or width):** number of realisations per stage $|\xi^t|$

The **total of scenarios** is $O(N^H)$ (assuming $|\xi_t| = N$ for $t \in [H]$)

- ▶ Larger H convey more **adaptability** to revealed information;
- ▶ Larger S convey a more **precise** description of the uncertainty;
- ▶ **Computational tractability** issues pressure them to be as small as possible.

Most scenario generation methods seek to find trees with **minimal** $|\xi|$ such that **representation quality** requirements are observed.

Data source

Typical **sources** for scenarios include:

1. **Historical data:** past observations as possible future observations;
2. **Simulation models:** Monte Carlo, systems dynamics, agent-based and discrete event simulation;
3. **Expert elicitation:** typically a small number of scenarios with no possible (out-of-sample) testing.

Data source

Typical **sources** for scenarios include:

1. **Historical data:** past observations as possible future observations;
2. **Simulation models:** Monte Carlo, systems dynamics, agent-based and discrete event simulation;
3. **Expert elicitation:** typically a small number of scenarios with no possible (out-of-sample) testing.


Often, a **combination** of the above is used:

1. Start from the **data**;
2. Define and fit a **parametric model**;
3. Generate **observations** from the model.

Scenario generation and modelling

Scenario generation must be part of the **modelling process**

- ▶ Problem dependent;
- ▶ The method for generating scenarios is a **modelling decision**;
- ▶ Often overlooked in applications;
- ▶ Quality of scenarios **majorly** influences quality of solution (“garbage in = garbage out”).



Quality measures for scenario trees

Apart from **epistemic error** questions, two measures must be considered when generating scenario trees:

1. Error

- Error introduced for using an **approximation** of the real stochastic process;
- Unlikely to be measurable, but possible to be approximated.

2. Stability

- Scenario-trees approximating the same stochastic process should yield the same solution;
- Likewise, objective function values should be **stable**.

Quality measures for scenario trees

Apart from **epistemic error** questions, two measures must be considered when generating scenario trees:

1. Error

- Error introduced for using an **approximation** of the real stochastic process;
- Unlikely to be measurable, but possible to be approximated.

2. Stability

- Scenario-trees approximating the same stochastic process should yield the same solution;
- Likewise, objective function values should be **stable**.

Let ξ be a scenario tree representing the original **stochastic process** η , and $\mathcal{F}(x, \xi) = \mathbb{E}_{\xi} [F(x, \xi)]$. We are interested in understanding how well

$$\min_x \mathcal{F}(x, \xi) \text{ approximates } \min_x \mathcal{F}(x, \eta)$$

Quality measures for scenario trees

Let ξ_k , for $k = 1, \dots, n$, be a collection of alternative scenario trees generated (e.g., by sampling) to represent η . We have that

$$x_k^* = \arg \min_x \mathcal{F}(x, \xi_k).$$

Quality measures for scenario trees

Let ξ_k , for $k = 1, \dots, n$, be a collection of alternative scenario trees generated (e.g., by sampling) to represent η . We have that

$$x_k^* = \arg \min_x \mathcal{F}(x, \xi_k).$$

The **approximation error** [Pflug, 2001] is defined as

$$\begin{aligned} e(\eta, \xi_k) &= \mathcal{F}(\arg \min_x \mathcal{F}(x, \xi_k), \eta) - \mathcal{F}(\arg \min_x \mathcal{F}(x, \eta), \eta) \\ &= \mathcal{F}(x_k^*, \eta) - \min_x \mathcal{F}(x, \eta). \end{aligned}$$

Quality measures for scenario trees

Let ξ_k , for $k = 1, \dots, n$, be a collection of alternative scenario trees generated (e.g., by sampling) to represent η . We have that

$$x_k^* = \arg \min_x \mathcal{F}(x, \xi_k).$$

The **approximation error** [Pflug, 2001] is defined as

$$\begin{aligned} e(\eta, \xi_k) &= \mathcal{F}(\arg \min_x \mathcal{F}(x, \xi_k), \eta) - \mathcal{F}(\arg \min_x \mathcal{F}(x, \eta), \eta) \\ &= \mathcal{F}(x_k^*, \eta) - \min_x \mathcal{F}(x, \eta). \end{aligned}$$

- ▶ Calculating $\mathcal{F}(x_k^*, \eta)$ requires evaluating the “true” objective function;
- ▶ Alternatively, **Monte Carlo simulation** is often employed to approximate $\mathcal{F}(x_k^*, \eta)$;
- ▶ Clearly, there is no way to evaluate $\min_x \mathcal{F}(x, \eta)$.

Stability of scenario trees

Out-of-sample stability

Assume that we can **approximate** $\mathcal{F}(x_k^*, \eta)$. This allows us to

- ▶ compare solutions x_1^* and x_2^* ;
- ▶ compare **alternative** scenario generation methods;
- ▶ perform **out-of-sample** stability test:
 1. Generate a set of scenario trees $\{\xi_1, \dots, \xi_n\}$;
 2. Obtain solutions x_k , $k = 1, \dots, n$;
 3. Test whether $\mathcal{F}(x_k^*, \eta) \approx \mathcal{F}(x_l^*, \eta)$, for $k, l = 1 \dots, n : k \neq l$.

Stability of scenario trees

Out-of-sample stability

Assume that we can **approximate** $\mathcal{F}(x_k^*, \eta)$. This allows us to

- ▶ compare solutions x_1^* and x_2^* ;
- ▶ compare **alternative** scenario generation methods;
- ▶ perform **out-of-sample** stability test:
 1. Generate a set of scenario trees $\{\xi_1, \dots, \xi_n\}$;
 2. Obtain solutions x_k , $k = 1, \dots, n$;
 3. Test whether $\mathcal{F}(x_k^*, \eta) \approx \mathcal{F}(x_l^*, \eta)$, for $k, l = 1 \dots, n : k \neq l$.

Remarks:

- ▶ $e(\eta, \xi_k) \approx 0 \Rightarrow e(\eta, \xi_k) \approx e(\eta, \xi_l) \equiv \mathcal{F}(x_k^*, \eta) \approx \mathcal{F}(x_l^*, \eta)$;
- ▶ The procedure above can also be used to **assess scenario tree** width (scenarios per stage).

Stability of scenario trees

In-sample stability

In-sample stability is defined as

$$\mathcal{F}(x_k^*, \xi_k) \approx \mathcal{F}(x_l^*, \xi_l), \text{ for } k, l = 1, \dots, n : k \neq l.$$

Stability of scenario trees

In-sample stability

In-sample stability is defined as

$$\mathcal{F}(x_k^*, \xi_k) \approx \mathcal{F}(x_l^*, \xi_l), \text{ for } k, l = 1, \dots, n : k \neq l.$$

In some contexts, can also be defined as

$$\|x_k^* - x_l^*\|_p \approx 0, \text{ for } k, l = 1, \dots, n : k \neq l.$$

where $\|\cdot\|_p$ is a vector p -norm.

Stability of scenario trees

In-sample stability

In-sample stability is defined as

$$\mathcal{F}(x_k^*, \xi_k) \approx \mathcal{F}(x_l^*, \xi_l), \text{ for } k, l = 1, \dots, n : k \neq l.$$


In some contexts, can also be defined as

$$\|x_k^* - x_l^*\|_p \approx 0, \text{ for } k, l = 1, \dots, n : k \neq l.$$


where $\|\cdot\|_p$ is a vector p -norm.

- ▶ No direct connection to **out-of-sample** stability;
- ▶ Useful for assessing the **internal** stability of a random scenario generation method;
- ▶ Translates into **confidence** in the objective function value reported.

Stability of scenario trees



(a) Out-of-sample stability



(b) In-sample stability

Figure: Trade-off analysis: error v. computational time [Dillon et al., 2017]

Outline of this lecture

Introduction

Scenario trees

Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)

Scenario generation methods

The main types of scenario-generation methods are:

1. **Moment matching:** artificially **generates** a set of scenarios with the **same** (four plus correlation, usually) **statistical moments** as the desired distribution;

Scenario generation methods

The main types of scenario-generation methods are:

1. **Moment matching:** artificially **generates** a set of scenarios with the **same** (four plus correlation, usually) **statistical moments** as the desired distribution;
2. **Metric-based:** form **smaller** scenario sets whilst **minimising** some probabilistic distance metric. Includes clustering (k-means and related methods) and scenario reduction.

Scenario generation methods

The main types of scenario-generation methods are:

1. **Moment matching:** artificially **generates** a set of scenarios with the **same** (four plus correlation, usually) **statistical moments** as the desired distribution;
2. **Metric-based:** form **smaller** scenario sets whilst **minimising** some probabilistic distance metric. Includes clustering (k-means and related methods) and scenario reduction.
3. **Sampling:** **Monte-Carlo sampling**, or quasi Monte-Carlo sampling using variance reduction techniques (e.g., Sobol sequences). Combined with Sample Average Approximation (SAA).

Scenario generation methods

Moment matching

Build a scenario tree $\xi = \{(z_s, p_s)\}_{s \in [S]}$ that has **statistical moments** $f_m(z, p)$ matching M_m^{VAL} **target** values.

Scenario generation methods

Moment matching

Build a scenario tree $\xi = \{(z_s, p_s)\}_{s \in [S]}$ that has **statistical moments** $f_m(z, p)$ matching M_m^{VAL} **target** values.

- ▶ Moments extracted from the original distribution, or data;

Scenario generation methods

Moment matching

Build a scenario tree $\xi = \{(z_s, p_s)\}_{s \in [S]}$ that has **statistical moments** $f_m(z, p)$ matching M_m^{VAL} **target** values.

- ▶ Moments extracted from the original distribution, or data;
- ▶ The following problem must be solved ([Høyland and Wallace, 2001]):

$$\begin{aligned} \min_{z, p \geq 0} \quad & \sum_{m \in M} w_m (f_m(z, p) - M_m^{\text{VAL}})^2 \\ \text{s.t.:} \quad & \sum_{j=1}^S p_j = 1, \end{aligned}$$

where w_m are weights.

Remark: [Høyland et al., 2003] show how the above problem can be **heuristically** solved.

Scenario generation methods

Metric-based methods

Probability-metric based methods use the following result [Pflug, 2001]

$$e(\eta, \xi_k) \leq K d(\eta, \xi_k)$$

where K is a (Lipschitz-related) constant and d is a **Wasserstein distance** between η and ξ_k . Thus, the focus is on obtaining trees that **minimise** d .

Scenario generation methods

Metric-based methods


Probability-metric based methods use the following result [Pflug, 2001]

$$e(\eta, \xi_k) \leq K d(\eta, \xi_k)$$

where K is a (Lipschitz-related) constant and d is a **Wasserstein distance** between η and ξ_k . Thus, the focus is on obtaining trees that **minimise** d .

Let $\xi^l = (z^l, p^l) \in \Xi^l$. The (p -order) Wasserstein distance $d(\xi^1, \xi^2)$ is given by:

$$\begin{aligned} \min_{\pi} \quad & \sum_{i \in \xi^1, j \in \xi^2} \|z_i^1 - z_j^2\|_p \pi_{ij} \\ \text{s.t.:} \quad & \sum_{j \in \xi^2} \pi_{ij} = p_i^1, \quad \forall i \in \xi^1 \\ & \sum_{i \in \xi^1} \pi_{ij} = p_j^2, \quad \forall j \in \xi^2. \end{aligned}$$



Scenario generation methods

Metric-based methods

1. “Clustering-like” methods:

- ▶ k -means, and variants incorporating Wasserstein distance as the metric [Condeixa et al., 2020]
- ▶ Work well in case scenarios are generated from data [Kaut, 2021];

Scenario generation methods

Metric-based methods

1. “Clustering-like” methods:

- ▶ k -means, and variants incorporating **Wasserstein distance** as the metric [Condeixa et al., 2020]
- ▶ Work well in case scenarios are generated from **data** [Kaut, 2021];

2. **Scenario reduction methods:** Obtain ξ^2 from ξ^1 where $|\xi^2| < |\xi^1|$.

- ▶ Based on the theory of stability of stochastic programs [Römisch, 2003]
 - Changes in the solution can be approximated using a Fortet-Mourier-type metric
 - Calculation amounts to solving a Monge-Kantorovich mass transportation problem
- ▶ “Historical” chronology:
 1. [Dupačová et al., 2003, Heitsch and Römisch, 2003]: first **backward reduction** and **forward selection** methods;
 2. [Heitsch and Römisch, 2007] improved versions of the heuristics;
 3. [Heitsch and Römisch, 2009] The above does not work for **multi-stage** problems. Provides a method that does.

Scenario generation methods

Scenario reduction

Types of reduction algorithms. Let K be a target value for $|\xi^2|$

- ▶ **Backward reduction:** repeat until $|\xi^2| = K$. Start from ξ^1
 1. Find the scenario whose removal causes the **smallest error increase**
 2. Remove the scenario and redistribute its probability
- ▶ **Forward selection:** repeat until $|\xi^2| = K$. Start from $\xi^2 = \emptyset$
 1. Find the scenario whose inclusion causes the **largest error decrease**
 2. Add the scenario and redistribute its probability

Scenario generation methods

Scenario reduction

Types of reduction algorithms. Let K be a target value for $|\xi^2|$

- ▶ **Backward reduction:** repeat until $|\xi^2| = K$. Start from ξ^1
 1. Find the scenario whose removal causes the **smallest error increase**
 2. Remove the scenario and redistribute its probability
- ▶ **Forward selection:** repeat until $|\xi^2| = K$. Start from $\xi^2 = \emptyset$
 1. Find the scenario whose inclusion causes the **largest error decrease**
 2. Add the scenario and redistribute its probability

Some final practical remarks:

- ▶ In [Heitsch and Römisch, 2003], their results indicate:
 - 50% of the scenarios gives 90% relative accuracy
 - 1% of the scenarios gives 50% accuracy
- ▶ **Forward selection** gives better results, but is slow for large $|\xi^1|$ and K .
- ▶ **Scenred2** (GAMS) is an available implementation.

Scenario generation methods

Some of my own experience






Figure: Relative accuracy for scenario reduction; x -axis is $|\xi^1|$, lines are different $|\xi^2|$.
[Oliveira et al., 2016]

Scenario generation methods

Some of my own experience



(a) In-sample



(b) Out-of-sample

Figure: Objective function standard deviation comparing 3 alternative scenario reduction methods. Original sample had 1000 scenarios [Fernández Pérez et al., 2018]

Scenario generation methods




Figure: Out-of-sample error comparison of various scenario generation methods [Kaut, 2021]

Outline of this lecture

Introduction

Scenario trees

Generating scenario trees

Scenario (tree) generation methods

Sample Average Approximation (SAA)

What is SAA?


SAA [Shapiro and Homem-de Mello, 1998] is an **alternative** to generating scenario trees in the context of stochastic programming.

- ▶ Purely based on **sampling**;
- ▶ Monte Carlo simulation for **estimating** objective function bounds;
- ▶ Useful for handling **large** scenario sets;
- ▶ The sample m scenario tree size N is such that $N \ll |\xi|$ or $|\eta|$;
- ▶ Requires solving M problems.

What is SAA?

SAA [Shapiro and Homem-de Mello, 1998] is an **alternative** to generating scenario trees in the context of stochastic programming.

- ▶ Purely based on **sampling**;
- ▶ Monte Carlo simulation for **estimating** objective function bounds;
- ▶ Useful for handling **large** scenario sets;
- ▶ The sample m scenario tree size N is such that $N \ll |\xi|$ or $|\eta|$;
- ▶ Requires solving M problems.



How SAA works

SAA is based on the **law of large numbers** (LLN) and the **central limit theorem** (CLT).

As such, we can

- ▶ Estimate bounds using mean values;
- ▶ Estimate confidence intervals.

¹ $f(x)$ is a shorthand for $\mathcal{F}(x, \xi)$.

How SAA works

SAA is based on the **law of large numbers** (LLN) and the **central limit theorem** (CLT).

As such, we can

- ▶ Estimate bounds using mean values;
- ▶ Estimate confidence intervals.

First, let us define our notation for **2SSPs**

$$z = \min_x f(x),$$

where:

- ▶ $f(x) = \mathbb{E}_\xi [F(x, \xi)]^1$
- ▶ $F(x, \xi) = \{c^\top x + Q(x, \xi) : x \in X\};$
- ▶ $Q(x, \xi) = \min_y \{q(\xi)^\top y : W(\xi)y = h(\xi) - T(\xi)x, y \geq 0\};$
- ▶ $X = \{x \in \mathbb{R}^n : Ax = b, x \geq 0\}.$

¹ $f(x)$ is a shorthand for $\mathcal{F}(x, \xi)$.

How SAA works

Calculating a lower bounds for z

Let N be the number of samples we draw from our original stochastic process, forming the **scenario tree** $\xi = \{\xi_1, \dots, \xi_N\}$.

Then, we can solve the **sample-based approximation** problem

$$\hat{z}_N = \min_x \left\{ \tilde{f}_N(x) = \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\}. \quad (1)$$

²LLN: $\lim_{N \rightarrow \infty} \mathbb{E} \left[\frac{\sum_{n=1}^N X_n}{N} \right] = \frac{N\bar{X}}{N} = \bar{X}$ for i.i.d. random variable X_n with mean value \bar{X} .

How SAA works

Calculating a lower bounds for z

Let N be the number of samples we draw from our original stochastic process, forming the **scenario tree** $\xi = \{\xi_1, \dots, \xi_N\}$.

Then, we can solve the **sample-based approximation** problem

$$\hat{z}_N = \min_x \left\{ \tilde{f}_N(x) = \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\}. \quad (1)$$

First, notice that $\tilde{f}_N(x)$ is an **unbiased estimator**² for $f(x)$:

$$\mathbb{E}_\xi \left[\tilde{f}_N(x) \right] = \frac{1}{N} \mathbb{E}_\xi \left[\sum_{n=1}^N F(x, \xi_n) \right] \xrightarrow{LLN} \frac{1}{N} (N f(x)) = f(x). \quad \square$$

²LLN: $\lim_{N \rightarrow \infty} \mathbb{E} \left[\frac{\sum_{n=1}^N X_n}{N} \right] = \frac{N\bar{X}}{N} = \bar{X}$ for i.i.d. random variable X_n with mean value \bar{X} .

How SAA works

Calculating lower bounds for z

We now show that $\mathbb{E} [\hat{z}_N]$ is a **lower bound** on z :

$$\hat{z}_N = \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \leq \frac{1}{N} \sum_{n=1}^N F(x, \xi_n)$$

How SAA works

Calculating lower bounds for z

We now show that $\mathbb{E}[\hat{z}_N]$ is a **lower bound** on z :

$$\begin{aligned}\hat{z}_N &= \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \leq \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \\ \mathbb{E}_\xi \left[\min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \right] &\leq \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right]\end{aligned}$$

How SAA works

Calculating lower bounds for z

We now show that $\mathbb{E} [\hat{z}_N]$ is a **lower bound** on z :

$$\begin{aligned}\hat{z}_N &= \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \leq \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \\ \mathbb{E}_\xi \left[\min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \right] &\leq \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right] \\ \mathbb{E}_\xi [\hat{z}_N] &\leq \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right]\end{aligned}$$

How SAA works

Calculating lower bounds for z

We now show that $\mathbb{E} [\hat{z}_N]$ is a **lower bound** on z :

$$\begin{aligned}\hat{z}_N &= \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \leq \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \\ \mathbb{E}_\xi \left[\min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\} \right] &\leq \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right] \\ \mathbb{E}_\xi [\hat{z}_N] &\leq \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right] \\ \mathbb{E}_\xi [\hat{z}_N] &\leq \min_x \left\{ \mathbb{E}_\xi \left[\frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right] \right\} \xrightarrow{N \rightarrow \infty} \\ &\quad \min_x \{ \mathbb{E}_\xi [F(x, \xi)] \} = \min_x f(x) = z. \quad \square\end{aligned}$$

How SAA works

Calculating lower bounds for z

In turn, we can approximate $\mathbb{E}[\hat{z}_N]$ using a sample estimate.

1. For that, we sample M scenario trees of size N :

$$\{\xi_1^1, \dots, \xi_N^1\}, \dots, \{\xi_1^M, \dots, \xi_N^M\}.$$

³Again an unbiased estimator, see footnote 2.

How SAA works

Calculating lower bounds for z

In turn, we can approximate $\mathbb{E}[\hat{z}_N]$ using a sample estimate.

1. For that, we sample M scenario trees of size N :

$$\{\xi_1^1, \dots, \xi_N^1\}, \dots, \{\xi_1^M, \dots, \xi_N^M\}.$$

2. For each scenario tree, we solve

$$\hat{z}_N^m = \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n^m) \right\}.$$

³Again an unbiased estimator, see footnote 2.

How SAA works

Calculating lower bounds for z

In turn, we can approximate $\mathbb{E}[\hat{z}_N]$ using a sample estimate.

1. For that, we sample M scenario trees of size N :

$$\{\xi_1^1, \dots, \xi_N^1\}, \dots, \{\xi_1^M, \dots, \xi_N^M\}.$$

2. For each scenario tree, we solve

$$\hat{z}_N^m = \min_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n^m) \right\}.$$

3. We can then estimate³ $\mathbb{E}[\hat{z}_N]$ as

$$L_N^M = \frac{1}{M} \sum_{m=1}^M \hat{z}_N^m.$$

³Again an unbiased estimator, see footnote 2.

How SAA works

Statistical bounds for L_N^M

We can use the CLT to provide **confidence intervals** for L_N^M . A sample-estimate for $\sigma_{L_N^M}^2$ can be obtained as

$$s_{L_N^M}^2 = \frac{1}{M-1} \sum_{m=1}^M (\hat{z}_N^m - L_N^M)^2.$$

How SAA works

Statistical bounds for L_N^M

We can use the CLT to provide **confidence intervals** for L_N^M . A sample-estimate for $\sigma_{L_N^M}^2$ can be obtained as

$$s_{L_N^M}^2 = \frac{1}{M-1} \sum_{m=1}^M (\hat{z}_N^m - L_N^M)^2.$$

We can use $s_{L_N^M}^2$ to obtain an **$1-\alpha$ confidence interval** for L_N^M :

$$\left[L_N^M - \frac{z_{\alpha/2} s_{L_N^M}}{\sqrt{M}}, L_N^M + \frac{z_{\alpha/2} s_{L_N^M}}{\sqrt{M}} \right],$$

where $z_{\alpha/2}$ is the standard normal $1 - \alpha/2$ quantile.

How SAA works

Calculating upper bounds for z

Let

$$\hat{x}_N^m = \operatorname{argmin}_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n^m) \right\}, \quad \forall m \in [M].$$

Under a relatively complete recourse assumption, we have that $f(\hat{x}_N^m) \geq z, \forall m \in [M]$.

How SAA works

Calculating upper bounds for z

Let

$$\hat{x}_N^m = \underset{x}{\operatorname{argmin}} \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n^m) \right\}, \quad \forall m \in [M].$$

Under a relatively complete recourse assumption, we have that $f(\hat{x}_N^m) \geq z$, $\forall m \in [M]$.

We can obtain an unbiased estimate for $f(\hat{x}_N^m)$ by

1. Choosing one solution $\hat{x}_N^{m'}$, $m' \in [M]$;
2. Sampling T scenario trees of size \bar{N}

$$\{\xi_1^1, \dots, \xi_{\bar{N}}^1\}, \dots, \{\xi_1^T, \dots, \xi_{\bar{N}}^T\}$$

3. For each scenario tree t , we evaluate

$$\check{z}_{\bar{N}}^t = \frac{1}{\bar{N}} \sum_{n=1}^{\bar{N}} F(\hat{x}_N^{m'}, \xi_n^t)$$

How SAA works

Calculating upper bounds for z

4. We can estimate $f(\hat{x}_N^m)$ as

$$U_N^T = \frac{1}{T} \sum_{t=1}^T \tilde{z}_N^t.$$

Analogously, we can use the sample-estimate for $\sigma_{U_N^T}^2$

$$s_{U_N^T}^2 = \frac{1}{T-1} \sum_{t=1}^T (\tilde{z}_N^t - U_N^T)^2$$

to calculate the **1- α confidence interval** for U_N^T as

$$\left[U_N^T - \frac{z_{\alpha/2} s_{U_N^T}}{\sqrt{T}}, U_N^T + \frac{z_{\alpha/2} s_{U_N^T}}{\sqrt{T}} \right].$$

On estimating optimality gaps

In this context, an **optimality gap** refers to the quantity

$$f(\hat{x}_N^{m'}) - z.$$

On estimating optimality gaps

In this context, an **optimality gap** refers to the quantity

$$f(\hat{x}_N^{m'}) - z.$$

On the other hand, we know that

$$\mathbb{E}[\hat{z}_N] \leq z \leq f(\hat{x}_N^{m'}).$$

Since we have estimates for $\mathbb{E}[\hat{z}_N]$ (L_N^M) and $f(\hat{x}_N^{m'})$ (U_N^T), we can calculate the **optimality gap** estimate

$$gap(N, M, \overline{N}, T) = U_N^T - L_N^M.$$

On estimating optimality gaps

In this context, an **optimality gap** refers to the quantity

$$f(\hat{x}_N^{m'}) - z.$$

On the other hand, we know that

$$\mathbb{E}[\hat{z}_N] \leq z \leq f(\hat{x}_N^{m'}).$$

Since we have estimates for $\mathbb{E}[\hat{z}_N]$ (L_N^M) and $f(\hat{x}_N^{m'})$ (U_N^T), we can calculate the **optimality gap** estimate

$$gap(N, M, \bar{N}, T) = U_N^T - L_N^M.$$

Confidence intervals can also be obtained for $gap(N, M, \bar{N}, T)$ using

$$\sigma_{gap(N, M, \bar{N}, T)}^2 = s_{L_N^M}^2 + s_{U_N^T}^2.$$

On estimating optimality gaps

Some remarks on $gap(N, M, \overline{N}, T)$:

- ▶ $gap(N, M, \overline{N}, T)$ is a **biased** estimator, since

$$f(\hat{x}_N^{m'}) - \mathbb{E}[\hat{z}_N] \geq f(\hat{x}_N^{m'}) - z;$$

On estimating optimality gaps

Some remarks on $\text{gap}(N, M, \overline{N}, T)$:

- ▶ $\text{gap}(N, M, \overline{N}, T)$ is a **biased** estimator, since

$$f(\hat{x}_N^{m'}) - \mathbb{E}[\hat{z}_N] \geq f(\hat{x}_N^{m'}) - z;$$

- ▶ As it overestimates $f(\hat{x}_N^{m'}) - z$, it is still useful in practice;

On estimating optimality gaps

Some remarks on $\text{gap}(N, M, \overline{N}, T)$:

- ▶ $\text{gap}(N, M, \overline{N}, T)$ is a **biased** estimator, since

$$f(\hat{x}_N^{m'}) - \mathbb{E}[\hat{z}_N] \geq f(\hat{x}_N^{m'}) - z;$$

- ▶ As it overestimates $f(\hat{x}_N^{m'}) - z$, it is still useful in practice;
- ▶ Confidence intervals for $\text{gap}(N, M, \overline{N}, T)$ can be **improved** by reducing:

On estimating optimality gaps

Some remarks on $gap(N, M, \overline{N}, T)$:

- ▶ $gap(N, M, \overline{N}, T)$ is a **biased** estimator, since

$$f(\hat{x}_N^{m'}) - \mathbb{E}[\hat{z}_N] \geq f(\hat{x}_N^{m'}) - z;$$

- ▶ As it overestimates $f(\hat{x}_N^{m'}) - z$, it is still useful in practice;
- ▶ Confidence intervals for $gap(N, M, \overline{N}, T)$ can be **improved** by reducing:
 1. $s_{L_N^M}^2$, via increasing N and M : larger N leads to larger problems, but they can be solved as M **parallel** problems;

On estimating optimality gaps

Some remarks on $gap(N, M, \overline{N}, T)$:

- ▶ $gap(N, M, \overline{N}, T)$ is a **biased** estimator, since

$$f(\hat{x}_N^{m'}) - \mathbb{E}[\hat{z}_N] \geq f(\hat{x}_N^{m'}) - z;$$

- ▶ As it overestimates $f(\hat{x}_N^{m'}) - z$, it is still useful in practice;
- ▶ Confidence intervals for $gap(N, M, \overline{N}, T)$ can be **improved** by reducing:
 1. $s_{L_N^M}^2$, via increasing N and M : larger N leads to larger problems, but they can be solved as M **parallel** problems;
 2. $s_{U_N^T}^2$, via increasing \overline{N} and T ; larger \overline{N} leads to more costly evaluation; solvable as T (as $\overline{N} \times T$ for 2SSPs) parallel problems.

Final practical remarks

Regarding choosing a solution $\hat{x}_N^{m'}$:

- ▶ If feasible, evaluate all distinct solutions \hat{x}_N^m for $m \in [M]$ and choose that with **best** L_N^M , U_N^T or $gap(N, M, \bar{N}, T)$;

Final practical remarks

Regarding choosing a solution $\hat{x}_N^{m'}$:

- ▶ If feasible, evaluate all distinct solutions \hat{x}_N^m for $m \in [M]$ and choose that with **best** L_N^M , U_N^T or $gap(N, M, \bar{N}, T)$;
- ▶ Too many **distinct** solutions may indicate that N is too **small**.
Perform stability analysis.

Final practical remarks

Regarding choosing a solution $\hat{x}_N^{m'}$:

- ▶ If feasible, evaluate all distinct solutions \hat{x}_N^m for $m \in [M]$ and choose that with **best** L_N^M , U_N^T or $gap(N, M, \bar{N}, T)$;
- ▶ Too many **distinct** solutions may indicate that N is too **small**.
Perform stability analysis.
- ▶ SAA holds for **non-independent** sampling schemes (e.g., Latin hypercube sampling or quasi Monte Carlo). These help keep N small.

Final practical remarks

Regarding choosing a solution $\hat{x}_N^{m'}$:

- ▶ If feasible, evaluate all distinct solutions \hat{x}_N^m for $m \in [M]$ and choose that with **best** L_N^M , U_N^T or $gap(N, M, \bar{N}, T)$;
- ▶ Too many **distinct** solutions may indicate that N is too **small**. Perform stability analysis.
- ▶ SAA holds for **non-independent** sampling schemes (e.g., Latin hypercube sampling or quasi Monte Carlo). These help keep N small.




Figure: Monte Carlo (top) and quasi-Monte Carlo sampling [Fernández Pérez et al., 2018]

Final practical remarks

Regarding the choice of N [Oliveira and Hamacher, 2012]:

- ▶ Notice that \hat{z}_N is the expected value of the random variable

$$z_N(\xi) = F(\hat{x}_N, \xi), \text{ where } \hat{x}_N = \operatorname{argmin}_x \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\}$$

Final practical remarks

Regarding the choice of N [Oliveira and Hamacher, 2012]:

- ▶ Notice that \hat{z}_N is the expected value of the **random variable**

$$z_N(\xi) = F(\hat{x}_N, \xi), \text{ where } \hat{x}_N = \underset{x}{\operatorname{argmin}} \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\}$$

- ▶ As such, we can estimate its sample-based variance and a $1 - \alpha$ confidence interval, given by

$$s_N^2 = \frac{1}{N-1} \sum_{n=1}^N (\hat{z}_N - z_N(\xi_n))^2 \text{ and } \hat{z}_N \pm \frac{z_{\alpha/2} s_N}{\sqrt{N}}.$$

Final practical remarks

Regarding the choice of N [Oliveira and Hamacher, 2012]:

- ▶ Notice that \hat{z}_N is the expected value of the **random variable**

$$z_N(\xi) = F(\hat{x}_N, \xi), \text{ where } \hat{x}_N = \underset{x}{\operatorname{argmin}} \left\{ \frac{1}{N} \sum_{n=1}^N F(x, \xi_n) \right\}$$

- ▶ As such, we can estimate its sample-based variance and a $1 - \alpha$ confidence interval, given by




$$s_N^2 = \frac{1}{N-1} \sum_{n=1}^N (\hat{z}_N - z_N(\xi_n))^2 \text{ and } \hat{z}_N \pm \frac{z_{\alpha/2} s_N}{\sqrt{N}}.$$

- ▶ If we predefine a desired **relative width** β for the confidence interval, we can infer that





$$N \geq \left(\frac{z_{\alpha/2} s_N}{(\beta/2) \hat{z}_N} \right)^2.$$

SAA example





References I

-  Condeixa, L., Oliveira, F., and Siddiqui, A. S. (2020).
Wasserstein-distance-based temporal clustering for capacity-expansion planning in power systems.
In 2020 International Conference on Smart Energy Systems and Technologies (SEST), pages 1–6. IEEE.
-  Dillon, M., Oliveira, F., and Abbasi, B. (2017).
A two-stage stochastic programming model for inventory management in the blood supply chain.
International Journal of Production Economics, 187:27–41.
-  Dupačová, J., Gröwe-Kuska, N., and Römisch, W. (2003).
Scenario reduction in stochastic programming.
Mathematical programming, 95:493–511.





References II

-  Fernández Pérez, M. A., Oliveira, F., and Hamacher, S. (2018).
Optimizing workover rig fleet sizing and scheduling using deterministic and stochastic programming models.
Industrial & engineering chemistry research, 57(22):7544–7554.
-  Heitsch, H. and Römisch, W. (2003).
Scenario reduction algorithms in stochastic programming.
Computational optimization and applications, 24:187–206.
-  Heitsch, H. and Römisch, W. (2007).
A note on scenario reduction for two-stage stochastic programs.
Operations Research Letters, 35(6):731–738.
-  Heitsch, H. and Römisch, W. (2009).
Scenario tree modeling for multistage stochastic programs.
Mathematical Programming, 118:371–406.

References III

-  Høyland, K., Kaut, M., and Wallace, S. W. (2003).
A heuristic for moment-matching scenario generation.
Computational optimization and applications, 24:169–185.
-  Høyland, K. and Wallace, S. W. (2001).
Generating scenario trees for multistage decision problems.
Management science, 47(2):295–307.
-  Kaut, M. (2021).
Scenario generation by selection from historical data.
Computational Management Science, 18(3):411–429.
-  Oliveira, F. and Hamacher, S. (2012).
Optimization of the petroleum product supply chain under uncertainty: A case study in northern brazil.
Industrial & Engineering Chemistry Research, 51(11):4279–4287.

References IV

-  Oliveira, F., Nunes, P. M., Blajberg, R., and Hamacher, S. (2016).
A framework for crude oil scheduling in an integrated terminal-refinery system under supply uncertainty.
European Journal of Operational Research, 252(2):635–645.
-  Pflug, G. C. (2001).
Scenario tree generation for multiperiod financial optimization by optimal discretization.
Mathematical programming, 89:251–271.
-  Römisch, W. (2003).
Stability of stochastic programming problems.
Handbooks in operations research and management science, 10:483–554.
-  Shapiro, A. and Homem-de Mello, T. (1998).
A simulation-based approach to two-stage stochastic programming with recourse.
Mathematical Programming, 81(3):301–325.