Put an agent inside your app.

Use Droid's agent harness from TypeScript. Bring the conversation, tools, and approval flow into the product you're building.

USE EXEC

Delegate a task from a script.

A natural fit for shell scripts and CI.

USE THE SDK

Make Droid part of your application.

Integrate sessions, functions, and your UI.

01 An agent inside your app

Stream a study-buddy response, ask a follow-up, or stop the run.

BUILD WITH: sessions + streaming + cancellation

02 An agent that uses your tools

Plan an afternoon using a local activity dataset. Swap in your own data.

BUILD WITH: TypeScript functions exposed as MCP tools

03 An agent that asks before acting

Answer a team-size question, then approve or deny a simulated booking.

BUILD WITH: AskUser + permission handlers

RUN THE STARTER

Open the supplied starter folder in your terminal:

```
npm ci
export FACTORY_API_KEY="your-own-key"
npm run hackathon
```

Open http://127.0.0.1:8421 · Node 20+ and Droid CLI required.
Live runs use Factory credits. Keep your API key on the server.

COMPETE AT CAL HACKS 13.0

Best Use of the Factory Droid SDK

Build meaningful TypeScript or Python SDK use into your running product, not just your coding workflow. Explain where and how in your README.

$2,000 cash + Factory credits + swag. Prizes subject to change.

Scan for the SDK guide

docs.factory.com/sdk/typescript

No Wi-Fi? Once dependencies are installed, run:
npm run hackathon:offline

Offline mode is a scripted walkthrough, not a live agent.

All activity data and bookings are fictional. This starter is a local, single-user teaching app, not a production deployment template.