Put an agent inside your app.

Use Droid’s agent harness from TypeScript. Bring the conversation, tools, and approval flow into the product you’re building.

USE EXEC

Delegate a task from a script.

A natural fit for shell scripts and CI.

USE THE SDK

Make Droid part of your application.

Integrate sessions, functions, and your UI.

01 An agent inside your app

Stream a study-buddy response, ask a follow-up, or stop the run.

BUILD WITH: sessions + streaming + cancellation

02 An agent that uses your tools

Plan an afternoon using a local activity dataset. Swap in your own data.

BUILD WITH: TypeScript functions exposed as MCP tools

03 An agent that asks before acting

Answer a team-size question, then approve or deny a simulated booking.

BUILD WITH: AskUser + permission handlers

RUN THE STARTER

Open the supplied starter folder in your terminal:

```
npm ci
export FACTORY_API_KEY="your-own-key"
npm run hackathon
```

Open http://127.0.0.1:8421 · Node 20+ and Droid CLI required.
Live runs use Factory credits. Keep your API key on the server.

Scan for the SDK guide

docs.factory.com/sdk/typescript

No Wi-Fi? Once dependencies are installed, run:
npm run hackathon:offline

Offline mode is a scripted walkthrough, not a live agent.

All activity data and bookings are fictional. This starter is a local, single-user teaching app, not a production deployment template.