A Universal Test-Scenario Roadmap for Open Research

Abstract

Open research often evaluates whether a proposed method, model, or system "works," but it does not always document whether the testing roadmap itself was adequate. A project may pass some tests and fail others, yet contributors may incorrectly conclude that the underlying idea has failed when the roadmap was incomplete, the metrics were inappropriate, or the system was tested outside its intended operating range. This paper proposes a **Universal Test-Scenario Roadmap (UTSR)**: a shared structure for documenting feasibility gates, test scenarios, regression models, recovery tests, and decision rules before results are interpreted. The framework is domain-neutral. It can be applied to biology, engineering, software, materials science, climate modeling, agriculture, robotics, or social-systems research. Its purpose is not to replace domain expertise; it is to make the rules of engagement visible so that open contributors can distinguish between **"the idea failed," "the test failed," "the metric was wrong,"** and **"the roadmap was incomplete."**

1. Introduction

Scientific testing usually begins with a hypothesis, a measurable outcome, and a comparison against a control or baseline. A useful test must be capable of producing evidence that could contradict the hypothesis; otherwise, it cannot meaningfully support the claim being made. In open research, however, many projects are distributed across contributors, instruments, datasets, and skill levels. A contributor may test one scenario, obtain a negative result, and conclude that the broader concept is invalid—even if the test did not measure the relevant mechanism, used the wrong operating range, or lacked the conditions required for the claim to be meaningful.

This problem is especially important when a project has multiple stages. Early-stage tests may establish whether a concept is physically or logically possible. Later-stage tests may determine whether it is practical, repeatable, efficient, safe, or scalable. If these stages are not separated, a late-stage failure can be mistaken for an early-stage impossibility. Conversely, an early success can be mistaken for proof that a system will work at scale.

The proposed solution is a **Universal Test-Scenario Roadmap**. It separates research testing into four layers:

1. **Feasibility gates:** conditions that must be true before a concept can proceed.

2. **Scenario tests:** controlled experiments that examine how the system behaves under defined conditions.
3. **Modeling and regression phases:** methods for relating inputs to outputs and identifying safe operating regions.
4. **Completion and decision rules:** criteria for accepting, revising, quarantining, or rejecting a proposed pathway.

The framework is designed for open contribution. Contributors can add scenarios, reproduce tests, report failures, and propose improvements, while the roadmap records what was tested, what was not tested, and what conclusions are justified.

2. Core Principle: Separate Possibility, Performance, and Scale

A central rule of the roadmap is that a test result must be interpreted according to the stage at which it was performed.

Question	Test type	Valid conclusion
Can this occur at all under defined conditions?	Feasibility gate	“Possible,” “not observed,” or “not demonstrated”
Does it perform better than a baseline?	Comparative test	“Improves,” “does not improve,” or “inconclusive”
Does the effect depend on specific conditions?	Factor or regression test	“Conditional,” “robust,” or “context-dependent”
Can it survive stress, variation, or failure?	Robustness test	“Resilient,” “limited,” or “unsafe outside range”
Can it be repeated by others?	Replication test	“Reproducible,” “partially reproducible,” or “not reproducible”
Can it operate at higher volume or scale?	Scale test	“Scales,” “degrades,” or “requires redesign”

This separation prevents a common open-research error: treating a failed optimization test as proof that a concept is impossible. For example, a biological process may fail at high nutrient concentration but succeed at a lower concentration. A software method may fail under high request volume but work reliably at low volume. A material may fail under thermal shock but remain stable under gradual heating. In each case, the result is meaningful only when the test stage, operating range, and decision rule are documented.

3. Universal Test Scenarios

The following four scenarios are proposed as reusable test patterns. They are not tied to one discipline. Each scenario defines a controlled perturbation, an expected observation, a failure condition, and a decision rule.

Scenario 1: Feasibility Gate Test

Purpose: Determine whether a proposed mechanism, pathway, or system can produce the required outcome under minimal, well-controlled conditions.

Universal structure:

Defined input→Controlled environment→Required observable→Pass/Fail gate\text{Defined input} \rightarrow \text{Controlled environment} \rightarrow \text{Required observable} \rightarrow \text{Pass/Fail gate}Defined input→Controlled environment→Required observable→Pass/Fail gate

Procedure:

1. Define the minimum conditions required for the claim to be meaningful.
2. Establish a negative control, positive control, or reference baseline where possible.
3. Apply the smallest input sufficient to test the proposed mechanism.
4. Measure a predefined observable outcome.
5. Record whether the outcome occurs, does not occur, or is ambiguous.

Example domains:

- **Biology:** Test whether a tissue explant produces callus under a defined medium and light condition.
- **Chemistry:** Test whether a catalyst produces the target product under a defined temperature and reagent ratio.
- **Software:** Test whether a proposed algorithm produces a valid output on a minimal benchmark case.
- **Materials science:** Test whether a material forms the intended phase under a defined thermal profile.
- **Agriculture:** Test whether a crop variety germinates under a defined moisture and temperature range.

Decision rule:
A failure at this stage does **not** prove that the broader concept is impossible. It proves only that the proposed mechanism did not produce the required observable under the tested conditions. The result should be classified as **not demonstrated**, **inconclusive**, or **failed under stated conditions**.

Scenario 2: Bounded Perturbation and Recovery Test

Purpose: Determine whether a system can absorb a controlled disturbance and return to an acceptable state.

Universal structure:

Baseline→Bounded pulse→Observe transient→Verify recovery→Adjust bound\text{Baseline} \rightarrow \text{Bounded pulse} \rightarrow \text{Observe transient} \rightarrow \text{Verify recovery} \rightarrow \text{Adjust bound}Baseline→Bounded pulse→Observe transient→Verify recovery→Adjust bound

Procedure:

1. Establish a stable baseline.
2. Apply one small, reversible perturbation.
3. Measure peak deviation, time to peak, recovery time, and residual error.
4. Require recovery within predefined limits before increasing the perturbation.
5. Increase the perturbation only after successful recovery.

Example domains:

- **Bioprocessing:** Apply a substrate pulse and measure dissolved oxygen recovery.
- **Thermal systems:** Apply a small temperature step and measure stabilization time.
- **Software:** Increase request volume briefly and measure latency and error recovery.
- **Power systems:** Apply a controlled load change and measure voltage or frequency recovery.
- **Plant chambers:** Increase nutrient delivery briefly and measure pH, conductivity, or growth response.

Decision rule:
If the system recovers within limits, record the tested bound as validated. If it does not recover, retain the last stable operating level and classify the higher level as **restricted**, **conditional**, or **not validated**.

Scenario 3: Factor-Screening and Interaction Test

Purpose: Determine which variables materially affect the outcome and whether variables interact.

Universal structure:

Candidate factors→Factorial or screening design→Main effects and interactions→Priority factors\text{Candidate factors} \rightarrow \text{Factorial or screening design} \rightarrow

\text{Main effects and interactions} \rightarrow \text{Priority factors}Candidate factors→Factorial or screening design→Main effects and interactions→Priority factors

Procedure:

1. Identify candidate input variables.
2. Define low and high levels for each variable.
3. Use a full or fractional factorial design to test combinations.
4. Measure the response for each combination.
5. Identify main effects, interactions, and variables with negligible effect.

Factorial designs vary more than one factor at a time, allowing researchers to estimate both main effects and interactions. Screening designs are commonly used to reduce a large set of candidate variables to the smaller set that most affects the response.dote.osd+2

Example domains:

- **Biology:** Test medium composition, light spectrum, temperature, and inoculation density.
- **Chemistry:** Test catalyst loading, reagent ratio, temperature, and reaction time.
- **Manufacturing:** Test pressure, temperature, material composition, and processing time.
- **Machine learning:** Test training-data size, learning rate, model architecture, and preprocessing method.
- **Agriculture:** Test irrigation level, fertilizer ratio, planting density, and light exposure.

Decision rule:
A variable that does not affect the response in the tested range should be recorded as **low-impact within this range**, not universally irrelevant. A variable that affects the outcome only in combination with another variable should be recorded as an **interaction-dependent factor**.

Scenario 4: Regression and Response-Surface Test

Purpose: Map how one or more important variables affect the outcome, identify curvature, and locate a safe operating region.

Universal structure:

Important factors→Designed levels→Regression model→Predicted response→Validation run\text{Important factors} \rightarrow \text{Designed levels} \rightarrow \text{Regression model} \rightarrow \text{Predicted response} \rightarrow \text{Validation run}Important factors→Designed levels→Regression model→Predicted response→Validation run

A common response-surface model is:

Y=β0+β1X1+β2X2+β12X1X2+β11X12+β22X22Y = \beta_0 + \beta_1X_1 + \beta_2X_2 + \beta_{12}X_1X_2 + \beta_{11}X_1^2 + \beta_{22}X_2^2Y=β0+β1X1+β2X2+β12X1X2+β11X12+β22X22

where YYY is the measured response, X1X_1X1 and X2X_2X2 are important input variables, and the coefficients describe linear effects, interactions, and curvature.

Procedure:

1. Select the most important factors from screening.
2. Choose a response-surface design, such as a central composite design or Box-Behnken design.
3. Run the designed experiments.
4. Fit a regression model.
5. Check model fit, residuals, and lack of fit.
6. Predict an improved or safe operating point.
7. Run a confirmation experiment.

Response-surface methodology is widely used to model relationships between operating variables and outcomes, including curvature and interactions that cannot be captured by simple one-factor-at-a-time testing. Common designs include factorial, central composite, and Box-Behnken designs.pmc.ncbi.nlm.nih+4

Example domains:

- **Bioprocessing:** Map feed rate, temperature, and pH against biomass or product yield.
- **Chemistry:** Map catalyst loading, temperature, and reagent ratio against yield.
- **Materials science:** Map curing temperature, pressure, and composition against strength.
- **Software:** Map concurrency, batch size, and cache size against latency and error rate.
- **Agriculture:** Map irrigation, fertilizer, and planting density against yield.

Decision rule:
A regression model may identify a promising region, but it does not validate the region by itself. A predicted optimum must be confirmed with new experimental runs before it is accepted as a validated operating point.pmc.ncbi.nlm.nih+1

4. Regression Phases for Volume or Throughput

Many open-research projects fail during scale-up because they treat volume, load, or throughput as a single binary transition: either the system works at the original scale or it fails at the larger scale. A more grounded approach is to treat volume as a **progressive, evidence-gated variable**.

Phase 1: Baseline Validation

Establish the lowest validated operating point.

- Record baseline volume, throughput, load, and environmental conditions.
- Measure normal variation across repeated runs.
- Define acceptable recovery time, maximum deviation, and maximum cumulative load.
- Confirm that the system is stable before testing higher levels.

Phase 2: Bounded Pulse Calibration

Apply a small, reversible increase in volume or load.

- Increase volume by a predefined small percentage.
- Measure peak deviation, time to peak, recovery time, and residual error.
- Return to baseline before the next test.
- Do not advance if recovery is incomplete or unsafe.

This follows the logic of pulse-feeding studies, where a bounded substrate pulse is used to observe whether the system can absorb the added load without entering an undesirable state.

Phase 3: Stepwise Ascent

Increase volume in small steps.

- Use a fixed-percentage or predefined progression.
- Hold each level long enough to observe both transient and steady-state behavior.
- Require repeated success before advancing.
- Retain the last stable level if the next level fails.

Stepwise feeding has been used in bioprocessing to allow a biological system to adapt between feed increases, rather than forcing an abrupt transition to a higher load. Pilot-scale fed-batch work has also used controlled feed-rate progression while monitoring dissolved oxygen to avoid oxygen limitation.

Phase 4: Regression Fitting

At each validated level, update a regression model relating volume to response.

R(V)=β0+β1V+β2V2R(V) = \beta_0 + \beta_1V + \beta_2V^2R(V)=β0+β1V+β2V2

The model may predict peak deviation, recovery time, throughput, quality, energy use, or failure probability. It should include uncertainty estimates and should not be used outside the tested range.

Response-surface methodology combines experimental design, regression analysis, and optimization to model the relationship between input factors and responses. Screening designs identify important factors; response-surface designs then estimate interactions and curvature among those factors.itl.nist+3

Phase 5: Constraint Mapping

Translate the regression model into operating zones.

Zone	Interpretation	Action
Approved	Response remains within validated limits	Permit normal operation
Caution	Response is acceptable but approaching a boundary	Reduce step size and increase monitoring
Restricted	Predicted or observed response violates a limit	Stop ascent or return to last stable level
Unvalidated	Beyond tested range	Do not claim scalability

Phase 6: Validation and Lock-In

Before accepting a higher-volume setpoint, run repeated validation tests.

- Confirm that observed results fall within the regression model's prediction interval.
- Confirm that no safety, recovery, or cumulative-load limit is violated.
- Record the validated level, uncertainty, and conditions under which it was tested.
- Treat the new level as a baseline only after successful validation.

This prevents a common roadmap failure: claiming scalability from a single successful high-load run.

5. Feasibility Gates: What Must Be True First

The first phase of any roadmap should contain only **minimum necessary conditions**. These are not performance targets; they are conditions without which later tests cannot be meaningfully interpreted.

Examples of feasibility gates:

- The measurement instrument is calibrated and functioning.
- The baseline is stable within a defined range.
- The input can be applied in a controlled and reversible manner.
- The outcome can be observed with sufficient resolution.
- Safety limits are defined before testing begins.
- The experiment includes a control, reference, or known comparison.
- The data can be recorded with time, conditions, operator or system identity, and version information.
- The test can be repeated or independently reproduced.

If a feasibility gate fails, the correct response is not “the idea failed.” The correct response is:

- Repair the instrument.
- Redefine the metric.
- Stabilize the baseline.
- Reduce the perturbation.
- Change the operating range.
- Redesign the test.
- Quarantine the result as inconclusive.

This distinction is essential for open research. A failed test should contribute to the roadmap by identifying a missing precondition, not by silently invalidating the entire project.

6. Rules of Engagement for Open Research

To make contributions comparable, each test should be documented using a common record structure.

Minimum Test Record

Field	Required content
Claim under test	The specific hypothesis or capability being evaluated
Test stage	Feasibility, comparative, robustness, regression, scale, or replication
Input variables	What was changed, by how much, and in what units
Controlled variables	What was held constant
Baseline	The reference condition used for comparison
Response variables	What was measured and how

Pass criteria	The predefined threshold for success
Failure criteria	The predefined condition for stopping or rejecting
Uncertainty	Measurement error, variability, confidence interval, or model uncertainty
Result	Pass, fail, inconclusive, conditional, or not demonstrated
Interpretation limit	What the result does and does not prove
Next action	Advance, repeat, revise, quarantine, or escalate

This record prevents a common problem: a contributor reports “it did not work” without stating whether the test measured the intended mechanism, whether the baseline was valid, or whether the operating range was appropriate.

7. Result Classification

Every test result should be assigned one of six categories.

Classification	Meaning	Appropriate next action
Validated	The predefined pass criteria were met under documented conditions	Advance, replicate, or expand cautiously
Conditional	The result holds only within a stated range or under specific conditions	Define boundaries and test adjacent conditions
Inconclusive	The test could not distinguish success from failure	Improve instrumentation, sample size, or design
Not demonstrated	The outcome did not occur under the tested conditions	Do not generalize beyond the tested range
Restricted	The system works only with reduced load, added safeguards, or modified conditions	Define limits and safeguards
Rejected for this pathway	The evidence supports abandoning the specific pathway under the tested assumptions	Document why and preserve the evidence

This classification prevents binary thinking. A result is not simply “working” or “not working”; it is a bounded statement about what was tested, under what conditions, and with what uncertainty.

8. Common Roadmap Failures

The roadmap should explicitly check for the following failure patterns.

Failure pattern	Problem	Roadmap correction
Stage confusion	A scale failure is treated as proof of impossibility	Separate feasibility, performance, and scale tests
Metric mismatch	The measured outcome does not represent the claimed mechanism	Define response variables before testing
Missing baseline	No valid reference condition exists	Require baseline validation before comparison
Uncontrolled variation	Multiple variables change at once without a design	Use factorial, fractional factorial, or controlled perturbation designs
Overfitting	A model fits existing data but does not predict new data	Require confirmation runs and holdout validation
Extrapolation	A model is used outside its tested range	Restrict predictions to the tested design space
Silent failure	A system appears to work but the measurement was invalid	Require sensor validation, controls, and data-quality checks
Survivorship bias	Only successful tests are reported	Require documentation of failed and inconclusive tests
Unclear stop condition	Contributors continue testing without a decision rule	Define pass, fail, hold, and escalation criteria in advance

9. Open-Research Contribution Model

The roadmap should be maintained as a living, versioned document. Contributors should be able to add:

- New test scenarios.
- New metrics.
- New failure modes.
- Replication results.
- Negative results.
- Revised feasibility gates.
- Improved regression models.

- Domain-specific safety constraints.
- Evidence that a proposed boundary is too conservative or too permissive.

Each contribution should include the minimum test record, the result classification, and an explicit statement of what the result does and does not prove.

A useful open-research rule is:

> **No result should be interpreted outside the stage, conditions, metrics, and uncertainty under which it was obtained.**

This rule allows open contributors to disagree productively. One contributor may show that a method works under one condition; another may show that it fails under another. Both results can be valid if the roadmap records the conditions and prevents inappropriate generalization.

10. Discussion

The proposed framework does not claim that every scientific question can be reduced to the same test. Domain knowledge remains essential. A biological experiment, a materials test, a software benchmark, and a field trial require different instruments, controls, safety rules, and statistical methods.

What can be universal is the **structure of the testing roadmap**:

1. Define what must be true before testing.
2. Apply controlled perturbations.
3. Measure predefined responses.
4. Separate transient response from steady-state behavior.
5. Fit models only within tested ranges.
6. Validate predictions with new runs.
7. Classify results with explicit uncertainty.
8. Preserve negative and inconclusive results.
9. Update the roadmap when a test reveals a missing condition.
10. Prevent conclusions from crossing stages without evidence.

This structure makes open research more useful because it turns isolated pass/fail results into a cumulative map of what is known, what is conditional, what is untested, and what requires redesign.

11. Conclusion

A research roadmap should not merely list experiments. It should define the conditions under which each experiment can produce a meaningful conclusion. The Universal Test-Scenario Roadmap proposed here separates feasibility, performance, robustness, regression, scale, and

replication into explicit stages. It uses bounded perturbation tests, factorial screening, response-surface modeling, and validation runs to prevent premature rejection of ideas and premature acceptance of untested claims.

The central contribution is a set of shared rules of engagement for open research:

- Define feasibility gates before performance testing.
- Use controlled scenarios rather than isolated pass/fail checks.
- Document every test's conditions, metrics, uncertainty, and interpretation limits.
- Use regression models only within validated ranges.
- Require confirmation before claiming an optimum or a scalable operating point.
- Preserve failed, conditional, and inconclusive results as part of the evidence base.
- Allow contributors to improve the roadmap itself.

By making the testing structure explicit, open-research projects can distinguish between a failed idea, a failed test, a failed metric, and an incomplete roadmap. That distinction is necessary for cumulative, reproducible, and trustworthy open science.

References

1. Hukerikar, S., & Engelmann, C. (2017). *Resilience Design Patterns: A Structured Approach to Resilience at Extreme Scale*.
2. Harrison, K. J. (2026). *Closed-Loop Controlled-Environment Platforms for Functional Isomorphism Verification*.
3. ExGenet: Integrating Design of Experiments and Response Surface Methodology. *PMC11159540*.pmc.ncbi.nlm.nih
4. NIST/SEMATECH e-Handbook of Statistical Methods, *Select an Experimental Design*.itl.nist
5. NIST/SEMATECH e-Handbook of Statistical Methods, *Response Surface Designs*.itl.nist
6. Design of Experiments, Analysis of Variance, and Response Surface Methodology. *PMC11726655*.pmc.ncbi.nlm.nih
7. Response Surface Methodology to Optimize the Extraction of Bioactive Compounds. *PMC10742715*.pmc.ncbi.nlm.nih
8. Dynamics in Bioprocess Development for *Pichia pastoris*. *PMC4601250*.
9. U.S. Department of Energy, *Development and Application of Advanced Process Control*.
10. Yokogawa, *Platform for Advanced Control and Estimation: Automatic Step Testing*.