

Assignment: Advanced set of SPARQL queries

① Get all the properties that can be applied to instances of the *Politician* class (`<http://dbpedia.org/ontology/Politician>`)

SPARQL Query Editor About Tables ▾

Conductor Facet Browser Personal link

Extensions: cxml save to dav sponge User: SPARQL

Default Data Set Name (Graph IRI)

Query Text

```
PREFIX dbo:<http://dbpedia.org/ontology/>
SELECT DISTINCT ?p
WHERE
{
  ?x a dbo:Politician.
  ?x ?p ?y.
}
```

Results Format

SPARQL | HTML5 table

p

<http://dbpedia.org/ontology/description>

<http://www.w3.org/1999/02/22-rdf-syntax-ns#type>

<http://www.w3.org/2002/07/owl#sameAs>

<http://xmlns.com/foaf/0.1/nick>

<http://xmlns.com/foaf/0.1/name>

<http://www.w3.org/2000/01/rdf-schema#label>

<http://dbpedia.org/property/honorificSuffix>

<http://dbpedia.org/property/loser>

<http://dbpedia.org/ontology/deathPlace>

<http://dbpedia.org/property/deathPlace>

<http://dbpedia.org/ontology/deathDate>

<http://dbpedia.org/ontology/birthPlace>

<http://dbpedia.org/property/birthPlace>

<http://dbpedia.org/ontology/birthDate>

<http://purl.org/dc/terms/subject>

<http://xmlns.com/foaf/0.1/homepage>

<http://dbpedia.org/property/name>

<http://xmlns.com/foaf/0.1/depiction>

② Get all the properties, except rdf type, that can be applied to instances of the Politician class

SPARQL Query Editor

AboutTables

ConductorFacet BrowserPermalink

Extensions: cxmlsave to davspongeUser: SPARQL

Default Data Set Name (Graph IRI)
http://dbpedia.org

Query Text
PREFIX dbo:<http://dbpedia.org/ontology/>
SELECT DISTINCT ?p
WHERE
{
 ?x a dbo:Politician.
 ?x ?p ?y.
 FILTER(?p != rdf:type)
}
ORDER BY ?p

Results Format
HTML

Execute QueryReset

SPARQL | HTML5 table (partial result: anytime timeout)

p
http://dbpedia.org/ontology/Person/height
http://dbpedia.org/ontology/Person/weight
http://dbpedia.org/ontology/PopulatedPlace/areaTotal
http://dbpedia.org/ontology/abbreviation
http://dbpedia.org/ontology/academicAdvisor
http://dbpedia.org/ontology/academicDiscipline
http://dbpedia.org/ontology/activeYearsEndDate
http://dbpedia.org/ontology/activeYearsEndYear
http://dbpedia.org/ontology/activeYearsStartDate
http://dbpedia.org/ontology/activeYearsStartYear
http://dbpedia.org/ontology/alias
http://dbpedia.org/ontology/allegiance
http://dbpedia.org/ontology/almaMater
http://dbpedia.org/ontology/appointer
http://dbpedia.org/ontology/areaCode
http://dbpedia.org/ontology/areaTotal
http://dbpedia.org/ontology/associate
http://dbpedia.org/ontology/award
http://dbpedia.org/ontology/awardDate

③ Which different values exist for the properties, except for rdf:type, applicable to the instances of Politician?

SPARQL Query Editor About Tables ▾

Conductor Facet Browser Permalink

Extensions: cxml save to dav sponge User: SPARQL

Default Data Set Name (Graph IRI)

Query Text

```
PREFIX dbo:<http://dbpedia.org/ontology/>
SELECT DISTINCT ?p ?y
WHERE
{
  ?x a dbo:Politician.
  ?x ?p ?y.
  FILTER(?p != rdf:type)
}
ORDER BY ?p
```

Results Format

SPARQL | HTML5 table

p	y
http://dbpedia.org/ontology/Person/height	"170.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"181.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"178.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"176.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"174.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"165.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"187.96"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"175.26"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"179.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"185.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"183.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"175.0"^^<http://dbpedia.org/datatype/centimetre>
http://dbpedia.org/ontology/Person/height	"167.0"^^<http://dbpedia.org/datatype/centimetre>

④ For each of these applicable properties, except for rdf type, which different values do they take globally all those instances?

SPARQL Query Editor
About
Tables
Conductor
Facet Browser
Permalink

Query Text

```

PREFIX dbo:<http://dbpedia.org/ontology/>
SELECT ?p (GROUP_CONCAT(DISTINCT STR(?y)) AS ?y2)
WHERE
{
  ?x a dbo:Politician.
  ?x ?p ?y.
  FILTER(?p != rdf:type).
}

```

Results Format
HTML

Execute Query
Reset

SPARQL | HTML5 table (partial result: anytime timeout)

p	y2
http://www.w3.org/2002/07/owl#sameAs	http://ar.dbpedia.org/resource/إدوارد إم. بيرنستاين http://ar.dbpedia.org/resou
http://dbpedia.org/property/birthPlace	,, Dutch East Indies, Nyasvzh District, Minsk Oblast, Byelorussian SSR, USSR1
http://dbpedia.org/ontology/birthName	Abdulkarim Sabo MuhammadAbdullahi Musa AshafaAbdulquawiy Abdulganiyu OlododoAb
http://dbpedia.org/ontology/country	http://dbpedia.org/resource/China http://dbpedia.org/resource/Germany http://dbp
http://dbpedia.org/ontology/thumbail	http://commons.wikimedia.org/wiki/Special:FilePath/1718282582550_20240611_IMAR
http://dbpedia.org/ontology/committee	* Budget and Appropriation Committee* Procedure and House Rules CommitteeAdmin
http://dbpedia.org/property/office	, Manitowoc, Marquette, Portage, Sheboygan & Winnebago counties--05-01--05-02- on Aberdeen City CouncilCouncillor of the City of BrisbaneCouncillor of the Ci
http://dbpedia.org/property/serviceyears	--12-1517921799183018631865187919241929193419431944194519481950195819671968197
http://dbpedia.org/property/stateHouse	AlabamaAlaskaArizonaColoradoFloridaGeorgiaHawaiiIdahoIowaKansasKentuckyLouisia
http://dbpedia.org/property/termEnd	----01-01--01-13--05-15--06-22--09-02101251157515921608-07-081616-07-261630163
http://dbpedia.org/property/governor	*M R Jois *Buta Singh *R.S. Gavai *R.L. BhatiaBill AnoatubbyLee CruceMurad IsmailRobert B. MeynerSaid Assagaffht

⑤ For each of these applicable properties, except for rdf type, how many distinct values do they take globally for all these instances?

SPARQL Query Editor About Tables ▾

Conductor Facet Browser Permalink

Query Text

```
PREFIX dbo:<http://dbpedia.org/ontology/>
SELECT ?p (COUNT (DISTINCT ?y) AS ?y2)
WHERE
{
  ?x a dbo:Politician.
  ?x ?p ?y.
  FILTER(?p != rdf:type).
}
```

Results Format

HTML ▾

Execute Query

Reset

SPARQL | HTML5 table (partial result: anytime timeout)

p	y2
http://www.w3.org/2002/07/owl#sameAs	656428
http://dbpedia.org/property/birthPlace	40730
http://dbpedia.org/ontology/birthName	21499
http://dbpedia.org/ontology/country	85
http://dbpedia.org/ontology/thumbnaill	54803
http://dbpedia.org/ontology/committee	541
http://dbpedia.org/property/office	57935
http://dbpedia.org/property/serviceyears	623
http://dbpedia.org/property/stateHouse	55
http://dbpedia.org/property/termEnd	32805
http://dbpedia.org/property/governor	2886
http://dbpedia.org/property/authorlink	25
http://xmlns.com/foaf/0.1/nick	986