

Laporan Vulnerability Assessment:

Scan DNS Server

```
[analyst@secOps ~]$ nmap -sV 192.168.56.20
Starting Nmap 7.80 ( https://nmap.org ) at 2026-06-02 02:56 UTC
Nmap scan report for 192.168.56.20
Host is up (0.00035s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.9p1 Ubuntu 3ubuntu0.15 (Ubuntu Linux; protocol 2.0)
53/tcp    open  domain   ISC BIND 9.18.39-0ubuntu0.22.04.3 (Ubuntu Linux)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 6.50 seconds
[analyst@secOps ~]$
```

Scan Victim

```
[analyst@secOps ~]$ nmap -sV 192.168.56.30
Starting Nmap 7.80 ( https://nmap.org ) at 2026-06-02 02:57 UTC
Nmap scan report for 192.168.56.30
Host is up (0.00036s latency).
Not shown: 997 closed ports
PORT      STATE SERVICE        VERSION
135/tcp    open  msrpc          Microsoft Windows RPC
139/tcp    open  netbios-ssn    Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds?
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.93 seconds
[analyst@secOps ~]$
```

Scan Keseluruhan Network

```
[analyst@secOps ~]$ nmap -sn 192.168.56.0/24
Starting Nmap 7.80 ( https://nmap.org ) at 2026-06-02 02:57 UTC
Nmap scan report for labvm (192.168.56.10)
Host is up (0.00015s latency).
Nmap scan report for 192.168.56.20
Host is up (0.00074s latency).
Nmap scan report for 192.168.56.30
Host is up (0.00066s latency).
Nmap scan report for labvm (192.168.56.99)
Host is up (0.0019s latency).
Nmap done: 256 IP addresses (4 hosts up) scanned in 2.35 seconds
[analyst@secOps ~]$
```

5 – Vulnerability Assessment

Berdasarkan hasil Nmap dari CyberOps (Attacker VM):

Temuan	Risiko	Penjelasan
Port 22 (SSH) terbuka pada DNS Server	Medium	Dapat menjadi target brute force jika password lemah
Port 53 (DNS/BIND9) terbuka	High	Dapat dieksploitasi untuk DNS Spoofing, Cache Poisoning, atau DNS Amplification
Port 135 (RPC) terbuka pada Windows Client	Medium	Dapat digunakan untuk enumerasi sistem Windows
Port 139 (NetBIOS) terbuka	Medium	Berpotensi membocorkan informasi jaringan
Port 445 (SMB) terbuka	High	Sering menjadi target malware dan lateral movement
Host Discovery berhasil menemukan 4 host aktif	low	Menunjukkan informasi topologi berhasil dipetakan attacker