

CSEN1002 Compilers Lab, Spring Term 2021
Task 5: CFG Left-Recursion Elimination

Due: Week starting 15.05.2021

1 Objective

For this task you will implement the context-free grammar (CFG) left-recursion elimination algorithm introduced in Lecture 3 of CSEN1003. Recall that a CFG is a quadruple (V, Σ, R, S) where V and Σ are disjoint alphabets (respectively, containing *variables* and *terminals*), $R \subseteq V \times (V \cup \Sigma)^*$ is a set of *rules*, and $S \in V$ is the *start variable*.

2 Requirements

- We make the following assumptions about input CFGs for simplicity.
 - a) The set V of variables consists of upper-case English symbols.
 - b) The start variable is the symbol S .
 - c) The set Σ of terminals consists of lower-case English symbols (except the letter **e**).
 - d) We only consider CFGs with no cycles and no ε -rules.
- You should implement a function **LRE** which takes an input string encoding a CFG and returns a string encoding an equivalent CFG which is not left-recursive.
- A string encoding a CFG is a semi-colon separated sequence of items. Each item represents a largest set of rules with the same left-hand side and is a comma-separated sequence of strings. The first string of each item is a member of V , representing the common left-hand side. The first string of the first item is S .
- For example, consider the CFG $(\{S, T, L\}, \{i, a, b, c, d\}, R, S)$, where R is given by the following productions.

$$\begin{aligned} S &\longrightarrow S c T \mid S a \mid T \mid b \\ T &\longrightarrow a S b \mid i a L b \mid i \\ L &\longrightarrow S d L \mid S \end{aligned}$$

This CFG will have the following string encoding.

S, ScT, Sa, T, b; T, aSb, iaLb, i; L, SdL, S

- The function **LRE** will assume the ordering of variables as they appear in the string encoding of the CFG. Thus, in the above example, the variables are ordered thus: S, T, L .

- LRE returns a string encoding the resulting CFG where a newly-introduced variable, for the elimination of immediate left-recursion for variable A , is the string A' . The letter e denotes the empty string. Newly added rules appear in the order indicated in Slides 33 and 34 of Lecture 3.
- Thus, for the above example, the output should be as follows (shown on two lines).

$$\begin{aligned} &S, TS', bS'; S', cTS', aS', e; T, aSb, iaLb, i; \\ &L, aSbS'dL, iaLbS'dL, iS'dL, bS'dL, aSbS', iaLbS', iS', bS' \end{aligned}$$

3 Evaluation

- Your implementation will be tested by running LRE on five CFGs.
- You get two points for each correct output of LRE; hence, a maximum of ten points.

4 Online Submission

- You should submit your code at the following link.

<https://forms.gle/6iP2wjJDMwU5tJ4G7>

- Submit one Java file (`.java`) containing executable code.
- The filename should be of form `<LabNo_ID_Name>`.
For example, `P13_40_1234_John_Smith.java`
- Online submission is due on Thursday, May 20th, by 23:59.