

"Improving Shareholder Value by Separating Verification from Design"

The semiconductor industry continues to strive to manage the ever increasing risk of leaving a corner case bug that becomes the next front page story for EETimes. With cost of failure test becoming a common agenda point in many semiconductor board room meetings around the world, how can you deliver to the ever growing demands of increasing shareholder value?

Managing scarce resources to deliver sustainable competitive advantage is the platform upon which most of today's strategic thinking is built. Yet in the complex world of semiconductor product design we continue to see the promotion of the "jack of all trades" designer in the false belief that it actually reduces costs.

Separating verification from design is a natural evolution to the necessary specialization that has become functional verification today. Why do accounting regulations demand that you employ armies of auditors to review your end of year accounts? When, not so many years ago, you could get away with your own accountants completing this function.

Auditors are much the same as verification engineers. They are approaching the problem from a completely different perspective. They do not come with the cognitive incompetence of "I know that's right, because I produced it!" The global company graveyard is littered with the tomb-stones of many household names that have made this mistake. Errors included.

In this presentation, Verity will deliver a solution to provide unique value that can be generated when you separate the concerns of functional verification from design. Reducing the cost of failure risks and significantly improving the effectiveness of your scarce engineering resource by automating the process of verification itself.

Presenter at ecdForum04, Dresden, Germany, December 8th/9th 2004:


Coby Henoch

Senior Vice President of Sales

Verity Design, Inc.

Kerstin Eder 1 University of Bristol November 12, 2013

Complete SN Verification Process



✿ The key is in the Verification Plan!

Kerstin Eder 5-1 University of Bristol November 12, 2013

On-line Help

All Specman and e language help is on-line:

- e language reference
- Command reference for Specman Elite
- User guide etc.

For sn and e help use `sn_help.sh` from command line.

- Make sure you change to "Tree View!"
 - Go to "Edit" menu.
 - Select "Settings".
 - Tick "Show Tree View on startup".

For IUS/ncsim help use `cdmsnhelp` from command line.

Kerstin Eder 8 University of Bristol November 12, 2013

Statements

Key statement types:

- **struct**: Defines a new data structure.
- (**unit**): Defines a new unit.)
- **type**: Defines an enumerated type or subtype.
- **extend**: Extends a previously defined struct or type.
- **define**: Extends language. ■ `define OFFSET 5;`
- **import**
- ... (more, see on line doc)

✿ Imports must be first (after defines).

Otherwise, order is not critical.

Kerstin Eder 12 University of Bristol November 12, 2013

High-level Verification

State-of-the-art Verification Methodology

Focus on **Automation** of the Verification Process

■ Tools: now from Cadence (who bought Verity in April 2005)

- Specman Elite (SN) and
- e verification language

✿ Raise level of abstraction and enhance productivity.


For local configuration info see Exercise 4: *Intro to Specman Tutorial*.

[Please work your way through the on-line Specman intro tutorial.]

[Credits: The material for this lecture is adapted from Verity training material.]

Kerstin Eder 2 University of Bristol November 12, 2013

Complete SN Verification Process



✿ The key is in the Verification Plan!

Coverage-driven stimulus generation!

Kerstin Eder 5-II University of Bristol November 12, 2013

File Format

- An e code segment is enclosed with a **begin-code marker** `<'` and an **end-code marker** `'>`.

- Both the begin-code marker and the end-code markers must be placed at the beginning of a line (left-most), with no other text on that same line.

■ e code segment:

```
<'
import cpu_test_env;
'>
```

- Several code segments can appear in one file, each segment consists of one or more statements.

Kerstin Eder 9 University of Bristol November 12, 2013

Structs vs Units:

Structs are the most basic building blocks in e.

- Used to keep data and operations together.
 - packets, instructions, frames
- Can be created at run-time, i.e. they are dynamic.
 - Data can be generated on-the-fly.

Units are a special kind of struct.

- Units are **static**! Can be generated during test phase only.
- Allow mapping to HDL path. (Best way to connect to DUV.)
- Used for generators/checkers/monitors, bus functional models (BFMs), self-checking structures, overall testbench.
 - **BFMs** package all bus functional procedures of an interface, i.e. all transactions supported by the interface. The transactions are abstracted from a physical-level interface to a procedural interface. BFM can be used to generate stimulus as well as to check the DUV response.

Kerstin Eder 13 University of Bristol November 12, 2013

SN Main Enabling Technologies

Constraint-driven Test Generation

- Create lots of meaningful tests quickly. :)
- Control over automatic test generation.
- Capture constraints from spec and verification plan.

Data and Temporal Checking

- Self-checking modules ensure data correctness and temporal properties.
- Checks are always active.
 - Unless turned off by: `set check IGNORE ;`)

Functional Coverage Collection/Analysis

- Automatic functional coverage collection.
- Analyse progress against functional coverage metrics.
 - Promotes *coverage driven* verification methodology.

Kerstin Eder 3 University of Bristol November 12, 2013

Basics of the e Language

High-level language for writing verification environments:

- test benches
- coverage collection
- test generation and checking

✿ *An e component is a representation of the "rest of the world" as seen from an interface of the design under verification (DUV).*

e supports:

- modular aspect-oriented design
- high-level data types
- pseudo-random constrained-based data generation
- events
- high-level checking
- checking of basic timing properties

Kerstin Eder 6 University of Bristol November 12, 2013

Comments

- e files begin with a comment!
- This comment ends when first begin-code marker `<'` is found.

- Comments in code segments can be marked with `--` or `//`.

✿ Use end-code `'>` and begin-code `<'` markers to write several consecutive lines of comment in the middle of code segments.

Kerstin Eder 10 University of Bristol November 12, 2013

Struct and Struct Members

Members are 2nd-level constructs: Valid only within a struct definition.

■ A simple struct for packets to be used in comms protocol:

```
type packet_kind: [atm, eth];
struct packet {
  len: int;
  keep len < 256;
  kind: packet_kind;
};
```


- **keep**: Specifies rules for constraints to influence data generation.

■ Another example struct for transactions:

```
struct transaction {
  address: uint;
  data: list of uint;
  transform(multiple:uint) is empty;
};
```

Kerstin Eder 14 University of Bristol November 12, 2013

SN Verification Automation



Kerstin Eder 4 University of Bristol November 12, 2013

Aspect-oriented Programming

AOP is the *next step up* from object-oriented programming.

- Testcases have specific purposes:
 - Does parity check on packets work?
 - Are timing properties of transmission protocol valid?
- Both are different concerns: They are orthogonal!
- ✿ Two **aspects** of same application DUV.

AOP provides mechanisms to separate these two concerns into separate aspects of the verification environment.

- Well-defined techniques for adding declarations, inserting or replacing code from the outside of a class, without editing the original class.

Kerstin Eder 7 University of Bristol November 12, 2013

Syntactic Elements

Statements are top-level constructs.

- Valid within `<'` and `'>` markers.
- Statements always end with a **semicolon** `“;”`!

Struct members are second-level constructs.

- Valid only within a **struct** definition.
- ✿ Associated with dynamic constructs of a testbench e.g. stimulus.
 - (There are also **Units** which are associated with testbench constructs such as drivers/checkers/scoreboards. They exist for the duration of the simulation.)

Actions are third-level constructs.

- Valid only when associated with a struct member, such as a method or an event.

Expressions are lower-level constructs.

- Can be used only within another e construct.

Kerstin Eder 11 University of Bristol November 12, 2013

Struct Members

Field: Defines data entry to be member of enclosing struct with explicit data type.

Method: Defines operational procedure that can manipulate fields of enclosing struct and access run-time values in DUV.

Subtype declaration: Defines instance of parent struct in which specific members have particular values or behaviour.

- Use **when** for conditional constraints on possible values of a field.

Constraint declaration: Influences distribution of values generated for data entries and the order in which values are generated. ■ **keep**

Coverage declaration: Defines functional verification goals and collects data on how well the testbench is meeting these goals.

- **cover** event-type is coverage-item-definition; ...;

Temporal declaration: Defines e events and their associated actions. ■ **event**

Kerstin Eder 15 University of Bristol November 12, 2013

```

type PCICommandType: [ IO_READ=0x2, IO_WRITE=0x3,
                      MEM_READ=0x6, MEM_WRITE=0x7 ];

struct pci_transaction like transaction {
  command : PCICommandType;
  keep soft data.size() in [0..7];
  dual_address: bool;
  when dual_address pci_transaction {
    address2: uint;
  };
  bus_id: uint;
  event initiate;
  on initiate {
    out("An event has been initiated on bus ", bus_id);
  };
  cover initiate is {
    item command;
  };
  transform(multiple:uint) is only {
    address = address * multiple;
  };
};

```

Kerstin Eder 16 University of Bristol November 12, 2013

Using Constraints

keep *constraint-bool-expr*; where *constraint-bool-expr* is a simple or compound Boolean expression.

- States restriction on the values generated for fields in the struct.

■ **keep kind!=tx or len==16;**

- Describes required relationships between field values and other struct items.

```

■ struct packet {
  kind : [tx, rx];
  len : int;
  keep kind == tx => len==16;
  --when tx packet { keep len == 16; }; exactly same effect
};

```

- Hard constraints are applied when the enclosing struct is generated. If constraints can't be met, generator issues **constraint contradiction message**.

Kerstin Eder 20 University of Bristol November 12, 2013

Randomized Test Generation needs...

...repeatability:

Same testbench version + same test
+ same random seed
= same stimulus data.

! Is this all? The testbench evolves over time!

and random stability:

- Changes to the testbench should not affect **orthogonal** aspects!

■ Packet data structure:

```

struct packet {
  ...
  payload: list of byte;
  ...};

```

Kerstin Eder 23--ii University of Bristol November 12, 2013

Packing Low

packing.low: 1st item at LSB

i_stream = pack(packing.low,addr,data);

packet.addr = 2'b11;


packet.data[0] = 0xaa;

packet.data[1] = 0xee;

17..... 0
i_stream = 11101110 10101010 11

Predefined Structs

An environment contains by default a number of predefined structs (and of course some user-defined ones).



- The system struct **sys** is the root for user-defined structs.

- Must instantiate **user-defined structs** under **sys**.
- Contents of **sys** can be viewed via SN GUI.
- Similar to **main** in C. :-)

Kerstin Eder 17 University of Bristol November 12, 2013

Generation with keep

Generation order is important: It influences the distribution of values!

```

■ struct packet {
  kind : [tx, rx];
  len : int;
  keep len > 15 => kind==rx;
};

```

- If **kind** is generated first, **kind** is **tx** about half the time because there are only two legal values for **kind**.
- If **len** is generated first, the distribution is different.

■ Consider using: **keep gen (kind) before (length);**

Kerstin Eder 21 University of Bristol November 12, 2013

Randomized Test Generation needs...

...repeatability:

Same testbench version + same test
+ same random seed
= same stimulus data.

! Is this all? The testbench evolves over time!

and random stability:

- Changes to the testbench should not affect **orthogonal** aspects!

■ Packet data structure with interrupted field:

```

struct packet {
  ...
  payload: list of byte;
  interrupted: bool;
  ...};

```

- With same seed should give the same **payload** data!

Kerstin Eder 23--iii University of Bristol November 12, 2013

Fields

Syntax: [!][%] field-name[: type] [(min-val .. max-val)] [(bits | bytes):num]

! Denotes an *ungenerated* field.

% Denotes a *physical* field.

The type for the field can be any scalar type, string, struct, or list.
(bits | bytes: num) specifies width of field in bits or bytes.

```

type NetworkType: [IP=0x0800, ARP=0x0806] (bits: 16);

struct header {
  %address: uint (bits: 48);
  %length: uint [0 .. 32];
};

struct packet {
  hdr_type: NetworkType;
  %hdr: header;
  is_legal: bool;
  %counter: uint;
};

```

- Field order is important!** It is the packing order for physical fields.

Kerstin Eder 27 University of Bristol November 12, 2013

Instantiation under sys

- Every user-defined struct (including units) must be instantiated as a (sub)field of **sys**.

```

struct packet {
  address : uint (bits : 2);
  payload : uint (bytes : 64);
};

```

```

unit router_bfm {
  packets : list of packet;
};

```

```

extend sys {
  router : router_bfm is instance;
};

```

Kerstin Eder 18 University of Bristol November 12, 2013

Using Soft Constraints

Using **keep soft** (e.g. to set default values) and **select**:

```

■ struct transaction {
  address : uint;
  keep soft address == select {
    50: [0..49];
    60: 50;
    30: [51..99];
  };
};

```

NOTE: *Soft constraints* can be overridden by hard constraints!

```

■ extend instruction {
  keep soft op_code == select {
    40: [ADD, ADDI, SUB, SUBI];
    20: [XOR, XORI];
    10: [JMP, CALL, RET, NOP];
  };
};

```

- In practice, getting the weights/bias right (for coverage closure) requires significant engineering skill.

Kerstin Eder 22 University of Bristol November 12, 2013

Packing: Driving Stimulus into the DUV

pack() function:

- pack(option:pack option, item: exp, ...): list of bit
- Specman Elite system function.
- Conversion from higher-level data structure to bit stream required by DUV.

■ **i_stream** = pack(packing.high, opcode, op1, op2);

pack options are: packing.high, packing.low or NULL

- packing.high: 1st item at MSB
- packing.low: 1st item at LSB
- NULL: Use global default - set initially to packing.low.

item: A legal expression that is a path to a scalar or a compound data item, such as a struct, field, list, or variable.

Kerstin Eder 24 University of Bristol November 12, 2013

Ungenerated Fields

- Marked with **!**.
- Values for this field are **not generated automatically**.
- Useful for fields that:**
 - Are explicitly assigned values during verification.
 - Must contain values whose computation is too complicated to be expressed with constraints.
- Ungenerated fields get **default initial value:** 0 for scalars, NULL for structs and empty list for lists.
- Ungenerated fields whose value is from a range (e.g. [20..30]) get initialized to the first value in range.
- If the field is a struct it won't be allocated and none of the fields in it will be generated.

Kerstin Eder 28 University of Bristol November 12, 2013

Generation with SN

Offline (prior to sim i.e. in Generate phase):

- Use **Generate** or **Test** command
 - Test calls **Generate** command!
- Recursively generates *everything* under **sys**.
- BEWARE: Can consume a lot of memory!

Online (during sim):

- Use **gen** action. ■ **gen gen-item [keeping {...}]**
- Allows to dynamically generate values based on DUV state.

Kerstin Eder 19 University of Bristol November 12, 2013

Randomized Test Generation needs...

...repeatability:

Same testbench version + same test
+ same random seed
= same stimulus data.

! Is this all? The testbench evolves over time!

Kerstin Eder 23--i University of Bristol November 12, 2013

Packing High

packing.high: 1st item at MSB

i_stream = pack(packing.high,addr,data);

packet.addr = 2'b11;

packet.data[0] = 0xaa;

packet.data[1] = 0xee;

17..... 0
i_stream = 11 10101010 11101110

Kerstin Eder 25 University of Bristol November 12, 2013

Physical Fields

- Marked with **%**.
- Physical fields are packed when the struct is packed.
- Used for fields that represent data that will be sent to HDL design in the simulator.
- Non-physical fields** are called **virtual fields**.
 - They are not packed automatically when the struct is packed. (They can be packed individually if needed.)
- If no range is specified, width of field is determined by field's type.
- If the field's type does not have a known width, you must use (bits | bytes: num) syntax to define the width. (Important for packing!)

Kerstin Eder 29 University of Bristol November 12, 2013

Limitations of e's AOP Implementation

- Many things can be extended!
 - So more discipline and structure is required.
- Fields can only be appended:
 - Fields are physically appended to existing fields
 - Might create a problem when packing!
- Variance control fields: Extensions can only be specified for a single value of the control field.
 - instructions **add** and **sub** with feature that applies to both
 - Needs to be specified for both or use trick! ☼ See next slide!
- Methods can only be appended, prepended or replaced.
- Aspects are order-dependent (on loading).

Kerstin Eder 30 University of Bristol November 12, 2013

SN Predefined Event: @sim

■ **event** `clk` is `rise (clk_p$) @sim;`

@sim is **special sampling event** occurring at any simulator callback.

- Expression must be an HDL signal path in the simulated model.


- ☼ Signal does not have to be a clock.
- No restriction for signal to be periodic or synchronous.
 - Might slow down simulation!

☼ Clock signal can also be emitted from e code and driven into DUV.
(But usually more efficient to generate clock in HDL.)

When not running with a simulator attached to SN, use **@sys.any**.

Kerstin Eder 34 University of Bristol November 12, 2013

Synch between SN and Simulator



Kerstin Eder 38 University of Bristol November 12, 2013

Extensions via *variance control fields* can only be specified for a **single value of the control field!**

- To get around this, introduce an additional *virtual* field.
- This field controls common extensions.
- Extension to an instruction struct (for Calc.1 design):

```
type opcode_t : [ NOP, ADD, SUB, SHL, SHR, SRL, SRR ] (bits : 4);
struct instruction_s {
  load_in : opcode_t;
  wdata1 : uint (bits:32);
  wdata2 : uint (bits:32);
  rwrap : uint (bits:2);
  idout : uint (bits:32);
  check_response(in : instruction_s) is empty;
}; // struct instruction_s
extend instruction_s {
  is_a_shift : bool;
  keep is_a_shift == opcode in {SHL, SHR};
  when is_a_shift instruction_s {
    // Common extension to SHL and SHR goes below.
    ...
  }
};
```

Kerstin Eder 31 University of Bristol November 12, 2013

Events in SN

- Events are used to **synchronize with the DUV** or to debug a test.
- **Events are struct members.**

■ **Automatic emission** of events:

```
<
  extend driver_s {
    event clk is fall(clk_p$) @sim;
    event resp is change(out_respl_p$)@clk;
  }
>
```

■ **Explicit emission** of event:

```
<
  extend driver_s {
    collect_response(cmd : command_s) @clk is also {
      emit cmd.cmd_complete;
    };
  }
>
```

Kerstin Eder 35 University of Bristol November 12, 2013

Temporal Checking Methodology

1. Capture important DUV temporal behaviour with events and TEs.
2. Use **expect** struct members to declare temporal checks.

Syntax: **expect** TE **else** `dut_error (string);`

Example temporal checks:

```
expect @req => {[..4];@ack} @clk
else dut_error("Acknowledge did not follow
               request within 1 to 5 clock cycles.");
```

```
expect @buffer_full => eventually @int @clk
else dut_error("Buffer full, but interrupt did not occur.");
```

☼ **eventually** Sometime *before the end of simulation!*

Kerstin Eder 39 University of Bristol November 12, 2013

Advanced Techniques: SN temporal checking

SN Temporal Language

- Capture behaviour over time for synchronization with DUV, functional coverage and **protocol checking**.
- Language consists of:
 - temporal expressions (TEs)
 - temporal operators
 - **event** struct members to define occurrences of events during sim run
 - **expect** struct members for checking temporal behaviour

Kerstin Eder 32 University of Bristol November 12, 2013

Conforming to Stimulus Protocol


Must be able to react to state of DUV during simulation!

■ clock, signal changes, sequences of events

e language provides **wait** (till next cycle) and **sync** actions which allow to pause procedural code until event occurs.

```
print a;
wait true(enable_p$==1)@clk;
print b;
```

```
print a;
sync true(enable_p$==1)@clk;
print b;
```



Kerstin Eder 36 University of Bristol November 12, 2013

Specman Elite Tutorial

DUV: simple CPU (ALU, 4 regs, PC, PC.Stack, fetch/exec FSM)

- **Interface:** clock, reset, instruction [8 bit]

Learn how to:

- Design the verification environment
- Define DUV interfaces
- Generate a simple test
- Drive and check the DUV
- Generate constraint-driven tests
- Define and analyse test coverage
- Create corner case tests
- Create temporal and data checks
- Analyse and bypass bugs

About 100 pages. A really easy "learn by doing" lab. Takes about 2h.
.)

Kerstin Eder 40 University of Bristol November 12, 2013

Temporal Expressions in e

- Each TE is associated with a **sampling event**.
- Sampling event indicates when the TE should be evaluated by SN.

Syntax examples:

- `true(boolean-exp)@sample-event`
- `rise/fall/change(expression)@sample-event`

Kerstin Eder 33 University of Bristol November 12, 2013

Methods with a Notion of Time

TCMs - Time Consuming Methods

- Depend on sampling event.
- Can be executed over several simulation cycles.
- `collect_response(cmd : command_s) @clk is {`
 - `wait @resp; -- wait for the response`
 - `cmd.resp = out_respl_p$;`
 - `cmd.dout = out_datal_p$;`
 - `}; // collect_response`
 - Implicit **sync** action at beginning of TCM.
 - TCM must be called or started to execute.
 - `run() is also {`
 - `start drive(); // spawn`
 - `}; // run`
 - Non-TCMs can't *call* TCMs because they have no notion of time.
 - TCMs can (only) be *started* (using **start**) from a non-TCM!

Kerstin Eder 37 University of Bristol November 12, 2013

We have now covered

- Basics of e language.
- Please do Specman Elite Tutorial with CPU DUV.

Next:

- Assignment 2 - Intro to .e code and verification method.
- Hands-on session with demo.

Kerstin Eder 41 University of Bristol November 12, 2013