COMS31700 Design Verification:

Checking

Kerstin Eder

University of BRISTOL

Department of COMPUTER SCIENCE

Checking - Outline

- **Motivation**
- **Issues in checking**
  - When to check
  - What to check
- **Checking technologies**
  - Reference models
  - Scoreboards
  - (Rule-based checking)
    - (Assertions)
- **Assertion-based verification (ABV) – later** ☺

The Yin-Yang of Verification

- Driving and checking are the yin and yang of verification

  - We cannot find bugs without creating the failing conditions
 - We cannot find bugs without detecting the incorrect behavior

Ideal Checking

- In theory – detect deviation from expected behavior as soon as it happens and where it happens
  - No need to worry about "disappearing errors"
  - Easy to debug – the checker points to the bug
- This is not easy (even if we ignore many practical aspects) because in many cases we understand that something bad happened only in retrospect
  - Several "good" behaviors collide to create a bad behavior
- And what about the bugs we are not looking for

"Good" Behavior Collision

- At cycle 1000 fdiv F1, F2, F3 is dispatched to the M unit
  - It reaches stage M2 at cycle 1001
  - Its execution time is 60 cycles
- At cycle 1023 fld F1,100(G2) is dispatched to the S unit
  - It reaches stage S2 at cycle 1024
- The data returns from the cache at cycle 1060
- At cycle 1061 the fdiv is ready to write
  - It moves to stage M3
- At cycle 1061 the fld is ready to write
  - It moves to stage S3
- Both instruction write to the same register together

```
        ┌──────────────┐
        │    Decode    │
        └──────┬───────┘
               │
        ┌──────┴───────┐
        │   Dispatch   │
        └──┬────────┬──┘
           │        │
        ┌──┴─┐   ┌──┴─┐
        │ S1 │   │ M1 │
        └──┬─┘   └──┬─┘
           │        │
        ┌──┴─┐   ┌──┴─┐
        │ S2 │   │ M2 │
        └──┬─┘   └──┬─┘
           │        │
    ┌────┬─┴──┬────┐│
    │S4f │ S3 │S4b ││
    └────┴────┴────┘│
        ┌───────────┴┐
        │    M3      │
        └────────────┘
```

"Good" Behavior Collision

- There are many possible causes for the problem

Practical Aspects

Consider:
- The cost of implementation and maintenance
  - Against the cost of debugging

- The cost of mistakes
  - Misdetection
    - We failed to detect a bug that was exposed by the stimuli.
  - False alarm
    - We mistakenly flagged a good behavior as bad.
 - Which is more expensive?

When to check

When to Check?

- Checking can be done at various stages of the verification job
  - During simulation
    - On-the-fly checking
  - At the end of simulation
    - End-of-test checking
  - After the verification job finishes
    - External checking

- Checking at each stage has its own advantages and disadvantages

On-the-fly Checking

- Checking is done **while the simulation is running**
- The DUV is continuously monitored to detect erroneous behavior

# On-the-fly Checking

- **Advantages**
  - Detection can be as close as possible (in time and space) to the bug source
  - Can stop test as soon as bug occurs; no wasted simulation cycles
  - Do not require large traces and external tools to do the checking

- **Disadvantages**
  - May **slow down simulation**
  - Checking is limited to allowed time and space complexity
  - Need to plan the checking in advance
    - To add a new checker, we need to rerun simulation

End-of-test Checking

- Checking is done **at the end of simulation**
- The checker checks the state of internal and external resources and makes sure that they are correct

End-of-test Checking

- **Disadvantages**
  - Provides limited checking capabilities
    - Static look at the state of resources at the end of the test
  - High probability of masking bugs by rewriting to the resources
  - Hard to detect performance bugs
    - Correct things are happening, but not at the right time
  - Hard to correlate symptoms to bugs
    - Hard to debug
- **Advantages**
  - Simpler than other forms
    - May not require a deep understanding of the DUV
  - Reduces probability of false alarms
    - Caused by disappearing bad effects

External Checking (Monitors)

- **Monitors** keep internal resources values and behaviors in trace files
- Checking is done by an external program that examines these files

External Checking

- External checking **separates the checking from the simulation**
  - We can perform any check we want without rerunning the simulation
    - As long as the data is in the trace files
  - We can perform more complicated checks
    - Use longer history, process events out-of-order
  - We can combine information coming from different sources
    - For example, different verification environments

In theory, external checking has all the powers of on-the-fly checking plus end-of-test checking - plus more

(Trace size and amount of traced facilities is a practical limitation.)

What to check

What to Check

- **There are five main sources of checkers**
  - The inputs and outputs of the design (specification)
  - The architecture of the design
  - The microarchitecture of the design
  - The implementation of the design
  - The context of the design
    - e.g. protocol compliance

- **Note that the source of checkers and their implementation are two different issues**

Coarser Classification – The What And the How

Checking the What

- **Check the final outcome of a behavior**
  - Data oriented
    - But not limited to data
  - Usually based on higher level of abstraction
    - Checking is less tight
    - Requires less familiarity with the DUV
    - Less false alarms, more misdetections
  - Low correlation between failure and bugs
    - Harder for debugging
    - Can find "unexpected" bugs

Checking the How

- **Check *how* things are done internally**
  - Control oriented
  - Usually at lower levels of abstraction
    - Closer to implementation
  - More false alarms, less misdetections
  - Tighter relations between failure and bugs

Stimuli Generation and Checking

- In general, checking should be isolated from the stimuli generation
  - **Modularity** – ability to replace the stimuli generator
  - **Reusability** – ability to use the checkers at higher level of the design hierarchy
  - **Independence of Checking from Generation**
- Exceptions
  - Self-checking tests
  - Golden vectors

- The stimuli generation can assist checking by improving observability
  - Help transfer events from dark corners to the spotlight

Self-Checking Testbenches

- Knowledge of the DUV functionality can be built into the TB.
  - This automates the checking process.
  - Verification engineers encode their knowledge of correct DUV functionality into the checkers, monitors and scoreboard using:
    - Golden Vectors,
    - Reference Models,
    - Protocols or Transactions.
- This results in a **"self-checking" TB**.
  - Checkers are "always" active.

Contemporary TB Architecture

Contemporary Testbench Architecture

★ Assertions

Monitors

- Monitors are TB components that observe the inputs, outputs, or internals of the DUV.
  - Monitors watch activity of the DUV.
    - Black box: DUV inputs and outputs
    - Grey box: potentially selected internals
  - Monitors can convert low-level signals to transactions.
  - Monitors can flag simple timing and protocol errors.
  - Monitors collect functional coverage.
  - Monitors update the scoreboard.
  - Monitors don't drive DUV pins; they are "passive".
    - Monitors are self-contained and don't cause "side effects".
   - Monitors are re-usable at different levels of abstraction.

Types of Monitors

- **Input monitors:**
  - Collect inputs to the DUV and pass them to scoreboard.
  - Can have checker components.

- **Output monitors:**
  - Observe the outputs from the DUV and pass them to the scoreboard.
  - Can have checker components.

- **Coverage monitors**
  - Collects inputs, outputs and selected internal signals.
  - Permit analysis of stimulus and functionality coverage.

Checking Technologies

Scoreboards

- Scoreboards are smart data structures that keep track of events in the DUV during simulation
- Usually, scoreboards are global
  - One scoreboard per verification environment
- Scoreboard are not checking mechanisms, but
  - The main purpose of using scoreboards is for checking
  - In practice, many checkers are implemented inside scoreboards
  - There are many typical checks that are done with scoreboards

Scoreboard Operation

Scoreboards Overview

- Scoreboards source information from
  - the inputs and outputs of the DUV, and
  - occasionally also from internal events in the DUV.
- Scoreboards are very useful in dataflow designs
  - Routers, cache designs, queues

- Types of checks enabled using a scoreboard:
  - Matching outputs with inputs
    - No loss of data
      - Detect inputs with no matching output.
    - No creation of data
      - Detect output with no matching input.
    - No unintended modification of data
  - Timing specification
    - Delay from input to output remains within specified limits.
  - Data order

Scoreboarding in e - 1

- Assume: DUV does not change order of packets.
  - Hence, first packet on scoreboard has to match received packet.

```
import packet_s;
unit scoreboard {
  !expected_packets : list of packet_s;
  add_packet(p_in : packet_s) is {
    expected_packets.add(p_in);
  };

  check_packet(p_out : packet_s) is {
    var diff : list of string;
     -- Compare physical fields of first packet on scb with p_out.
     -- Report up to 10 differences.
    diff = deep_compare_physical(expected_packets[0], p_out, 10);
                                 check that (diff.is_empty())
          else dut_error(''Packet not found on scoreboard'',
 diff);
    -- If match was successful, continue.
    out(''Found received packet on scoreboard.'');
    expected_packets.delete(0);
  };
};
```

Scoreboarding in e - 2

Recording a packet on the scoreboard:

Extend driver such that

- When packet is driven into DUV call `add_packet` method of scoreboard.
  - Current packet is copied to scoreboard.
- It is useful to define an event that indicates when packet is being driven.

Checking for a packet on the scoreboard:

Extend receiver such that

- When a packet was received from DUV call `check_packet`.
  - Try to find the matching packet on scoreboard.
- It is useful to define an event that indicates when a packet is being received.

Side Note – Graceful End-of-test

- Checking that nothing is lost is very important
- If an input does not have a matching output, how can we distinguish between two cases
  - The input is lost or hopelessly stuck in the DUV
  - The DUV did not have enough time to handle the input
- Possible solution – Start a timer when a new input enters the DUV
  - If the timer expires, that input is lost or stuck
  - But, what if the delay cannot be bound?
- Alternative (or complementary) solution – stop the inputs before the end of the test and let the design clean itself
  - Because there are no new inputs, things that are stuck inside have a chance to get free

Reference Models

- A reference model is an oracle that tells how the DUV should behave
  - Usually in the form of an alternative implementation

- It runs in parallel to the DUV, using the same inputs and provides the checking mechanisms with information about the expected behavior
  - Checking is done by comparing the expected behavior to the actual one

- Pure reference models can run independently of the DUV
  - But not all reference models are pure (example later)

Reference Model Operation

Reference Models

- **Reference models have many uses**
  - Checking
  - Aids for stimuli generation
  - "Smart" BFM – imitate the function of the DUV
  - Vehicles for SW development
- **What can we check with a reference model**
  - In principal, anything
  - In practice it depends on the level of details and accuracy of the reference model
    - And how much of its behavior we are willing to expose

Levels of Abstraction

- The level of abstraction in a reference model dictates the type of information we can get out of it for checking
  - Functionally accurate models can be used only to check correctness of data, usually at the end of the test or at well defined points in time
    - Timing, order, and other checks need other means
  - Cycle accurate models can be used for checking all aspects of I/O behavior
  - Cycle accurate and latch accurate models can be used also for checking the internal state of the DUV
    - The book calls this type of model deep function reference model

Impure Reference Model

- Sometimes it is impossible (or very hard) for the reference model to duplicate significant decisions made by the DUV

- Possible solution:
  Use information from the DUV to assist the reference model!

Rule-based Checking

- Checks that a set of rules hold in the DUV
- Essentially, all checking is rule-based

> `if (not something) then error`

- Something can be
  - Value of a register matches value in reference model
  - Data in a packet at the DUV output matches data in the input as stored in the scoreboard
  - response_out == 0 → data_out == 0
- Rule-based checking usually refers to the last case

Rule-based Checking

- Rules can come from many sources
  - All levels of the design process
    - Spec, high-level design, implementation
  - Behavior of neighboring units
- Rules checking can be implemented in many places
  - External checking tools
  - Various places in the verification environment
    - Interface monitors
    - Scoreboards
    - End-of-test checkers
  - In the DUV itself
- Rule-based checking that is embedded in the DUV code is called assertions
- Lecture on Assertion-Based Verification

Putting Coverage, Generation and Checking together:

The Verification Environment

(With many thanks to Cadence for providing the animations in this section.)

Traditional Approach: Directed Testing

Verification engineer sets goals and writes directed test for each item in the Verification Plan:

DUT

Redo if design changes

Automation Significant manual effort to write all the tests

Automation Work required to verify each goal was reached

Completeness Poor coverage of non-goal scenarios
… especially the cases that you didn't "think of"

Coverage Driven Verification Methodology:
Defining Coverage "Goals" Enables Automation

Focuses on reaching **goal areas** (*versus execution of test lists)*:

Add constraints to target a specific corner case

Simply changing seeds generates new stimulus

DUT

Constrained-random stimulus **generation** explores goal areas (& beyond)

**Coverage** shows which *goals* have been exercised and which need attention

(Self-Checking ensures proper DUT response.)   *Even for non-goal states!*

Automation – Constrained-random stimulus accelerates hitting coverage goals and exposing bugs. Coverage and checking results indicate effectiveness of each simulation, which enables scaling many parallel runs.

Coverage Driven Environment

- Composition of a coverage driven environment
    - Reusable stimulus sequences developed with "constrained random" generation
    - Running unique seeds allows the environment to exercise different functionality
    - Monitors independently watch the environment
    - Independent checks ensure correct behavior.
    - Independent coverage points indicate which functionality has been exercised.

Summary

- Stimuli Generation
- Coverage and
- Checking

Coverage Driven Verification Methodology