SystemC CCI WG
Simple Mutable Integer Parameter

R. Swaminathan, Texas Instruments Inc.

January 2011

accellera

SYSTEMS INITIATIVE

Basic usage of a Mutable Integer Parameter

- **Report the parameter's default value following construction**
  - Note: No preset value is supplied in this example.

- **Update the parameter's value (directly) from within the owning module**

- **Update the parameter's value from a different module, referred to as "EXTERNAL"**
  - This requires obtaining a parameter handle from the broker

Example Sequence Diagram

sim_ip: simple_ip

cfg_ip: config_ip

@t = 0ns

cci_param<int> int_param;

int_param=0

int_param = 1;

@t = 10ns

int_param=1

int_param_handle.set_cci_value (cci::cci_value(2));

@t = 20ns

int_param=2

int_param 'Owner' module

EXTERNAL module updating int_param

accellera
SYSTEMS INITIATIVE

Expected Output (ex01_Simple_Int_Param.log)

```
SystemC Simulation

Info: sim_ip: @0 s, Ctor: Default value of sim_ip.int_param is 0

Info: sc_main: Begin Simulation.

Info: sim_ip: @10 ns, execute: Set value of int_param to 1

Info: sim_ip: @10 ns, execute: Current value of int_param is 1

Info: cfg_ip: @20 ns, execute: [EXTERNAL] Set value of sim_ip.int_param to 2

Info: cfg_ip: @20 ns, execute: [EXTERNAL] Current value of sim_ip.int_param is 2

Info: sc_main: End Simulation.

Info: sim_ip: Dtor: Current value of sim_ip.int_param is 2
```