Name: Md. Fahim Ferdous Khan ID: IT-16018

Experiment N0:02

Name of Experiment: TCP Variants

Objective:

 Create a simple dumbbell topology, two client Node1 and Node2 on the left side of the dumbbell and server nodes Node3 and Node4 on the right side of the dumbbell. Let Node5 and Node6 form the bridge of the dumbbell. Use point to point links.

- 2. Install a TCP socket instance on Node1 that will connect to Node3.
- 3. Install a UDP socket instance on Node2 that will connect to Node4.
- 4. Start the TCP application at time 1s.
- 5. Start the UDP application at time 20s at rate Rate1 such that it clogs half the dumbbell bridge's link capacity.
- 6. Increase the UDP application's rate at time 30s to rate Rate2 such that it clogs the whole of the dumbbell bridge's capacity.
- 7. Use the ns-3 tracing mechanism to record changes in congestion window size of the TCP instance over time. Use gnuplot/matplotlib to visualise plots of cwnd vs time.
- 8. Mark points of fast recovery and slow start in the graphs.
- 9. Perform the above experiment for TCP variants Tahoe, Reno and New Reno, all of which are available with ns-3.

Source Code:

#include <fstream>

#include "ns3/core-module.h"

```
#include "ns3/network-module.h"
#include "ns3/internet-module.h"
#include "ns3/point-to-point-module.h"
#include "ns3/applications-module.h"
using namespace ns3;
NS_LOG_COMPONENT_DEFINE ("FifthScriptExample");
//
//
// node 0 node 1
// +----+
// | ns-3 TCP | | ns-3 TCP |
// +-----+
// | 10.1.1.1 | | 10.1.1.2 |
// +-----+
// | point-to-point | | point-to-point |
// +-----
```

```
//
//
           5 Mbps, 2 ms
//
//
// We want to look at changes in the ns-3 TCP congestion window. We need
// to crank up a flow and hook the CongestionWindow attribute on the socket
// of the sender. Normally one would use an on-off application to generate a
// flow, but this has a couple of problems. First, the socket of the on-off
// application is not created until Application Start time, so we wouldn't be
// able to hook the socket (now) at configuration time. Second, even if we
// could arrange a call after start time, the socket is not public so we
// couldn't get at it.
//
// So, we can cook up a simple version of the on-off application that does what
// we want. On the plus side we don't need all of the complexity of the on-off
// application. On the minus side, we don't have a helper, so we have to get
// a little more involved in the details, but this is trivial.
//
// So first, we create a socket and do the trace connect on it; then we pass
// this socket into the constructor of our simple application which we then
```

// install in the source node.
//
//
class MyApp : public Application
{
public:
MyApp ();
virtual ~MyApp();
void Setup (Ptr <socket> socket, Address address, uint32_t packetSize, uint32_t nPackets,</socket>
DataRate dataRate);
private:
virtual void StartApplication (void);
virtual void StopApplication (void);
void ScheduleTx (void);
void SendPacket (void);

```
Ptr<Socket>
               m_socket;
 Address
             m_peer;
            m_packetSize;
 uint32_t
 uint32_t
            m_nPackets;
              m_dataRate;
 DataRate
             m_sendEvent;
 EventId
 bool
           m_running;
            m_packetsSent;
 uint32_t
};
MyApp::MyApp ()
 : m_socket (0),
  m_peer (),
  m_packetSize (0),
  m_nPackets (0),
  m_dataRate (0),
  m_sendEvent (),
  m_running (false),
  m_packetsSent (0)
{
```

```
}
MyApp::~MyApp()
{
 m_socket = 0;
}
void
MyApp::Setup (Ptr<Socket> socket, Address address, uint32_t packetSize, uint32_t nPackets,
DataRate dataRate)
{
 m_socket = socket;
 m_peer = address;
 m_packetSize = packetSize;
 m_nPackets = nPackets;
 m_dataRate = dataRate;
}
void
MyApp::StartApplication (void)
{
```

```
m_running = true;
 m_packetsSent = 0;
 m_socket->Bind ();
 m_socket->Connect (m_peer);
 SendPacket ();
}
void
MyApp::StopApplication (void)
{
 m_running = false;
 if (m_sendEvent.IsRunning ())
  {
   Simulator::Cancel (m_sendEvent);
  }
 if (m_socket)
  {
   m_socket->Close ();
```

```
}
}
void
MyApp::SendPacket (void)
{
 Ptr<Packet> packet = Create<Packet> (m_packetSize);
 m_socket->Send (packet);
 if (++m_packetsSent < m_nPackets)
  {
   ScheduleTx ();
  }
}
void
MyApp::ScheduleTx (void)
{
 if (m_running)
  {
```

```
Time tNext (Seconds (m_packetSize * 8 / static_cast<double> (m_dataRate.GetBitRate ())));
   m_sendEvent = Simulator::Schedule (tNext, &MyApp::SendPacket, this);
  }
}
static void
CwndChange (uint32_t oldCwnd, uint32_t newCwnd)
{
 NS_LOG_UNCOND (Simulator::Now ().GetSeconds () << "\t" << newCwnd);
}
static void
RxDrop (Ptr<const Packet> p)
{
 NS_LOG_UNCOND ("RxDrop at " << Simulator::Now ().GetSeconds ());
}
int
main (int argc, char *argv[])
{
```

```
CommandLine cmd;
cmd.Parse (argc, argv);
NodeContainer nodes;
nodes.Create (2);
PointToPointHelper pointToPoint;
pointToPoint.SetDeviceAttribute ("DataRate", StringValue ("5Mbps"));
pointToPoint.SetChannelAttribute ("Delay", StringValue ("2ms"));
NetDeviceContainer devices;
devices = pointToPoint.Install (nodes);
Ptr<RateErrorModel> em = CreateObject<RateErrorModel> ();
em->SetAttribute ("ErrorRate", DoubleValue (0.00001));
devices.Get (1)->SetAttribute ("ReceiveErrorModel", PointerValue (em));
InternetStackHelper stack;
stack.Install (nodes);
```

```
Ipv4AddressHelper address;
 address.SetBase ("10.1.1.0", "255.255.255.252");
 lpv4InterfaceContainer interfaces = address.Assign (devices);
 uint16_t sinkPort = 8080;
 Address sinkAddress (InetSocketAddress (interfaces.GetAddress (1), sinkPort));
 PacketSinkHelper packetSinkHelper ("ns3::TcpSocketFactory", InetSocketAddress
(Ipv4Address::GetAny (), sinkPort));
 ApplicationContainer sinkApps = packetSinkHelper.Install (nodes.Get (1));
sinkApps.Start (Seconds (0.));
 sinkApps.Stop (Seconds (20.));
 Ptr<Socket> ns3TcpSocket = Socket::CreateSocket (nodes.Get (0), TcpSocketFactory::GetTypeId
());
 ns3TcpSocket->TraceConnectWithoutContext ("CongestionWindow", MakeCallback
(&CwndChange));
 Ptr<MyApp> app = CreateObject<MyApp> ();
 app->Setup (ns3TcpSocket, sinkAddress, 1040, 1000, DataRate ("1Mbps"));
 nodes.Get (0)->AddApplication (app);
 app->SetStartTime (Seconds (1.));
 app->SetStopTime (Seconds (20.));
```

```
devices.Get (1)->TraceConnectWithoutContext ("PhyRxDrop", MakeCallback (&RxDrop));
Simulator::Stop (Seconds (20));
Simulator::Run ();
Simulator::Destroy ();
return 0;
}
```

OUTPUT:

```
fahim@fahim-HP-ProBook-450-G3: ~/ns-allinone-3.30/ns-3.30
File Edit View Search Terminal Help
1.12151 85/6
1.12983 9112
RxDrop at 1.13696
1.13815 9648
1.1548 1072
1.16476 1340
1.17332 1554
1.17232 1554
1.18064 1738
 .18896 1903
1.19728 2053
1.2056 2192
1.21392 2323
1.22224 2446
1.23056 2563
1.23888 2675
1.2472 2782
1.25552 2885
1.26384 2984
1.27216 3080
1.28048 3173
1.2888 3263
1.29712 3351
1.30544 3436
1.31376 3519
```



