



|   |  |  |  |                      |  |                             |  |                |
|---|--|--|--|----------------------|--|-----------------------------|--|----------------|
| GENERAL NOTES   |  | FIRST ANGLE PROJECTION                     |  | MATERIAL:            |  | QTY-1 Pcs                   |  |                |
| DIMENSIONS ARE IN MM  |  |  |  | ALUMINUM             |  | Senecio Robotics Tamir LTD. |  |                |
| DO NOT SCALE DRAWING  |  | MACHINING NOTES                            |  | HEAT TREATMENT:      |  | TITLE:                      |  |                |
| TRUE POSITION TOLERANCES ARE AT MMC.  |  | TOLERANCES UNLESS OTHERWISE SPECIFIED      |  | PROTECTIVE COATING:  |  | 524-400-005                 |  |                |
| PROPRIETARY   |  | ON HOLE & INT. THREAD                      |  | Anodize for Aluminum |  | DRWG. NO.                   |  | REV. NO.       |
| THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FLEX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT |  | LOCATION IS                                |  | DRAWN                |  | 524-400-005                 |  |                |
|   |  | ON PIN HOLE                                |  | DESIGNED             |  | SCALE: 1.5:1                |  | SHEET No. 1    |
|   |  | LOCATION IS                                |  | APPROVED             |  | DATE:                       |  | TOTAL SHEETS 1 |
|   |  | GENERAL TOLERANCES:                        |  | iso 4762             |  |                             |  | PAGE SIZE: A4  |
|   |  | LINEAR: ± 0.10 0.01 10-50 0.04 50-250 0.08 |  | METRIC               |  |                             |  |                |
|   |  | HOLE: + 0.02 ROD: - 0.02                   |  |                      |  |                             |  |                |
|   |  | ANGEL: ± 1°                                |  |                      |  |                             |  |                |
|   |  | BREAK ALL SHARP EDGES                      |  |                      |  |                             |  |                |
|   |  | 0.1-0.4 RAD. OR 45 CHAMFER                 |  |                      |  |                             |  |                |