

BX51WI

Fixed Stage Upright Microscope

The BX51WI microscope is ideal for all physiological experiments such as patch clamping and intravital microscopy. The fixed stage and vibration-free frame design ensure excellent stability throughout the experiment. Use of infrared light protects living cells and offers high penetration depths of thick tissue slices, while high NA optics allow magnification changes without moving the objective.

Specifications

Illumination	Transmitted light 12 V 100 W halogen Köhler illumination; Light adjustment: less than DC2 V~12 V (continuous adjustment)
Focusing	Nosepiece focus by roller guide; Stroke per rotation: fine: 0.1 mm, coarse: 15 mm; Maximum stroke: 25 mm; Coarse lower limit stopper mechanism, Torque adjustment mechanism for coarse focus
Observation tube	Trinocular (FN 22), erect image trinocular (FN 22), double port magnification change unit (FN 22)
Nosepiece	Swing, Slide, Single position, Swing-slide
Stage	Mechanical, bridge
Condenser	8-position universal, long working distance oblique, long working distance DIC, swing-out
Dimensions (W × D × H)	317.5 mm × 567 mm × 503.8 mm (Epifluorescence Configuration)
Weight	19 kg (Epifluorescence Configuration)



BX53-P

Polarizing Microscope

The BX53-P polarizing microscope provides superb performance in polarized light applications using a combination of UIS2 infinity- corrected optics and a distinctive optical design. The microscope is versatile to handle observation and measuring applications in virtually any field thanks to an extended line of compatible compensators.

- Bertrand lens for conoscopic and orthoscopic observations ·
- An extensive range of compensators and wave plates
- Supports BX3 series accessories and camera system

Specifications

Illumination	High intensity high color rendering index LED, Köhler illumination
Polarizing intermediate tube	Swing-out focusable Bertrand lens with slot for 360° rotatable analyzer for conoscopic & orthoscopic observation (U-CPA)
Test plate	1 wavelength (1λ), 1/4 wavelength (1/4λ)
Compensators	Berek, Senarmont, Brace-Köhler, quartz wedge, etc. (6 types available)
Focusing	Coarse & fine coaxial handle; full stroke: 25 mm; minimum fine adjustment: 1 μm
Observation tube	Trinocular (FN 22)
Nosepiece	Detachable quadruple nosepiece with centering adjustment function
Stage	Circular rotatable stage with centering adjustment function and attachable mechanical stage. 360° graduated in 1° increments, lockable in any position
Condenser	Achromat strain-free condenser with built-in 360° rotatable polarizer (NA 0.18 – 0.9)
Dimensions (W × D × H)	274 mm × 436 mm × 535 mm
Weight	16 kg



EVIDENT
OLYMPUS

LABEX
FLUOCCA
IMARIS

GREINER
BIOSCIENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTEK

TEKSQRAY
FEATHER

DYNAMICA
FROILABO

FASTER
ARCTIKO
KÜHNER
HEITICH

HBK
CAMECA
IX CAMERAS

THERMO EM
CRYSTAL