

DP28

Microscope Digital Camera

The DP28 camera combines powerful features, precise color accuracy, and 4K resolution across a wide field of view to provide stunning images for conferencing, teaching, and clinical research. 4K image resolution creates images on the screen that look exactly as they appear through the microscope's eyepieces, so you know you're not missing details or data. From image capture to collaboration, smart camera and software features simplify and accelerate your workflow.

Specifications

Camera type		Single chip color CCD camera
Image sensor	Size	2/3 inch color CCD
	Effective pixels	5.05 megapixels (total: 5.24 megapixels)
	Scanning mode	Progressive scan
	Color filter	RGB Bayer primary color filter
	Recording range	8.45 mm (H) × 6.62 mm (V) 10.733 mm (diagonal length)
Maximum recorded pixels		4.7 megapixels (2448 × 1920)
Camera mount		C-mount
ISO Sensitivity		Equivalent to ISO 100/200/400
		PC connection Stand-alone
Image size (file format)	2448 × 1920	TIFF
	1920 × 1080	JPEG-LOW (Compression ratio 1/27)
	1224 × 960	JPEG-HIGH (Compression ratio 1/8)
	According to cellSens specifications	2448 × 1920
		1920 × 1080
Live image display (frame rate)	15 fps (2448 × 1920)	15 fps (2448 × 1920)
	22 fps (1920 × 1080)	22 fps (1920 × 1080)
	30 fps (1224 × 960)	30 fps (1224 × 960)



DP75

Microscope Digital Camera

The DP75 digital microscope camera is a high-performance, multi-application imaging tool that makes it easy to capture high-resolution brightfield or fluorescence images using a single camera. It simplifies your microscopy imaging, so you can focus more on your work.

Specifications

Camera type		Single-chip color camera (pixel shifting) Cooling system: Peltier device (active cooling)
Image sensor	Size	1.1-inch, 12.37-megapixel color CMOS image sensor
	Scanning mode	Progressive scan
Camera mount		C-mount
Effective image resolution		8192 × 6000 (pixel shifting) 4096 × 3000 (3CMOS mode) 4096 × 3000 (1 × 1) 3840 × 2160 (1 × 1) (by cropped) 2048 × 1500 (2 × 2) 2048 × 1500 (1 × 1), 1920 × 1080 (1 × 1), ROI
ISO Sensitivity		ISO 100/200/400/800/1600/3200
A/D		12-bit
Live frame rate		4096 × 3000 (1 × 1): 22 fps, 2048 × 1500 (2 × 2): 22 fps, 2048 × 1500 (1 × 1): 44 fps, 1920 × 1080 (1 × 1): 60 fps

