

EP50

Wireless Digital Imaging up to 6 Devices

Interactive Learning

- Control the EP50 camera using the EPview app for mobile devices or software for PCs/laptops
- Up to **6 users** can connect their devices to the same WLAN-enabled EP50 camera
- Access the images of other EP50 cameras in the classroom
- Capture, process, store, and share the EP50 camera's images through the easy-to-use software interface
- Simultaneous live image output via WLAN and HDMI



Engaging Lectures

- Live stream images to a group of students on their mobile devices or WLAN-enabled PCs/laptops
- Display specimen images on a high-resolution monitor, projector, or interactive white board connected to the camera's HDMI port
- Present Full HD videos
- Connect an SD card and save captured image data for further analysis

Specifications

Image Sensor	Color CMOS
Sensor Size	1/1.8 inch (7.140 mm × 4.980 mm)
Resolution	2592 × 1944 pixels (Snapshot only) 1920 × 1080 pixels (HDMI, WLAN, on PC)
(Max.) Pixel Size	2.4 × 2.4 μm
A/D Converter (Bit Depth)	8 bits
Exposure Times	1 ms – 918 ms
Live Frame Rates	Snapshot only (2592 × 1944 pixels)
	Up to 30 fps (on PC, 1920 × 1080 pixels)
	Up to 60 fps (HDMI output, 1920 × 1080 pixels)
	Up to 25 fps (WLAN output, 1920 × 1080 pixels)****
Data Transfer	HDMI, WLAN (using the WLAN adapter), Ethernet (using the USB-to-Ethernet adapter)
Annotation Functions	Text, arrow, rectangle, circle, hand writing (EPview only)
Measurement Functions	Line: Length measurement Parallel lines Circle: Diameter, area, perimeter measurement Angle: Angle measurement Rectangle: Area, perimeter measurement Polygon: Area, perimeter measurement Point: Coordinates, number scale bar

Supported mobile device OS: EPview is available for iOS 11 and later Android 8.1 and later

Remarks



Supported number of connections to one camera: 6****
WLAN adapter not included. Please contact your local sales representative.

PC Control

Microsoft Windows 11 (64 bit)

Microsoft Windows 10 (64 bit)

Dimensions (W × D × H)

78 mm × 65 mm × 88 mm (3.08 in. × 2.56 in. × 3.47 in.)

Weight

Approx. 470g (1.04 lb)

Camera Mount

C-mount

Storage

SD (HC I, UHS-I, Class 10) card



EVIDENT
OLYMPUS

LABEX
FLUOCCA
IMARIS

GREINER
BIOSCIENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTEK

TEKSQRAY
FEATHER

DYNAMICA
FROILABO

FASTER
ARCTIKO
KUHNERT
HEITICH

HBK
CAMERA
IX CAMERAS

THERMO EM
CRYSTAL