

EVIDENT
OLYMPUS

LABEX
FLUOCCA
IMARIS

GREINER
BIOSENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTTEK

TEKSGRAY
FEATHER

DYNAMICA
FROLABO

FASTER
ARCHIKO
KUNHERR
HEITICH

HBK
CAMECA
IX CAMERAS


THERMO
EM
CRYSTAL

LC35

Microscope Digital Camera

Specifications

Image Sensor	Color CMOS
Sensor Size	1/2.5-inch
Resolution (max)	2160 × 1620 pixels 1920 × 1080 pixels (full HD 16:9) 1296 × 972 pixels (fast mode)
Pixel Size	2.64 × 2.64 μm
A/D Converter (Bit Depth)	10-bits
Exposure Time	25 μs-1.5 s
Live Frame Rates*	Up to 19 fps at 2160 × 1620 pixels (full resolution) Up to 25 fps at 1920 × 1080 pixels (full HD) Up to 40 fps at 1296 × 972 pixels (fast mode)
Data Transfer	USB 3.1 Gen1 Type-C
PC Requirements	CPU: Intel® Xenon, Intel® Core i5, i7, i9, or the equivalent USB 3.1 Gen1 Type-C RAM: 8 GB Recommended: · 4 or more physical CPU cores · 8 GB RAM (dual channel)
PC Control	Windows 10 64-bit
Imaging Platform	· LGMicro · cellSens Entry, Standard, and Dimension v. 3.2 or higher** · Olympus Stream Start, Basic, and Essentials v.2.5 or higher*** · PRECIS Capture, Core, and Pro v1.1 or higher**** · DP2-TWAIN
Dimension (W × D × H)	47 mm × 46 mm × 28.8 mm (1.9 in. × 1.7 in. × 1.13 in.)
Weight	Approx. 33 g (1.16 oz)
Mount	C-mount



DP23

Microscope Digital Camera

The DP23 camera is easy to use for routine life science and clinical research imaging. The camera offers smooth live images, easy precision focusing, and clear images of dim samples. Image capture is made even easier with Olympus Smart Image Averaging (OSIA), which automatically maximizes the camera's image quality with no adjustments. Like all DP series cameras, the DP23 camera provides reliable color reproduction to show samples in their natural colors.

Specifications

Camera type	C-mount CCD camera head	
Image Sensor	Size	1/1.8 inch color CCD
	Effective pixels	2.83 million pixels (total pixels: 2.98 million pixels)
	Scanning mode	Progressive scan
	Color filter	RGB primary color on-chip filters
	Recording range	7.08 mm (H) × 5.31 mm (V), 8.8 mm (diagonal length)
	Maximum recorded pixels	2.76 megapixels (1920 × 1440)
Camera mount	C-mount	
ISO Sensitivity	Equivalent to ISO 200/400/800	
Image size (file format)	Stand Alone	PC Connection
	TIFF	1920 × 1440
	JPEG-LOW (Compression ratio 1/27)	1920 × 1080
	JPEG-HIGH (Compression ratio 1/8)	960 × 720
	1920 × 1440 1920 × 1080 960 × 720 Video recording pixels: AVI 960 × 720	File format according to cellSens specifications
Live image display (frame rate)	25 fps (1920 × 1440)	25 fps (1920 × 1440)
	25 fps (960 × 720)	25 fps (960 × 720)
	30 fps (1920 × 1080)	28 fps (1920 × 1080)

