


BX43


Manual System Microscope

The BX43 microscope enables you to choose between cost- efficient and advanced configurations, depending on your needs. Modular components, such as ergonomic observation tubes and stages, make it simple to customize the microscope to your application.

Observation Images



Maintain brightness when changing magnifications



Observe cellular tissue with LPLN40X objectives
Image: Cervical Cell (Papanicolaou Stain)

Specifications

Illumination	Built-in Köhler illumination for transmitted light, light intensity manager switch High color rendering index LED light source
Focusing	Vertical stage movement: 25 mm stage stroke with coarse adjustment limit stopper, Torque adjustment for coarse adjustment knobs, Stage mounting position variable, High sensitivity fine focusing knob (minimum adjustment gradations: 1 µm)
Observation tube	Widefield (FN 22) • Widefield tilting, telescopic and lifting binocular • Widefield tilting trinocular • Widefield erect image trinocular • Widefield tilting binocular • Widefield binocular • Widefield ergo binocular
	Super Widefield (FN 26.5) • Super widefield trinocular • Super widefield erect image tilting trinocular
Nosepiece	Interchangeable reversed quintuple/coded quintuple, sextuple/coded sextuple, septuple/coded septuple nosepiece
Stage	Ceramic-coated coaxial stage with left or right hand drive control; with rotating mechanism and torque adjustment mechanism, optional rubber grips available (non-stick grooved coaxial, plain, rotatable stages are also available)
Condenser	• Abbe (NA 1.1), for 4X – 100X • Swing out Achromatic (NA 0.9), for 1.25X – 100X (swing-out: 1.25X – 4X) • Achromatic Aplanatic (NA 1.4), for 10X – 100X • Phase contrast, darkfield (NA 1.1), [phase contrast: for 10X – 100X, darkfield: for 10X – 100X (up to NA 0.80)] • Universal (NA 0.9), for 1.25X – 100X [swing-out: 1.25X – 4X, with oil top lens: (NA 1.4)] • Low (NA 0.75), for 2X – 100X (Dry) • Ultra low (NA 0.16), for 1.25X – 4X • Darkfield dry (NA 0.8 – 0.92), for 10X – 100X • Darkfield oil (NA 1.20 – 1.40), for 10X – 100X
Dimensions (W × D × H)	274.5 mm × 362 mm × 410 mm (Standard configuration)
Weight	13.2 kg (Standard configuration)



EVIDENT
OLYMPUS

LABEX
FLUOCCA
IMARIS

GREINER
BIOSCIENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTEK

TEKSQRAY
FEATHER

DYNAMICA
FROILABO

FASTER
ARCTIKO
KUHNERT
HETTICH

HBK
CAMECA
IX CAMERAS

THERMO EM
CRYSTAL