

CX23

Educational microscope


Focused on improving the workflow for educational microscopy, the CX23 upright microscope requires minimal setup. The system is easy to carry, use, and store in the classroom with a compact, lightweight design.

This user-friendly microscope offers ergonomic components to ease sample handling and support comfortable observation. Plan achromat objectives help ensure image clarity and flatness throughout the field of view.



- Ergonomic grips add safety when retrieving the microscope from high places.
- The CX23 microscope is one of the lightest in its class.
- The arm is angled to keep users' wrists in a comfortable, neutral position.
- An inward-facing rotating nosepiece facilitates a larger working area above the stage, enabling easier operation and specimen exchange or making it easier to apply oil to immersion objectives.

Observation Images



Specifications

Illumination	Built-in transmitted illumination system, LED power consumption 0.5 W (nominal values)
Focusing	Stage height movement (coarse movement stroke 15 mm) Fine focus graduation: 2.5 μ m
Revolving nosepiece	Fixed quadruple nosepiece
Stage	Wire movement mechanical fixed stage Traveling range: 76 mm (X) $\times$ 30 mm (Y), specimen holder, specimen position scale
Observation tube	30° inclined binocular tube Interpupillary distance adjustment range: 48 – 75 mm Eyepoint adjustment: 370.0 – 432.9 mm
Objectives	Plan Achromat, anti-fungus 4X NA: 0.10 W.D.: 27.8 mm 10X NA: 0.25 W.D.: 8.0 mm 40X NA: 0.65 W.D.: 0.6 mm 100X Oil NA: 1.25 W.D.: 0.13 mm (CX23LEDRFS1 only)
Eyepiece	(10x)Field Number (FN): 20 (anti-fungus)
Accessories	Reflection mirror (CH20-MM), 15X eyepiece (WHSZ15X-H; FN 12, anti-fungus), Dedicated wooden case, Eyepiece micrometer, Darkfield stop (CH2-DS+CH2-FH)
Dimensions	Binocular: 198 mm $\times$ 398 mm $\times$ 386 mm, (W $\times$ D $\times$ H)
WeightApprox.	5.9 kg

