

IXplore IX85

Specifications

	IX85PIZF	IX85P2ZF
Microscope frame	Optical system	UIS2 optical system
	Revolving nosepiece	Motorized 6-position revolving nosepiece (DIC slider attachable) One position for Automated Correction Collar Simple water proof structure
	Focus	Stroke: 10.5 mm Minimum increment: 0.01 um Maximum nosepiece movement speed: 3mm/s
	Intermediate Magnification Changer	3 positions (Coded) 1X / 1.6X / 2X
	Light path selection	Motorized 4 positions Eyepiece 100%, left 100%, right 100%, eyepiece 50%/left 50%
	Deck insert layer	1 layer2 layers
	Maximum port field number	Left/Right side port: FN26.5 BI port: FN22 Deck right side port: FN18Left/Right side port: FN18 BI port: FN22 Deck right side port: FN18
	Dimensions (IX85 Microscope frame with illumination pillar)	540mm (D) x 321mm (W) x 667mm (H)540mm (D) x 321mm (W) x 732mm (H)
Focus compensator	TruFocus Z drift compensator	Offset method (Focus search, one-shot focus, continuous focus), Class 1 laser product, laser wavelength: 830nm
Transmitted light illuminator		Pillar tilt mechanism (30° inclination angle, with vibration reducing mechanism), Condenser holder (with with 88 mm stroke, refocusing mechanism), Field iris diaphragm adjustable, 4 filter holders Light source: High power LED light source
Observation tube	Widefield (FN22)	· U-TB190BK Wide field tilting binocular · U-B190 Wide field binocular · U-TR30-2/U-TR30NIR Wide field trinocular
Stage	Motorized stage	· IX5-SSA: Stage stroke: X: 116mm x Y: 78mm, maximum stage movement speed: 40mm/s. Knob controller · 3rd party motorized stage
	Mechanical stage with left handle Mechanical stage with right handle	Stage stroke: X: 116mm x Y: 78mm, stage position locking function
	Right handle stage	Stage stroke: X: 50mm x Y: 50mm
	Gliding stage	Upper circular stage 360° rotatable, 20 mm (X/Y) travel
	Plain stage	232 mm (X) x 240 mm (Y) stage size, stage insert plate exchangeable (ø110 mm)
Condenser	Motorized long working distance condenser	W.D. 27 mm, NA 0.55, motorized turret with 7 position slots for optical devices (3 positions for ø30 mm and 4 positions for ø38 mm), motorized aperture and polarizer
	Long working distance universal condenser	NA 0.55, W.D. 27 mm 5 positions for optical devices (3 positions for ø30 mm and 2 position for ø38 mm)
	Ultra long working distance	NA 0.3, W.D. 73.3 mm, 4 positions for optical devices (for ø29 mm)
Fluorescence illuminator	L-shape-fluorescence illuminator	L-shaped design with exchangeable FS and AS modules, slider shutter and ND filter pocket
Fluorescence mirror turret	Motorized fluorescence mirror turret	Motorized turret with 8 positions, built-in shutter, simple waterproof structure
Fluorescence light source		· U-LGPS: LED and LDP light source, Class 1 laser product · 3rd party LED light source
Control unit (IX5-MCZ)		Nosepiece position, light path selection, filter turret position, FL shutter ON/OFF, DIA LED power, DIA LED ON/OFF, 4 customizable buttons
Control box	PC interface	USB (Type-C), RS-232C
Operating environment	- Indoor use - Ambient temperature: 5o to 40o C (41o to 104o F) - Maximum relative humidity: 80% for temperatures up to 31 oC (88 oF), decreasing linearly through 70% at 34 oC (93 oF), 60% at 37o C (99o F), to 50% relative humidity at 40o C (104o F) - Supply voltage fluctuations: Not to exceed ±10% of the normal voltage¹⁾	



EVIDENT
OLYMPUS

LABEX
FLUOCCA
IMARIS

GREINER
BIOSCIENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTK

TEKSQRAY
FEATHER

DYNAMICA
FROILABO

FASTER
ARCTIKO
KUHNER
HETTICH

HBK
CAMECA
IX CAMERAS

THERMO EM
CRYSTAL