

SZX16 / SZX10

Research Stereo Microscope System

SZX2 series stereo microscopes are up to the challenge of leading-edge microscopy applications, offering an exceptionally wide zoom ratio and high numerical aperture (NA). Excellent image clarity and a flexible optical system make the SZX2 series easy to use, while their advanced optics, improved functionality, and ergonomic design deliver an outstanding user experience.

SZX16

Designed for advanced research, the SZX16 stereo microscope's darkfield and polarization capabilities, 0.3 numerical aperture, and large 16.4:1 zoom ratio enable you to image whole organisms down to fine microscopic and individual cell structures.

SZX10

A flexible imaging tool for routine research, the SZX10 stereo microscope offers darkfield and polarized light imaging, a maximum numerical aperture of 0.2, a 10:1 zoom ratio, and a Galileian optical system that minimizes distortion.

Specifications

	SZX16	SZX10
Optical system	Telescope type system	
Zoom range	0.7X – 11.5X (zoom ratio 1: 16.4) Click stop equipped (releasable)	0.63X – 6.3X (zoom ratio 1: 10.0)
Aperture diaphragm	Built-in	
Total mag. range	2.1X – 690X	3.15X – 378X
Working distance	141 (with SDFPLFL0.3X) – 20 mm (with SDFPLAPO2XPFC)	171 (with DFPL 0.5X) – 33.5 mm (with DFPL2X-4)
Observation tube	SZX2-TTR/SZX2-TTRPT: tilting trinocular, 5 – 45° variable inclination SZX2-TR30/SZX2-TR30PT: 30 degree trinocular, 30° inclination SZX2-LTTR: Ergonomic long tilting trinocular, 5 – 45° variable inclination	
	—	SZX-BI30: 30° binocular, 30° inclination SZX-BI45: 45° binocular, 5 – 45° variable inclination
Extendable eyepoint adjuster	SZX2-EEPA: Height adjustment range: adjuster 30–150 mm (with a scale attached)	
Objective	SDFPLFL0.3X, SDFPLAPO0.5XPF, SDFPLAPO0.8X, SDFPLAPO1XPF, SDFPLAPO1.6XPF, SDFPLAPO2XPFC	DFPL0.5X-4, DFPL0.75X-4 DFPLAPOIX-4, SZX-ACHIX, DFPLAPOI25X, SZX-ACHI25X-2 DFPLI5X-4, DFPL2X-4
Eyepiece	WHNIOX-H (FN 22)	WHSZIOX-H (FN 22)
	WHSZI5X-H (FN 16), WHSZ20X-H (FN 12.5), WHSZ30X-H (FN 7)	
Focusing	SZX2-FO : Focusing unit, coarse handle stroke 80 mm SZX2-FOF : Fine focusing unit, coarse handle stroke 80 mm, fine handle stroke 80 mm SZX2-FOFH : Fine focusing unit for heavy loading, stroke 80 mm fine handle stroke 80 mm SZX2-FOA: Motorized focus unit, focusing stroke 78 mm	
Accessories	Fluorescence illuminator, coaxial illuminator, light beam splitter, revolving nosepiece, large stage plate, stage adapter	
	—	Eyepoint adjuster, arrow pointer, drawing attachment, side by side discussion tube, etc.
Dimensions (W × D × H)	SZX16: 268 mm × 386 mm × 413 mm (Standard Set Configuration), SZX10: 268 mm × 386 mm × 410 mm (Standard Set Configuration)	



SZX16
with fluorescence system



SZX10



LABEX
FLUOCCA
IMARIS

GREINER
BIOSCIENCE

APPLIED
SPECTRAL
IMAGING

SAKURA
FINETEK

ZTEC
CRAFTEK

TEKSQRAY
FEATHER

DYNAMICA
FROILABO

FASTER
ARCTIKO
KUHNER
HEITICH

HBK
CAMECA
IX CAMERAS

THERMO EM
CRYSTAL