# **API Endpoints**

#### Accounts

# Registration

# POST http://127.0.0.1:8000/accounts/register/

Registers a user with username, first name, last name, email, phone number, avatar(optional). All fields are mandatory, except for avatar.

# Payload

- username
- password
- first\_name
- last\_name
- email
- phone\_num
- avatar

# Login

# POST http://127.0.0.1:8000/accounts/login/

Logins a user with username and password. Returns an access token (to be used in subsequent calls) and refresh token.

**Note:** Set {{access\_token}} in Authorization header as the given access token for all subsequent views.

#### **Payload**

- username
- password

## **Password Change**

## PATCH http://127.0.0.1:8000/accounts/changepassword/

Change password for user. Requires the user to enter the old password (password) and new password (password2). Authorization required.

#### Payload

- password
- password2

### View Profile

#### **GET** http://127.0.0.1:8000/accounts/profile/view/

Returns user's profile information, including first name, last name, email, phone number, and avatar. Authorization required.

#### **HEADERS**

Authorization: Bearer {{access token}}

#### **Edit Profile**

### PATCH <a href="http://127.0.0.1:8000/accounts/profile/edit/">http://127.0.0.1:8000/accounts/profile/edit/</a>

Allows user to edit any field of their profile, including first name, last name, email, phone number, and avatar. Authorization required.

**Note:** Only include fields to change in the payload. Keys with empty values not allowed.

# **HEADERS**

Authorization: Bearer {{access token}}

#### Payload

- first\_name
- last\_name
- email

- phone\_num
- avatar

# Logging out

# POST http://127.0.0.1:8000/accounts/logout/

Logs out user by deleting the refresh token. Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

**Payload** 

refresh

#### Studios & Classes

### Sort by Current Location

# **GET** http://127.0.0.1:8000/studio/sortby/currlocation/

Returns a list of studio objects based on proximity to user's current location. Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

# Sort by Geographical Point

# GET http://127.0.0.1:8000/studio/sortby/point/

Returns a list of studio objects based on a geographical point. Studios are sorted by proximity (closest listed first). Authorization required.

**HEADERS** 

### **Payload**

- latitude
- longitude

### Sort by Postal Code

**GET** http://127.0.0.1:8000/studio/sortby/postcode/

Returns a list of studio objects based on proximity to a given post code. Authorization required.

#### **HEADERS**

Authorization: Bearer {{access token}}

### Payload

post\_code

#### **Get Studio Details**

**GET** <u>http://127.0.0.1:8000/studio/{{studio\_num}}/details/</u>

Returns studio details for given studio id (e.g. details for studio 5). Authorization required

#### **HEADERS**

Authorization: Bearer {{access token}}

### **Get Studio Classes**

GET <a href="http://127.0.0.1:8000/studio/{{studio\_num}}/classes">http://127.0.0.1:8000/studio/{{studio\_num}}/classes</a>

Returns all the class instances in a studio for given studio id (e.g. classes for studio 5). Classes are sorted based on their start time (past and canceled classes are not included). Authorization required

#### **HEADERS**

# **Enroll In Class Instance**

**POST** http://127.0.0.1:8000/class/{{class num}}/enrol

Enroll in any of the currently available class instances for some class (e.g. an instance from class 2). Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

Payload

• enrolled\_time

Note: enrolled\_time is the id of the class instance, e.e 242

### **Enroll In All Class Instances**

**POST** http://127.0.0.1:8000/class/{{class\_num}}/enrol/all

Enroll in all of the currently available class instances for some class (e.g. instances for class 2). Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

# **Drop Class Instance**

POST http://127.0.0.1:8000/class/{{class\_num}}/drop

Drop any of the currently enrolled class instances for some class (e.g. an instance from class 2). Authorization required.

**HEADERS** 

### Payload

enrolled\_time

Note: enrolled\_time is the id of the class instance, e.g. 242

# **Drop All Class Instances**

**POST** http://127.0.0.1:8000/class/{{class num}}/drop/all

Drop all of the currently enrolled class instances for some class (e.g. instances for class 2). Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

# Class Schedule

**GET** http://127.0.0.1:8000/class/schedule

Returns the user's schedule, i.e., all the class instances the user is currently enrolled in .

**HEADERS** 

Authorization: Bearer {{access token}}

### Class History

**GET** http://127.0.0.1:8000/class/history

Returns the user's history, i.e., all the class instances the user enrolled in in the past.

**HEADERS** 

# Filter Studios

# **GET** http://127.0.0.1:8000/<u>studio</u>/filter

Filter the available studios based on one or more of the given input query parameters (eg. <a href="http://127.0.0.1:8000/studio/filter/?studio\_name=UStudio&amenity=Pool&class\_name=Yoga&coach=Bob">http://127.0.0.1:8000/studio/filter/?studio\_name=UStudio&amenity=Pool&class\_name=Yoga&coach=Bob</a>

#### **HEADERS**

Authorization: Bearer {{access token}}

#### **PARAMS**

- studio\_name
- amenity
- class\_name
- coach

### Filter Studio Class Schedule

### GET <a href="http://127.0.0.1:8000/studio/{{class\_num}}/classes/filter">http://127.0.0.1:8000/studio/{{class\_num}}/classes/filter</a>

Filter the available class instances for a studio based on one or more of the given input query parameters (eg. <a href="http://127.0.0.1:8000/studio/5/classes/filter/?">http://127.0.0.1:8000/studio/5/classes/filter/?</a> class name=Yoga&coach=Bob&date=2022-01-01&start time=07:00:00&end time=08:00:00)

#### **HEADERS**

Authorization: Bearer {{access token}}

#### **PARAMS**

- class\_name
- coach
- date (YYYY-MM-DD)
- start\_time (HH:MM:SS)
- end\_time (HH:MM:SS)

# Subscriptions

# Subscribe to Plan Options

# POST http://127.0.0.1:8000/subscriptions/subscribe/

Subscribes the user to a unique membership plan. Authorization required.

#### **HEADERS**

Authorization: Bearer {{access token}}

## Payload

- membership
- card\_num
- card\_expiry\_month
- card\_expiry\_year
- card\_cvv

# **Update Card Information**

### PUT <a href="http://127.0.0.1:8000/subscriptions/card/edit/">http://127.0.0.1:8000/subscriptions/card/edit/</a>

Updates the card information for the payment method. Authorization and subscription required.

#### **HEADERS**

Authorization: Bearer {{access token}}

### Payload

- card\_num
- card\_expiry\_month
- card\_expiry\_year
- card\_cvv

# View Payment History

**GET** <a href="http://127.0.0.1:8000/subscriptions/payments/history/">http://127.0.0.1:8000/subscriptions/payments/history/</a>

Displays a list of past payments for the user. Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

View Future Payments

GET http://127.0.0.1:8000/subscriptions/payments/future/

Displays the next payment for a user. Authorization required.

**HEADERS** 

Authorization: Bearer {{access token}}

**Cancel Subscription** 

**DELETE** <a href="http://127.0.0.1:8000/subscriptions/cancel/">http://127.0.0.1:8000/subscriptions/cancel/</a>

Cancels the membership for a user. Authorization and current subscription required.

**HEADERS** 

Authorization: Bearer {{access token}}

**Update Subscription** 

PUT http://127.0.0.1:8000/subscriptions/edit/

Updates the membership for a user. Authorization and current subscription required.

**HEADERS** 

# Payload

membership

# Design of Models

### UserProfile

- Username
- First\_name
- Last\_name
- Password
- Password2
- Email - Avatar
- phone\_num



