

Experiment-9

Aim: Consider the following tables namely “DEPARTMENTS” and “EMPLOYEES” Their schemas

Code:

```
1 • CREATE DATABASE company_db;
2 • USE company_db;

1 • CREATE TABLE Departments (
2     dept_no      INT PRIMARY KEY,
3     dept_name    VARCHAR(50),
4     dept_location VARCHAR(50)
5 );
6 • CREATE TABLE Employees (
7     emp_id       INT PRIMARY KEY,
8     emp_name     VARCHAR(50),
9     emp_salary   DECIMAL(10,2),
10    dept_no      INT,
11    FOREIGN KEY (dept_no) REFERENCES Departments(dept_no)
12 );

1 • INSERT INTO Departments VALUES
2     (10, 'HR', 'Delhi'),
3     (20, 'Finance', 'Mumbai'),
4     (30, 'IT', 'Pune');
5
6     INSERT INTO Employees VALUES
7     (1, 'Faiz', 50000, 10),
8     (2, 'Muskan', 60000, 20),
9     (3, 'Amisha', 55000, 30);

1 • CREATE USER 'user1'@'localhost' IDENTIFIED BY '1234';
```

(a) Grant ALL privileges

```
1 GRANT ALL PRIVILEGES
2 ON Employees
3 TO 'user1'@'localhost';
```

(b) Grant SOME privileges

```
1 GRANT SELECT, INSERT, UPDATE
2 ON Employees
3 TO 'user1'@'localhost';
```

(c) Revoke ALL privileges

```
1 REVOKE ALL PRIVILEGES
2 ON Employees
3 FROM 'user1'@'localhost';
```

(d) Revoke SOME privileges

```
1 REVOKE INSERT, UPDATE
2 ON Employees
3 FROM 'user1'@'localhost';
```

```
1 SET autocommit = 0;
2
3 START TRANSACTION;
4
5 INSERT INTO Employees VALUES (4, 'Muskan', 70000, 10);
6
7 SAVEPOINT sp1;
8
9 UPDATE Employees
10 SET emp_salary = 80000
11 WHERE emp_id = 4;
12
13 ROLLBACK TO sp1;
14
15 COMMIT;
```