

SCSS Fundamentals

To install SASS (Windows):

```
npm install -g sass
```

To convert SASS to CSS file:

```
sass style.scss style.css
```

Variable:

```
$primary-color: blue;
$secondary-color: orange;
$warning-color: yellow;
$danger-color: red;
$success-color: green;
$title-font-size: 20px;

.text{
    color: $danger-color;
}

body{
    background-color: $secondary-color;
}
```

To convert SASS to CSS file:

```
sass variable.scss variable.css
```

Converted CSS:

```
.text {
  color: red;
}

body {
  background-color: orange;
}

/*# sourceMappingURL=variable.css.map */
```

```
<body>
  <h1 class="text">Hello</h1>
</body>
```

Import and Partial file:

Create another file (partial file) for variables, for partial we write like this: **__variable.scss**

```
$primary-color: blue;
$secondary-color: rgb(0, 217, 255);
$warning-color: yellow;
$danger-color: red;
$success-color: green;
$title-font-size: 20px;
```

import that partial file to main file (style.scss)

```
@import "variable";

.text{
  color: $danger-color;
}

body{
  background-color: $secondary-color;
}
```

Mixin:

Just like variables, if we have any code block which will be repeated, we can use that code block with @mixin keyword and can use this mixin with @include repeatedly.

Created a partial file **_mixin.scss**

```
@mixin btn-default-style {
  border: 2px solid $danger-color;
  color: #fff;
  padding: 40px 50px;
  border-radius: 5px;
  font-size: 16px;
}
```

main SASS file:

```

@import "variable";
@import "mixin";

.btn1{
    @include btn-default-style();
    background-color: $primary-color;
    cursor: grab;
}

.btn2 {
    @include btn-default-style();
    background-color: $secondary-color;
    cursor: pointer;
}

.btn3 {
    @include btn-default-style();
    background-color: $warning-color;
    cursor: not-allowed;
}

.btn4 {
    @include btn-default-style();
    background-color: $danger-color;
    cursor: zoom-in;
}

```

Converted CSS file:

```

.btn1 {
    border: 2px solid red;
    color: #fff;
    padding: 40px 50px;
    border-radius: 5px;
    font-size: 16px;
    background-color: blue;
    cursor: grab;
}

.btn2 {
    border: 2px solid red;
    color: #fff;
    padding: 40px 50px;
    border-radius: 5px;
    font-size: 16px;
    background-color: rgb(0, 217, 255);
    cursor: pointer;
}

```

```

.btn3 {
  border: 2px solid red;
  color: #fff;
  padding: 40px 50px;
  border-radius: 5px;
  font-size: 16px;
  background-color: yellow;
  cursor: not-allowed;
}

.btn4 {
  border: 2px solid red;
  color: #fff;
  padding: 40px 50px;
  border-radius: 5px;
  font-size: 16px;
  background-color: red;
  cursor: zoom-in;
}

/*# sourceMappingURL=mixin.css.map */

```

```

<body>
  <button class="btn1">Submit1</button>
  <button class="btn2">Submit2</button>
  <button class="btn3">Submit3</button>
  <button class="btn4">Submit4</button>
</body>

```

Mixin with Parameters:

```

@mixin default-button-style($color, $background-color, $cursor) {
  color: $color;
  border: 5px solid $fourth-color;
  border-radius: 5px;
  padding: 20px 25px;
  background-color: $background-color;
  cursor: $cursor;
}

```

main SASS file:

```

@import 'variable';
@import 'mixin';

.btn1{

```

```

    @include default-button-style(black, $fifth-color, pointer);
}

.btn2{
    @include default-button-style(black, $third-color, grab);
}

.btn3{
    @include default-button-style(white, $fourth-color, not-allowed);
}

.btn4{
    @include default-button-style(blue, $second-color, default);
}

```

Inheritance (like Mixin, used for code repetition purpose):

```

.button-base-style{
    border: 5px solid black;
    border-radius: 5px;
    color: white;
}

.button-primary{
    @extend .button-base-style;
    background-color: blue;
}

.button-secondary{
    @extend .button-base-style;
    background-color: red;
}

```

```

.button-base-style, .button-secondary, .button-primary {
    border: 5px solid black;
    border-radius: 5px;
    color: white;
}

.button-primary {
    background-color: blue;
}

.button-secondary {
    background-color: red;
}

```

```
<body>
  <button class="button-primary">Submit</button>
  <button class="button-secondary">Cancel</button>
</body>
```

Mathematical Operations:

```
$default-font-size: 16px;

.text-1{
  font-size: $default-font-size + 10px;
}

.text-2 {
  font-size: $default-font-size - 10px;
}

.text-3 {
  font-size: $default-font-size * 2;
}

.text-4 {
  font-size: $default-font-size / 2;
}
```

```
.text-1 {
  font-size: 26px;
}

.text-2 {
  font-size: 6px;
}

.text-3 {
  font-size: 32px;
}

.text-4 {
  font-size: 8px;
}
```

```
<body>
  <div class="my-div">
    <p class="text-1">text1</p>
    <p class="text-2">text2</p>
    <p class="text-3">text3</p>
```

```
<p class="text-4">text4</p>
</div>
</body>
```

For Loop:

```
$default-font-size: 16px;

@for $i from 1 through 10{
  .text-#{ $i } {
    font-size: $default-font-size + $i;
  }
}
```

```
.text-1 {
  font-size: 17px;
}

.text-2 {
  font-size: 18px;
}

.text-3 {
  font-size: 19px;
}

.text-4 {
  font-size: 20px;
}

.text-5 {
  font-size: 21px;
}

.text-6 {
  font-size: 22px;
}

.text-7 {
  font-size: 23px;
}

.text-8 {
  font-size: 24px;
}

.text-9 {
  font-size: 25px;
}
```

```
}

.text-10 {
  font-size: 26px;
}
```

```
<body>
  <div class="my-div">
    <p class="text-1">text1</p>
    <p class="text-2">text2</p>
    <p class="text-3">text3</p>
    <p class="text-4">text4</p>
    <p class="text-5">text5</p>
    <p class="text-6">text6</p>
    <p class="text-7">text7</p>
    <p class="text-8">text8</p>
    <p class="text-9">text9</p>
    <p class="text-10">text10</p>
  </div>
</body>
```

If-else:

```
$dark-mode: false;

.navbar{
  @if $dark-mode {
    background-color: black;
    color: white;
  }

  @else{
    background-color: white;
    color: black;
  }
}
```

```
.navbar {
  background-color: white;
  color: black;
}
```