

General details

Shielded LED bollard with wide beam light distribution for a high degree of illuminance on the ground surface.

A reflector directs the light directly onto the surface to be illuminated.

Robust and striking luminaires that can divide up and structure outdoor spaces. They have an orienting, guiding and demarcating function.

For the illumination of squares entrance or rectangular it's a perfect choice.


Dettagli generali

Paletto LED schermato con distribuzione luminosa a fascio largo per un elevato illuminamento al suolo.



Un riflettore dirige la luce direttamente sulla superficie da illuminare.

Apparecchi robusti e suggestivi in grado di dividere e strutturare gli spazi esterni. Hanno una funzione di orientamento, guida e delimitazione.


Per l'illuminazione di piazze d'ingresso o rettangolari è una scelta perfetta.



Mounting plate



Description :

Code	Wattage	Lumen	Size	
LL-BL-4408-15W	15 W	1650 lm	150 x 150 x 800 H mm	-----
LL-BL-4408-18W	18 W	1980 lm	150 x 150 x 800 H mm	-----
LL-BL-4408-20W	20 W	2200 lm	150 x 150 x 1000 H mm	-----

360°



3000 K
4000 K
6000 K

IP 67

AC220-240V

CRI
>80

85~265V
50/60Hz



PHASE
DIMMING



LED



TRIDONIC
enlightening your ideas



OSRAM CREE PHILIPS