

<PROJECT PDF DUMP>

Generated at: 2026-04-23T13:22:51.688077 UTC

Root: C:\Users\morty\video-exchange-bot

Files included: 16

```
=====
FILE: .env
=====
```

```
BOT_TOKEN=8747618457:AAHz0LNqPr4wnSW0dDhT0xLwyREc-JKHINI
ADMINS=5272076117
WEBHOOK_BASE=https://placeholder.onrender.com
WEBHOOK_PATH=/webhook
DATABASE_URL=sqlite+aiosqlite:///bot.db
PORT=10000
```

```
=====
FILE: .env.example
=====
```

```
BOT_TOKEN=123456:ABC-DEF
ADMINS=123456789
WEBHOOK_BASE=https://your-app.onrender.com
WEBHOOK_PATH=/webhook
DATABASE_URL=postgresql+asyncpg://user:password@host:5432/dbname
```

```
=====
FILE: app\__init__.py
=====
```

```
=====
FILE: app\admin_handlers.py
=====
```

```
from datetime import datetime
from decimal import Decimal
```

```
from aiogram import Router, F
from aiogram.filters import Command
from aiogram.fsm.state import State, StatesGroup
from aiogram.fsm.context import FSMContext
from aiogram.types import Message, CallbackQuery, InlineKeyboardMarkup, InlineKeyboardButton
```

```
from sqlalchemy import select
```

```
from app.config import ADMINS
from app.db import async_session
from app.models import User
from app.services import (
```

```
    get_user,
    get_user_by_id,
    get_user_by_username,
    get_user_dossier,
    update_user_balance,
    set_user_ban_status,
    count_pending_videos,
    count_approved_videos,
    count_rejected_videos,
```

```
)
```

```
router = Router()
```

```
# =====
# STATES
# =====
```

```
class AdminUserState(StatesGroup):
    waiting_user_id = State()
    waiting_coins_amount = State()
    waiting_message_text = State()
```

```

class AdminManageState(StatesGroup):
    waiting_new_admin = State()
    waiting_remove_admin = State()

# =====
# HELPERS
# =====

def is_super_admin(tid: int) -> bool:
    return tid in ADMINS

async def check_admin(tid: int) -> bool:
    if tid in ADMINS:
        return True

    async with async_session() as session:
        user = await get_user(session, tid)
        if user and user.is_admin:
            return True

    return False

# =====
# ADMIN PANEL ENTRY
# =====

@router.message(Command("admin"))
async def cmd_admin(message: Message):
    if not await check_admin(message.from_user.id):
        return

    sa = is_super_admin(message.from_user.id)

    buttons = [
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_queue_info")],
        [InlineKeyboardButton(text="■ ■■■■■■■■■■■■", callback_data="admin_manage_users")],
    ]

    if sa:
        buttons.append(
            [InlineKeyboardButton(text="■ ■■■■■■■■■■ ■■■■■■■■", callback_data="admin_manage_admins")]
        )

    kb = InlineKeyboardMarkup(inline_keyboard=buttons)

    await message.answer("■ <b>■■■■■-■■■■■</b>", parse_mode="HTML", reply_markup=kb)

# =====
# QUEUE INFO
# =====

@router.callback_query(F.data == "admin_queue_info")
async def cb_queue(callback: CallbackQuery):
    if not await check_admin(callback.from_user.id):
        return

    async with async_session() as session:
        p = await count_pending_videos(session)
        a = await count_approved_videos(session)
        r = await count_rejected_videos(session)

    text = (
        f"■ <b>■■■■■■■■■■ ■■■■■</b>\n\n"
        f"■ ■ ■■■■■■■■: <b>{p}</b>\n\n"

```

```

        f"■ ■■■■■■■■: <b>{a}</b>\n"
        f"■ ■■■■■■■■: <b>{r}</b>"
    )

    await callback.message.edit_text(text, parse_mode="HTML")
    await callback.answer()

# =====
# ADMIN MANAGEMENT SYSTEM
# =====

@router.callback_query(F.data == "admin_manage_admins")
async def manage_admins_menu(callback: CallbackQuery):
    if not is_super_admin(callback.from_user.id):
        return

    kb = InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_list_admins")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_add_admin")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_remove_admin")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_back")],
    ])

    await callback.message.edit_text(
        "■ <b>■■■■■■■■■ ■■■■■■■■</b>",
        parse_mode="HTML",
        reply_markup=kb
    )
    await callback.answer()

@router.callback_query(F.data == "admin_back")
async def admin_back(callback: CallbackQuery):
    await cmd_admin(callback.message)
    await callback.answer()

# ■ LIST ADMINS
@router.callback_query(F.data == "admin_list_admins")
async def list_admins(callback: CallbackQuery):
    if not is_super_admin(callback.from_user.id):
        return

    async with async_session() as session:
        result = await session.execute(
            select(User).where(User.is_admin == True)
        )
        admins = result.scalars().all()

    if not admins:
        text = "■■■■■■■ ■■■."
    else:
        text = "■ <b>■■■■■■■ ■■■■■■■■:</b>\n\n"
        for admin in admins:
            text += f"• {admin.first_name or '■■■ ■■■■■'} (ID: <code>{admin.telegram_id}</code>"
    text += ">)\n"

    await callback.message.answer(text, parse_mode="HTML")
    await callback.answer()

# ■ ADD ADMIN
@router.callback_query(F.data == "admin_add_admin")
async def add_admin_start(callback: CallbackQuery, state: FSMContext):
    if not is_super_admin(callback.from_user.id):
        return

    await state.set_state(AdminManageState.waiting_new_admin)
    await callback.message.answer(

```

```

    "■■■■■■■■ Telegram ID ■■■■■■■■ ■■■ ■■■■■■■■: "
)
await callback.answer()

@router.message(AdminManageState.waiting_new_admin)
async def process_add_admin(message: Message, state: FSMContext):
    if not is_super_admin(message.from_user.id):
        return

    if not message.text.isdigit():
        await message.answer("■■■■■ ■■■■■■ ■■■■■■■■ Telegram ID.")
        return

    telegram_id = int(message.text)

    async with async_session() as session:
        user = await get_user(session, telegram_id)
        if not user:
            await message.answer(
                "■■■■■■■■■■■■■■ ■■ ■■■■■■.\n"
                "■■ ■■■■■■ ■■■■■■■■ ■■■■■■■■ ■■■■ /start."
            )
            await state.clear()
            return

        user.is_admin = True
        await session.commit()

    await message.answer(f"■ ■■■■■■■■■■■■ {telegram_id} ■■■■■■ ■■■■■.")
    await state.clear()

# ■ REMOVE ADMIN
@router.callback_query(F.data == "admin_remove_admin")
async def remove_admin_start(callback: CallbackQuery, state: FSMContext):
    if not is_super_admin(callback.from_user.id):
        return

    await state.set_state(AdminManageState.waiting_remove_admin)
    await callback.message.answer(
        "■■■■■■■ Telegram ID ■■■■■■ ■■■ ■■■■■■■■: "
    )
    await callback.answer()

@router.message(AdminManageState.waiting_remove_admin)
async def process_remove_admin(message: Message, state: FSMContext):
    if not is_super_admin(message.from_user.id):
        return

    if not message.text.isdigit():
        await message.answer("■■■■■ ■■■■■■ ■■■■■■■■ Telegram ID.")
        return

    telegram_id = int(message.text)

    async with async_session() as session:
        user = await get_user(session, telegram_id)
        if not user or not user.is_admin:
            await message.answer("■■■■■ ■■■■■■■■■■■■■■ ■■ ■■■■■■■■ ■■■■■■■■.")
            await state.clear()
            return

        user.is_admin = False
        await session.commit()

    await message.answer(f"■ ■■■■■■■■■■■■ {telegram_id} ■■■■■■ ■■ ■■■■■.")
    await state.clear()

```

```

=====
FILE: app\config.py
=====

import os
from dotenv import load_dotenv

load_dotenv()

def _get_str(name: str, default: str = "") -> str:
    return os.getenv(name, default).strip()

def _get_int(name: str, default: int) -> int:
    raw = os.getenv(name)
    if raw is None:
        return default
    raw = raw.strip()
    try:
        return int(raw)
    except Exception:
        return default

def _get_float(name: str, default: float) -> float:
    raw = os.getenv(name)
    if raw is None:
        return default
    raw = raw.strip()
    try:
        return float(raw)
    except Exception:
        return default

BOT_TOKEN = _get_str("BOT_TOKEN")
DATABASE_URL = _get_str("DATABASE_URL")
BOT_USERNAME = _get_str("BOT_USERNAME")
PROVIDER_TOKEN = _get_str("PROVIDER_TOKEN")
WEBHOOK_BASE = _get_str("WEBHOOK_BASE")
WEBHOOK_PATH = _get_str("WEBHOOK_PATH")
LOG_CHAT_ID = _get_str("LOG_CHAT_ID")

ADMINS_RAW = _get_str("ADMINS")
ADMINS = []
for x in ADMINS_RAW.split(","):
    x = x.strip()
    if x.isdigit():
        ADMINS.append(int(x))

PORT = _get_int("PORT", 10000)

STARTING_BALANCE = _get_float("STARTING_BALANCE", 2.0)
WATCH_COST = _get_float("WATCH_COST", 1.0)
UPLOAD_REWARD = _get_float("UPLOAD_REWARD", 0.5)

REFERRAL_REWARD_INVITER = _get_float("REFERRAL_REWARD_INVITER", 2.0)
REFERRAL_REWARD_NEW_USER = _get_float("REFERRAL_REWARD_NEW_USER", 1.0)

STARS_TO_COINS_RATE = _get_float("STARS_TO_COINS_RATE", 2.0)

STARS_PACKAGES = {
    "pack_1": {"stars": 1, "coins": 2, "title": "2 \u043c\u043e\u043d\u0435\u0442\u044b"},
    "pack_5": {"stars": 5, "coins": 10, "title": "10 \u043c\u043e\u043d\u0435\u0442"},
    "pack_10": {"stars": 10, "coins": 20, "title": "20 \u043c\u043e\u043c\u0435\u0442"},
    "pack_25": {"stars": 25, "coins": 50, "title": "50 \u043c\u043e\u043c\u0435\u0442"},
    "pack_50": {"stars": 50, "coins": 100, "title": "100 \u043c\u043e\u043c\u0435\u0442"},
}

MONEY_PACKAGES = {

```

```

    "money_99": {"amount": 9900, "coins": 250, "title": "250 \u043c\u043e\u043d\u0435\u0442"},
    "money_199": {"amount": 19900, "coins": 600, "title": "600 \u043c\u043e\u043d\u0435\u0442"},
    "money_499": {"amount": 49900, "coins": 1800, "title": "1800 \u043c\u043e\u043d\u0435\u0442"}
},
}

OFFER_BROADCAST_INTERVAL_HOURS = _get_float("OFFER_BROADCAST_INTERVAL_HOURS", 2.5)

# === LEVELS ===
LEVEL_XP_BASE = _get_int("LEVEL_XP_BASE", 100)
LEVEL_XP_MULTIPLIER = _get_float("LEVEL_XP_MULTIPLIER", 1.5)

XP_PER_WATCH = _get_int("XP_PER_WATCH", 5)
XP_PER_UPLOAD = _get_int("XP_PER_UPLOAD", 20)
XP_PER_RATING = _get_int("XP_PER_RATING", 2)
XP_PER_COMMENT = _get_int("XP_PER_COMMENT", 3)
XP_PER_REACTION = _get_int("XP_PER_REACTION", 1)
XP_PER_GAME = _get_int("XP_PER_GAME", 3)

# === VIP ===
VIP_PRICE_STARS = _get_int("VIP_PRICE_STARS", 50)
VIP_DURATION_DAYS = _get_int("VIP_DURATION_DAYS", 30)
VIP_BONUS_MULTIPLIER = _get_float("VIP_BONUS_MULTIPLIER", 3.0)
VIP_FREE_PHOTOS = True
VIP_WATCH_DISCOUNT = _get_float("VIP_WATCH_DISCOUNT", 0.5)

# === GAMES ===
DICE_MIN_BET = _get_int("DICE_MIN_BET", 1)
DICE_MAX_BET = _get_int("DICE_MAX_BET", 50)

# === QUESTS ===
DAILY_QUESTS = [
    {"type": "watch", "target": 3, "reward": 2, "desc": "\u041f\u043e\u0441\u043c\u043e\u0442\u0438 3 \u0432\u0438\u0434\u0435\u043d\u0438\u044f"},
    {"type": "upload", "target": 1, "reward": 3, "desc": "\u0417\u0430\u0433\u0440\u0443\u043d\u0438\u0442\u0438 1 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442\u0438\u0442"},
    {"type": "rate", "target": 3, "reward": 1, "desc": "\u041e\u0446\u0435\u043d\u0438\u0442\u0438 3 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442"},
    {"type": "comment", "target": 2, "reward": 2, "desc": "\u041e\u0441\u0442\u0430\u0432\u0438\u0442\u0438 2 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442\u0438\u0442"},
    {"type": "react", "target": 5, "reward": 1, "desc": "\u041f\u043e\u0442\u0440\u0430\u0442\u0438 5 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442"}
]

PREMIUM_DAILY_QUESTS = [
    {"type": "watch", "target": 10, "reward": 8, "desc": "VIP: \u041f\u043e\u0441\u043c\u043e\u0442\u0438 10 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442"},
    {"type": "comment", "target": 5, "reward": 5, "desc": "VIP: \u041e\u0441\u0442\u0430\u0432\u0438\u0442\u0438 5 \u0432\u0438\u0434\u0435\u043d\u0438\u0442\u0438\u0442"}
]

REACTION_TYPES = ["\u0001f525", "\u2764\u2765", "\u0001f602", "\u0001f44d", "\u0001f4af"]

# === ANTI-SPAM COMMENTS ===
COMMENTS_PER_10_MIN = _get_int("COMMENTS_PER_10_MIN", 5)
COMMENT_MIN_INTERVAL_SEC = _get_int("COMMENT_MIN_INTERVAL_SEC", 15)

# === WEEKLY REWARDS ===
WEEKLY_TOP1_REWARD = _get_float("WEEKLY_TOP1_REWARD", 25.0)
WEEKLY_TOP2_REWARD = _get_float("WEEKLY_TOP2_REWARD", 15.0)
WEEKLY_TOP3_REWARD = _get_float("WEEKLY_TOP3_REWARD", 10.0)

# === MONETIZATION ===
PIN_OFFER_COST = _get_float("PIN_OFFER_COST", 100.0)
BUMP_VIDEO_COST = _get_float("BUMP_VIDEO_COST", 25.0)

=====
FILE: app\db.py
=====
from sqlalchemy.ext.asyncio import create_async_engine, async_sessionmaker, AsyncSession

```

```
from app.config import DATABASE_URL
from app.models import Base
```

```
def _fix_url(url: str) -> str:
    if url.startswith("postgres://"):
        return url.replace("postgres://", "postgresql+asyncpg://", 1)
    if url.startswith("postgresql://"):
        return url.replace("postgresql://", "postgresql+asyncpg://", 1)
    return url
```

```
engine = create_async_engine(
    _fix_url(DATABASE_URL),
    echo=False,
)
```

```
async_session = async_sessionmaker(
    engine,
    class_=AsyncSession,
    expire_on_commit=False,
)
```

```
async def init_db():
    async with engine.begin() as conn:
        await conn.run_sync(Base.metadata.create_all)
```

```
async def reset_db():
    async with engine.begin() as conn:
        await conn.run_sync(Base.metadata.drop_all)
        await conn.run_sync(Base.metadata.create_all)
```

```
=====
FILE: app\keyboards.py
=====
```

```
from aiogram.types import InlineKeyboardMarkup, InlineKeyboardButton, ReplyKeyboardMarkup, KeyboardButton
```

```
# Buttons
BTN_WATCH = "■ ■■■■■■■■"
BTN_UPLOAD = "■ ■■■■■■■■"
BTN_PROFILE = "■ ■■■■■■■■"
BTN_BUY = "■ ■■■■■■■■"
BTN_OFFERS = "■ ■■■■■■■■"
BTN_REFERRALS = "■ ■■■■■■■■"
BTN_BONUS = "■ ■■■■■■■■"
BTN_ADMIN = "■ ■■■■■■■■"
BTN_GAMES = "■ ■■■■■■■■"
BTN_TOPS = "■ ■■■■■■■■"
BTN_QUESTS = "■ ■■■■■■■■"
BTN_VIP = "■ VIP"
BTN_LEVEL = "■ ■■■■■■■■"
```

```
def main_menu(is_admin: bool = False) -> ReplyKeyboardMarkup:
    kb = [
        [KeyboardButton(text=BTN_WATCH), KeyboardButton(text=BTN_UPLOAD)],
        [KeyboardButton(text=BTN_PROFILE), KeyboardButton(text=BTN_GAMES)],
        [KeyboardButton(text=BTN_OFFERS), KeyboardButton(text=BTN_BUY)],
        [KeyboardButton(text=BTN_REFERRALS), KeyboardButton(text=BTN_BONUS)],
        [KeyboardButton(text=BTN_QUESTS), KeyboardButton(text=BTN_TOPS)],
        [KeyboardButton(text=BTN_LEVEL), KeyboardButton(text=BTN_VIP)],
    ]
    if is_admin:
        kb.append([KeyboardButton(text=BTN_ADMIN)])
    return ReplyKeyboardMarkup(keyboard=kb, resize_keyboard=True)
```

```
def admin_center_keyboard(is_super_admin: bool = False) -> InlineKeyboardMarkup:
```

```

        buttons = [
            [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_queue_info")],
            [InlineKeyboardButton(text="■ ■■■■■■■■■■+", callback_data="admin_extended_stats")],
            [InlineKeyboardButton(text="■ ■■■■■■■■■■ ■■■■■■■■■■■■", callback_data="admin_manage_users")],
            [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data="admin_get_pending")],
            [InlineKeyboardButton(text="■ ■■■■■■■■ ■■■■", callback_data="admin_approve_all")],
            [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="admin_offers_menu")],
        ]
        if is_super_admin:
            buttons.append([InlineKeyboardButton(text="■ ■■■■■■■■■■ ■■■■■■■■■■", callback_data="admin_manage_admins")])
        return InlineKeyboardMarkup(inline_keyboard=buttons)

def moderation_keyboard(video_id: int) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [
            InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data=f"mod_approve:{video_id}"),
            InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data=f"mod_reject:{video_id}"),
        ],
        [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data="admin_get_pending")],
    ])

def rejection_reason_keyboard(video_id: int) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data=f"reject_reason:{video_id}:duplicate")],
        [InlineKeyboardButton(text="■ ■■ ■■ ■■■■■■■■■■", callback_data=f"reject_reason:{video_id}:off_topic")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data=f"reject_reason:{video_id}:other")],
    ],
    ])

def admin_after_action_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data="admin_get_pending")],
        [InlineKeyboardButton(text="■ ■■■■■■-■■■■■■", callback_data="admin_center")],
    ])

def offer_view_keyboard(offer_id: int, channel_url: str) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■ ■ ■■■■■■■■", url=channel_url)],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data=f"offer_start:{offer_id}")],
        [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data=f"offer_check:{offer_id}")],
    ])

def games_menu_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="game_dice")],
        [InlineKeyboardButton(text="■ ■■■■■■■■■■", callback_data="game_coinflip")],
        [InlineKeyboardButton(text="■ ■■■■■■■■ ■■■■■■■■", callback_data="game_guess")],
    ])

def tops_menu_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■ ■■■■■■■■■■■■", callback_data="top_uploaders")],
        [InlineKeyboardButton(text="■ ■■■ ■■■■■■■■■■■■", callback_data="top_viewers")],
        [InlineKeyboardButton(text="■ ■■■ ■■ XP", callback_data="top_levels")],
        [InlineKeyboardButton(text="■ ■■■ ■■■■■■■■■■■■", callback_data="top_richest")],
    ])

def watch_choice_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="watch_video_content")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="watch_photo_content")],
    ])

def video_rating_keyboard(video_id: int) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[

```



```

        InlineKeyboardButton(text="■ 1", callback_data=f"rate:{video_id}:1"),
        InlineKeyboardButton(text="■ 2", callback_data=f"rate:{video_id}:2"),
        InlineKeyboardButton(text="■ 3", callback_data=f"rate:{video_id}:3"),
        InlineKeyboardButton(text="■ 4", callback_data=f"rate:{video_id}:4"),
        InlineKeyboardButton(text="■ 5", callback_data=f"rate:{video_id}:5"),
    ],
    [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data=f"comments:{video_id}")),
    [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="watch_next")],
])

def photo_actions_keyboard(photo_id: int) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■ ■■■■", callback_data="watch_next_photo")],
    ])

def rules_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■■■■ ■■■■■■■", callback_data="accept_rules")],
    ])

def buy_coins_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ 10 ■■■■■ (5 Stars)", callback_data="buy:pack_5")],
        [InlineKeyboardButton(text="■ 20 ■■■■■ (10 Stars)", callback_data="buy:pack_10")],
        [InlineKeyboardButton(text="■ 50 ■■■■■ (25 Stars)", callback_data="buy:pack_25")],
        [InlineKeyboardButton(text="■ 100 ■■■■■ (50 Stars)", callback_data="buy:pack_50")],
        [InlineKeyboardButton(text="■ ■■■■ ■■■■■", callback_data="buy_custom")],
    ])

def vip_buy_keyboard() -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text="■ ■■■■■ VIP", callback_data="buy_vip")],
    ])

def offers_list_keyboard(offers) -> InlineKeyboardMarkup:
    buttons = []
    for o in offers:
        icon = "■" if o.is_active else "■"
        buttons.append([InlineKeyboardButton(text=f"{icon} {o.title}", callback_data=f"offer_open:{o.id}"))]
    return InlineKeyboardMarkup(inline_keyboard=buttons)

def quests_keyboard(quests) -> InlineKeyboardMarkup:
    buttons = []
    for q in quests:
        status = "■" if q.completed else "■"
        buttons.append([InlineKeyboardButton(text=f"{status} {q.quest_type}: {q.progress}/{q.target}", callback_data=f"quest_claim:{q.id}"))]
    return InlineKeyboardMarkup(inline_keyboard=buttons)

def reaction_menu_keyboard(video_id: int) -> InlineKeyboardMarkup:
    return InlineKeyboardMarkup(inline_keyboard=[
        [
            InlineKeyboardButton(text="■", callback_data=f"react:{video_id}:■"),
            InlineKeyboardButton(text="♥■", callback_data=f"react:{video_id}:♥■"),
            InlineKeyboardButton(text="■", callback_data=f"react:{video_id}:■"),
            InlineKeyboardButton(text="■", callback_data=f"react:{video_id}:■"),
            InlineKeyboardButton(text="■", callback_data=f"react:{video_id}:■"),
        ]
    ])

```

```

=====
FILE: app\logger.py
=====
import json
import logging
import traceback
from datetime import datetime

```

```

def get_logger(name: str) -> logging.Logger:
    return logging.getLogger(name)

def _make_payload(message: str, **kwargs) -> str:
    payload = {
        "time": datetime.utcnow().isoformat() + "Z",
        "message": message,
    }
    payload.update(kwargs)
    return json.dumps(payload, ensure_ascii=False)

def setup_logging(level: int = logging.INFO):
    root = logging.getLogger()
    root.setLevel(level)

    while root.handlers:
        root.handlers.pop()

    handler = logging.StreamHandler()
    handler.setLevel(level)
    handler.setFormatter(logging.Formatter("%(message)s"))
    root.addHandler(handler)

def log_info(logger: logging.Logger, message: str, **kwargs):
    logger.info(_make_payload(message, **kwargs))

def log_warning(logger: logging.Logger, message: str, **kwargs):
    logger.warning(_make_payload(message, **kwargs))

def log_error(logger: logging.Logger, message: str, **kwargs):
    logger.error(_make_payload(message, **kwargs))

def log_exception(logger: logging.Logger, message: str, **kwargs):
    kwargs["traceback"] = traceback.format_exc()
    logger.error(_make_payload(message, **kwargs))

def log_event(logger: logging.Logger, level: int, message: str, **kwargs):
    logger.log(level, _make_payload(message, **kwargs))

```

```

=====
FILE: app\main.py
=====
import asyncio
import logging
from aiohttp import web
from aiogram import Bot, Dispatcher
from aiogram.client.default import DefaultBotProperties
from aiogram.enums import ParseMode
from app.config import BOT_TOKEN, PORT
from app.db import engine, async_session, init_db
from app.user_handlers import router as user_router
from app.admin_handlers import router as admin_router
from app.logger import setup_logging, get_logger, log_info

setup_logging()
logger = get_logger(__name__)

async def on_startup(app):
    from app.migrate import main as run_migrations
    await init_db()
    try:
        await run_migrations()

```

```

except Exception as e:
    log_info(logger, f"Migrations warning: {e}")
log_info(logger, "Bot starting up... DB initialized")

async def main():
    if not BOT_TOKEN:
        raise RuntimeError("BOT_TOKEN is empty")

    bot = Bot(
        token=BOT_TOKEN,
        default=DefaultBotProperties(parse_mode=ParseMode.HTML),
    )

    dp = Dispatcher()
    dp.include_router(user_router)
    dp.include_router(admin_router)

    app = web.Application()
    app.on_startup.append(on_startup)

    runner = web.AppRunner(app)
    await runner.setup()
    site = web.TCPSite(runner, "0.0.0.0", int(PORT or 10000))
    await site.start()

    try:
        log_info(logger, "Polling started")
        await dp.start_polling(bot)
    finally:
        await runner.cleanup()
        await bot.session.close()
        await engine.dispose()

if __name__ == "__main__":
    asyncio.run(main())

=====
FILE: app\make_project_pdf.py
=====
import os
from pathlib import Path
from datetime import datetime

from reportlab.lib.pagesizes import A4
from reportlab.pdfbase.pdfmetrics import stringWidth
from reportlab.pdfgen import canvas

PROJECT_ROOT = Path(".")
OUTPUT_FILE = "project_dump.pdf"

MAX_PAGES = 90
MAX_SIZE_MB = 15

INCLUDE_EXTENSIONS = {
    ".py",
    ".txt",
    ".md",
    ".json",
    ".yaml",
    ".yml",
    ".toml",
    ".ini",
    ".env",
    ".sql",
}

SPECIAL_FILENAMES = {

```

```

    "Dockerfile",
    "Procfile",
    "requirements.txt",
    "runtime.txt",
    ".env",
}

EXCLUDED_DIRS = {
    ".git",
    ".venv",
    "venv",
    "__pycache__",
    "node_modules",
    ".idea",
    ".vscode",
    "dist",
    "build",
    ".pytest_cache",
    ".mypy_cache",
    ".ruff_cache",
    ".cache",
}

EXCLUDED_FILES = {
    OUTPUT_FILE,
}

MAX_FILE_SIZE_KB = 300

def is_text_candidate(path: Path) -> bool:
    if path.name in SPECIAL_FILENAMES:
        return True
    if path.suffix.lower() in INCLUDE_EXTENSIONS:
        return True
    if path.name.startswith(".env"):
        return True
    return False

def should_skip(path: Path) -> bool:
    if path.is_dir():
        return True

    if path.name in EXCLUDED_FILES:
        return True

    parts = set(path.parts)
    if parts & EXCLUDED_DIRS:
        return True

    if not is_text_candidate(path):
        return True

    try:
        if path.stat().st_size > MAX_FILE_SIZE_KB * 1024:
            return True
    except Exception:
        return True

    return False

def iter_project_files(root: Path):
    files = []
    for path in root.rglob("*"):
        if should_skip(path):
            continue
        files.append(path)
    files.sort(key=lambda p: str(p).lower())

```

```

return files

def safe_read_text(path: Path) -> str:
    for enc in ("utf-8", "utf-8-sig", "cp1251", "latin-1"):
        try:
            return path.read_text(encoding=enc)
        except Exception:
            pass
    return "[[FAILED TO READ FILE]]"

def wrap_line(line: str, font_name: str, font_size: int, max_width: float):
    if not line:
        return [""]

    if stringWidth(line, font_name, font_size) <= max_width:
        return [line]

    parts = []
    current = ""

    for ch in line:
        test = current + ch
        if stringWidth(test, font_name, font_size) <= max_width:
            current = test
        else:
            if current:
                parts.append(current)
            current = ch

    if current:
        parts.append(current)

    return parts

def build_blocks(root: Path):
    files = iter_project_files(root)
    blocks = []

    header = [
        "<PROJECT PDF DUMP>",
        f"Generated at: {datetime.utcnow().isoformat()} UTC",
        f"Root: {root.resolve()}",
        f"Files included: {len(files)}",
        "",
    ]
    blocks.append("\n".join(header))

    for path in files:
        rel = path.relative_to(root)
        content = safe_read_text(path).rstrip()

        block = [
            "=" * 80,
            f"FILE: {rel}",
            "=" * 80,
            content,
            "",
        ]
        blocks.append("\n".join(block))

    return blocks, files

def render_pdf(blocks, output_path: str):
    page_width, page_height = A4

    configs = [

```

```

        {"font_size": 9, "line_gap": 11, "margin": 36},
        {"font_size": 8, "line_gap": 9, "margin": 26},
        {"font_size": 7, "line_gap": 8, "margin": 18},
        {"font_size": 6, "line_gap": 7, "margin": 14},
    ]

    best_result = None

    for cfg in configs:
        c = canvas.Canvas(output_path, pagesize=A4)
        font_name = "Courier"
        font_size = cfg["font_size"]
        line_gap = cfg["line_gap"]
        margin = cfg["margin"]

        usable_width = page_width - margin * 2
        y = page_height - margin
        pages = 1

        c.setFont(font_name, font_size)

        def new_page():
            nonlocal y, pages
            c.showPage()
            c.setFont(font_name, font_size)
            y = page_height - margin
            pages += 1

        for block in blocks:
            for raw_line in block.splitlines():
                wrapped = wrap_line(raw_line, font_name, font_size, usable_width)
                for line in wrapped:
                    if y < margin:
                        new_page()
                    c.drawString(margin, y, line)
                    y -= line_gap

            if y < margin:
                new_page()
            y -= line_gap

        c.save()

        size_bytes = os.path.getsize(output_path)
        size_mb = size_bytes / (1024 * 1024)

        best_result = {
            "pages": pages,
            "size_bytes": size_bytes,
            "size_mb": size_mb,
            "config": cfg,
        }

    if pages <= MAX_PAGES and size_mb <= MAX_SIZE_MB:
        return best_result

    return best_result


def main():
    blocks, files = build_blocks(PROJECT_ROOT)
    result = render_pdf(blocks, OUTPUT_FILE)

    print("=" * 60)
    print(f"PDF created: {OUTPUT_FILE}")
    print(f"Files included: {len(files)}")
    print(f"Pages: {result['pages']}")
    print(f"Size: {result['size_mb']:.2f} MB")
    print(f"Config used: {result['config']}")
    print("=" * 60)

```

```

    if result["pages"] > MAX_PAGES:
        print(f"WARNING: PDF exceeds page limit ({result['pages']} > {MAX_PAGES})")

    if result["size_mb"] > MAX_SIZE_MB:
        print(f"WARNING: PDF exceeds size limit ({result['size_mb']:.2f} MB > {MAX_SIZE_MB} MB)")
)

```

```

if __name__ == "__main__":
    main()

```

```

=====
FILE: app\migrate.py
=====

```

```

import asyncio
from sqlalchemy import text
from app.db import engine

```

```

MIGRATIONS = [
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS created_by_user_id INTEGER NULL;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS offer_kind VARCHAR(30) DEFAULT 'system';
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS promotion_tier VARCHAR(30) DEFAULT 'basic';
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS payment_method VARCHAR(20) NULL;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS promo_price_coins NUMERIC(12,2) DEFAULT 0;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS promo_price_rub INTEGER DEFAULT 0;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS promo_price_stars INTEGER DEFAULT 0;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS priority_level INTEGER DEFAULT 10;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS is_featured BOOLEAN DEFAULT FALSE;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS moderation_comment TEXT NULL;
    """,
    """
    ALTER TABLE offers
    ADD COLUMN IF NOT EXISTS approved_at TIMESTAMPTZ NULL;
    """,
    """
    CREATE INDEX IF NOT EXISTS ix_offers_created_by_user_id ON offers (created_by_user_id);
    """,
    """
    CREATE INDEX IF NOT EXISTS ix_offers_status ON offers (status);
    """,

```

```

"""
CREATE TABLE IF NOT EXISTS game_sessions (
    id SERIAL PRIMARY KEY,
    user_id INTEGER NOT NULL REFERENCES users(id),
    window_start TIMESTAMP NOT NULL,
    games_played INTEGER DEFAULT 0,
    paid_at TIMESTAMP NULL
);
"""
"""
CREATE INDEX IF NOT EXISTS ix_game_sessions_user_id ON game_sessions (user_id);
"""
]

```

```

async def main():
    async with engine.begin() as conn:
        for sql in MIGRATIONS:
            await conn.execute(text(sql))
    await engine.dispose()
    print("Migrations applied successfully")

```

```

if __name__ == "__main__":
    asyncio.run(main())

```

```

=====
FILE: app\models.py
=====
from datetime import datetime
from decimal import Decimal

```

```

from sqlalchemy import (
    BigInteger,
    String,
    Numeric,
    Boolean,
    Integer,
    DateTime,
    ForeignKey,
    UniqueConstraint,
    Text,
    Date,
)
from sqlalchemy.orm import DeclarativeBase, Mapped, mapped_column, relationship

```

```

class Base(DeclarativeBase):
    pass

```

```

class User(Base):
    __tablename__ = "users"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    telegram_id: Mapped[int] = mapped_column(BigInteger, unique=True, nullable=False, index=True)
)
    username: Mapped[str | None] = mapped_column(String(255), nullable=True, index=True)
    first_name: Mapped[str | None] = mapped_column(String(255), nullable=True)
    last_name: Mapped[str | None] = mapped_column(String(255), nullable=True)
    phone_number: Mapped[str | None] = mapped_column(String(50), nullable=True)
    balance: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    status: Mapped[str] = mapped_column(String(50), default="active")
    is_admin: Mapped[bool] = mapped_column(Boolean, default=False)
    agreed_to_rules: Mapped[bool] = mapped_column(Boolean, default=False)
    referral_code: Mapped[str | None] = mapped_column(String(50), unique=True, nullable=True)
    referred_by_user_id: Mapped[int | None] = mapped_column(ForeignKey("users.id"), nullable=True)
e)
    referral_earnings: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    last_bonus_at: Mapped[datetime | None] = mapped_column(DateTime, nullable=True)

```



```

xp: Mapped[int] = mapped_column(Integer, default=0)
level: Mapped[int] = mapped_column(Integer, default=1)
vip_until: Mapped[datetime | None] = mapped_column(DateTime, nullable=True)
created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

videos: Mapped[list["Video"]] = relationship(back_populates="uploader")
views: Mapped[list["VideoView"]] = relationship(back_populates="user")
ratings: Mapped[list["VideoRating"]] = relationship(back_populates="user")
payments: Mapped[list["Payment"]] = relationship(back_populates="user")
comments: Mapped[list["Comment"]] = relationship(back_populates="user")
reactions: Mapped[list["ContentReaction"]] = relationship(back_populates="user")
game_history: Mapped[list["GameHistory"]] = relationship(back_populates="user")
quest_progress: Mapped[list["DailyQuestProgress"]] = relationship(back_populates="user")
game_sessions: Mapped[list["GameSession"]] = relationship(back_populates="user")
action_logs: Mapped[list["UserActionLog"]] = relationship(back_populates="user")
user_offers: Mapped[list["Offer"]] = relationship(back_populates="creator")

class UserActionLog(Base):
    __tablename__ = "user_action_logs"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False, index=True)
    action: Mapped[str] = mapped_column(String(255), nullable=False)
    details: Mapped[str | None] = mapped_column(Text, nullable=True)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="action_logs")

class Video(Base):
    __tablename__ = "videos"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    uploader_user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    content_type: Mapped[str] = mapped_column(String(20), default="video")
    telegram_file_id: Mapped[str] = mapped_column(Text, nullable=False)
    telegram_file_unique_id: Mapped[str] = mapped_column(String(255), nullable=False, index=True)

    status: Mapped[str] = mapped_column(String(20), default="pending")
    duration_seconds: Mapped[int | None] = mapped_column(Integer, nullable=True)
    file_size: Mapped[int | None] = mapped_column(BigInteger, nullable=True)
    rejection_reason: Mapped[str | None] = mapped_column(String(255), nullable=True)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    uploader: Mapped["User"] = relationship(back_populates="videos")
    views: Mapped[list["VideoView"]] = relationship(back_populates="video")
    ratings: Mapped[list["VideoRating"]] = relationship(back_populates="video")
    comments: Mapped[list["Comment"]] = relationship(back_populates="video")
    reactions: Mapped[list["ContentReaction"]] = relationship(back_populates="video")

class VideoView(Base):
    __tablename__ = "video_views"

    __table_args__ = (
        UniqueConstraint("user_id", "video_id", name="uq_user_video_view"),
    )

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    video_id: Mapped[int] = mapped_column(ForeignKey("videos.id"), nullable=False)
    watched_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="views")
    video: Mapped["Video"] = relationship(back_populates="views")

class VideoRating(Base):
    __tablename__ = "video_ratings"

```

```

__table_args__ = (
    UniqueConstraint("user_id", "video_id", name="uq_user_video_rating"),
)

id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
video_id: Mapped[int] = mapped_column(ForeignKey("videos.id"), nullable=False)
rating: Mapped[int] = mapped_column(Integer, nullable=False)
created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

user: Mapped["User"] = relationship(back_populates="ratings")
video: Mapped["Video"] = relationship(back_populates="ratings")

class Comment(Base):
    __tablename__ = "comments"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    video_id: Mapped[int] = mapped_column(ForeignKey("videos.id"), nullable=False)
    text: Mapped[str] = mapped_column(Text, nullable=False)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="comments")
    video: Mapped["Video"] = relationship(back_populates="comments")

class ContentReaction(Base):
    __tablename__ = "content_reactions"

    __table_args__ = (
        UniqueConstraint("user_id", "video_id", name="uq_user_video_reaction"),
    )

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    video_id: Mapped[int] = mapped_column(ForeignKey("videos.id"), nullable=False)
    reaction_type: Mapped[str] = mapped_column(String(10), nullable=False)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="reactions")
    video: Mapped["Video"] = relationship(back_populates="reactions")

class Payment(Base):
    __tablename__ = "payments"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    payload: Mapped[str] = mapped_column(String(255), unique=True, nullable=False)
    stars_amount: Mapped[int] = mapped_column(Integer, nullable=False)
    coins_amount: Mapped[Decimal] = mapped_column(Numeric(10, 2), nullable=False)
    status: Mapped[str] = mapped_column(String(50), default="pending")
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="payments")

class Offer(Base):
    __tablename__ = "offers"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    creator_user_id: Mapped[int | None] = mapped_column(ForeignKey("users.id"), nullable=True)
    title: Mapped[str] = mapped_column(String(255), nullable=False)
    description: Mapped[str] = mapped_column(Text, nullable=False)
    channel_url: Mapped[str] = mapped_column(Text, nullable=False)
    reward_preview: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=5)
    reward_final: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=35)
    penalty_unsubscribe: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=40)

```

```

is_active: Mapped[bool] = mapped_column(Boolean, default=True)
status: Mapped[str] = mapped_column(String(20), default="approved")
created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

creator: Mapped["User"] = relationship(back_populates="user_offers")

class OfferParticipation(Base):
    __tablename__ = "offer_participations"

    __table_args__ = (
        UniqueConstraint("user_id", "offer_id", name="uq_user_offer"),
    )

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    offer_id: Mapped[int] = mapped_column(ForeignKey("offers.id"), nullable=False)
    status: Mapped[str] = mapped_column(String(50), default="started")
    reward_given: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)
    checked_at: Mapped[datetime | None] = mapped_column(DateTime, nullable=True)

class GameHistory(Base):
    __tablename__ = "game_history"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    game_type: Mapped[str] = mapped_column(String(50), nullable=False)
    bet: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    result: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    details: Mapped[str | None] = mapped_column(Text, nullable=True)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="game_history")

class DailyQuestProgress(Base):
    __tablename__ = "daily_quest_progress"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    quest_type: Mapped[str] = mapped_column(String(50), nullable=False)
    quest_date: Mapped[datetime] = mapped_column(Date, nullable=False)
    progress: Mapped[int] = mapped_column(Integer, default=0)
    target: Mapped[int] = mapped_column(Integer, nullable=False)
    reward: Mapped[Decimal] = mapped_column(Numeric(10, 2), default=0)
    completed: Mapped[bool] = mapped_column(Boolean, default=False)
    reward_claimed: Mapped[bool] = mapped_column(Boolean, default=False)
    created_at: Mapped[datetime] = mapped_column(DateTime, default=datetime.utcnow)

    user: Mapped["User"] = relationship(back_populates="quest_progress")

class GameSession(Base):
    __tablename__ = "game_sessions"

    id: Mapped[int] = mapped_column(Integer, primary_key=True, autoincrement=True)
    user_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False, index=True)
    window_start: Mapped[datetime] = mapped_column(DateTime, nullable=False)
    games_played: Mapped[int] = mapped_column(Integer, default=0)
    paid_at: Mapped[datetime | None] = mapped_column(DateTime, nullable=True)

    user: Mapped["User"] = relationship(back_populates="game_sessions")

```

```

=====
FILE: app\services.py
=====
import uuid
import random

```

[illegible]

```

async def get_or_create_user(session, telegram_id, username=None, first_name=None, last_name=None, referral_code=None):
    user = await get_user(session, telegram_id)
    if user:
        user.username = username
        user.first_name = first_name
        user.last_name = last_name
        await session.commit()
        return user, False

    referred_by = None
    if referral_code:
        inviter = (await session.execute(select(User).where(User.referral_code == referral_code))).scalar_one_or_none()
        if inviter and inviter.telegram_id != telegram_id:
            referred_by = inviter.id
            inviter.balance += to_decimal(REFERRAL_REWARD_INVITER)
            inviter.referral_earnings += to_decimal(REFERRAL_REWARD_INVITER)

    user = User(
        telegram_id=telegram_id,
        username=username,
        first_name=first_name,
        last_name=last_name,
        balance=to_decimal(STARTING_BALANCE) + (to_decimal(REFERRAL_REWARD_NEW_USER) if referred_by else 0),
        referral_code=uuid.uuid4().hex[:8],
        referred_by_user_id=referred_by,
        is_admin=False,
    )
    session.add(user)
    await session.commit()
    await log_user_action(session, user.id, "registration", f"Referred by: {referred_by}")
    return user, True

async def approve_video(session: AsyncSession, video_id: int):
    """ ██████████ ██████████ ██████████ ██████████ ██████████ ██████████ ██████████ """
    v = (await session.execute(select(Video).where(Video.id == video_id))).scalar_one_or_none()
    if not v or v.status != "pending":
        return v
    v.status = "approved"
    up = await get_user_by_id(session, v.uploader_user_id)
    if up:
        reward = PHOTO_UPLOAD_REWARD if v.content_type == "photo" else to_decimal(UPLOAD_REWARD)
        up.balance += reward
        await log_user_action(session, up.id, "video_approved", f"Video ID: {v.id}, Reward: {reward}")
    await session.commit()
    return v

async def reject_video(session: AsyncSession, video_id: int, reason: str):
    v = (await session.execute(select(Video).where(Video.id == video_id))).scalar_one_or_none()
    if not v: return None
    v.status = "rejected"
    v.rejection_reason = reason
    await session.commit()
    await log_user_action(session, v.uploader_user_id, "video_rejected", f"Video ID: {v.id}, Reason: {reason}")
    return v

async def get_user_dossier(session: AsyncSession, user_id: int):
    """ ██████████ ██████████ ██████████ ██████████ ██████████ ██████████ ██████████ """
    user = await get_user_by_id(session, user_id)
    if not user: return None

    games_count = (await session.execute(select(func.count(GameHistory.id)).where(GameHistory.user_id == user_id))).scalar_one()
    videos_uploaded = (await session.execute(select(func.count(Video.id)).where(Video.uploader_user_id == user_id))).scalar_one()

```

```

        videos_watched = (await session.execute(select(func.count(VideoView.id)).where(VideoView.user_id == user_id))).scalar_one()

        # =====
        logs = (await session.execute(select(UserActionLog).where(UserActionLog.user_id == user_id).order_by(desc(UserActionLog.created_at)))).scalars().all()

        return {
            "user": user,
            "games_count": games_count,
            "videos_uploaded": videos_uploaded,
            "videos_watched": videos_watched,
            "logs": logs
        }

    async def update_user_balance(session: AsyncSession, user_id: int, amount: Decimal, admin_id: int):
        user = await get_user_by_id(session, user_id)
        if user:
            user.balance += amount
            await log_user_action(session, user_id, "balance_update", f"By admin {admin_id}, Amount: {amount}")
            await session.commit()
            return True
        return False

    async def set_user_ban_status(session: AsyncSession, user_id: int, is_banned: bool, admin_id: int):
        user = await get_user_by_id(session, user_id)
        if user:
            user.status = "banned" if is_banned else "active"
            await log_user_action(session, user_id, "ban_status_change", f"By admin {admin_id}, Banned: {is_banned}")
            await session.commit()
            return True
        return False

    # =====
    async def get_next_pending_video(session):
        return (await session.execute(select(Video).where(Video.status == "pending").order_by(Video.created_at).limit(1))).scalar_one_or_none()

    async def count_pending_videos(session):
        return (await session.execute(select(func.count(Video.id)).where(Video.status == "pending"))).scalar_one()

    async def count_approved_videos(session):
        return (await session.execute(select(func.count(Video.id)).where(Video.status == "approved"))).scalar_one()

    async def count_rejected_videos(session):
        return (await session.execute(select(func.count(Video.id)).where(Video.status == "rejected"))).scalar_one()

    async def get_admin_extended_stats(session):
        return {
            "users": (await session.execute(select(func.count(User.id)))).scalar_one(),
            "vip": (await session.execute(select(func.count(User.id)).where(User.vip_until > datetime.utcnow()))).scalar_one(),
            "comments": (await session.execute(select(func.count(Comment.id)))).scalar_one(),
            "reactions": (await session.execute(select(func.count(ContentReaction.id)))).scalar_one(),
            "games": (await session.execute(select(func.count(GameHistory.id)))).scalar_one(),
            "offers": (await session.execute(select(func.count(Offer.id)))).scalar_one(),
        }

    async def save_video(session: AsyncSession, user_id: int, file_id: str, file_unique_id: str, duration: int = None, file_size: int = None):
        video = Video(
            uploader_user_id=user_id,
            content_type="video",

```

```

        telegram_file_id=file_id,
        telegram_file_unique_id=file_unique_id,
        duration_seconds=duration,
        file_size=file_size,
        status="pending",
    )
    session.add(video)
    await session.commit()
    await log_user_action(session, user_id, "upload_video", f"File: {file_unique_id}")
    return video

async def save_photo(session: AsyncSession, user_id: int, file_id: str, file_unique_id: str, file_size: int = None):
    photo = Video(
        uploader_user_id=user_id,
        content_type="photo",
        telegram_file_id=file_id,
        telegram_file_unique_id=file_unique_id,
        file_size=file_size,
        status="pending",
    )
    session.add(photo)
    await session.commit()
    await log_user_action(session, user_id, "upload_photo", f"File: {file_unique_id}")
    return photo

async def get_random_video_for_user(session: AsyncSession, user_id: int):
    viewed = select(VideoView.video_id).where(VideoView.user_id == user_id)
    stmt = select(Video).where(
        Video.status == "approved",
        Video.content_type == "video",
        Video.uploader_user_id != user_id,
        ~Video.id.in_(viewed)
    ).order_by(func.random()).limit(1)
    return (await session.execute(stmt)).scalar_one_or_none()

async def get_random_photo_for_user(session: AsyncSession, user_id: int):
    stmt = select(Video).where(
        Video.status == "approved",
        Video.content_type == "photo",
        Video.uploader_user_id != user_id,
    ).order_by(func.random()).limit(1)
    return (await session.execute(stmt)).scalar_one_or_none()

async def record_view_and_charge(session: AsyncSession, user_id: int, video_id: int):
    user = await get_user_by_id(session, user_id)
    if not user:
        return False
    cost = to_decimal(WATCH_COST)
    if user.balance < cost:
        return False
    user.balance -= cost
    user.xp += 5
    view = VideoView(user_id=user_id, video_id=video_id)
    session.add(view)
    try:
        await session.commit()
    except Exception:
        await session.rollback()
    return True

async def record_photo_view(session: AsyncSession, user_id: int, photo_id: int):
    view = VideoView(user_id=user_id, video_id=photo_id)
    session.add(view)
    try:
        await session.commit()
    except Exception:
        await session.rollback()

async def count_photo_views_last_4h(session: AsyncSession, user_id: int) -> int:

```

```

since = datetime.utcnow() - timedelta(hours=4)
stmt = select(func.count(VideoView.id)).where(
    VideoView.user_id == user_id,
    VideoView.watched_at >= since,
)
return (await session.execute(stmt)).scalar_one()

async def rate_video(session: AsyncSession, user_id: int, video_id: int, rating: int):
    existing = (await session.execute(
        select(VideoRating).where(VideoRating.user_id == user_id, VideoRating.video_id == video_
id)
    )).scalar_one_or_none()
    if existing:
        existing.rating = rating
    else:
        session.add(VideoRating(user_id=user_id, video_id=video_id, rating=rating))
    await session.commit()

async def claim_daily_bonus(session: AsyncSession, user_id: int):
    user = await get_user_by_id(session, user_id)
    if not user:
        return False, "██████████ █ ██████"
    now = datetime.utcnow()
    if user.last_bonus_at and (now - user.last_bonus_at).total_seconds() < 86400:
        remaining = 86400 - (now - user.last_bonus_at).total_seconds()
        hours = int(remaining // 3600)
        minutes = int((remaining % 3600) // 60)
        return False, f"██████████ ██████████. ██████████ ██████████ {hours} ██████████ {minutes}██████████"
    bonus = to_decimal(1.0)
    user.balance += bonus
    user.last_bonus_at = now
    await session.commit()
    return True, bonus

async def count_referrals(session: AsyncSession, user_id: int) -> int:
    stmt = select(func.count(User.id)).where(User.referred_by_user_id == user_id)
    return (await session.execute(stmt)).scalar_one()

async def create_payment(session: AsyncSession, user_id: int, pack_key: str):
    pack = STARS_PACKAGES.get(pack_key)
    if not pack:
        return None
    payload = f"{user_id}_{pack_key}_{uuid.uuid4().hex[:8]}"
    payment = Payment(
        user_id=user_id,
        payload=payload,
        stars_amount=pack["stars"],
        coins_amount=to_decimal(pack["coins"]),
        status="pending",
    )
    session.add(payment)
    await session.commit()
    return payment

async def create_custom_payment(session: AsyncSession, user_id: int, stars: int):
    coins = to_decimal(stars) * to_decimal(STARS_TO_COINS_RATE)
    payload = f"{user_id}_custom_{uuid.uuid4().hex[:8]}"
    payment = Payment(
        user_id=user_id,
        payload=payload,
        stars_amount=stars,
        coins_amount=coins,
        status="pending",
    )
    session.add(payment)
    await session.commit()
    return payment

async def apply_successful_payment(session: AsyncSession, payload: str):
    payment = (await session.execute(

```



```

        select(Payment).where(Payment.payload == payload)
   )).scalar_one_or_none()
    if not payment or payment.status == "completed":
        return None
    payment.status = "completed"
    user = await get_user_by_id(session, payment.user_id)
    if user:
        user.balance += payment.coins_amount
    await session.commit()
    return payment

async def get_active_offers(session: AsyncSession):
    stmt = select(Offer).where(Offer.is_active == True, Offer.status == "approved")
    return (await session.execute(stmt)).scalars().all()

async def get_offer_by_id(session: AsyncSession, offer_id: int):
    return (await session.execute(select(Offer).where(Offer.id == offer_id))).scalar_one_or_none()

async def start_offer_participation(session: AsyncSession, user_id: int, offer_id: int):
    existing = (await session.execute(
        select(OfferParticipation).where(
            OfferParticipation.user_id == user_id,
            OfferParticipation.offer_id == offer_id
        )
    )).scalar_one_or_none()
    if existing:
        return existing, False
    offer = await get_offer_by_id(session, offer_id)
    if not offer:
        return None, False
    user = await get_user_by_id(session, user_id)
    if user:
        user.balance += offer.reward_preview
    part = OfferParticipation(user_id=user_id, offer_id=offer_id, status="started", reward_given=offer.reward_preview)
    session.add(part)
    await session.commit()
    return part, True

async def verify_offer_subscription(session: AsyncSession, user_id: int, offer_id: int):
    part = (await session.execute(
        select(OfferParticipation).where(
            OfferParticipation.user_id == user_id,
            OfferParticipation.offer_id == offer_id
        )
    )).scalar_one_or_none()
    if not part:
        return False
    if part.status == "completed":
        return True
    part.status = "completed"
    part.checked_at = datetime.utcnow()
    offer = await get_offer_by_id(session, offer_id)
    user = await get_user_by_id(session, user_id)
    if offer and user:
        additional = offer.reward_final - part.reward_given
        if additional > 0:
            user.balance += additional
            part.reward_given = offer.reward_final
    await session.commit()
    return True

```

```

=====
FILE: app\user_handlers.py
=====

```

```

from decimal import Decimal
from aiogram import Router, F
from aiogram.filters import CommandStart, CommandObject
from aiogram.types import Message, CallbackQuery, LabeledPrice, PreCheckoutQuery, InlineKeyboard

```

```

Markup, InlineKeyboardButton
from aiogram.fsm.context import FSMContext
from aiogram.fsm.state import State, StatesGroup
from app.config import (
    ADMINS, WATCH_COST, STARS_PACKAGES, STARS_TO_COINS_RATE, REACTION_TYPES,
    XP_PER_WATCH, XP_PER_UPLOAD, XP_PER_RATING, XP_PER_COMMENT, XP_PER_REACTION, XP_PER_GAME,
    PIN_OFFER_COST
)
from app.db import async_session
from app.services import (
    get_or_create_user, get_user, save_video, save_photo, get_random_video_for_user,
    get_random_photo_for_user, record_view_and_charge, record_photo_view,
    count_photo_views_last_4h, rate_video, claim_daily_bonus, count_referrals,
    create_payment, create_custom_payment, apply_successful_payment,
    get_active_offers, get_offer_by_id, start_offer_participation,
    verify_offer_subscription, log_user_action, to_decimal
)
from app.keyboards import (
    rules_keyboard, main_menu, video_rating_keyboard, photo_actions_keyboard,
    watch_choice_keyboard, buy_coins_keyboard, vip_buy_keyboard,
    offers_list_keyboard, offer_view_keyboard, games_menu_keyboard,
    tops_menu_keyboard, quests_keyboard, reaction_menu_keyboard,
    BTN_WATCH, BTN_UPLOAD, BTN_PROFILE, BTN_BUY, BTN_OFFERS, BTN_REFERRALS,
    BTN_BONUS, BTN_ADMIN, BTN_GAMES, BTN_TOPS, BTN_QUESTS, BTN_VIP, BTN_LEVEL
)
from app.logger import get_logger, log_info, log_warning, log_exception

logger = get_logger(__name__)
router = Router()

class UserOfferState(StatesGroup):
    waiting_title = State()
    waiting_description = State()
    waiting_url = State()
    waiting_payment = State()

def is_any_admin(telegram_id: int, user_obj=None) -> bool:
    if telegram_id in ADMINS: return True
    if user_obj and user_obj.is_admin: return True
    return False

@router.message(CommandStart())
async def cmd_start(message: Message, command: CommandObject, state: FSMContext):
    print("START COMMAND RECEIVED")
    if not message.from_user: return
    await state.clear()
    referral_code = command.args.strip() if command and command.args else None
    async with async_session() as session:
        user, is_new = await get_or_create_user(
            session, message.from_user.id, message.from_user.username,
            message.from_user.first_name, message.from_user.last_name, referral_code
        )
        if user.status == "banned":
            await message.answer("❗ ❗ ❗❗❗❗❗❗❗❗ ❗ ❗❗❗❗.")
            return

        if not user.agreed_to_rules:
            await message.answer("❗ <b>❗❗❗❗❗❗❗❗❗❗</b>\n\n❗❗❗❗❗❗❗❗❗❗, ❗❗❗❗❗❗❗❗❗❗❗❗❗❗❗❗.", parse_mode="HTML", reply_markup=rules_keyboard())
            return

        admin_flag = is_any_admin(message.from_user.id, user)
        await message.answer(f"❗ ❗ ❗❗❗❗❗❗❗❗❗❗❗❗❗❗: <b>{user.balance}</b>", parse_mode="HTML", reply_markup=main_menu(is_admin=admin_flag))

@router.message(F.text == BTN_ADMIN)
async def cmd_admin_redirect(message: Message):
    if await is_any_admin(message.from_user.id):
        from app.admin_handlers import cmd_admin
        await cmd_admin(message)

```

```

@router.message(F.text == BTN_PROFILE)
async def show_profile(message: Message):
    async with async_session() as session:
        user = await get_user(session, message.from_user.id)
        if not user: return

        text = (
            f"■ <b>■■■■■■■■■■</b>\n\n"
            f"ID: <code>{user.id}</code>\n"
            f"■■■■■■■■: <b>{user.balance}</b>\n"
            f"■■■■■■■■: <b>{user.level}</b> (XP: {user.xp})\n"
            f"■■■■■■■■: {user.status}"
        )
        await message.answer(text, parse_mode="HTML")
        await log_user_action(session, user.id, "view_profile")

# User Offers System
@router.message(F.text == "■ ■■■■■■■■ ■■■■■■")
async def create_user_offer_start(message: Message, state: FSMContext):
    await state.set_state(UserOfferState.waiting_title)
    await message.answer("■■■■■■■■ ■■■■■■■■ ■■■■■■ ■■■■■■ (■■■■■■/■■■■■■):")

@router.message(UserOfferState.waiting_title)
async def process_offer_title(message: Message, state: FSMContext):
    await state.update_data(title=message.text)
    await state.set_state(UserOfferState.waiting_description)
    await message.answer("■■■■■■■■ ■■■■■■■■ ■■■■■■:")

@router.message(UserOfferState.waiting_description)
async def process_offer_desc(message: Message, state: FSMContext):
    await state.update_data(description=message.text)
    await state.set_state(UserOfferState.waiting_url)
    await message.answer("■■■■■■■■ ■■■■■■ ■■ ■■■■■■ (t.me/...):")

@router.message(UserOfferState.waiting_url)
async def process_offer_url(message: Message, state: FSMContext):
    await state.update_data(url=message.text)
    cost = PIN_OFFER_COST
    kb = InlineKeyboardMarkup(inline_keyboard=[
        [InlineKeyboardButton(text=f"■ ■■■■■■■■ ■■■■■■■■ ({cost})", callback_data="pay_offer_coins")],
        [InlineKeyboardButton(text="■ ■■■■■■■■ Stars (50 Stars)", callback_data="pay_offer_stars")],
        [InlineKeyboardButton(text="■ ■■■■■■■■", callback_data="cancel_offer")]
    ])
    await message.answer(f"■■■■■■■■■■ ■■■■■■■■■■ ■■■■■■: <b>{cost} ■■■■■</b> ■■■■ <b>50 Telegram Stars</b>.\n■■■■■■■■■■ ■■■■■■ ■■■■■■:", parse_mode="HTML", reply_markup=kb)
    await state.set_state(UserOfferState.waiting_payment)

@router.callback_query(UserOfferState.waiting_payment, F.data == "pay_offer_coins")
async def pay_offer_coins(callback: CallbackQuery, state: FSMContext):
    data = await state.get_data()
    async with async_session() as session:
        user = await get_user(session, callback.from_user.id)
        if user.balance < PIN_OFFER_COST:
            await callback.answer("■■■■■■■■■■■■■■■■■■■■■■■■!", show_alert=True)
            return

        user.balance -= to_decimal(PIN_OFFER_COST)
        from app.models import Offer
        new_offer = Offer(
            creator_user_id=user.id,
            title=data['title'],
            description=data['description'],
            channel_url=data['url'],
            status="pending",
            is_active=False
        )
        session.add(new_offer)

```

```

        await log_user_action(session, user.id, "create_offer", f"Offer: {data['title']}, Paid:
{PIN_OFFER_COST} coins")
        await session.commit()
        await callback.message.answer("■ ■■■■■ ■■■■■■■■■■ ■■ ■■■■■■■■■■! ■■■■■ ■■■■■■■■■■
■■ ■■■■■■■■ ■ ■■■■■■■■.")
        await state.clear()
        await callback.answer()

```

```
# Stars payment would involve send_invoice, skipping for brevity but structure is there.
```

```
=====
FILE: requirements.txt
=====
aiogram==3.15.0
aiohttp>=3.9.0,<3.11
sqlalchemy==2.0.36
aiosqlite==0.20.0
asyncpg==0.29.0
python-dotenv==1.0.1
reportlab==4.2.2
```

```
=====
FILE: TODO.md
=====
# ■■■■■ ■■■■■■ ■■ ■■■■■■ 9d077153a1783450b8c27d83bc10e277dff7e60c - ■■■■
```

```
## [REDACTED] ([REDACTED], [REDACTED]):
1. [x] [REDACTED] TODO.md [REDACTED]
2. [x] git reset --hard 9d077153a1783450b8c27d83bc10e277dff7e60c (HEAD now at 9d07715)
3. [x] git push origin master --force (forced update to 9d07715)
4. [x] [REDACTED]:
    - git log: HEAD -> 9d07715 (TODO Delete)
    - git status: clean, up to date with origin/master
5. [x] [REDACTED] [REDACTED] [REDACTED] TODO.md
6. [x] [REDACTED] [REDACTED]
```

```
**■■■■■■■■■■ ■■■■■■■■:** ■■■■■■ ■■■■■■■ ■ ■■■■■■■■ ■■■■■■■■ ■■■■■■■■ ■ ■■ origin/master (Render.com ■■■■■■■■ ■■■■■■■■■■■■■■■■■■■).  
  
■■■■■■ ■■■■■■■■■■■■■■■■■ ■■■■ ■■ Render: ■■■■■■■■■■ ■ Render dashboard ■ redeploy, ■■■■ ■■■■ ■■■.
```