

RTR DAILY 6

1. The instruction "RESET SQUAWK 2200" means the pilot should:

Mark only one oval.

- ☐ a) Confirm that code 2200 is set
- ☐ b) Reselect the assigned code 2200
- ☐ c) Turn the transponder to standby and then back to 2200

2. The phrase "CLEARED TOUCH AND GO" authorizes the pilot to:

Mark only one oval.

- ☐ a) Land, roll, and take off again without stopping
- ☐ b) Land and make a full stop before taking off
- ☐ c) Touch the wheels to the runway and immediately go around

3. The instruction is to "GO AROUND." The correct initial response is:

Mark only one oval.

- ☐ a) "GOING AROUND"
- ☐ b) "ROGER"
- ☐ c) "WILCO"

4. The primary purpose of radar vectoring is to:

Mark only one oval.

- ☐ a) Provide the most direct route to the destination
- ☐ b) Establish separation between aircraft
- ☐ c) Assist pilots in navigating unfamiliar airspace

5. A "Blind Transmission" is made when:

Mark only one oval.

- ☐ a) The pilot is flying in Instrument Meteorological Conditions (IMC) and the sky is obscured.
- ☐ b) Two-way communication cannot be established, but the called station is believed able to receive.
- ☐ c) The pilot is unable to look out due to clouds /poor visibility while transmitting.

6. The code "TAF" in aviation meteorology is an abbreviation for:

Mark only one oval.

- ☐ a) Terminal Approach Forecast
- ☐ b) Temporary Airfield Forecast
- ☐ c) Terminal Aerodrome Forecast

7. The phraseology "ADVISE ABLE TO ACCEPT VISUAL APPROACH RUNWAY 27" is used to:

Mark only one oval.

- ☐ a) Request if the controller is able to clear a visual approach RUNWAY 27
- ☐ b) Request if the pilot on a VFR plan is able to execute a visual approach RUNWAY 27
- ☐ c) Request if the pilot is able to accept a visual approach RUNWAY 27

8. The primary goal of a controller upon receiving an "EMERGENCY DESCENT" call is to:

Mark only one oval.

- ☐ a) Instruct all other aircraft to switch frequencies
- ☐ b) Request the aircraft's full details as per MAY day call provisions
- ☐ c) Clear the airspace below the descending aircraft as quickly as possible

9. The abbreviation "CPDLC" stands for:

Mark only one oval.

- ☐ a) Controller-Pilot Data Link Communications
- ☐ b) Clearance and Position Data Link Check
- ☐ c) Central Processing for Data Link Control

10. The instruction "CONTACT DELHI APPROACH 119.7 NOW" means the pilot should:

Mark only one oval.

- ☐ a) Acknowledge and change frequency immediately
- ☐ b) Change frequency after passing the next waypoint
- ☐ c) Change frequency when convenient

11. A "SPECI" report is issued by a meteorological station when:

Mark only one oval.

- ☐ a) A routine forecast is updated.
- ☐ b) The visibility drops below 10 km.
- ☐ c) There is a significant change in weather between routine METAR reports.

12. The phraseology for a visual hold is:

Mark only one oval.

- ☐ a) "HOLD AS PUBLISHED, MAINTAIN VMC"
- ☐ b) "HOLD VISUAL [OVER] (position)"
- ☐ c) "ORBIT WITHIN VISUAL RANGE OF (landmark)"

13. The primary purpose of using standard ICAO phraseology is:

Mark only one oval.

- ☐ a) To reduce the need for English language proficiency
- ☐ b) To make communications faster than plain language
- ☐ c) To ensure communication is uniform, concise, and unambiguous

14. A pilot is instructed to "ORBIT LEFT". What maneuver should the pilot

Mark only one oval.

- ☐ a) Follow the left-hand traffic pattern
- ☐ b) Make a 360-degree turn to the left
- ☐ c) Continue turn left till asked to roll out by ATC

15. The phrase "EXPEDITE CLIMB" requires the pilot to:

Mark only one oval.

- ☐ a) Climb at the maximum possible rate
- ☐ b) Climb without delay to avoid conflicting traffic
- ☐ c) Climb at a faster-than-normal rate

16. A conditional clearance, such as "BEHIND LANDING A320, LINE UP BEHIND," can only be used if:

Mark only one oval.

- ☐ a) The controller and the pilot have the relevant traffic in sight
- ☐ b) The landing aircraft is at 10-mile on finals
- ☐ c) The runway is cleared by the landing aircraft and lined up aircraft has started rolling for take off

17. After landing, a pilot should report "RUNWAY VACATED":

Mark only one oval.

- ☐ a) When the nose wheel crosses the holding point
- ☐ b) When the entire aircraft is beyond the runway holding position
- ☐ c) While turning onto the taxiway, tail has crossed the runway edge marking

18. The instruction "SQUAWK CHARLIE" instructs the pilot to:

Mark only one oval.

- ☐ a) Select the pressure altitude transmission feature
- ☐ b) Operate the IDENT feature
- ☐ c) Set the emergency code 7700

19. The code "FEW" in a METAR report indicates that the cloud cover is:

Mark only one oval.

- ☐ a) 1-2 octas
- ☐ b) 3-4 octas
- ☐ c) 5-7 octas

20. The "initial climb level" reported by an IFR departure is:

Mark only one oval.

- ☐ a) The final cruise flight level after departure
- ☐ b) The first level at which the aircraft will level off unless otherwise cleared
- ☐ c) The altitude at which the aircraft will leave controlled airspace

21. A controller transmitting "RVR runway 27, 800" is indicating the:

Mark only one oval.

- ☐ A) Runway visual range for runway 27 is 800 meters.
- ☐ b) Required visibility for landing on runway 27 is 800 meters.
- ☐ c) Radar vectoring range for approach to runway 27 is 800 meters from threshold.

22. The term "TEMPO" in a TAF indicates that forecast conditions are expected to occur:

Mark only one oval.

- ☐ a) For less than one hour at a time and less than half the forecast period
- ☐ b) For short durations of less than 30 minutes over the forecast period
- ☐ c) As a gradual change over a period of 2 hours during the forecast period

23. A pilot transmitting "WILCO" in response to an ATC instruction is confirming that he::

Mark only one oval.

- ☐ a) Has received the message and will coordinate with next ATSU
- ☐ b) Will comply with the instruction
- ☐ c) Will confirm receipt of instructions

24. The term "CAVOK" in a meteorological report implies which conditions?

Mark only one oval.

- ☐ a) Visibility 10km or more, no cloud below 5000ft, no significant weather
- ☐ b) Visibility 5km, scattered clouds at 1500ft
- ☐ c) Cloud and visibility are OK, but significant weather is present in patches

25. King air VT-ABC receives the following instruction: "V-BC climb straight ahead until 2500 feet before turning right, wind 270 degrees 6 knots, cleared for take-off". What is the correct read back:

Mark only one oval.

- ☐ a) Straight ahead, 2500 feet right, wind westerly 6 knots, cleared for take-off, V-BC
- ☐ b) Straight ahead, at 2500 feet right turn, cleared for take-off, V-BC
- ☐ c) Wilco, cleared for take-off, V-BC

26. Air traffic service at a smaller airfield visited by you is provided by an Aerodrome Control Tower. What will be the RT call-sign used by you for start up clearance?

Mark only one oval.

- ☐ a) Delivery
- ☐ b) Ground
- ☐ c) Tower

27. Aircraft transmission "Cleared to Lucknow via R 460, FL 190, ALI 2 departure, squawk 5501 Skyjet 120" is in response to a:

Mark only one oval.

- ☐ a) ATC route clearance
- ☐ b) Taxi clearance
- ☐ c) SID

28. Aircraft transmission "Cleared to Lucknow via R 460, FL 190, ALI 2 departure, squawk 5501 Skyjet 120" is in response to a:

Mark only one oval.

- ☐ a) ATC route clearance
- ☐ b) Taxi clearance
- ☐ c) SID

29. The authority that implements ITU-framed policies for radio communication in India is the:

Mark only one oval.

- ☐ a) Directorate General of Civil Aviation (DGCA)
- ☐ b) Airport Authority of India (AAI)
- ☐ c) Wireless Planning and Coordination (WPC) Wing

30. How is heading 090 stated?

Mark only one oval.

- ☐ a) Heading East, nine zero degrees
- ☐ b) Heading zero nine zero
- ☐ c) Nine zero

31. What is the radiotelephony call sign for the aeronautical station indicating area control centre (no radar):

Mark only one oval.

- ☐ a) ... CENTRE
- ☐ b) ... CONTROL
- ☐ c) ... AREA

32. Which of the following statements is correct?

Mark only one oval.

- ☐ a) The urgency communications have priority over all the other communications
- ☐ b) The urgency communications have priority over all the other communications, except distress
- ☐ c) ATC clearances have the same priority as urgency communications

33. What is the Q-code for "magnetic bearing from the station1?

Mark only one oval.

- ☐ a) QDM
- ☐ b) QTE
- ☐ c) ODR

34. . The primary purpose of the ITU Radio Regulations (RR), Article 18, is to state that:

Mark only one oval.

- ☐ a) All radio stations must be operated by a licensed amateur radio operator
- ☐ b) No transmitting station can be operated without a valid license from the government
- ☐ c) All radio equipment must be manufactured in the country of registry

35. The initial call from an aircraft, callsign AIR INDIA 285 weighing more than 136 tonnes would be:

Mark only one oval.

- ☐ a) AIR INDIA 285 HEAVY
- ☐ b) HEAVY AIR INDIA 285
- ☐ c) AIR INDIA 285 SUPER

36. What is the radiotelephony call sign for the aeronautical station providing approach control radar departures:

Mark only one oval.

- ☐ a) RADAR APPROACH
- ☐ b) RADAR ARRIVAL
- ☐ c) APPROACH RADAR

37. An aircraft encountering radio communication failure on an IFR flight in IMC should commence descent over the designated navigation aid serving the destination aerodrome (no EAT received):

Mark only one oval.

- ☐ a) After 3 minutes of the last ETA acknowledged
- ☐ b) After 5 minutes of ETA, if an expected approach time is not acknowledged
- ☐ c) At, or as close to, the ETA resulting from the current flight plan

38. . In the event that a pilot is required to make a blind transmission, this should be made:

Mark only one oval.

- ☐ a) Once on 121.5 and once on the designated frequency
- ☐ b) Twice on the designated frequency
- ☐ c) Once on the designated frequency

39. What is the wavelength and waveband of a radio aid that uses a wavelength of 19 cm.

Mark only one oval.

- ☐ a) 1.579 Ghz / VHF
- ☐ b) 1.579 Ghz/UHF
- ☐ c) 1.579 Mhz / VHF

40. The overall objective of the Aeronautical Information Service (AIS) is to ensure the flow of information necessary for the safety, regularity, and efficiency of

Mark only one oval.

- ☐ a) Local Aerodrome Flight Information Service (AFIS)
- ☐ b) Air Traffic Control (ATC) system
- ☐ c) Global Air Traffic Management System

41. Primary purpose of Position Report is:

Mark only one oval.

- ☐ a) Traffic control and separation
- ☐ b) Providing position and meteorological/operational data
- ☐ c) Report significant, or hazardous weather condition

42. An aircraft station fails to establish radio contact with an aeronautical station on the designated frequency. What action is required by the pilot?

Mark only one oval.

- ☐ a) Return to the airport of departure
- ☐ b) Land at the nearest airport
- ☐ c) Attempt to establish contact with the station on an alternative frequency

43. The number 4 would be pronounced as:

Mark only one oval.

- ☐ a) 'FOW-er'
- ☐ b) 'FOUR'
- ☐ c) 'FOE-WER'

44. The key advantage of ADS-C in Oceanic Control is that it allows for:

Mark only one oval.

- ☐ a) Reduced lateral separation standards between aircraft
- ☐ b) Direct voice communication without HF radio
- ☐ c) Transfers data packet every half-second over a dedicated radio frequency (usually 1090 MHz) to anyone with a compatible receiver

45. A protected medical transport is identified by the prefix:

Mark only one oval.

- ☐ a) PAN PAN PAN PAN PAN PAN MEDICAL PRIORITY
- ☐ b) AIR AMBULANCE
- ☐ c) PAN PAN MEDICAL

46. Which phrase shall be used if you want to say: "Yes":

Mark only one oval.

- ☐ a) Affirm
- ☐ b) Affirmative
- ☐ c) Roger

47. The maximum theoretical range at which an aircraft at FL80 can obtain bearings from a ground VHF facility sited at 325ft above MSL is:

Mark only one oval.

- ☐ a) 107NM
- ☐ b) 134NM
- ☐ c) 158NM

48. What is the primary purpose of a Special VFR flight?

Mark only one oval.

- ☐ a) It allows a VFR flight to operate in the airspace classified as A in a Control Area
- ☐ b) It allows a VFR flight to operate within an Aerodrome Traffic Zone without ATC clearance
- ☐ c) It authorizes a VFR flight to operate in a Control Zone in IMC or at night

49. The exact, official, and updated frequencies for every airport and navigation aid are published in the:

Mark only one oval.

- ☐ a) Local aerodrome SOP
- ☐ b) Aircraft's operational manual
- ☐ c) India Aeronautical Information Publication (AIP)

50. When the term "Overcast" is used in an aviation routine weather report (METAR), the amount of clouds covering the sky is:

Mark only one oval.

- ☐ a) 100%
- ☐ b) No clouds but poor visibility
- ☐ c) 50% or more

51. The function of an SSR (Secondary Surveillance Radar) is to:

Mark only one oval.

- ☐ a) "See" aircraft by reflecting radio waves off their skin.
- ☐ b) Interrogate an aircraft's transponder for information like altitude and identity.
- ☐ c) Provide a precise lateral and vertical guidance to a runway.

This content is neither created nor endorsed by Google.

Google Forms