

RTR DAILY 2

1. A flashing red light from control tower during an approach to land means:

Mark only one oval.

- ☐ The airport is unsafe, do not land
- ☐ The airport is temporarily closed, continue circling
- ☐ Give way to other aircraft in emergency

2. On aerodromes aircraft taxiing on the manoeuvring area of an aerodrome shall give way to:

Mark only one oval.

- ☐ aircraft taking off or about to take off
- ☐ other converging aircraft
- ☐) all vehicles moving on the apron except the "follow me" vehicle

3. The VMC minima for an airspace classified as "G" above 10 000 feet MSL are :

Mark only one oval.

- ☐ 1500 m horizontally and 1 000 feet vertically from clouds, 8 km visibility
- ☐ 1500 m horizontally and 1 000 feet vertically from clouds, 5 km visibility
- ☐ 1 nautical mile horizontally and 1 000 feet vertically from clouds, 5 km visibility

4. An aircraft intercepted by another aircraft, if equipped with SSR transponder shall, unless otherwise instructed by the appropriate ATS unit, select one of the following code on mode "A"

Mark only one oval.

- ☐ 7 700
- ☐ 7600
- ☐ 7500

5. Which of the following flights has the greatest priority to land ?

Mark only one oval.

- ☐ Emergency aircraft
- ☐ Military aircraft
- ☐ VIP (Head of state) aircraft

6. A red flare addressed to a flying aircraft means :

Mark only one oval.

- ☐ Not with standing any previous instructions, do not land for the time being.
- ☐ Come back and land.
- ☐ Give way to another aircraft and hold the circuit.

7. What does the abbreviation DER mean?

Mark only one oval.

- ☐ Depature end of runway.
- ☐ Distance end of route.
- ☐ Departure end of route.

8. In a precision approach (ILS), the final approach segment begins at the:

Mark only one oval.

- ☐ FAP.
- ☐ FAF
- ☐ MAP

9. In which zone of a jet stream is the strongest CAT to be expected ?

Mark only one oval.

- ☐ The cold air side of the core.
- ☐ The warm air side of the core.
- ☐ Exactly in the centre of the core.

10. How long does it take a NAVSTAR/GPS satellite to orbit the earth?

Mark only one oval.

- ☐ Approximately 12 hours (1/2 of a sidereal day)
- ☐ Approximately 24 hours (one sidereal day)
- ☐ 12 days

11. At what approximate height above the WGS-84 ellipsoid are NAVSTAR/GPS satellites circling the earth?

Mark only one oval.

- ☐ 20200 km
- ☐ 10900 km
- ☐ 36000 km

12. The main task of the user segment (receiver) of the satellite navigation system NAVSTAR/GPS is to:

Mark only one oval.

- ☐ select appropriate satellites automatically, to track the signals and to measure the time taken by signals from the satellites to reach the receiver
- ☐ transmit signals which, from the time taken, are used to determine the distance to the satellite
- ☐ to monitor the status of the satellites, determine their positions and to measure the time

13. One of the tasks of the space segment of the satellite navigation system NAVSTAR/ GPS is to:

Mark only one oval.

- ☐ transmit signals which can be used, by suitable receivers, to determine time, position and velocity
- ☐ transmit signals to suitable receivers and to monitor the orbital planes autonomously
- ☐ compute the user position from the received user messages and to transmit the computed position back to the user segment

14. The orbital planes of the satellite navigation system NAVSTAR/GPS are:

Mark only one oval.

- ☐ inclined 55° to the equatorial plane
- ☐ inclined 55° to the earth axis
- ☐ inclined 90° to the equatorial plane

15. In which frequency bands are the L1 and L2 frequencies used by the satellite navigation system NAVSTAR/GPS for transmission of the navigation message?

Mark only one oval.

- ☐ UHF
- ☐ VHF
- ☐ HF

16.) In the NAVSTAR/GPS satellite navigation system, what is the maximum time taken to receive the complete set of almanac data from all satellites?

Mark only one oval.

- ☐ 12.5 minutes (= 30 seconds per data frame)
- ☐ 12 hours (= period of the satellites orbit)
- ☐ 25 seconds (= 1 second per data frame)

17. A ""resolution advisory"" (RA) is represented on the display system of the TCAS 2 (Traffic Collision Avoidance System) by a :

Mark only one oval.

- ☐ red full square.
- ☐ blue or white full lozenge.
- ☐ blue or white empty lozenge.

18. Flight recorder duration must be such that flight data, cockpit voice and sound warnings may respectively be recorded during at least:

Mark only one oval.

- ☐ 25 hours for flight data, 30 minutes for cockpit voices and warnings horns.
- ☐ 24 hours for flight data, 60 minutes for cockpit voices and warnings horns.
- ☐ 20 hours for flight data, 15 minutes for cockpit voices and warnings horns.

19. In accordance with (ICAO) Annex 6 part I, the flight data recorder is to be located in the aircraft :

Mark only one oval.

- ☐ as far to the rear as practicable
- ☐ as far forward as practicable
- ☐ as near to the landing gear as practicable

20. Field length is balanced when

Mark only one oval.

- ☐ take-off distance equals accelerate-stop distance.
- ☐ calculated V2 is less than 110% VMCA and V1, VR, VMCG.
- ☐ all engine acceleration to V1 and braking distance for rejected take-off are equal.

21. ATC gives the instruction: "Climb FL140, expedite through FL110 due crossing traffic." You are currently at FL095. According to Doc 9432, which is the correct readback?

Mark only one oval.

- ☐ "Roger, expediting."
- ☐ "Climbing FL140, expediting through FL110."
- ☐ "Climbing to FL140."

22. ATC issues a conditional clearance: "After the A320 on short final passes your left, line up runway 27." Which of the following makes the clearance invalid per Doc 9432

Mark only one oval.

- ☐ Not referencing the aircraft type.
- ☐ Condition refers to aircraft position, not movement.
- ☐ Condition references "after" instead of "following."

23. ATC says: "Stop transmitting." What is the operational expectation according to Doc 9432?

Mark only one oval.

- ☐ Cease transmission immediately, continue to monitor.
- ☐ Change to another frequency silently.
- ☐ Maintain position and stay silent for 1 minute.

24. A pilot says: "Request repeat." Why is this phrase incorrect as per Doc 9432?

Mark only one oval.

- ☐ It implies military phraseology.
- ☐ Only ATC may request a full repeat.
- ☐ "Say again" is the only ICAO-approved phrase.

25. Which RT call is prohibited under Doc 9432 unless instructed?

Mark only one oval.

- ☐ Roger, continuing."
- ☐ "Standing by."
- ☐ "Over and out."

26. You missed part of a clearance. Correct Doc 9432 recovery phrase:

Mark only one oval.

- ☐ "Say again all after altitude."
- ☐ Repeat the clearance."
- ☐ "Confirm level for Bravo India Mike?"

27. ATC instructs: "Orbit right." What is the implicit ICAO assumption?

Mark only one oval.

- ☐ Turn at pilot-selected rate.
- ☐ Maintain altitude unless stated.
- ☐ All above.

28. Which ATC instruction requires an exact readback, NOT "roger"?

Mark only one oval.

- ☐ "Report leaving FL120."
- ☐ "Contact 122.8."
- ☐ "Climb to 7,000 ft QNH 1012."

29. Which phrase ATC uses when pilot reads back incorrectly?

Mark only one oval.

- ☐ "Wrong."
- ☐ "Negative, I say again..."
- ☐ "Correction required."

30. A pilot states: "Ready for takeoff." At a controlled aerodrome, Doc 9432 classifies this phrase as?

Mark only one oval.

- ☐ Acceptable in low workload conditions
- ☐ Acceptable if holding short
- ☐ Incorrect – must use "Ready for departure"

31. Tower says: "Cleared for immediate takeoff." Operational meaning per ICAO:

Mark only one oval.

- ☐ Enter runway and depart at best rate
- ☐ Takeoff within 15 seconds
- ☐ Expedite entering runway; rolling takeoff without stopping

32. Correct ICAO phrase to delay the action of a clearance but keep the clearance valid:

Mark only one oval.

- ☐ "Hold position."
- ☐ "Standby for my clearance."
- ☐ "Hold for release."

33. A controller uses "Words Twice." What is he expecting YOU to do?

Mark only one oval.

- ☐ Transmit each phrase twice
- ☐ Halt transmissions
- ☐ Confirm weather

34. Your instruction was unclear and ATC responds: "Correction, maintain heading 230." What is the meaning?

Mark only one oval.

- ☐ You misunderstood earlier
- ☐ The controller is revising the original instruction
- ☐ Only the new heading is valid now

35. You have a stuck mic. Which Doc 9432 principle applies?

Mark only one oval.

- ☐ ATC may instruct "Stop transmitting."
- ☐ ATC will broadcast instructions on guard.
- ☐ ATC will attempt to override with carrier wave.

36. ATC will attempt to override with carrier wave.

Mark only one oval.

- ☐ Below 1500 ft AGL
- ☐ Aircraft already at max performance climb
- ☐ Opposite traffic descending ≥ 2500 fpm

37. During an RA, which rule overrides the other?

Mark only one oval.

- ☐ ATC instructions override TCAS
- ☐ TCAS override ATC
- ☐ Both must be balanced

38. TCAS coordination uses which combination?

Mark only one oval.

- ☐ Mode C altitude + Mode S identity
- ☐ Mode C + ADS-B
- ☐ Mode S interrogations only

39. A "don't climb" RA may occur even if ATC instructed climb because:

Mark only one oval.

- ☐ TCAS sees horizontal conflict
- ☐ Mode C + ADS-B
- ☐ Mode S interrogations only

40. TCAS RA reversal (e.g., climb→descend) occurs when:

Mark only one oval.

- ☐ Pilot is too slow to respond
- ☐ Intruder's transponder type changes
- ☐ TCAS detects intruder following same RA

41. The 'Cone of Silence' is a characteristic associated with which navigation aid?

Mark only one oval.

- ☐ VOR
- ☐ ADF
- ☐ ILS

42. Which type of wave propagation is primarily used for Long Range HF communication?

Mark only one oval.

- ☐ Space Wave
- ☐ Ground Wave
- ☐ Surface Wave

43. What is the maximum range of a VHF signal for an aircraft at 10,000 feet

Mark only one oval.

- ☐ Approximately 123 NM
- ☐ Approximately 50 NM
- ☐ 250 NM

44. What is the standard spacing for a 'Localizer' frequency?

Mark only one oval.

- ☐ Even decimals (e.g., 108.2)
- ☐ Odd decimals (e.g., 108.1, 108.15)
- ☐ 8.33 kHz only

45. Which frequency is the 'Military Emergency' frequency?

Mark only one oval.

- ☐ 121.5 MHz
- ☐ 243.0 MHz
- ☐ 406.0 MHz

46. SSR Mode S squitter is crucial for ACAS because:

Mark only one oval.

- ☐ It contains pressure altitude only
- ☐ It sends unsolicited identity + capability data
- ☐ It eliminates the need for interrogations

47. SBAS improves vertical accuracy primarily by:

Mark only one oval.

- ☐ Removing multipath
- ☐ Removing tropospheric error
- ☐ Providing ionospheric delay model

48. A VOR shows erratic but smooth bearing deviation every few seconds. Most likely cause:

Mark only one oval.

- ☐ Cone of confusion
- ☐ Scalloping due ground reflection
- ☐ Station calibration error

49. Which condition MOST affects SATCOM reliability?

Mark only one oval.

- ☐ Low look angle to GEO
- ☐ Climb at constant thrust
- ☐ Cold-soaked antenna

50. A weather radar tilted too high will most commonly give the illusion of:

Mark only one oval.

- ☐ Overstated storm intensity
- ☐ Undershooting of nearby weather
- ☐ Clear path where storm tops obscure returns

This content is neither created nor endorsed by Google.

Google Forms