

RTR DAILY 3

1. You receive: "After the departing Boeing 737 passes your right, line up Runway 10." Visibility is 3 km, haze, and the aircraft is not yet visually confirmed. As per Doc 9432, the correct action is:

Mark only one oval.

- ☐ Line up once you estimate the 737 has passed.
- ☐ Ask ATC "Confirm line up now?"
- ☐ State "Unable conditional clearance, traffic not in sight."

2. Which phraseology pair is legally distinct under Doc 9432?

Mark only one oval.

- ☐ "Stop transmitting" vs "Stop communications"
- ☐ Standby" vs "Wilco"
- ☐ "Affirm" vs "Correct"

3. Pilot receives: "Descend now to 7,000 ft." Pilot is unsure if terrain clearance exists. The Doc 9432–compliant RT response is:

Mark only one oval.

- ☐ "Unable due terrain."
- ☐ "Negative, 7,000 ft."
- ☐ "Request further descent."

4. ATC says: "Callsign ABC123, acknowledge last transmission." This means:

Mark only one oval.

- ☐ Read back the entire last transmission.
- ☐ Simply respond with "Roger."
- ☐ Correct your previous readback.

5. Which phrase is not allowed in ICAO RT because it implies dual meaning?

Mark only one oval.

- ☐ "Climb immediately"
- ☐ "Stopping climb"
- ☐ "Holding short"

6. During radio congestion, ATC uses "Words twice" directed at YOU. Correct action:

Mark only one oval.

- ☐ Repeat your message twice.
- ☐ Speak slower.
- ☐ Increase mic gain.

7. ATC: "Cleared to cross Runway 09 behind the ATR on short final." The ATR is on 4 NM final, in IMC. Legal RT response:

Mark only one oval.

- ☐ "Traffic not in sight, unable cross."
- ☐ "Crossing Runway 09."
- ☐ Wilco."

8. Which RT scenario creates loss of separation risk due to phraseology misuse?

Mark only one oval.

- ☐ Using "Roger" instead of readback for heading.
- ☐ Saying "Affirm" on guard frequency.
- ☐ Using "Standby" during emergency.

9. Doc 9432: What is the correct pilot response when uncertain whether a clearance was addressed to them?

Mark only one oval.

- ☐ "Say again."
- ☐ Confirm clearance was for ?"
- ☐ "Negative, repeat."

10. ATC says: "Leave controlled airspace immediately." What is permissible?

Mark only one oval.

- ☐ "Unable"
- ☐ "Leaving controlled airspace now"
- ☐ Any of the above

11. Pilot receives two conflicting ATC instructions: Tower says "Line up," Approach says "Hold short." Correct action?

Mark only one oval.

- ☐ Obey Tower.
- ☐ Obey the earliest instruction.
- ☐ Query both: "Confirm instruction for ?"

12. Which is the correct ICAO method to request ATC to slow down their speech?

Mark only one oval.

- ☐ "Say slower."
- ☐ "Say again slower."
- ☐ "Speak slowly, please."

13. A pilot mishears a frequency instruction as 118.7 instead of 118.17. Best safety practice?

Mark only one oval.

- ☐ Repeat back: "Confirm 118.17 for ?"
- ☐ Simply read back 118.7
- ☐ Switch and see if ATC replies

14. Which phrase legally places the timing of execution back onto the pilot, not ATC?

Mark only one oval.

- ☐ At your discretion"
- ☐ When ready"
- ☐ . All the above

15. You are asked: "Report reaching altitude 9000 ft." Pilot should report at:

Mark only one oval.

- ☐ Passing 9000 ft
- ☐ Approaching 9000 ft
- ☐ Stabilized at 9000 ft

16. ATC transmits an amended clearance while you are executing a TCAS RA. The correct RT is:

Mark only one oval.

- ☐ "Unable, TCAS RA."
- ☐ Negative."
- ☐ "Standby."

17. Which is considered a non-compliant RT readback?

Mark only one oval.

- ☐ "Maintain heading 240."
- ☐ "Heading two four zero."
- ☐ Roger."

18. During HF interference, ATC instructs "Stop transmitting." Correct pilot procedure:

Mark only one oval.

- ☐ Cease all transmissions on ALL radios
- ☐ Cease only on that frequency, continue monitoring
- ☐ Switch to guard and transmit

19. "Correction" must be used:

Mark only one oval.

- ☐ Before giving corrected phrase
- ☐ After giving corrected phrase
- ☐ Only when pilot makes an error

20. A pilot hears ATC transmission partially blocked. Best ICAO practice:

Mark only one oval.

- ☐ "Say again all after..."
- ☐ "Say again from beginning."
- ☐ "Repeat entire message."

21. What ensures ACAS/TCAS compatibility across different states?

Mark only one oval.

- ☐ Mode C
- ☐ Annex 10 Vol II interoperability requirements
- ☐ SSR code assignment

22. Which frequency pair is globally protected for SSR operation?

Mark only one oval.

- ☐ 1030/1090 MHz
- ☐ 121.5/243 MHz
- ☐ 118–137 MHz

23. Loss of TCAS surveillance occurs when:

Mark only one oval.

- ☐ 1030 MHz interference saturates the channel
- ☐ VHF guard active
- ☐ HF interference

24. ADS-B 1090ES provides ATC with:

Mark only one oval.

- ☐ Identity + position + velocity
- ☐ Only pressure altitude
- ☐ Only identity

25. Which occurs if antenna shadowing affects Mode S?

Mark only one oval.

- ☐ Squitter rate increases
- ☐ Intermittent loss of altitude reporting
- ☐ Constant altitude but no identity

26. Which phrase is required when deviating due to onboard equipment alerts?

Mark only one oval.

- ☐ "Deviation due [alert], returning when able."
- ☐ "Standby."
- ☐ "Unable, traffic."

27. In high-density airspace, surveillance overlap requires:

Mark only one oval.

- ☐ Multilateration + ADS-B + Mode-S coordination
- ☐ HF + PSR
- ☐ VOR/DME only

28. Which of the following may cause false Mode-S altitude codes?

Mark only one oval.

- ☐ Incorrect baro setting inside aircraft
- ☐ Radio altimeter data frozen
- ☐ ADS-B position lost

29. During simultaneous use of SATCOM and HF, which condition causes SATCOM dropout?

Mark only one oval.

- ☐ Low satellite elevation angle
- ☐ HF skywave
- ☐ RAIM hole

30. Which system MOST depends on Annex 10-defined integrity requirements?

Mark only one oval.

- ☐ ADS-B OUT
- ☐ Marker beacons
- ☐ VOR

31. Annex 1: A pilot medically unfit must:

Mark only one oval.

- ☐ Self-ground and inform licensing authority
- ☐ Continue flying until exam
- ☐ Fly only VFR

32. DGCA requires RT license validity check:

Mark only one oval.

- ☐ With every medical
- ☐ Once at renewal only
- ☐ At check ride only

33. . Which best describes PIC responsibility under ICAO during comms failure?

Mark only one oval.

- ☐ Follow the state's published comm failure procedure
- ☐ Follow airline SOP regardless
- ☐ Continue following ATC last instruction indefinitely

34. During IFR comms failure in controlled airspace, pilot must:

Mark only one oval.

- ☐ Maintain last assigned level for 7 minutes then proceed
- ☐ Squawk 7600, follow loss procedures
- ☐ Squawk 7700

35. Which license privilege is specifically tied to proficiency in ICAO Doc 9432 RT standards?

Mark only one oval.

- ☐ RTR(A) or equivalent
- ☐ Multi-engine rating
- ☐ Type rating

36. DGCA CAR requires pilots to report:

Mark only one oval.

- ☐ Any safety hazard including RT failure
- ☐ Only major equipment failures
- ☐ Only medical issues

37. Which factor MOST affects operational decision-making in RT emergencies?

Mark only one oval.

- ☐ Authority gradient + workload + frequency congestion
- ☐ Aircraft color
- ☐ Time of day only

38. Annex 1: A pilot must carry valid RT license when:

Mark only one oval.

- ☐ Operating any aircraft requiring radio communication
- ☐ Only during international flights
- ☐ Only in controlled airspace

39. Pilot self-assessment responsibilities derive from:

Mark only one oval.

- ☐ Annex 1
- ☐ Annex 10
- ☐ Annex 2

40. DGCA expects what when an RT error is made?

Mark only one oval.

- ☐ Immediate correction, concise, no apology
- ☐ Pilot must justify error
- ☐ Wait for ATC reprimand

41. During ILS CAT II approach, a Mode 5 GPWS "Glideslope" alert triggers due to an excessive deviation. ATC simultaneously instructs: "Descend 300 ft." Proper action:

Mark only one oval.

- ☐ Ignore ATC, stabilize, then inform "Unable, GPWS alert."
- ☐ Descend 300 ft immediately
- ☐ Climb per GPWS

42. A TCAS "DESCEND" RA and ATC "Climb immediately" occur together. Correct procedure:

Mark only one oval.

- ☐ Follow TCAS RA; notify ATC
- ☐ Follow ATC
- ☐ Ignore both

43. Which condition may produce ADS-B integrity warning before RAIM warning?

Mark only one oval.

- ☐ GPS antenna shading
- ☐ HF static discharge
- ☐ Low cabin pressure

44. Which sequence ensures safe compliance when ATC contains a constraint but GPWS warns simultaneously?

Mark only one oval.

- ☐ GPWS → Level off → Inform ATC → Request new clearance
- ☐ ATC first → GPWS next
- ☐ Maintain as before

45. Which would cause a false TCAS intruder track?

Mark only one oval.

- ☐ Mode S reflection or "ghosting" from multilateration
- ☐ Incorrect QNH
- ☐ Low COM1 volume

46. EGPWS database mismatch during RNAV approach results in:

Mark only one oval.

- ☐ Predictive terrain caution before loss of guidance
- ☐ TCAS caution
- ☐ VOR failure

47. Simultaneous HF SELCAL alert and VHF lost comms occur. Pilot should:

Mark only one oval.

- ☐ Answer SELCAL through HF first
- ☐ Troubleshoot VHF first
- ☐ Switch to CPDLC

48. A radar controller gives heading while aircraft's weather radar shows strong returns directly ahead. Pilot must:

Mark only one oval.

- ☐ Say "Unable due weather" and offer alternate
- ☐ Follow heading
- ☐ Switch to TCAS vertical guidance

49. Which combination leads to both PSR and SSR surveillance loss?

Mark only one oval.

- ☐ Terrain masking + 1090 MHz interference
- ☐ Low visibility + humidity
- ☐ Poor QNH

50. During go-around, ATC instructs "Turn left now," but EGPWS "Terrain ahead" triggers. Correct action:

Mark only one oval.

☐ Reject turn, inform ATC, comply with EGPWS

☐ Follow ATC

☐ Maintain runway track silently

This content is neither created nor endorsed by Google.

Google Forms