

RTR DAILY 4

1. The phrase "REMAIN OUTSIDE CONTROLLED AIRSPACE, EXPECT JOINING CLEARANCE AT TIME 55" indicates that

Mark only one oval.

- ☐ a) The aircraft is cleared to enter immediately"
- ☐ b) The aircraft's flight plan has been cancelled
- ☐ c) The clearance cannot be issued immediately due to traffic

2. When an aircraft is required to "HOLD EN-ROUTE", the holding pattern is normally based on

Mark only one oval.

- ☐ The track of the ATS route (left- or right-hand pattern)
- ☐ A random selection by the pilot
- ☐ 360° circling pattern

3. An ADS-C "contract" between an aircraft and ATC specifies:

Mark only one oval.

- ☐ a) The financial terms of the flight to receive ADS services
- ☐ b) The parameters for when and what data the aircraft should report
- ☐ c) The duration of the ADS services to be provided

4. The reduction of oceanic lateral separation standards (e.g., to 23 NM) is made possible primarily by the use of:

Mark only one oval.

- ☐ a) High-Frequency (HF) radio reports.
- ☐ b) Primary Surveillance Radar (PSR).
- ☐ c) ADS-C-based procedural control.

5. CPDLC is used in conjunction with ADS-C to:

Mark only one oval.

- ☐ a) Control the aircraft's autopilot remotely
- ☐ b) Provide in-flight entertainment to passengers
- ☐ c) Exchange routine clearances and messages via data link

6. The correct phraseology for a pilot to declare a fuel emergency, indicating imminent danger, is:

Mark only one oval.

- ☐ a) PAN-PAN, PAN-PAN, PAN-PAN
- ☐ b) MAYDAY, MAYDAY, MAYDAY
- ☐ c) SECURITY SECURITY

7. The transponder code 7500 is reserved for which situation?

Mark only one oval.

- ☐ a) Unlawful seizure (hijack)
- ☐ b) General emergency
- ☐ c) Radio communication failure

8. Upon receiving a distress message, the first station to hear it must:

Mark only one oval.

- ☐ a) Impose silence on all other stations immediately
- ☐ b) Transfer the aircraft to a different frequency
- ☐ c) Immediately acknowledge the distress message

9. The signal "PAN PAN MEDICAL" is used for an aircraft involved in:

Mark only one oval.

- ☐ a) Any medical diversion
- ☐ b) A protected medical transport under the Geneva Convention
- ☐ c) Transporting medical supplies for a hospital use

10. Q10. If a pilot's radio receiver fails, they should prefix their transmissions with:

Mark only one oval.

- ☐ a) "TRANSMITTING BLIND DUE TO RECEIVER FAILURE"
- ☐ b) "RECEIVER INOPERATIVE"
- ☐ c) "UNABLE TO RECEIVE"

11. An IFR flight experiencing communications failure in IMC should:

Mark only one oval.

- ☐ a) Descend immediately to VMC
- ☐ b) Continue on the last assigned route and altitude
- ☐ c) Divert immediately to the nearest suitable aerodrome

12. The Global Reporting Format (GRF) provides a standardized:

Mark only one oval.

- ☐ a) Runway Condition Code (RWYCC)
- ☐ b) List of dimensions of all available runways at an airport
- ☐ c) Format for reporting Navigation aid status

13. A Runway Condition Code (RWYCC) of 1 corresponds to which pilot report of braking action?

Mark only one oval.

- ☐ a) Good
- ☐ b) Medium
- ☐ c) Poor

14. A SNOWTAM is a special report that provides detailed information on:?

Mark only one oval.

- ☐ The presence of snow, ice, or slush on runways
- ☐ Snowfall on and in the vicinity of aerodrome
- ☐ Snowfall forecast at the aerodrome

15. The primary purpose of SELCAL is to:

Mark only one oval.

- ☐ Allow pilots to call the ground crew
- ☐ b) Alert the flight crew of an incoming message without continuous listening
- ☐ c) Automatically transmit the aircraft's position

16. The primary purpose of SELCAL is to:

Mark only one oval.

- ☐ Allow pilots to call the ground crew
- ☐ b) Alert the flight crew of an incoming message without continuous listening
- ☐ c) Automatically transmit the aircraft's position

17. SELCAL codes are composed of:

Mark only one oval.

- ☐ a.) four numbers
- ☐ b) Three letters and one number
- ☐ c) Four letters (from A-S, excluding I, N, O)

18. Fuel dumping should normally be conducted:

Mark only one oval.

- ☐ a) Above 10,000 feet AGL and clear of populated areas
- ☐ b) below 5000 feet for quicker disposal
- ☐ c) Over the ocean/water bodies only

19. A pilot reporting "UNABLE RVSM DUE TURBULENCE" is indicating:

Mark only one oval.

- ☐ a) Aircraft will not be able to handle any turbulence in RVSM airspace due weight
- ☐ b) Severe turbulence is preventing pilot from maintaining the required height-keeping accuracy
- ☐ c) Caution to other pilots in the vicinity to keep away for safety reasons

20. . When an ACAS Resolution Advisory (RA) is issued, the pilot must:

Mark only one oval.

- ☐ a) Follow the RA immediately, ignoring any conflicting ATC instruction
- ☐ b) Ask ATC for permission to follow the RA
- ☐ c) Only follow the RA if they can also see the conflicting traffic

21. The correct phraseology to report deviating due to an ACAS RA is:

Mark only one oval.

- ☐ a) "DEVIATING FOR TRAFFIC"
- ☐ b) "ACAS WARNING"
- ☐ c) "TCAS RA"

22. In RVSM airspace, the standard vertical separation minimum is:

Mark only one oval.

- ☐ a) 1,000 feet
- ☐ b) 2,000 feet
- ☐ c) 500 feet

23. A "NON-RVSM APPROVED" aircraft is one that:

Mark only one oval.

- ☐ a) Has special permission to operate in RVSM airspace
- ☐ b) Lacks RVSM approval or is temporarily non-compliant
- ☐ c) Is only allowed to fly in RVSM airspace in VMC

24. The Strategic Lateral Offset Procedure (SLOP) is used to reduce the risk of:

Mark only one oval.

- ☐ a) Bird strikes in high intensity bird activity areas
- ☐ b) Collision with obstacles
- ☐ c) Mid-air collisions and wake turbulence

25. . If a pilot must deviate from the assigned track due to adverse weather and cannot obtain ATC clearance, on which backup frequency must they broadcast their intentions?

Mark only one oval.

- ☐ a) 123.45 MHz only.
- ☐ b) 121.5 MHz (or backup 123.45 MHz).
- ☐ c) The next ACC sector frequency.

26. The purpose of "Inter-pilot air-to-air communication" is to allow aircraft over remote areas to:

Mark only one oval.

- ☐ a) Broadcast Special Air Report
- ☐ b) Exchange operational information
- ☐ c) Relay their position to the nearest ground station

27. If a pilot's transmission is "BLOCKED" by another station, they should inform ATC by saying:

Mark only one oval.

- ☐ a) "FREQUENCY JAMMED BY (call sign of the station blocking)"
- ☐ b) "STOP TRANSMITTING (call sign of the station blocking)"
- ☐ c) "TRANSMISSION BLOCKED BY (call sign of the station blocking), SAY AGAIN"

28. the correct procedure for an IFR flight in a radar enviroment after RCF is to continue on the last assigned flight level for ___ minutes?

Mark only one oval.

- ☐ 7
- ☐ 20
- ☐ 30

29. In Non-RVSM airspace below FL 290, an IFR cruising level for a magnetic track of 090° would be:

Mark only one oval.

- ☐ a) An even flight level (e.g., FL 260).
- ☐ b) An odd flight level (e.g., FL 250).
- ☐ c) Even + 500 feet (e.g. FL 265).

30. . An aircraft in distress shall send the following signal by radiotelephony:

Mark only one oval.

- ☐ a) URGENCY, URGENCY, URGENCY
- ☐ b) DETRESFA, DETRESFA, DETRESFA
- ☐ c) MAYDAY, MAYDAY, MAYDAY

31. Which of these statements is true?

Mark only one oval.

- ☐ a) When making an initial call from an aircraft to a ground station you must state the ground station name and suffix first and then your abbreviated call-sign.
- ☐ b) When making an initial call from an aircraft to a ground station you must state the ground station name and suffix first and then your full call-sign.
- ☐ c) When making an initial call from an aircraft to a ground station you must state your full call-sign first and then the ground station name and suffix.

32. The ICAO location indicator for Delhi's IGI Airport is:

Mark only one oval.

- ☐ a) VIDP.
- ☐ b) VECT.
- ☐ e) VIDD

33. For Indian-registered passenger aircraft, the mandatory requirement for Emergency Locator Transmitters (ELTs) is:

Mark only one oval.

- ☐ a) At least one automatic ELT.
- ☐ b) At least two (one automatic fixed, one portable),
- ☐ c) Three ELTs, one for each crew member.

34. What is the minimum vertical separation between IFR flights in opposite directions below FL 290?

Mark only one oval.

- ☐ a) 500 feet.
- ☐ a) 2000 feet.
- ☐ c) 1000 feet.

35. Which elements of instructions or information shall always be read back?

Mark only one oval.

- ☐ a) Runway in use, altimeter settings, SSR codes, level instructions, heading and speed instructions
- ☐ b) Runway-in-use, visibility, surface wind, heading instructions, altimeter settings
- ☐ e) Time check, runway in use, altimeter settings, level instructions, weather

36. The purpose of the squelch control is to:

Mark only one oval.

- ☐ a) Boost weak signals
- ☐ b) Adjust microphone gain
- ☐ c) Mute background noise

37. When flying on a SW heading at 3500 feet you would report your heading and level as:

Mark only one oval.

- ☐ a) HEADING 225 AT THREE THOUSAND FIVE HUNDRED FEET
- ☐ b) SOUTHWEST AT THREE FIVE ZERO ZERO FEET
- ☐ c) HEADING 045 DEGREES AT THREE THOUSAND FIVE HUNDRED FEET

38. What was the primary safety lesson learned from the incident where a pilot mistakenly set FL100 in response to "Head one hundred degrees and climb Flight Level eight zero?"

Mark only one oval.

- ☐ a) Pilot mistakenly set FL100 on autopilot, influenced by ATC's phrase "one hundred."
- ☐ b) Pilot's poor knowledge of English language.
- ☐ c) Controller's failure to give correct level instructions.

39. What is the frequency range for the Very High Frequency (VHF) band, which primarily supports line-of-sight communication?

Mark only one oval.

- ☐ a) 3 MHz to 30 MHz
- ☐ b) Below 3 MHz
- ☐ c) Above 30 MHz

40. At, The maximum recommended rate of speech for Radiotelephony (RT) transmissions should generally not exceed:

Mark only one oval.

- ☐ a) 120 words per minute.
- ☐ b) 100 words per minute.
- ☐ c) 80 words per minute.

41. What is the correct ICAO phonetic pronunciation for the numeral 1?

Mark only one oval.

- ☐ a) SEV-en
- ☐ b) SEVAN
- ☐ c) SEEVN

42. The phraseology "MAINTAIN AT LEAST (number) FEET ABOVE (or BELOW) (aircraft call sign)" is used to ensure:

Mark only one oval.

- ☐ a) Vertical separation from a specific aircraft.
- ☐ b) Wake turbulence clearance
- ☐ c) Compliance with RVSM requirements.

43. When a pilot initiates a missed approach, the mandatory phraseology to be used is:

Mark only one oval.

- ☐ a) ABORTING LANDING.
- ☐ b) EXECUTING MISSED APPROACH.
- ☐ c) GOING AROUND.

44. When a route is specified using a DME ARC, the phraseology must include the distance, direction, and the:

Mark only one oval.

- ☐ a) True track.
- ☐ b) Name of the DME station.
- ☐ c) Radial from the station.

45. Which letter is excluded from the alphabetical range A-S used for assigning SELCAL codes?

Mark only one oval.

- ☐ a) I, N, and O.
- ☐ b) E, T, and Z.
- ☐ c) V, X, and Y.

46. Runway Condition Code (RWYCC) is:

Mark only one oval.

- ☐ a) A number that summarizes the braking action
- ☐ b) Not based on the ICAO Global Reporting Format (GRF)
- ☐ c) Based solely on Pilot Reports

47. What is the pilot braking action report that corresponds to Runway Condition Code (RWYCC) 3 (Wet Compacted Snow, Slush, or Wet Ice/Snow)?

Mark only one oval.

- ☐ a) Poor
- ☐ b) Medium to Poor
- ☐ c) Medium

48. In a runway contamination report, the sequence of three depth numbers (e.g., 06/12/12) represents the contamination depth in which unit?

Mark only one oval.

- ☐ a) Centimeters (cm).
- ☐ b) Millimeters (mm).
- ☐ c) Inches (in).

49. When a controller corrects a mistake in a previously transmitted instruction, the correct standard phraseology is:

Mark only one oval.

- ☐ a) CORRECTION.
- ☐ b) AMEND TO READ.
- ☐ c) IGNORE, I SAY AGAIN.

50. During a Precision Radar Approach (PAR), if the aircraft is "SLIGHTLY LEFT OF TRACK," the controller will typically instruct the pilot to turn:

Mark only one oval.

- ☐ a) Right.
- ☐ b) Left.
- ☐ c) At pilot's discretion.

51. In the formula $V=IR$ (Ohm's Law), the 'I' represents the electrical unit for:

Mark only one oval.

- ☐ a) Voltage (Volt).
- ☐ b) Current (Ampere).
- ☐ c) Resistance (Ohm).

This content is neither created nor endorsed by Google.

Google Forms